


BUSWAYS




SAF-KEY Fusible Plug-in Devices for Use with UNI-BUS® Plug-in Duct

WHEN ORDERING SPECIFY


- Catalog number




Type LD




Type ND



Type HD



Type LD with
cover open



Type ND or HD
with cover open

PLUGS FOR USE WITH 2 AND 3 POLE DUCT SYSTEMS (6 inch Face) Premium, High Performance, Economy and Slimway Type Ducts.

Amps.	2 Pole, 240 Volts A-c				2 Pole, 480 Volts A-c				3 Pole, 240 Volts A-c				3 Pole, 480 Volts A-c			
	Max. Hp. Ratings		Catalog Number	Price	Max. Hp. Ratings		Catalog Number	Price	Max. Hp. Ratings		Catalog Number	Price	Max. Hp. Ratings		Catalog Number	Price
	Std. Fuses	Dual Element Fuses			Std. Fuses	Dual Element Fuses			Std. Fuses	Dual Element Fuses			Std. Fuses	Dual Element Fuses		
HANDLE OPERATED—NORMAL DUTY—QUICK MAKE—QUICK BREAK CONTACTS																
30	1½	3	ND221	\$37.	3	7½	ND261	\$39.	3	7½	ND321	\$39.	7½	15	ND361	\$41.
60	3	10	ND222	39.	5	20	ND262	41.	7½	15	ND322	43.	15	30	ND362	45.
100	7½	15	ND223	52.	10	30	ND263	54.	15	30	ND323	56.	25	50	ND363	63.
HANDLE OPERATED AND HOOK STICK OPERABLE—HEAVY DUTY—QUICK MAKE—QUICK BREAK CONTACTS																
30	1½	3	HD221	\$45.	3	7½	HD261	\$47.	3	7½	HD321	\$49.	7½	15	HD361	\$50.
60	3	10	HD222	50.	5	20	HD262	54.	7½	15	HD322	57.	15	50	HD362	60.
100	7½	15	HD223	76.	10	30	HD263	80.	15	30	HD323	84.	30	50	HD363	87.
200	15	---	HD224	140.	30	50	HD264	150.	25	50	HD324	148.	50	---	HD364	156.
HANDLE OPERATED AND HOOK STICK OPERABLE—HEAVY DUTY—BOLT-ON TYPE MUST BE BOLTED ON AT JOINT SECTION—QUICK MAKE—QUICK BREAK CONTACTS																
400	---	---	---	---	---	---	---	---	---	---	HD325	\$368.	---	---	HD365	\$368.
600	---	---	---	---	---	---	---	---	---	---	HD326	502.	---	---	HD366	502.
FOR NON-OPERATING DISCONNECT PURPOSES																
30	---	---	① LD221	\$15.	---	---	LD261	\$29.	---	---	① LD321	\$16.	---	---	LD361	\$29.
② 30	---	---	LDR221	26.	---	---	---	---	---	---	LDR321	26.	---	---	---	---
60	---	---	LD222	26.	---	---	LD262	30.	---	---	LD322	26.	---	---	LD362	30.
100	---	---	LD223	46.	---	---	LD263	48.	---	---	LD323	50.	---	---	LD363	54.
200	---	---	LD224	100.	---	---	LD264	114.	---	---	LD324	110.	---	---	LD364	122.
400	---	---	LD225	260.	---	---	LD265	270.	---	---	LD325	275.	---	---	LD365	288.

① 30 ampere LD plugs must be connected by flexible cable only since to replace fuses on these plugs they must be removed from the duct.

② 60 ampere plugs (cover removable) with 30 ampere fuse clips permitting the use of rigid conduit.

DISCOUNT SCHEDULE 17 CD-1

CUTLER-HAMMER