

(1-1)

FINEST Professional F

SANI-GIE

DAY-LITE WHITE HIGH-GLOSS

1003 V

CAUTION!
COMBUSTIBLE

Keep from heat and open flame. Avoid breathing vapor or spray mist and prolonged contact with skin may cause skin irritation. Do not take internally — may contain compounds harmful if eaten. Keep container closed when not in use. Keep Out of the Reach of Children. Use with Adequate Ventilation.

(1-361)



ORANGE WHITE PLEST

SANI-GIENE DAY-LITE WHITE HIGH-GLOSS ENAMEL

A sanitary, highest quality, ready-mixed enamel for use on walls and ceilings in Bakeries, Dairy Products plants, Food processing plants, Bottling plants, Breweries and other industries, which have departments normally affected by mold or mildew growing in or on the enamel — where hygiene and sanitation are a paramount housekeeping necessity. Contains a water insoluble fungicide that does not evaporate or leach out. SANI-GIENE controls the growth of mold and mildew in or on the enamel during its entire service life. Withstands repeated washings. Maintains its extreme whiteness.

DIRECTIONS

Surface Preparation: All surfaces must be dry, free from mold, mildew, dirt, grease, loose particles, food deposits and all foreign matter. Remove mold and mildew by scrubbing with sol soda solution or tri-sodium phosphate solution (1/2 pound sol soda, or tri-sodium to 1 gallon water). Rinse thoroughly with clean water. Glossy surfaces should be scuff-sanded or dulled with Surfacene.

Unpainted Surfaces: Prime plaster with No. 16 Alkyd Wall Primer and Sealer. Prime wood and metal with No. 5 White Alkyd Enamel Undercoater. Apply finish coat Sani-Giene.

Painted Surfaces: If in good condition need only be cleaned and apply coat Sani-

Giene. If badly worn, scraping or wire brushing may be necessary. Spot prime as needed with above primers. If complete removal is necessary, use Glid Strip Paint & Varnish Remover, and refinish as for unpainted surface.

Material Preparation: Mix thoroughly by stirring or boxing. Thin sparingly with mineral spirits if necessary for better brushing. Thin with VM & P Naphtha for spraying. May be tinted with Dramatone Multi-Purpose Tinting Colors or Colors-In-Oil.

Application: Apply liberally and uniformly when brushing or spraying. Allow to dry overnight between coats. Covers up to 500 square feet per gallon. L.C. 95723

THE GLIDDEN COMPANY, CLEVELAND 2, OHIO

Factories and Branches in Principal Cities Throughout United States and Canada

ONE GALLON
U. S. MEASURE

Made in U. S. A.

Glidden
Painting
and
Decorative
Finishes
Co.
Cleveland, Ohio 44106
V-30068
100-051