

MADE FOR DIXIE TRADE

Climatic



TIME

PAINTS · VARN

SEALLETTE

(SEMI-PASTE)

FLAT WALL PAINT

2024 WHITE

THE AMERICAN PAINT WORKS

DIVISION

THE GLIDDEN COMPANY

* NEW ORLEANS, LOUISIANA *

Seallette seals, prim
be applied over d
paints. Also plast
or cement surface
paintable surface.

All surfaces must
Loose and scaling
Reduce Seallette F
Spirits or Turpenti
face and method c
nishes, or patent
coats.

Pigment 70%
Vehicle 30%
No lead: Lithopone, Magnesium Silicate (6.1%), Calcium Carbonate (21.1%)
Silica (6.1%)

GL031605

N 4164

TIME TESTED

PAINTS • VARNISHES • LACQUERS • ENAMELS

SEALETTE FLAT

Sealette seals, primes and finishes in one operation. Sealette can be applied over dry surfaces of casein, calcimine and texture paints. Also plaster wall board, wood previously painted, brick or cement surfaces or any other clean, dry and solid interior paintable surface.

DIRECTIONS

All surfaces must be clean and free from dust, dirt, and grease. Loose and scaling surfaces should be wire brushed or scraped. Reduce Sealette Flat by adding two or three pints of Mineral Spirits or Turpentine to the gallon, depending on porosity of surface and method of application. Do not use Linseed Oil, Varnishes, or patented oils for reducing Sealette Flat for finishing coats.

77

GLD31606