


The Waterman-Waterbury Co.

Minneapolis 13, Minnesota
Manufacturers of WATERBURY Coal, Oil and Gas
Fired Furnaces and Air Conditioning Equipment



WATERBURY GAS-TITE FURNACE 700 Series


The welded steel furnace body keeps dust, smoke and fumes out of the air stream. A large combustion chamber and radiator with long fire travel insure efficiency and economy.

Also furnished in a complete home Air Conditioner.

Size Furnace	Diameter		Height		Steel Thickness			Diam. Smoke Pipe	Approx. Shipping Wt Lbs Furnace less Casing	Output Ratings	
	Furnace Body	Pipe Casing	Furnace Body	Pipe Casing & Hood	Body	Head	Radiator			Sq In. Leader Pipe	Btu at Bonnet
720	20"	39"	49"	64"	10 Ga.	10 Ga.	12 Ga.	8"	531	482	87,529
722	22"	41"	49"	64"	10 Ga.	7 Ga.	12 Ga.	8"	603	505	91,730
724	24"	44"	49"	64"	7 Ga.	7 Ga.	12 Ga.	9"	730	541	98,056
727	27"	46"	55"	70"	7 Ga.	1/4"	12 Ga.	9"	866	672	121,856

Gas-tite Air Conditioner

Size	Width	Length	Height	Size Outlet Opening	Size Inlet Opening	No. of Filters	Size thru Unit Filter	Blower CfmRange	Btu Per Hour Output at Bonnet
720-10	36"	50"	55"	32x24	32x16	2	16x16	375 to 1050	87,963
722-10	40"	56"	55"	36x26	36x22	2	20x20	375 to 1050	94,011
724-10	40"	56"	55"	36x26	36x22	2	20x20	375 to 1050	100,193
724-12	40"	56"	55"	36x26	36x22	2	20x20	645 to 1677	100,193




WATERBURY GAS FIRED AIR CONDITIONER

The latest achievement of Waterbury's engineers, designed specifically for gas. Completely automatic—filtered, humidified forced air—enclosed in a compact, baked enamel casing. Can also be furnished for Propane or Butane.

Size	Input Rating Btu per Hr	Output Capacity Btu per hour at Register	*Blower Cfm Range	Width In.	Length (Heater Casing Plus Blower Casing) In.	Height Overall In.	Size Outlet Opening	Size Return Inlet Opening	No. of Filters	Size each Filter	** Rec. Flue Pipe Diam.	Size Gas Connection Required
6413-9	90,000	72,000	400 to 800	28	50	20x24	15 x24	2	1	16x25	5"	3/4"
6413-9 High	90,000	72,000	400 to 800	28	50	24x24	16 x24	2	1	16x25	5"	3/4"
6415-10	120,000	96,000	600 to 1200	28	58	20x24	16 x24	2	1	16x25	5"	3/4"
6426-12	180,000	144,000	800 to 1800	55	52	24x51	19 1/2x26	1	1	20x25	2-5 to 7"	1"
6426-15	180,000	144,000	1000 to 2800	55	56	24x51	25 1/2x34 1/4	4	1	16x20	2-5 to 7"	1"
6430-15	240,000	192,000	1000 to 2800	55	56	24x51	25 1/2x34 1/4	4	1	16x20	2-6 to 8"	1 1/4"
6430-18	240,000	192,000	1232 to 3204	55	72	24x51	40 x36	6	1	16x25	2-6 to 8"	1 1/4"

WATERBURY GAS GRAVITY FURNACE

Size Furnace	Input Rating Btu per Hr	Output Rating Sq In. Warm Air Pipe	Width In.	Length In.	Height Overall In.	Size Outlet Opening	**Rec. Flue Pipe Diam.	Size Gas Connection Required In.
6413	90,000	67,500	28	28	50	24x24	5"	3/4"
6415	120,000	90,000	30	30	58	26x26	6"	3/4"
6426	180,000	135,000	28	55	50	24x51	2-5 to 7"	1"
6430	240,000	180,000	30	58	58	26x54	2-6 to 8"	1 1/4"




The Waterman-Waterbury Co.

Minneapolis 13, Minnesota

WATERBURY 6300 Series OIL FIRED AIR CONDITIONER

Completely automatic oil heat with forced, filtered, humidified air, all enclosed in one compact casing finished in baked enamel.




Size	Input Rating Gal Oil per Hr	Output Capacity Btu per Hr at Bonnet	Width Casing	Length Casing	Height Overall	Size Outlet Opening	Size Return Inlet Opening	Distance Between Opening	No. of Filters	Size each Filter	Diam. Smoke Pipe
W-6315-10	1 gal	97,000	28"	58"	58"	24x20	24x16	3"	2	16x25	7"

2320-12 OIL FIRED AIR CONDITIONER


This unit has a side mounted burner and can be furnished with a burner hood at slight additional cost.

Size	Input Rating Gal Oil per Hr	Output Capacity Btu per Hr at Register	Width Not Incl. Burner Hood	Length	Height Overall	Size Outlet Opening	Size Return Inlet Opening	Distance Between Opening	No. of Filters	Size Each Filter	Diam. Smoke Pipe	Dimens. Burner Hood Wdt. Dpth. Hgt.
2320-12	1.20	120,000	30	60	61	26x24 1/8	26x24 1/8	6 1/8"	2	{ 1-16x25 1-20x25	7"	23 17 28



SEAMLESS OIL FIRED FURNACE BODY

Specially engineered for oil firing only, it may be used as a gravity circulating pipe furnace. It is the heating element of the Comfortrol Oil Fired Air Conditioners.



Specifications Comfortrol Oil Fired Air Conditioners


Size	Input Rating Gal per Hr	Btu per Hr at Register	Normal Cfm Range	Width Less Front Hood	Length Overall	Height	Size Outlet	Size Inlet	Filters		Smoke Pipe
									No.	Size	
1322-12	1.5	142,763	645 to 1677	44"	72"	64"	36x36	19 1/2x26	{ 1 4	20x25 16x25	8
1322-15	1.5	142,763	922 to 2397	44"	74"	64"	36x36	25 1/2x34 1/4	{ 1 4	16x20 16x20	8
1324-15	2.0	190,350	922 to 2397	48"	78"	64"	40x40	25 1/2x34 1/4	{ 1 4	16x20 16x20	8
1324-18	2.0	190,350	1232 to 3204	48"	81"	64"	40x40	40 x36	{ 1 4	20x25 20x25	9
1327-18	2.5	237,938	1232 to 3204	52"	85"	64"	44x44	40 x36	{ 1 4	16x25 16x25	9
1327-21	2.5	237,938	1450 to 3770	52"	85"	64"	44x44	38 x44	{ 1 4	16x25 16x25	9
1330-21	3.0	285,525	1450 to 3770	56"	89"	70"	48x48	38 x44	{ 1 4	16x25 16x25	9
1332-24	3.5	333,113	1968 to 5118	60"	104"	72"	52x52	46 x48	{ 1 4	20x25 20x25	9
1336-24	4.0	380,700	1968 to 5118	66"	110"	81"	58x58	46 x48	{ 1 4	20x25 20x25	9

†Burner hood all sizes is 24 in. wide, 10 in. deep.

*Add 140 lbs for oil burner and controls. Add 80 lbs for burner hood.

GAS CONVERSION BURNER

A real gas burner, the same as used in the Gas-Air Conditioner. Can also be furnished for Propane or Butane.



Number	Maximum Btu Input	Maximum Cubic Feet of Mixed Gas	Maximum Cubic Feet of Manuf'd. Gas	Minimum Fire Pot Size
C-100	165,000	208	300	18 Inch