
Sheldons
ENGINEERING LIMITED
GALT . CANADA


SALES OFFICES: MONTREAL, OTTAWA, TORONTO, HAMILTON, LONDON
AGENTS: HALIFAX, ST. JOHN, N.B., WINNIPEG, CALGARY, EDMONTON, VANCOUVER

Fan Manufacturers For More Than 50 Years


Member Canadian Fan Manufacturers' Association.




Silavent Fans



Keith Fans



Utility Sets



Axial Flow Fans

ATTENTION

AMERICAN ENGINEERS WORKING ON PROJECTS IN CANADA

We invite your inquiries for specifcations and full information on SHELDON Fans, Blowers, Exhausters, Heating, Ventilating and Air-Conditioning Apparatus, and allied equipment required on your Canadian projects.

For more than fifty years this Company has been well and favorably known in Canada as manufacturers of high-quality, air-handling equipment. SHELDON products are accepted as "EQUAL" to any other similar apparatus produced on the American Continent.


Air Conditioning Units • Keith and Silavent Fans • Utility Sets • Forced Draft Fans • Induced Draft Fans • Airscrew Fans • Axial Flow Fans • Medium Blowers and Exhausters • Mill Exhausters • Dust Separators and Collectors • Dust Filters • Centrifugal Blowers • Unit Heaters • Drying Equipment • Chemical Plant Fans • Mine Ventilating Fans •




Roof Ventilators



Air-Conditioners



Mill Exhausters



Pressure Blowers


Complete engineering data and catalogs available upon request

Trade-Wind Motorfans, Inc.

7755 Paramount Blvd.
Rivera, Calif.

Representatives In All Principal Cities. Carried in Stock By Many Electrical Jobbers

TRADE-WIND CLIPPER CEILING VENTILATORS




New axial flow design gives excellent performance against pressure.

THE TRADE-WIND is a small capacity VENTILATOR, primarily used for exhaust application. While used extensively for home kitchen ventilation, it is adaptable for other applications, such as in school toilets, therapy and treatment rooms in hospitals, dental laboratories, ticket booths, offices and x-ray and photographic dark rooms.

This is a complete "unit package" assembly. It is *Underwriters'* approved and listed. It carries a (pro-rata) five year guarantee. The installation requires only the application of a discharge duct of the same dimension as the outlet collar and the optional addition of an automatic shutter for the end of the duct. The assembly is inherently quiet and is installed rigidly in the structure without need for resilient mountings or flexible duct connections. The blower is normally quiet at its maximum speed. The motor and wheel unit is removed easily without tools through the ceiling inlet opening.

LEFT: Blower unit and grille in all Trade-Wind models are easily removed without tools. Unit shown is Model 1501.

RIGHT: Model 3501 installs in a cabinet over the stove. Inlets, equipped with washable filters, are provided in base of unit and at ceiling. Hood is optional.



Selection Chart and Specifications
TRADE-WIND VENTILATORS—115 Volt, 60 Cycles, A.C.

Cat No.	Description	Type Blower	Net Air CFM	Recomm. Max. Room Size Cu Ft	Duct Size	Motor Watts
1201 Clipper	Horizontal discharge complete with grille.	Single Wheel	100	Bathrooms Only	4" Round	50
1501 Clipper	Interchangeable horizontal or vertical discharge, complete with grille.	Two Wheels	300	1000	10"x3½"	105
2501 Clipper	Interchangeable horizontal or vertical discharge complete with grille, 4-speed switch.	Two Wheels	425	2000	10"x3½"	130
3501 Super Clipper	Cabinet Installation Includes housing, 2 filters, 4-speed switch; stainless steel or copper hood optional.	Two Wheels	550	3000	13"x4"	140
AF-7 Axial Flow	Ceiling or wall Installation.	Impellers	300	1000	7" Round	50