

Ray Oil Burner Co.

Since 1872


1301 San Jose Avenue
San Francisco 12, Cal.



Atlantic Seaboard Division
629 Grove Street
Jersey City 2, N. J.

There is a RAY Burner for every Heating Purpose.

RAY FORCED DRAFT PACKAGED BURNER




FD-ARC Size #6 fully automatic, combination gas-oil, Forced Draft Packaged Burner.

A factory assembled unit readily applied to any type of boiler designed for forced draft operation. Fully automatic operation on oil, gas or combination gas-oil.

The combination gas-oil unit includes a rotary oil burner, integrated ring type gas burner, secondary air control with a forced draft fan, windbox, refractory support ring, completely wired control panel and pre-piping completely factory assembled for quick and easy installation to the boiler.

Oil components may be selected to burn any grade of oil with the secondary air control providing increased efficiency even with the difficult-to-burn catalytic residual #6 fuel oils. From 83 to 540 equivalent boiler horsepower.

RAY COMBINATION OIL-GAS BURNERS



ARC-144 Model 50 for heavy oil and Low Pressure Gas



Type PC for Oil and Low Pressure Gas




Type AR-HN Combination Oil and High Pressure Gas

ARC-MODEL 50. Consists of a rotary type oil burner of Ray conventional design coupled with a gas housing for low pressure gas, from 2 in. WC to 10 in. WC. The gas burner parts provide for the introduction of gas in a manner which fully utilizes the energy in the high pressure air supplied by the rotary burner fan. Gas and primary air are intimately combined, in two stages, before mixing with the secondary air which is introduced through a vaned annular opening concentric with the nozzle. Change-over requires less than one minute. Available to burn any grade of oil in 9 sizes with capacities to 31,500,000 Btu/hr.


TYPE HN for gas pressures above 1 lb/sq in. may be used alone or in combination with a Ray Oil Burner. Built in ten sizes; in capacities to 48,000,000 Btu/hr.

TYPE PC. Combination gas-oil burner of the pressure atomizing type. Available in three sizes with capacities from 560,000 to 2,500,000 Btu/hr.

RAY DOMESTIC AND MARINE BURNERS



Fully Automatic, Type JP, #2 or lighter oil



Steam Turbine Drive, Type TG, all grades oil. Tested and approved for U. S. Navy Service.



Ray Warm Air Oil Furnace

RAY PRESSURE ATOMIZING OIL BURNERS Fully automatic for No. 2 oil, or lighter. AC or DC; capacities 1 to 18 gallons per hour.

WARM AIR FURNACES Built in five sizes, with input capacities of 105,000; 140,000; 230,000; 350,000; 450,000 Btu.

RAY OIL WATER HEATERS Five sizes. Capacities: 35, 45, 60, 75 and 100 gal. Maximum recovery rates: 100 to 240 gph.

Ray Oil Burner Co.

Since 1872

1301 San Jose Avenue
San Francisco 12, Cal.




Atlantic Seaboard Division
629 Grove Street
Jersey City 2, N. J.

Distributors in
All Principal Cities of the World

Consult your local
Telephone Directory

Products: A complete line of Horizontal Rotary and Pressure Atomizing Oil Burners; Combination Oil-or-Gas Burners; Industrial Gas Burners; Forced Draft, packaged Burners; Oil Burning Water Heaters; Warm Air Furnaces.



Type AR-144 Size 10 for No. 6 oil. Available in 10 sizes from 8 to 110 gph. Fully automatic.



Fully Automatic Type AR-134, for No. 5 oil.



1 to 1000 Boiler hp Type AG. Manual, Semi-automatic control.




Type ARJP, Fully Automatic for heavy oil where gas for ignition not available.

RAY HORIZONTAL ROTARY OIL BURNERS

Built in fully automatic, semi-automatic and manual types; in sizes from 1 to 1000 Boiler hp; to burn all grades of fuel oil.

Standard models include both direct and belt drives—the latter being recommended for use where other than 50 or 60 Cycles AC, or only DC is available. Types for straight electric or straight gas ignition; pump or gravity feeds. Direct drive types include a steam turbine driven model.

All fully automatic types for heavy oil incorporate the Ray Dual Pump and Reservoir, with the Ray VISCOSITY Valve, a patented, exclusive feature which automatically meters the correct amount of fuel at all times, regardless of changes in viscosity of the oil due to temperature variations. All larger sizes employ dual ignition system, consisting of dual high-voltage transformers, dual electric ignitors and dual gas valves. Fully automatic sizes 9 and 10 include as standard equipment electronic pilot and flame failure control.



Type BR-144, Belt Drive, Fully Automatic, Available in 8 sizes. Capacities from 8 to 110 gph.

HOURLY CAPACITY RATINGS of RAY OIL BURNERS

Burner Size	No. of H.P.	Oil Capacity U. S. Gallons		Equivalent Boiler HP		Equivalent Lbs. Steam Generated*		Heat Capacity Input Thou. Btu Oil or 1000 Btu Gas		Equivalent Sq. Ft Steam Radiation	
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
JP	1/4	1	3	3	9	110	325	140	420	440	1300
0-P	1/4	1	4	3	12	110	430	140	560	440	1750
1-P	1/4	3	8	9	25	325	860	1120	2500	1300	3500
2-P	1/4	8	18	25	55	860	1950	1120	2500	3500	7900
0	1/4	2	5	7	16	230	580	300	750	938	2340
1	1/4	4	11	13	35	460	1270	600	1650	1880	5160
2	1/4	5	15	17	50	580	1740	750	2250	2340	7030
3	1/4	8	25	27	83	930	2900	1200	3750	3750	11720
5	1	10	35	33	116	1160	4050	1500	5250	4690	16400
6	1 1/4	12	50	40	165	1400	5800	1800	7500	5620	23500
7	2	15	70	50	230	1740	8100	2250	10500	7030	32800
8	3	25	110	83	365	2900	12700	3750	16500	11700	51500
9	5	35	150	116	500	4050	17400	5250	22500	16400	70500
10	7 1/2	50	210	165	700	5800	24400	7500	31500	23400	98300
12	7 1/2	75	320	250	1000	8700	37000	11250	48000	35100	149800

NOTE: These ratings are predicated upon specific conditions of draft and furnace volume. It may be permissible, under desirable conditions, to operate at higher rates, or advisable under restricted conditions, to operate at reduced rates. Heating capacities are based upon 150,000 Btu per gal of oil for rotary burners and 140,000 Btu per gal of oil for pressure atomizing burners and upon an overall boiler efficiency of 75 per cent.

* Steam capacity based on steam F and A 212 F.