

E. I. du Pont de Nemours & Co., Inc.
Richmond, Virginia

CC: File (3)

Textile Fibers Department

SPRUANCE FIBERS PLANT
September 20, 1972

R. B. Hayden, Staff Engineer
Division Engineer's Office
Textile Fibers Division
Nemours Building
Wilmington, Delaware

ENGINEERING STANDARD - ASBESTOS DUST EXPOSURE, MEASUREMENT AND CONTROL

Reference: Letter September 15, 1972 to Committee Members

Requested comments on tentative Safety Engineering Standard S 4 T are listed below with proposal as written and comment indented.

- 33) 3.4.1 "Insulation to be removed and discarded should be dampened prior to and during removal whenever possible."
- Suggest consideration for rewording with reference to "prior to" as a glazed or painted exterior surface will not absorb moisture. Agree with dampening during removal.
- 34) 5.1 "Respirators and masks must be kept clean and sterilized prior to reissue".
- Suggest consideration for expanding to allow the issuance of respiratory equipment to individuals, to be kept and maintained by them as personal protective items.
- 35) 6.2.2 "Millipore No. MAWP-037-AO filter, white, nongridded.
0.8 micron pore Millipore Corporation, Bedford, Mass. 01730"
- Suggest consideration be given to allow use of No. MAWG-037-AO filters (gridded) by those who may have a current, plentiful supply on hand.

DUP 0902955

SC-DP-03945