ONE GALLON

O'BRIEN'S®

FLOOR and DECK ENAMEL

TILE RED

WARNING!
FLAMMABLE
See cautions elsewhere on label.

CONTAINS O'BRIEN'S EXCLUSIVE Alki-therm

MADE IN U. S. A. • MANUFACTURED BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA

49 TNC 001657

FLOOR ENAMEL

QUICK DRYING

O'Brien's Floor Enamel is a quick drying, waterproof finish which may be used **indoors** or **outdoors** on any type of surface . . . wood, concrete, metal, linoleum, etc., or over old paint. This floor enamel is easy to apply and will hold its appearance and lustre under the strain of heavy foot traffic and the battering of the elements. — Also excellent for boat finishing — wood or metal.

GENERAL DIRECTIONS

The surface to be painted should be clean and dry. Remove any loose paint by scraping, wire brushing or sandpapering. Remove all dirt, grease and wax by scouring with a washing powder. Then rinse well with clean water and allow the surface to dry thoroughly. **Stir the paint well before and during use.** Apply thin, well brushed coats with a good brush. Allow sufficient drying time between coats.

NOTE — Floors which are in direct contact with the ground and which show a tendency to remain damp should not be finished with an oil-type paint or enamel.

REGISTERED
REG'TL No. 2513
DATE 1/22/63

NEW, UNPAINTED FLOORS

Apply two, or preferably three, thin, well brushed coats of O'Brien's Floor Enamel. "Glazed Finish" concrete floors, before painting, should be etched by applying muriatic acid, 10% dilute, allowing it to stand fifteen minutes and then rinsing with clean water. Before painting freshly laid concrete floors or those surfaces where free lime or alkali are present, neutralize and harden with O'Brien's Neutralizing Solution, according to directions.

OLD PAINTED FLOORS

Apply two thin coats of O'Brien's Floor Enamel. Allow sufficient drying time between coats.

NOTE—This floor enamel may be thinned 25% with pure turpentine. It should be remembered that thin, well brushed coats are longer wearing than heavily applied coats.

DO NOT TAKE INTERNALLY

CAUTION!

Keep away from heat, sparks and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.



FLOOR & DECK ENAMEL TILE RED

Pigment	27.31%
C. P. Red Iron Oxide	15.82%
Limonite	24.96%
Calcium Carbonate	48.57%
Zinc Stearate	.45%
	100.00%
Vehicle	72.69%
*Alkyd Resin Solution	70.05%
Hydrogenated Naphtha	6.74%
Mineral Spirits & Drier	23.21%
	100.00%
*Alkyd Resin Solution:	
Non Volatile: Soya Bean Oil, Modified Alkyd Resin	50.00%
Volatile: Mineral Spirits	50.00%
	100.00%

THE O'BRIEN CORPORATION

OKLA. CITY, OKLA. SAN FRANCISCO, CAL.
SOUTH BEND, IND. BALTIMORE, MD.
LOS ANGELES, CAL.

49 TOC 001658