MAKING INSTRUCTIONS: BATCH UNIT

V. 246, ~~247~~ C.V. D.V.

PROCESSES	APPROVED BY
( ) KO-786-D (P)	EWK 9-21-76
( ) ( )	DCG 9-21-76
( ) ( )	MTW 10-1-76
( ) ( )	
TYPED BY	
JJC 11-16-76	

OG 04 CODE KO-786-D PKG.

DEC26 33509

EST. WGT. 862 LBS.

STD. HRS. 10.5 TIME 7 AM

OK EK

01	YC-10-B	93	4	33051 , 3700 #	Bay temp
01	YC-10-B	93	4	32821 , 400 #	
01	YC-10-B	93	4	, #	

Homog #2

Total Weight 4962# (Req. 497)

NON-BLEEDING

EQUIPMENT		NAME: "KROLOR" ORANGE R	USE LBS.	N CODE	ACCT. LBS.
211	1	Run 60" (990 G) water in V-211 and add Assume 50%	30	7-D	15
&	2	Weigh in drum and pour in V-211	270	32-D	270
208	3	Dump in and stir 5 minutes LOT	82 x 50	YC-10-B	4100
1		Record: Start 8:00 AM 33051	3700		
		" Fin 10:00 AM 32821	400		
		75" (1256)			
	4	Adjust to ~~80" (1370 G)~~			
	5	Pump V-211 thru Homog #2 at 1800-2200 psi into V-208			
	6	When V-211 MTY, wash color thru Homog at 1800-2200 psi using minimum water			
	7	Record: V-208 Vol 42 " and adjust to 50" (1840 G)			
	8	Inspect homog strainer and clean if necessary			
208	9	Run 15" (771 G) water into V-246 and start agitator and			
&		install temperature chart			
SV	10	Pump V-208 thru Homog at 4800-5200 psi into SV			
2		Record: Time Start 1:20PM Total Minutes 130			
		Note: If homog pressure falls below 4800 psi, 3-Way valve will recirculate slurry to V-208			
	11	When V-208 MTY, run in 5" (240 G) water and pump thru Homog at 4800-5200 psi			
349	12	While Homog, run 6" (284 G) water into V-349			
&	13	Run ±1000# water into V-384 and heat to 110-120°F			
384	14	Weigh into V-384 and pump to V-349 ✓	2400	32-D	2400
3	15	Run ±1000# water into V-384 and pump to V-349			
	16	Adjust V-349 to 22" (1040 G) & stir 15 minutes or longer			
	17	Record: ~~°Be'~~ 10.80 ~~(10.9 ±0.2)~~ (1.078-1.081) g/ml			
SV	18	When S 11 Homog complete, adjust to 66" (3400 G) in SV			
4	19	Record: pH 11.6 and adjust to 10.4-10.8 using N-7-D diluted to 5% (10 parts water to 1 part N-7-D) Assume 50%	✓	7-D	
		Siphon N-7-D into SV and Record: pH			
	20	Heat to 190-194°F in 55-65 minutes & Record: HT F and Rec F			
		Note: Strike must be started immediately on completion of heating			
343	21	While heating SV, run 51" (1400 G) water into V-343			
&	22	Meter in from V-386 M 83 #/Gal 9.88 Gal 35.9	V/M	27-D	355
386	23	Stir 15 minutes or longer			
5	24	Record: ~~°Be'~~ 1.018 ~~(2.8 ±0.1)~~ (1.017-1.019) g/ml			

V-246

UIPMENT		PAGE 2 CG 04 CODE KO-786-D (R) EST. WGT. 4962 LBS.	USE LBS.	N CODE	A
SV 6	25	When S 20 heating complete, Record: pH 10.1 (9.6-10.2)			
	26	Set V-343 acid pump at 72 setting (±225 minutes)			
	27	Set V-349 silicate pump at 66 setting (±180 minutes)			
	28	Immediately meter in V-343 & V-349. Maintain SV at 190-193°F during strike			
	29	Record: Start Finish Minutes V-343 7:10PM 11:15PM 245 V-349 180			

Record:	Time	V-343 Inches	V-349 Inches	SV pH	Normal pH
at 20 min	7.30	(47) 47	(20) 20	9.9	9.3-10.0
40 min	7.50	(43) 40	(17) 17	9.9	9.3-10.0
1 hr	8.10	(38) 40	(15) 15	9.9	9.3-10.0
2 hrs	9.10	(24) 26	(7) 7	9.9	9.3-10.0
3 hrs	10.10	(10) 12	(0) 0	9.9	9.3-10.0
Finish	10.35	(0) ←	—	9.9	7.5- 8.5

		Note: if pH drops below 9.3 in 1st hour, stop pumps and see supervisor. If final pH is above 8.5, adjust to (7.5-8.5) and Record: pH _____ Assume 77%		27-D	
357 7	30	Run 21" (150 G) water into V-357 and heat to 135-140°F			
	31	Dump in and stir to dissolve	300	15-A	300
302 8	32	Add 42" (514 G) water to V-302			
	33	Add and stir 2 minutes Assume 50%	150	7-D	75
SV 9	34	When V-349 MTY, rinse in with minimum water then set pump to zero setting			
	35	When V-343 MTY, rinse in with minimum water, then turn off pump motor			
	36	TURN OFF STEAM			
	37	Run in V-357 from S 31 and stir 5 minutes			
	38	Record: pH 3.0 (3.3-3.7)			
	39	If necessary, adjust pH to 3.3-3.7 (Downward only) Record: pH		15-A	
	40	Run in N-7-D from S 33 in 4-6 minutes and stir 5 minutes			
	41	Record: pH 5.5 (4.0-4.2) & if necessary, adjust to pH 4.0-4.2 and Record: pH 4.1 Assume 77%	12	27-D	
		(Dilute 10 parts water to 1 part N-7-D) Assume 50%		7-D	
		Siphon N-7-D into SV			
	42	Stop agitator			

START	FINISH	OPTR
10:00 AM	3:00 PM	235
3 PM	11 PM	223-438
11:00 PM	12-30 AM	145

DUP050095461



DUP050095462