Form Approved OMB No. 44-R1387
Approval Expires: July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

81094

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME: MONSANTO COMPANY
EMERGENCY TELEPHONE NO: (314) 694-1000
ADDRESS (Number, Street, City, State, and ZIP Code): 800 North Lindbergh Boulevard, St. Louis, Missouri 63166
CHEMICAL NAME AND SYNONYMS: Mixture
TRADE NAME AND SYNONYMS: Inerteen 5#201 K.I
CHEMICAL FAMILY: Chlorinated Aromatic
FORMULA: mixture

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III PHYSICAL DATA

BOILING POINT (°F.) 760 mm	200-350°C	SPECIFIC GRAVITY (H_2O = 1) (25/15.5°C)	1.333
VAPOR PRESSURE (mm Hg.)	Not Avail.	PERCENT VOLATILE BY VOLUME (%)	N.A.
VAPOR DENSITY (AIR = 1)	Not Avail	EVAPORATION RATE (n-BuAc = 1)	<1
SOLUBILITY IN WATER 29°C negligible			
APPEARANCE AND ODOR	colorless oil	aromatic odor	

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	None	FLAMMABLE LIMITS	LEL N.A.	UEL N.A.

EXTINGUISHING MEDIA

SPECIAL FIRE FIGHTING PROCEDURES
Respiratory protection when fighting fires where exposure to vapors or gases is possible.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.

DSW 009572

LEXOLDMON006361
WATER_PCB-00035372

Interlocen 54201 KJ

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Not available.

EFFECTS OF OVEREXPOSURE: Skin irritation in the form of chloracne, systematic intoxication, leads to nausea, vomiting, loss of weight, edema and abdominal pain

EMERGENCY AND FIRST AID PROCEDURES: Remove contaminated clothing. Wash contacted area. Remove from exposure. Wash with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	X	

INCOMPATABILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO_2, smoke, soot, chlorides and chlorine.

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.

WASTE DISPOSAL METHOD: Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type): Bureau of Mines approved respirator for organic vapors

VENTILATION		
	LOCAL EXHAUST: Yes - for vapors	SPECIAL
	MECHANICAL (General)	OTHER

PROTECTIVE GLOVES	EYE PROTECTION
Rubber	Chemical goggles

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid skin and eye contact, avoid inhalation of vapors.

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP 3/26/82

DSW 009573

LEXOLDMON006362
WATER_PCB-00035373