49 TNT 881502

LIQUID VELVET ALKYD

Flat Wall Enamel

Liquid Velvet Alkyd, made with O'Brien's sensational new Alki-Therm (alkyds combined with special Thermolyzed Oils), provides odorless painting, easier application, one coat hiding and extra washability. It may be used with superior results over almost any interior surface — plaster, wood, wallboard, metal, wallpaper, etc.

REGISTERED
REGN. No. 15136
DATE 1-11-67

LIQUID VELVET WALL PRIMER & SEALER — A pigmented primer-sealer undercoat for Liquid Velvet Alkyd or other flat, semi-gloss or gloss paints.

DIRECTIONS FOR USE

Light Shades Over Unpainted Surfaces

1st Coat — Liquid Velvet Wall Primer & Sealer tinted toward finish coat with O'Brien's Tone-All, Pure Liquid Oil Colors or Liquid Velvet Deep Colors. (Over dry wall, plaster board or fresh plaster, use New Vite, tinted with Tone-All Colors.)

2nd Coat — Liquid Velvet Alkyd.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CALIF.
LOS ANGELES, CALIF.

49 TOC 001597

Light Shades Over Painted Surfaces

1 Coat Work — One coat of Liquid Velvet Alkyd will do an excellent job.

2 Coat Work — If paint film is in bad condition or a radical color change is made, follow two coat system under "Unpainted Surfaces." Or, apply two coats Liquid Velvet Alkyd.

Application — Surface should be washed perfectly free of kalsomine, dirt, grease, glue size or soluble casein paints. Apply with brush, roller or spray. If thinning is necessary, use O'Brien's Odorless Thinner. Allow at least 24 hours drying at temperature not less than 68° F. between coats. Stir thoroughly before and during use.

IMPORTANT — USE OF DEEP COLORS

Liquid Velvet Alkyd Deep Colors have a slight sheen for extra protection against burnishing. They may be inter-mixed with Liquid Lite Satin Enamel.

NEW WOOD OR METAL — one coat Double-Up or White Surfacer, followed by one or two coats Liquid Velvet Alkyd.

NEW SEASONED PLASTER — one coat of Liquid Velvet Wall Primer & Sealer (tinted with Deep Color), followed by one or two coats of Liquid Velvet Alkyd. (Over dry wall, plaster board or fresh plaster, use New Vite, tinted with Tone-All colors.)

PREVIOUSLY PAINTED SURFACE — one or two coats of Liquid Velvet Alkyd.

LEAD FREE
DO NOT TAKE INTERNALLY
CAUTION! COMBUSTIBLE
Keep away from heat and open flame. Keep out of reach of children. Avoid breathing of vapor or spray mist and prolonged contact with skin. Keep container closed when not in use. USE WITH ADEQUATE VENTILATION.

LIQUID VELVET ALKYD
LEAF GOLD

Pigment	56.00%
Titanium Calcium Pigment	49.46%
Phthalocyanine Green	.02%
AZO Nickel Yellow	.15%
C.P. Chrome Yellow	.52%
Ferrite Yellow	5.70%
Calcium Carbonate	39.87%
Silica	4.28%
	100.00%
Vehicle	44.00%
Soya Modified Alkyd Resin	18.54%
Heat Treated Linseed Oil	1.98%
Heat Treated Fish Oil	1.98%
Thermolyzed Tung Oil	.99%
Odorless Mineral Spirits and Driers	76.51%
	100.00%