


**PUSHBUTTONS and LIGHTS****Type T—Oil Tight****POTENTIOMETERS—Vertical or Horizontal One Hole Mounting**

Pot. Ohms	1 2 Watt Single Potentiometer		2 Watt Dual Potentiometer		25 Watt Single Potentiometer	
	Catalog Number	Price	Catalog Number	Price	Catalog Number	Price
1000	10250T		10250T		10250T	
2500	331		341		351	
10000	332		342		352	
25000	333	\$20.	343	\$28.	353	\$35.
50000	334		344		354	
Operator Only	335		345		355	
	330	14.	340	15.	350	17.

① Can be converted to base mounting per instructions included with unit.

ACCESSORIES

Description	Catalog Number	Price
Maintained contact attachment—mechanically interlocks two buttons and provides position indication for one—Use with two pushbutton operators and a contact block	10250T	
	A1	\$3.
Maintained contact attachment with indicating button—mechanically interlocks provided button with another and both pushbuttons provide position indication—Use with a pushbutton and a contact block.	Black Red Green Yellow Brown	A17 A18 A19 A20 A21
		5.70
Padlock attachment complete with red flush pushbutton operator. Permits locking NC contacts in open position or vice versa	A16	5.70
Locking attachment for Knob Selector Switches—provision for up to 5 padlocks	A11	5.
Wobble stick complete with retaining nut	A5	3.
Plug—for unused holes	A7	1.
Spacer ring—Used when legend plate is not required	A8	0.30
Retaining nut wrench	A9	3.
Flexible weather resistant boot for flush or long button operators	Black Red Green	A3 A4 A10
		2.
Extended retaining nut—Replaces standard nut and provides guard for flush head pushbutton operators	A12	1.
Standard Flush pushbuttons with extended retaining nut substituted for standard nut—Includes operator and nut.	Black Red	114 115
		2.70

Description	Catalog Number	Price
Roto-Push Lever operator—Used to provide lever operation for Roto-Push operators	10250T A13	\$3.
Lever operator for use with two vertically mounted flush pushbuttons	A14	6.
Shroud for mushroom head operator—prevents accidental operation	A6	4.
Guard for Illuminated Pushbutton	A15	1.
Intermittent Flashing Bulb for use with transformer type, pilot or Prestest® indicating lights—10250-T181-T185, T191-T195, T221-T225 and T321-T325 EXAMPLE: 10250 T181 except G.E. lamp #455		1.
Base Mounting Spacers—Equivalent to contact block in depth—Complete with screws, washers, etc.	1 Block Deep 2 Block Deep	A22 A23
		0.30
Special Retaining Nut for Thick Panel Mounting—Not to be supplied separately—Part No. 15-837 for Indicating Lights—Part No. 15-837-2 for all other elements except Potentiometers. EXAMPLE: 10250 T181 except Retaining Nut 15-837		N/C
Indicating Light Lens Shade—Affords better indication as to whether pilot light is on when subjected to bright external illumination	A24	2.

3 PHASE FULL VOLTAGE
MOTOR CONTROL3 PHASE REDUCED
VOLTAGE & MULTISPEED
MOTOR CONTROL

1 PHASE MOTOR CONTROL

AC-DC CONTACTORS,
RELAYS & TIMERSPUSHBUTTONS & LIGHTS,
LIMIT SWITCHES,
FOOT SWITCHESMISCELLANEOUS
ACCESSORIES &
COMPONENTS