

POWER

AUGUST, 1944

VOLUME 88, NUMBER 8

A CROSS-INDEX OF SUBJECTS FOR THE MONTH

PLANT OPERATING METHODS, MAINTENANCE AND SAFETY

STEAM GENERATION, FUELS, FIRING AND COMBUSTION

TURBINES, ENGINES, AUXILIARIES, HYDRO POWER

DIESELS, GAS ENGINES AND ACCESSORIES

AIR CONDITIONING AND REFRIGERATION

ELECTRICAL EQUIPMENT, ELEVATORS

PIPING, VALVES AND SPECIALTIES

TRANSMISSION, LUBRICATION

STEAM SERVICES, HEATING

INSTRUMENTS, CONTROLS

PUMPS, COMPRESSORS

W. L. KOOP, Publisher P. W. SWAIN, Editor

Associate Editors:

W. A. TUCKER L. N. ROWLEY E. W. FELLER

Editor: C. F. SANDERS Art Editor: E. P. DEMAREST

Business Manager: E. J. TANGERMAN

Paul Wooten San Francisco: E. J. Strickland

FEATURES

Boilers lick floor-space shortage.....	64	→	◀	◀	◀	◀
Centrifugal-pump packing a break.....	67	→				
With magnetic couplings for fan drive.....	70	→	◀	◀	◀	◀
4-mill power—Ponca City's diesel record.....	72	→				
Convert a gas analysis.....	75	→	◀			
Preventable losses on compressors.....	76	→				
Proof motors for hazardous-gas locations.....	79	→		◀	◀	
Contribution to gas-turbine development—II.....	82	→				
Double old boilers' output.....	85	→				
Portable power: Pittsburgh ASME meeting.....	88	→	◀		◀	
"Synchronous condenser"?	90	→				
Production during off-peak hours.....	91	→				
Chief's problem children.....	94	→				
Boilers: (1) marine motors (2) moving a boiler.....	95-98	→				
Speed reducers versatile in application.....	99	→		◀	◀	
Electronic converter ties 25 cycles to 60.....	101	→				

THE OPERATING ENGINEER

Tightened this coupling fit.....	103	→				
For cleaning..... 105	Practical Aids.....	106	→	◀	◀	
Problems..... 110	Questions, Answers.....	114	→	◀	◀	
Question Notebook... 120	"How to—".....	122	→			

OTHER DEPARTMENTS

Equipment Corner... 124	New Equipment.....	126	→	◀	◀	
Editorials..... 128	Power News.....	130	→	◀	◀	
..... 134	Catalogs and booklets...	168	→	◀	◀	

NUMBER 8 • ABC • A MCGRAW-HILL PUBLICATION • ABP • COPYRIGHT 1944, By MCGRAW-HILL PUBLISHING CO., INC.


Editor and Honorary Chairman: James H. McGraw Jr., President; Howard Ehrlich, Executive Vice-President for Business Operations; John Abbink, Executive Vice-President for Sales; C. W. McGraw, Vice-President and Treasurer; J. A. Gerardi, Secretary; J. E. Blackburn Jr., Director of Circulation • DISTRICT MANAGERS: New York: Philadelphia, C. R. Long; Cleveland, F. B. Godley; Chicago, C. Boughton; Boston, C. L. Marlon; St. Louis, G. G. Sears • PUBLICATION OFFICE: 99-129 N. Broadway, Albany, N. Y. • CABLE ADDRESS: "McGrawhill New York" • DISTRICT OFFICES: 520 N. Michigan Ave., Chicago; 14 S. Broad St., Philadelphia 2; 738-9 Oliver Bldg., Pittsburgh 22; 1510 Hanna Bldg., Cleveland 15; 2-144 General Bldg., St. Paul 2; 1066 Paul Brown Bldg., St. Louis 8; 1427 Statler Bldg., Boston 14; 1011 Rhodes-Haverly Bldg., Atlanta 3; 401 W. 5th St., Los Angeles 13; Aldwych Bldg., London WC2 • POWER articles are indexed in both the Industrial Arts and the Engineering Index, at public libraries • POWER issues its own index annually.

PLAINTIFF'S
EXHIBIT

WH 786


THE TURBINE WITH

Bu




Steam turbines are expected to perform—and do, in all probability—for longer periods, with less attention than any other type of power drive. To meet these severe service demands, Westinghouse offers a complete line of Type C General Purpose Turbines with "built-in protection" against overspeed . . . steam leakage . . . explosion . . . unbalance.


Built-in protection is typical of the plus features of Westinghouse General Purpose Turbines . . . features that result in extra reliability, extra safety, and economy in operation. Competent engineering help in application problems and a nationwide maintenance service are as near as your telephone. Westinghouse Electric & Mfg. Co., Box 868, Pittsburgh 30




DUAL PROTECTION—During normal operation the turbine speed is controlled by the centrifugal-weight governor, or a regulator. If for any reason this control should fail, the overspeed trip device takes charge—simultaneously closing the butterfly valve and the governor valve when speed reaches 10 per cent above normal.



SHAFT PROTECTION—to prevent steam leakage and consequent oil contamination resulting from rust-cut carbon gland segments, shaft is sprayed with a generous thickness of high chrome-nickel steel at the two gland zones. Shaft is grooved, undercut and knurled to provide a permanent anchor for the sprayed metal. After spraying, entire shaft is finish-ground.



EXPLOSION PROTECTION—The only possible place a spark can occur in a turbine is on the overspeed trip lever. In applications where the turbine must operate in an explosive atmosphere, a sparkless overspeed trip lever with an insert of a special Westinghouse-developed plastic, Micarta, is used.



ROTOR PROTECTION—to insure smooth operation, the rotor is served its original shape and balance in service. Placed in the Westinghouse-developed machine, the rotor is then with corrosion-resistant paint to insure maintenance of original shape and balance. Particularly important in stand-by or intermittent operation.

EASY TO INSPECT
continually split
to lower half
NO SOFT PACK
bushings have
ment of valve
off . . . minimiz
Governor val
stems are hig

CORROSION AN
tain proportio
curately drille
that holds pro
tions—insures



Westinghouse
PLANTS IN 25 CITIES . . . OFFICES EVERYWHERE

Steam Headquarters

POWER • AUGUST • POWER • AUGUST

Built-in

PROTECTION

STAINLESS STEEL BLADES
AND SHROUDS

CARBON RING GLAND

VENTILATED
BEARING HOUSING

SEALING STEAM SUPPLY
CONNECTION FOR USE IN
CONDENSING SERVICE

RING OILED - BRONZE
BEARING LINED WITH
TIN-BASED BABBITT

VALVE STEM
AND GATE SHAFT

GLAND LEAK-OFF

WATER CONNECTION FOR
COOLING BEARING OIL

STEEL ROTOR DISC NUTS
AND KEYS ON SHAFT

NOZZLES OF CORROSION-
RESISTANT MATERIAL

BALANCED COVER FOR VALVE WITH
CYLINDRICAL STEAM INLET

VALVE LIFT MECHANISM
WITH REMOVABLE COVER



DESIGN FEATURES

EASY TO INSPECT . . . by removing cover of horizontally split casing. All pipe connections are made in lower half of casing.

SOFT PACKING . . . for valve stems. Nickel-iron rings have sufficient clearance for free movement of valve stems. Each stem has intermediate leak-off, minimizes leakage of steam into engine room. Governor valve and cage, butterfly valve and valve stems are highly resistant to corrosion and erosion.

CORROSION AND EROSION-RESISTANT NOZZLES . . . main proportions permanently. Passages are accurately drilled and reamed on a special machine which holds proportions precisely to design specifications—insures highest nozzle efficiency.

POSITIVE LUBRICATION . . . assured by ring-oiled bronze bearings lined with tin-base babbitt. Either bearing may be removed by unbolting bearing cover.

EFFICIENT CARBON GLANDS . . . held around the shaft by stainless steel garter springs, control steam leakage at points where the rotor shaft extends through the casing. A leak-off at each gland minimizes leakage past the outer ring.

EACH TURBINE FACTORY TESTED . . . by a running trial with steam for adjusting governor, setting overspeed trip, checking smoothness of operation, testing glands and steam joints.

J-50447

Steam Headquarters

Westinghouse
PLANTS IN 25 CITIES . . . OFFICES EVERYWHERE

