



Revised 8/1/86

**MATERIAL SAFETY DATA SHEET**

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910, 1200.  
Standard must be consulted for specific requirements.

The product identity on this page meets the OSHA definition of an article and is exempt from the Hazard Communication Standard as to all normally careful uses. Some potential may exist for exposure to dust.

The ingredients in these products are resin-bonded and hazards normally associated with contact to pure dusts of the listed ingredients should not be significant. Abex has listed all of the essential ingredients present in a series of products of this general description. All products identified on this MSDS contain asbestos-free material but will not contain all of the other materials shown. The recommended exposure limits are those for the most hazardous substance in a class of substances. Exact formulation is considered proprietary and confidential. Precise product information will not be disclosed, other than to a health professional in accordance with the regulations, without an approved Secrecy Agreement.

The information herein is believed to be accurate, however, Abex makes no representation or warranty as to its accuracy. This data is furnished gratuitously and independently of any sale of the product, and only for customer investigation and independent verification.

Abex shall in no event be responsible for any damages of whatever nature directly or indirectly resulting from the publication or use of or reliance upon data contained herein. No express or implied warranty of any kind, including warranties of merchantability or fitness for use, with respect to the product or to the data herein is made hereunder.

**IDENTITY (As Used on Label and List)**

931-(66, 83, 162&162A), 987-8, 3027-(73.85&88), 3041-29, ABEX (647GG, 697EE, 685FF, 6009FF, 6000GG, 6008FF, 6014FF, 6011FF), ABB (281GG, 294EE, 282FF, 296GG, 2003FF, 2010FF, 2007FF, 2005FF), COM (371GG, 383EE, 372FF, 395FF, 385GG, 392FF, 3000FF, 397FF) ABEX 6012FF, ABB2008FF, COM398FF, NA27, NA27R, ABEX 6020FF, ABB2015FF, COM3005FF, 3030-67, 1047-47

**SECTION I**

|                                                                                                                        |                                                        |
|------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| <b>Manufacturer's Name:</b> ABEX CORPORATION<br>Friction Products Division                                             | <b>Emergency Telephone Number</b> (703) 662-3842       |
|                                                                                                                        | <b>Telephone Number for Information</b> (703) 662-3871 |
|                                                                                                                        | <b>Date Prepared</b> November 12, 1985                 |
| <b>Address:</b> (Number, Street, City, State, Zip Code)<br>2410 Papermill Road, P.O. Box 3250<br>Winchester, VA. 22601 | <b>Preparer</b> M. K. Leung                            |

**SECTION II - Hazardous Ingredients/Identity Information**

| Hazardous Components<br>(Specific Chemical Identity: Common Name(s)) | OSHA                   | PEL | ACGIH                  | TLV |
|----------------------------------------------------------------------|------------------------|-----|------------------------|-----|
| Glass Fiber                                                          | 10.0 mg/M <sup>3</sup> |     | 10.0 mg/M <sup>3</sup> |     |
| Silica, Silicate, Tripoli, Talc                                      | 0.1 mg/M <sup>3</sup>  |     | 0.1 mg/M <sup>3</sup>  |     |
| Carbon Black, Graphite, Coal, Coke                                   | 2.0 mg/M <sup>3</sup>  |     | 2.0 mg/M <sup>3</sup>  |     |
| Phenolic and Elastomer Compounds                                     | 19.0 mg/M <sup>3</sup> |     | 19.0 mg/M <sup>3</sup> |     |
| Wood Flour and Other Fillers                                         | 1.0 mg/M <sup>3</sup>  |     | 1.0 mg/M <sup>3</sup>  |     |
| Iron, Zinc, Aluminum, Brass and their Oxides                         | 10.0 mg/M <sup>3</sup> |     | 10.0 mg/M <sup>3</sup> |     |

**SECTION III - Physical / Chemical Characteristics**

|                                                                           |    |                                                 |                      |
|---------------------------------------------------------------------------|----|-------------------------------------------------|----------------------|
| <b>Boiling Point</b>                                                      | NA | <b>Specific Gravity (H<sub>2</sub>O = 1)</b>    | 1.5-3.5              |
| <b>Vapor Pressure (mm Hg.)</b>                                            | NA | <b>Melting Point</b>                            | NA                   |
| <b>Vapor Density (Air = 1)</b>                                            | NA | <b>Evaporation Rate<br/>(Butyl Acetate = 1)</b> | 0                    |
| <b>Solubility in Water</b> No                                             |    |                                                 |                      |
| <b>Appearance and Odor</b> Solid, Dark Grey Color, Friction Material Odor |    |                                                 | Warner SBC-25-000007 |

| SECTION IV - Fire and Explosion Hazard Data |                                                                                                                                                                                                                            |                  |         |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|---------|
| Flash Point (Method Used)                   | NA                                                                                                                                                                                                                         | Flammable Limits | LEL UEL |
| Extinguishing Media                         | Water, (Class A, B, or C)                                                                                                                                                                                                  |                  |         |
| Special Fire Fighting Procedures            | Positive pressure self-contained breathing apparatus should be used. Personnel not having suitable respiratory protection should leave the area to prevent significant exposure to toxic combustion gases from any source. |                  |         |
| Unusual Fire and Explosion Hazards          | NK                                                                                                                                                                                                                         |                  |         |

| SECTION V - Reactivity Data           |                                                                |   |                        |
|---------------------------------------|----------------------------------------------------------------|---|------------------------|
| Stability                             | Unstable                                                       |   | Conditions to Avoid NK |
|                                       | Stable                                                         | X |                        |
| Incompatibility (Materials to Avoid)  | NK                                                             |   |                        |
| Hazardous Decomposition or Byproducts | Incomplete combustion will create carbon monoxide and dioxide. |   |                        |
| Hazardous Polymerization              | May Occur                                                      |   | Conditions to Avoid NK |
|                                       | Will Not Occur                                                 | X |                        |

| SECTION VI - Health Hazard Data                                                                                                                                                                                                                                                                                                                                                                          |                 |                       |                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------|-----------------------|
| Route(s) of Entry:                                                                                                                                                                                                                                                                                                                                                                                       | Inhalation? Yes | Skin? Yes             | Ingestion? No         |
| <b>Health Hazards (Acute and Chronic)</b><br>Some persons may be sensitive to cashew resins and develop dermatitis-type problems. Dust of silica, graphite, carbon black, and coal can produce pneumoconiosis and other lung damage. Metal dusts can be irritants of the eyes and upper respiratory system. There is little evidence of chronic industrial poisoning from iron, aluminum, and zinc dust. |                 |                       |                       |
| Carcinogenicity:                                                                                                                                                                                                                                                                                                                                                                                         | NTP?<br>—       | IARC Monographs?<br>— | OSHA Regulated?<br>NO |
| <b>Signs and Symptoms of Exposure</b><br>Cashew resins - skin eruptions similar in appearance to poison ivy. Pneumoconiosis - coughing, wheezing, shortness of breath, impaired pulmonary function. Dusts in eye may cause irritation. Gastrointestinal disturbances possible from ingestion.                                                                                                            |                 |                       |                       |
| <b>Medical Conditions</b><br>Generally Aggravated by Exposure NK                                                                                                                                                                                                                                                                                                                                         |                 |                       |                       |
| <b>Emergency and First Aid Procedures</b><br>Should not be necessary from the handling of this product.                                                                                                                                                                                                                                                                                                  |                 |                       |                       |

Warner SBC-25-000008

| SECTION VII - Precautions for Safe Handling and Use                                                                                                                                                                       |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>Steps to Be Taken in Case Material is Released or Spilled</b><br>Grinding, drilling, milling, etc. can result in the release of airborne dust. Measures as outlined in Section VIII should be followed if this occurs. |  |
| <b>Waste Disposal Method</b><br>Hazardous ingredients: 40 CFR, Part 261, 262 and applicable State and Local regulations.                                                                                                  |  |
| <b>Other Precautions</b><br>Pre-employment screening for allergies and histories of skin sensitivities may be beneficial in determining persons sensitive to cashew materials.                                            |  |

| SECTION VIII - Control Measures                                                                                                                                                                                                                                                                                                                                                                                 |                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| <b>Respiratory Protection (Specify Type)</b> NIOSH approved for pneumoconiosis and dust with TLV not less than 0.05 mg/M <sup>3</sup> .                                                                                                                                                                                                                                                                         |                                                                               |
| Ventilation                                                                                                                                                                                                                                                                                                                                                                                                     | <b>Local Exhaust</b> For dust exposures exceeding TLV.                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Mechanical (General)</b> Not recommended for dust exposures.               |
|                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Special</b> NK                                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Other</b> Barrier creams for persons with skin sensitive to cashew resins. |
| <b>Protective Gloves</b><br>Recommended.                                                                                                                                                                                                                                                                                                                                                                        |                                                                               |
| <b>Eye Protection</b><br>Should not be needed for normal handling of product. Eye protection is good practice where dust is propelled by grinding or drilling activities.                                                                                                                                                                                                                                       |                                                                               |
| <b>Other Protective Clothing or Equipment</b><br>Long sleeved shirts or other protective clothing may be beneficial to prevent skin contact of persons sensitive to cashew resins.                                                                                                                                                                                                                              |                                                                               |
| <b>Work/Hygienic Practices</b><br>Employees should be properly instructed in the use of control measures as indicated above when there is a need for it. If dust from this product is produced, unnecessary exposures should be avoided by using a vacuum in place of dry brooming. Use wet method of cleaning for other surfaces. Proper and adequate personal hygiene should be practiced by exposed workers. |                                                                               |

NA - Not Available

NK - Not Known

\* 720 W &amp; R may contain asbestos backing. For Asbestos MSDS, See Abex MSDS Form #1

Warner SBC-25-000009