FROM (LOCATION) verett, Massachusetts cc: Mr. J.J. McNamara-Everett

DATE March 1, 1971

SUBJECT W. R. GRACE

REFERENCE

TO ~~MR. W. S. CLARK~~
~~ST. LOUIS~~

AF

~~S-326 PF~~

WRG is working with two blends to replace discontinued A-1200's. For coatings, they will use A-6070/10% Xylene and in polysulfide caulks and sealants, a blend of 60% A-5460/40% S-261 is the current choice.

Regarding both these blends, WRG has noticed significant viscosity changes over time with temperatures held constant.

They have requested some information from us:

1. Temperature/viscosity curves on both blends.

2. They would like to know our method of blending A-5460 in liquid A-1221 or S-261 (order of addition) (temperature time, and mixing procedures). This info is to help them in preparing laboratory samples for their own use.

Thanks.

JHG/ims John H. Gannon

P.S. I am expecting WRG to order 10-15 drums of the A-5460/S-261 blend in the near future for plant trials.

(1) Check w/ Kagan on availability of S-261 @ Anniston
(2) Have Mills start on a spec.
(3) Develop blend sheet and get prices approved
(4) Get Surtigen no. and Product Code.
- check listing around S-271 to make sure we dont have one.

0460810

IN-10 REV. 8-64

LEXOLDMON006737