



## Skidmore Corporation

St. Joseph, Michigan

Quality Heating Pumps for over a quarter of a century



Write for  
Bulletin No. 18-A  
on Type UV Pump  
Bulletin No. 21  
on Type CV Pump




### SKIDMORE TYPE UV PUMP


The Skidmore Type UV Condensation Pump, single or duplex unit, is designed for use where returns are too low to permit the operation of horizontal type pumps. Type UV Pump operates very satisfactorily where condensate is to be returned to the boiler or other points, from all types of steam heating systems or process equipment. Type UV Pump consists of vertical pump and motor unit with float and float switch mechanism mounted on cover plate which is bolted to pump type receiver. Capacities 2000 to 40,000 sq ft EDR and discharge pressures from 10 to 75 lbs.

### SKIDMORE TYPE CV PUMP

The Skidmore Vertical Type CV Condensate Pump and receiver is designed for maximum efficiency in returning condensate to the boiler, or other points, from all types of low pressure steam heating systems and process equipment. Type CV Pump requires a minimum of space. The integral pump casing and motor is of cast iron construction, bolted to top of receiver. Pump is bronze fitted throughout, with enclosed centrifugal impeller of special design for hot water. Capacities 500 to 10,000 sq ft. EDR pressures from 10 to 20 lbs.



Write for  
Bulletin No. 14-A  
on Type HS Pump  
Bulletin No. 17  
on Type TM Pump



### SKIDMORE TYPE HS PUMP

The model HS Condensation pump is economically designed to offer maximum efficiency with lower operating cost. The Type HS will operate at high temperature encountered in condensation pump service. The pump can be disassembled without disturbing piping connections. Furnished in either single or duplex type. Pump casing is constructed of heavy close grain cast iron, vertically split, bronze fitted throughout. Capacities 1,000 to 65,000 sq ft EDR, pressures 10 to 75 lbs.

### SKIDMORE TYPE TM PUMP

Type TM pump consists of motor, steel receiver, automatic make-up valve mounted on receiver, water level gage glass mounted on receiver, self-cleaning strainer between pump and receiver, assembled and mounted on steel base. Cast iron base furnished if required. Electric boiler water level controller furnished for mounting on boiler. The Type TM Condensate and make-up water pump is of turbine type designed for boilers up to 250 hp and pressures up to 150 lbs.

Write for Complete Engineering Data

Bulletins on Skidmore Condensate or Vacuum Pumps will be sent on request.

1468

## C. H. Wheeler Manufacturing Co.

Economy Pumps Division

19th & Lehigh, Philadelphia 32, Pa.

For name of nearest distributor, check your phone directory or write to factory in Philadelphia

### WHEELER-ECONOMY HOT WATER CIRCULATING PUMPS

Type SCV—Vertical direct connected centrifugal. 1 in. to 3 in. Up to 500 gpm. 1150 to 3450 rpm. Heads to 225 ft.

Type SCC—Close coupled vertical or horizontal mounted. 1½ in. and 2 in. Up to 100 gpm. 3450 rpm. Heads to 120 ft.

### WHEELER-ECONOMY VACUUM PUMPS

Type VV—Vertical. For operating between 3 and 12 inches vacuum. Discharge pressures to 150 lb sq in. EDR 2500 to 15,000 sq ft. Single and duplex units. Also available in Special Capacities.

Type SVA—Horizontal. For operating between 3 and 12 inches vacuum. Discharge pressures to 150 lb sq in. EDR 20,000 to 100,000 sq ft. Single and duplex units. Also available in Special Capacities.

### WHEELER-ECONOMY RETURN CONDENSATION PUMPS

Type E—1750 rpm. (1450 rpm at 50 cycle current). Quiet operation. Single and duplex units. Direct C.I. radiation or equivalent: 1000 to 65,000 sq ft.

Type MR—Lightweight Pump for low pressure steam heating systems. Capacities to 65,000 sq ft. EDR. Single and Duplex Units.

Type EC—For same or higher pressure than Type E. 3450 rpm. (2880 rpm for 50 cycle current). Direct C.I. radiation or equivalent 1000 to 65,000 sq ft. Single and duplex units.


Types B and C—Horizontal Return Condensation Pumps—Types B multi-stage for pressures to 150 lbs. 1750 rpm. Quiet operation. Direct C.I. radiation or equivalent, 6000 to 65,000 sq ft.

Type U—Vertical Underground. For returns below floor level, etc. No pit required for pump. Low and medium pressure units equipped with single stage pumps of vertical design. For higher pressure units a multi-stage pump of special design is used. Direct C.I. radiation or equivalent 2000 to 50,000 sq ft. Single and duplex units.


Type C multi-stage for pressures to 175 lbs 3600 rpm 60 cycle. Identical to type B except for higher speed operation.

Type S—Condensation Pumps with Steel Receiver. Where steel receiver is satisfactory and low cost is important. Single and duplex units.


Type G—Horizontal Return Condensation Pump—Single suction, single stage for medium and high pressures. 1800 to 3450 rpm.



Type SCV




Type VV



Types E & EC



Type U



Types B & C

1469