

Ventilator, ventilators, 217
control, 218
roof, 217
unit, 540, 812
control, 812
window, 544
Vertical blow unit heater, 533

Vertical openings, 211
sealing of, 211
Vibration machine, 881
Viscous filters, 694
automatic, 695
impingement, 694
Vitiation of air, 115
Volume
control, 635
furnace, 336, 343
specific, 10

W

Wall, walls
heat flow through, 179, 239,
265, 270
heat transfer coefficients, 101,
169, 179
infiltration through, 205
time lag of solar radiation, 265

Warm air
gravity heating system, 415
combination carrying capacity, 421
design procedure, 422
furnace capacity, 369
installation practice, 415
standardized combinations, 418
mechanical heating systems, 425
automatic control, 369, 429
cooling methods, 439
continuous circulation, 439
dampers, 427
design procedure, 428
ducts, 427
fans, 369, 439
filters, 368
furnace, 367
heavy duty, 368
selection, 439
humidification, 373

Warm air (continued)
mechanical (continued)
large systems, 429
registers and grilles, 426
standard combinations, 427,
428
panel heating, 518
radiant heating, 518
radiators, 346

Washer, washers, 709
air, 1, 709

Water
analysis, 874
atmospheric cooling equipment, 709, 719
characteristics, 874
classification, 874
coils, 735, 989
control temperature service, 994
cooled
condenser, 781
corrosion treatment, 873
demand, 977
faucets, 978, 983
fittings, loss, 985
fixtures, 978
fixture units, 978
formed deposits, 873
heater
coal-fired, 989
solar, 985
heating, 888, 988
load, 988
make-up, 733
maximum, main temperature, 712
meters, 983, 984
mineralized, 874
properties of, 88
supply piping, 977, 978, 986,
993
arrangement, 993
services, 977
storage capacity, 986
supply, 977
temperature control, 994
thermodynamic properties of, 36
treating chemicals, 873, 891
well temperatures, 714

Water (continued)
Water vapor, 24, 36, 197
saturation pressure, 36
specific enthalpy, 4
specific volume, 10, 36
surface condensation, 198

Welding, 557

Wet-bulb temperature (see Temperature), 9, 725
Wet return, 8, 443

Wind, winds
forces, 205
due to stack effect, 205
natural draft equipment, 719
selection of, velocity, 226, 252

Window, windows
coefficients of transmission, 196
leakage, 207
solar radiation through, 277
ventilators, 544
Winter
air conditioning system, 601
comfort zone, 130
freezing, equipment, 732
Wound rotor motor, 833
Wrought-iron pipe, 557
Wrought-steel pipe, 557

Y

Year-round air conditioning system, 601

Z

Zone control, 602
Zone of evaporative regulation, 119
Zoning, 602
control, 602, 810
recycling, 603
reheat, 603
volume control, 635

TERMINOLOGY

Glossary of Physical and Heating, Ventilating, Refrigerating and Air Conditioning Terms Used in the Text

Absolute Zero: The zero from which absolute temperature is reckoned. Approximately -273.2°C or -459.8°F .

Absorbent: A sorbent which changes physically or chemically, or both, during the sorption process.

Absorption: The action of a material in extracting one or more substances present in an atmosphere or mixture of gases or liquids; accompanied by physical change chemical change, or both, of the sorbent.

Acceleration: The time rate of change of velocity, i.e., the derivative of velocity with respect to time. In the cgs system the unit of acceleration is the centimeter per (second) (second); in the fps system the unit is the foot per (second) (second), $a = \frac{dv}{dt}$.

Acceleration Due to Gravity: The rate of gain in velocity of a freely falling body, the value of which varies with latitude and elevation. The international gravity standard has the value of 980.665 cm per (sec) (sec) or 32.174 ft per (sec) (sec) which is the actual value of this acceleration at sea level and about 45 deg latitude.

Adiabatic: An adjective descriptive of a process such that no heat is added to, or taken from, a substance or system undergoing the process.

Adsorbent: A sorbent which does not change physically or chemically during the sorption process.

Adsorption: The action, associated with surface adherence, of a material in extracting one or more substances present in an atmosphere or mixture of gases and liquid, unaccompanied by physical or chemical change. Commercial adsorbent materials have enormous internal surfaces.

Aerosol: An assemblage of small particles, solid or liquid, suspended in air. The diameters of the particles may vary from 100 microns down to 0.01 micron or less, e.g., dust, fog, smoke.

Air Cleaner: A device designed for the purpose of removing airborne impurities such as dusts, gases, vapors, fumes and smokes. (Air cleaners include air washers, air filters, electrostatic precipitators and charcoal filters.)

Air Conditioning: The simultaneous control of all, or at least the first three, of those factors affecting both the physical and chemical conditions of the atmosphere within any structure. These factors include temperature, humidity, motion, distribution, dust, bacteria, odors and toxic gases, most of which affect in greater or lesser degree human health or comfort. (See *Comfort Air Conditioning*.)

Air, Dry: In psychrometry, air unmixed with, or containing no, water vapor.

Air, Saturated: A mixture of dry air and saturated water vapor, all at the same dry-bulb temperature.

Air, Standard: Air with a density of 0.075 lb per cu ft and an absolute viscosity of 1.22×10^{-4} lb mass per (ft) (sec). This is substantially equivalent to dry air at 70 F and 29.92 in. (Hg) barometer.

Air Washer: An enclosure in which air is drawn or forced through a spray of water in order to cleanse, humidify, or dehumidify the air.

Anemometer: An instrument for measuring the velocity of a fluid.

Aspect Ratio: In air distribution outlets, the ratio of the length of the core of a grille, face or register to the width.

In rectangular ducts, the ratio of the width to the depth.

Atmospheric Pressure: The pressure due to the weight of the atmosphere. It is the pressure indicated by a barometer. *Standard Atmospheric Pressure* or *Standard Atmosphere* is the pressure of 76 cm of mercury having a density of 13.5951 grams per cu cm, under standard gravity of 980.665 cm per (sec) (sec). It is equivalent to 14.696 lb psi or 29.921 in. of mercury at 32 F.

Baffle: A surface used for deflecting fluids, usually in the form of a plate or wall.