V 7063

DOW CHEMICAL U.S.A.

50983

TEXAS DIVISION
FREEPORT, TEXAS 77541

ENVIRONMENTAL HEALTH REPORT

AIRBORNE ASBESTOS
CELL SERVICES, BUILDINGS
A-1024 AND A-1030

FILE NO. A10-671
DATE June 23, 1975
AUTHOR H. N. Edwards

CHECKED R. L. Daniel
DATE June 25, 1975

Summary

Asbestos levels in the A-1030 area reach a level of 5.6 fibers/cc while mixing asbestos. The workman is not being overexposed for an eight-hour time-weighted average or with a peak exposure. He also wears proper protective clothing and approved respirator.

Since there is a potential for asbestos exposure we recommend the following

(1) Good housekeeping, (2) job rotation, (3) training program and (4) a continued effort to reduce levels.

We also recommend regular re-evaluations.

ST0003091

DOW CONFIDENTIAL

PLAINTIFF'S EXHIBIT
DOW-2963

Distribution

N. E. Eberspacher A1003
R. E. Flake B-101
W. H. Fletcher B101
O. F. Schumm B101
J. R. Taylor A1003
J. A. Vanwestenburg A606
File

(2) H. R. Hoyle 1803 Bldg.-Midland
Marlene Swank 1803 Bldg.-Midland
*F. D. Axe - Pittsburg
*C. E. Caldwell - OCD
*C. E. Halphen - Plaquemine
*R. R. Langner 607 Bldg.-Midland
*C.L. Sercu - Ohio



INTRODUCTION

The Occupational Safety and Health Act (OSHA) requires that occupational exposure to airborne asbestos dust be controlled so that no worker is exposed to more than 5.0 asbestos fibers per cubic centimeters of air based on a count of fibers greater than 5 micrometers in length. These are determined by a time-weighted average (TWA) exposure for an eight-hour work day, and no peak concentrations of asbestos more than 10.0 fibers per cubic centimeter as determined by a minimum sampling time of 15 minutes. This survey was made at Cell Services on June 3, 1975.

METHODOLOGY

The dry storage area for asbestos is A1024 (Fig. 1). This area remains hot and dry to store both anodes and the dry asbestos. No one is allowed in this area without proper respiratory equipment.

The mixing area is A1030. This is a totally enclosed area and no one is allowed within this building without proper protective equipment, including disposable coveralls, head covering and approved respirator.

The mixing operator enters the building, closes the door, removes the asbestos from between area 8-9 (Fig. 2), wets them before opening, and dumps them into conveyor. The asbestos is then mixed and pumped into the vat within another area.

Airborne asbestos samples were collected using the Micronair II permissible air sampling pump (Bendix Environmental Science Division, Baltimore, Maryland). The fibers were collected by pulling air through a Millipore filter (AAWG04700) using an open face filter holder. Flow rates for the pumps were calibrated at 1600 cubic centimeters per minute and sample times varied as shown in Table I.

All analyses were done by Sylvia Markham of B1218 using the following procedures:

> Four marked squares are cut from a filter about halfway from the edge to the center. This section is then placed on a drop of clearing solution[1] and placed on a microscope slide. The sample is covered with a coverslip and allowed to clear (about 15 minutes). The sample count is made on a Reichert Zetopan optical microscope using Normarski interference contrast at 500 magnification. Counts are made for particles greater than 5 microns.

ST0003092

RESULTS

The results of analyses are shown in Table I. The dry storage area shows some fibers within the near vicinity of the asbestos bags. Since some loose asbestos was evident on the floor, this could account for the results.

The workman received for a short period of time (17 min) 5.6 fibers/cc. Since he was wearing proper protective clothing and equipment, this is only a potential exposure.

DISCUSSION

The new mixing area A1030 (Fig. 2) seems to comply with 1910.93a of the Federal Registar(Enclosure 1). Section (c) states "Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection shall be used to meet exposure limits." This new area certainly is well contained and is isolating the asbestos.

CONCLUSIONS

Workmen handling asbestos in this manner are probably not being overexposed, but do have a potential for overexposure.

RECOMMENDATIONS

1. Good housekeeping - " All external surfaces in any place of employment shall be maintained free of accumulation of asbestos fibers if, with their dispersion, there would be an excessive concentration."
2. Job rotation - the task of mixing the asbestos should be rotated within each day rather than day to day rotation.
3. Training program - a continuous training effort should be made to inform the workmen of importance of proper asbestos handling, the extreme hazards of overexposure and proper care and use of their protective equipment.
4. Continued effort to reduce levels - the continued efforts should be made to find engineering designs to reduce the asbestos levels. The progress that you have made is commendable but your efforts should be continued.

[1] Clearing Solution: 0.1 g/ml of clean Millipore filter paper in 1:1 diethyloxalate: dimethyl phthalate.

ST0003093

RECOMMENDATIONS (continued)

5. This survey should be repeated within six months and sooner if work conditions or job procedures change.

S10003094

EHS
HNE/bbs
6-23-75

TABLE I
AIRBORNE ASBESTOS
CELL SERVICES STORAGE AND MIXING AREA
JUNE 3, 1975

LOCATION	SAMPLE TIME	VOLUME OF AIR SAMPLED	FIBERS GREATER THAN 5 MICROMETERS/CUBIC CENTIMETER
Fig. 1 #1	30 min.	48 liters	1.1
#2	30 min.	48 liters	2.2
#3	30 min.	48 liters	1.6
#4	30 min.	48 liters	0.5
#5	30 min.	48 liters	0.6
#6	30 min.	48 liters	0.6
Fig. 2 #7	30 min.	48 liters	1.8
#8	30 min.	48 liters	2.2
#9	30 min.	48 liters	3.6
#7A	20 min.	32 liters	4.3
#8A	20 min.	32 liters	2.7
* #9P	17 min.	27.2 liters	5.6

* W. A. Williams 134395 Vat Operator Class 1, was wearing proper protective equipment and respirator.

ST0003095



Fig. 2 - A-1030

ST0003096



Fig. 1 - A 1024

ST0003097

TABLE G-2

Material	8-hour time weighted average	Acceptable ceiling concentration	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift.	
			Concentration	Maximum duration
Benzene (Z37.4-1969)	10 p.p.m	25 p.p.m	50 p.p.m	10 minutes.
Beryllium and beryllium compounds (Z37.29-1970).	2 μg./M³	5 μg./M³	25 μg./M³	30 minutes.
Cadmium fume (Z37.5-1970)	0.1 mg./M³	3 mg./M³		
Cadmium dust (Z37.5-1970)	0.2 mg./M³	0.6 mg./M³		
Carbon disulfide (Z37.3-1968)	20 p.p.m	30 p.p.m	100 p.p.m	Do.
Carbon tetrachloride (Z37.17-1967)	10 p.p.m	25 p.p.m	200 p.p.m	5 minutes in any 4 hours.
Ethylene dibromide (Z37.31-1970)	20 p.p.m	30 p.p.m	50 p.p.m	5 minutes.
Ethylene dichloride (Z37.21-1969)	50 p.p.m	100 p.p.m	200 p.p.m	5 minutes in any 3 hours.
Formaldehyde (Z37.16-1967)	3 p.p.m	5 p.p.m	10 p.p.m	30 minutes.
Hydrogen fluoride (Z37.28-1969)	do			
Fluoride as dust (Z37.28-1969)	2.5 mg./M³			
Lead and its inorganic compounds (Z37.11-1969).	0.2 mg./M³			
Methyl chloride (Z37.18-1969)	100 p.p.m	200 p.p.m	300 p.p.m	5 minutes in any 3 hours.
Methylene Chloride (Z37.3-1968)	500 p.p.m	1,000 p.p.m	2,000 p.p.m	5 minutes in any 2 hours.
Organo (alkyl) mercury (Z37.30-1969)	0.01 mg./M³	0.04 mg./M³		
Styrene (Z37.15-1969)	100 p.p.m	200 p.p.m	600 p.p.m	5 minutes in any 3 hours.
Trichloroethylene (Z37.19-1967)	do	do	300 p.p.m	5 minutes in any 2 hours.
Tetrachloroethylene (Z37.22-1967)	do	do	do	5 minutes in any 3 hours.
Toluene (Z37.12-1967)	200 p.p.m	300 p.p.m	500 p.p.m	10 minutes.
Hydrogen sulfide (Z37.2-1966)		20 p.p.m	50 p.p.m	10 minutes once only if no other measurable exposure occurs.
Mercury (Z37.8-1971)		1 mg./10M³		
Chromic acid and chromates (Z37.7-1971)		do		

TABLE G-3—MINERAL DUSTS

Substance	Mppcf	Mg/M³
Silica:		
Crystalline:		
Quartz (respirable)	250	10mg/M³ ÷ (%SiO₂+2)
Quartz (total dust)	%SiO₂+5	%SiO₂+2 30mg/M³
Cristobalite: Use ½ the value calculated from the count or mass formulae for quartz.		%SiO₂+2
Tridymite: Use ½ the value calculated from the formulae for quartz.		
Amorphous, including natural diatomaceous earth	20	80mg/M³ ÷ %SiO₂
Silicates (less than 1% crystalline silica):		
Mica	20	
Soapstone	20	
Talc (non-asbestos form)	20	
Talc (fibrous). Use asbestos limit		
Tremolite (see talc, fibrous)		
Portland cement	50	
Graphite (natural)	15	
Coal dust (respirable fraction less than 5% SiO₂)		2.4mg/M³ or
For more than 5% SiO₂		10mg/M³ ÷ (%SiO₂+2)
Inert or Nuisance Dust:		
Respirable fraction	15	5mg/M³
Total dust	50	15mg/M³

NOTE: Conversion factors—
mppcf×35.3=million particles per cubic meter
=particles per c.c.

* Millions of particles per cubic foot of air, based on impinger samples counted by light-field technics.

† The percentage of crystalline silica in the formula is the amount determined from air-borne samples, except in those instances in which other methods have been shown to be applicable.

‡ As determined by the membrane filter method at 430X phase contrast magnification.

§ Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size selector with the following characteristics:

Aerodynamic diameter (unit density spheres)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of an AEC instrument. If the respirable fraction of coal dust is determined with a MRE the figure corresponding to that of 2.4 M/g/M³ in the table for coal dust is 4.5 M/g/M³.

§ 1910.93a Asbestos.

(a) *Definitions.* For the purpose of this section, (1) "Asbestos" includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos fibers longer than 5 micrometers.

(b) *Permissible exposure to airborne concentrations of asbestos fibers*—(1) *Standard effective July 7, 1972.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(2) *Standard effective July 1, 1976.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed two fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(3) *Ceiling concentration.* No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(c) *Methods of compliance*—(1) *Engineering methods.* (i) *Engineering controls.* Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection, shall be used to meet the exposure limits prescribed in paragraph (b) of this section.

(ii) *Local exhaust ventilation.* (a) Local exhaust ventilation and dust collection systems shall be designed, constructed, installed, and maintained in accordance with the American National Standard Fundamentals Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2-1971, which is incorporated by reference herein.

(b) See § 1910.6 concerning the availability of ANSI Z9.2-1971, and the maintenance of a historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(iii) *Particular tools.* All hand-operated and power-operated tools which may produce or release asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, such as, but not limited to, saws, scorers, abrasive wheels, and drills, shall be provided with local exhaust ventilation systems in accordance with subdivision (ii) of this subparagraph.

(2) *Work practices*—(i) *Wet methods.* Insofar as practicable, asbestos shall be handled, mixed, applied, removed, cut, scored, or otherwise worked in a wet state sufficient to prevent the emission of airborne fibers in excess of the exposure limits prescribed in paragraph (b) of this section, unless the usefulness of the product would be diminished thereby.

(ii) *Particular products and operations.* No asbestos cement, mortar, coating, grout, plaster, or similar material containing asbestos shall be removed from bags, cartons, or other containers in which they are shipped, without being either wetted, or enclosed, or ventilated so as to prevent effectively the release of airborne asbestos fibers in excess of the limits prescribed in paragraph (b) of this section.

(iii) *Spraying, demolition, or removal.* Employees engaged in the spraying of asbestos, the removal, or demolition of pipes, structures, or equipment covered or insulated with asbestos, and in the removal or demolition of asbestos insulation or coverings shall be provided with respiratory equipment in accordance with paragraph (d)(2)(iii) of this section and with special clothing in accordance with paragraph (d)(3) of this section.

(d) *Personal protective equipment*—(1) Compliance with the exposure limits prescribed by paragraph (b) of this section may not be achieved by the use of respirators or shift rotation of employees, except:

(i) During the time period necessary to install the engineering controls and to institute the work practices required by paragraph (c) of this section;

(ii) In work situations in which the methods prescribed in paragraph (c) of

ST0003098

ENCLOSURE (1)

this section are either technically not feasible or feasible to an extent insufficient to reduce the airborne concentrations of asbestos fibers below the limits prescribed by paragraph (b) of this section; or

(iii) In emergencies.

(iv) Where both respirators and personnel rotation are allowed by subdivisions (i), (ii), or (iii) of this subparagraph, and both are practicable, personnel rotation shall be preferred and used.

(2) Where a respirator is permitted by subparagraph (1) of this paragraph, it shall be selected from among those approved by the Bureau of Mines, Department of the Interior, or the National Institute for Occupational Safety and Health, Department of Health, Education, and Welfare, under the provisions of 30 CFR Part 11 (37 F.R. 6244, Mar. 25, 1972), and shall be used in accordance with subdivisions (i), (ii), (iii), and (iv) of this subparagraph.

(i) *Air purifying respirators.* A reusable or single use air purifying respirator, or a respirator described in subdivision (ii) or (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed no more than 10 times those limits.

(ii) *Powered air purifying respirators.* A full facepiece powered air purifying respirator, or a powered air purifying respirator, or a respirator described in subdivision (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average concentrations of asbestos fibers are reasonably expected to exceed 10 times, but not 100 times, those limits.

(iii) *Type "C" supplied-air respirators, continuous flow or pressure-demand class.* A type "C" continuous flow or pressure-demand, supplied-air respirator shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed 100 times those limits.

(iv) *Establishment of a respirator program.* (a) The employer shall establish a respirator program in accordance with the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z88.2–1969, which is incorporated by reference herein.

b. See § 1910.6 concerning the availability of ANSI Z88.2–1969 and the maintenance of an historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(c) No employee shall be assigned to tasks requiring the use of respirators if, based upon his most recent examination, an examining physician determines that the employee will be unable to function normally wearing a respirator, or that the safety or health of the employee or other employees will be impaired by his use of a respirator. Such employee shall be rotated to another job or given the opportunity to transfer to a different position whose duties he is able to perform with the same employer, in the same geographical area and with the same seniority, status, and rate of pay he had just prior to such transfer, if such a different position is available.

(3) Special clothing: The employer shall provide, and require the use of, special clothing, such as coveralls or similar whole body clothing, head coverings, gloves, and foot coverings for any employee exposed to airborne concentrations of asbestos fibers, which exceed the ceiling level prescribed in paragraph (b) of this section.

(4) Change rooms: (i) At any fixed place of employment exposed to airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, the employer shall provide change rooms for employees working regularly at the place.

(ii) Clothes lockers: The employer shall provide two separate lockers or containers for each employee, so separated or isolated as to prevent contamination of the employee's street clothes from his work clothes.

(iii) Laundering: (a) Laundering of asbestos contaminated clothing shall be done so as to prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(b) Any employer who gives asbestos-contaminated clothing to another person for laundering shall inform such person of the requirement in (a) of this subdivision to effectively prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(c) Contaminated clothing shall be transported in sealed impermeable bags, or other closed, impermeable containers, and labeled in accordance with paragraph (g) of this section.

(e) *Method of measurement.* All determinations of airborne concentrations of asbestos fibers shall be made by the membrane filter method at 400–450 × (magnification) (4 millimeter objective) with phase contrast illumination.

(f) *Monitoring*—(1) *Initial determinations.* Within 6 months of the publication of this section, every employer shall cause every place of employment where asbestos fibers are released to be monitored in such a way as to determine whether every employee's exposure to asbestos fibers is below the limits prescribed in paragraph (b) of this section. If the limits are exceeded, the employer shall immediately undertake a compliance program in accordance with paragraph (c) of this section.

(2) *Personal monitoring*—(i) Samples shall be collected from within the breathing zone of the employees, on membrane filters of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) *Environmental monitoring*—(i) Samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) *Sampling frequency and patterns.* After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposures to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) *Employee observation of monitoring.* Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records thereof.

(g) *Caution signs and labels.* (1) *Caution signs.* (i) *Posting.* Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches to areas containing excessive concentrations of airborne asbestos fibers.

(ii) *Sign specifications.* The warning signs required by subdivision (i) of this subparagraph shall conform to the requirements of 20" x 14" vertical format signs specified in § 1910.145(d)(4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

ST0003099

Legend	Notation
Asbestos	1" Sans Serif, Gothic or Block.
Dust Hazard	¾" Sans Serif, Gothic or Block.
Avoid Breathing Dust	¼" Gothic.
Wear Assigned Protective Equipment.	¼" Gothic.
Do Not Remain In Area Unless Your Work Requires It.	¼" Gothic.
Breathing Asbestos Dust May Be Hazardous To Your Health.	14 point Gothic.

Spacing between lines shall be at least equal to the height of the upper of any two lines.

(2) *Caution labels*—(i) *Labeling.* Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) *Label specifications.* The caution labels required by subdivision (i) of this subparagraph shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

CAUTION

Contains Asbestos Fibers

Avoid Creating Dust

Breathing Asbestos Dust May Cause Serious Bodily Harm

(h) *Housekeeping*—(1) *Cleaning.* All external surfaces in any place of employment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) *Waste disposal.* Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(i) *Recordkeeping*—(1) *Exposure records.* Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 3 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National Institute for Occupational Safety and Health, and to authorized representatives of either.

(2) *Employee access.* Every employee and former employee shall have reasonable access to any record required to be maintained by subparagraph (1) of this paragraph, which indicates the employee's own exposure to asbestos fibers.

(3) *Employee notification.* Any employee found to have been exposed at any time to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall also be timely notified of the corrective action being taken.

(j) *Medical examinations*—(1) *General.* The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) *Preplacement.* The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination, which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(3) *Annual examinations.* On or before January 31, 1973, and at least annually thereafter, every employer shall provide, or make available, comprehensive medical examinations to each of his employees engaged in occupations exposed to airborne concentrations of asbestos fibers. Such annual examination shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(4) *Termination of employment.* The employer shall provide, or make available, within 30 calendar days before or after the termination of employment of any employee engaged in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(5) *Recent examinations.* No medical examination is required of any employee, if adequate records show that the employee has been examined in accordance with this paragraph within the past 1-year period.

(6) *Medical records*—(i) *Maintenance.* Employers of employees examined pursuant to this paragraph shall cause to be maintained complete and accurate records of all such medical examinations. Records shall be retained by employers for at least 20 years.

(ii) *Access.* The contents of the records of the medical examinations required by this paragraph shall be made available, for inspection and copying, to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of NIOSH, to authorized physicians and medical consultants of either of them, and, upon the request of an employee or former employee, to his physician. Any physician who conducts a medical examination required by this paragraph shall furnish to the employer of the examined employee all the information specifically required by this paragraph, and any other medical information related to occupational exposure to asbestos fibers.

§ 1910.94 *Ventilation.*

(a) *Abrasive blasting*—(1) *Definitions applicable to this paragraph.*—(i) *Abrasive.* A solid substance used in an abrasive blasting operation.

(ii) *Abrasive-blasting respirator.* A continuous flow air-line respirator constructed so that it will cover the wearer's head, neck, and shoulders to protect him from rebounding abrasive.

(iii) *Blast cleaning barrel.* A complete enclosure which rotates on an axis, or which has an internal moving tread to tumble the parts, in order to expose various surfaces of the parts to the action of an automatic blast spray.

(iv) *Blast cleaning room.* A complete enclosure in which blasting operations are performed and where the operator works inside of the room to operate the blasting nozzle and direct the flow of the abrasive material.

(v) *Blasting cabinet.* An enclosure where the operator stands outside and operates the blasting nozzle through an opening or openings in the enclosure.

(vi) *Clean air.* Air of such purity that it will not cause harm or discomfort to an individual if it is inhaled for extended periods of time.

(vii) *Dust collector.* A device or combination of devices for separating dust from the air handled by an exhaust ventilation system.

(viii) *Exhaust ventilation system.* A system for removing contaminated air from a space, comprising two or more of the following elements (a) enclosure or hood, (b) duct work, (c) dust collecting equipment, (d) exhauster, and (e) discharge stack.

(ix) *Particulate-filter respirator.* An air purifying respirator, commonly referred to as a dust or a fume respirator, which removes most of the dust or fume from the air passing through the device.

(x) *Respirable dust.* Airborne dust in sizes capable of passing through the upper respiratory system to reach the lower lung passages.

(xi) *Rotary blast cleaning table.* An enclosure where the pieces to be cleaned are positioned on a rotating table and are passed automatically through a series of blast sprays.

(xii) *Abrasive blasting.* The forcible application of an abrasive to a surface by pneumatic pressure, hydraulic pressure, or centrifugal force.

(2) *Dust hazards from abrasive blasting.* (i) Abrasives and the surface coatings on the materials blasted are shattered and pulverized during blasting