

NATURAL SLAG, LUMP AND
ASBESTOS FIBERS, UNDER

CAUTION: DO NOT BREATHE LARGE QUANTITIES OF SPRAY MISTS. SEE
SPDS A-20.
FURNISHED BY: 

1. **Contracting & Supply Co.**, 120 N Lime St, Lancaster, Pa
 ORDER FROM SUPPLIER AS
 For 542510, limit is
 For 542510, limit is

CHARACTERISTICS - (54251AP) (800 g./100 g.) covered asbestos fiber free from adulterants such as alk., silic. and heavy wool. Material contains an inorganic binder which when mixed with water makes it suitable for spraying. It provides good insulation for temperatures up to 700 F. (316 C.) incl. an insulating layer the same as 54251AP except applicable for insulation for temperatures over 700 to 1350 F. (377 - 732 C.) incl.

APPLICATION - (54251AP) Gas turbine sprayed insulation for temperatures to 700 F. incl.

(54251A2) Gas turbine sprayed insulation for temperatures over 700 to 1150 F.

Issued by Corporate Standards, R&D Center, Pch 35, Pa.
Printed in U.S.A.

Issued by Corporate Standards, R&D Center, Pch 35, Pa
in U.S.A.

Printed in U.S.A.

Numbering Co. B112

PLAINTIFF'S
EXHIBIT
1011-83

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

CONFIDENTIAL

THEY DO NOT HAVE ANY OTHER INFORMATION TO REPORT.