

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OSHA No. 44-R1387

MATERIAL SAFETY DATA SHEET

Handwritten: P.S. 239

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I	
MANUFACTURER'S NAME Rogers Corporation	EMERGENCY TELEPHONE NO. 203-774-9605
ADDRESS (Number, Street, City, State, and ZIP Code) Rogers, Conn. 06263	
CHEMICAL NAME AND SYNONYMS N/A	TRADE NAME AND SYNONYMS GP/Duroid 3102
CHEMICAL FAMILY N/A	FORMULA N/A

SECTION II - HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Asbestos fiber (bound)				73	*
*No ACGIH limit on bound asbestos					

SECTION III - PHYSICAL DATA			
BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	1.50
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT. VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____=1)	N/A
SOLUBILITY IN WATER	negligible		
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A
EXTINGUISHING MEDIA		Water or Dry Chemical	
SPECIAL FIRE FIGHTING PROCEDURES		none	
UNUSUAL FIRE AND EXPLOSION HAZARDS		none	