

FILE NAME: Eagle-Picher (EP)

DATE: 1932


DOC#: EP005

DOCUMENT DESCRIPTION: Report of Dust Investigation of the
Rock Wool Plant in Joplin, MO

GENERAL SERVICES ADMINISTRATION
National Archives and Records Service

To all to whom these presents shall come, Greeting:

By virtue of the authority vested in me by the Administrator of General Services, I certify on his behalf, under the seal of the National Archives of the United States, that the attached reproduction(s) is a true and correct copy of documents in his custody.



SIGNATURE <i>Janet L. Hargett</i>	
NAME Janet L. Hargett	DATE 10-3-84
TITLE Chief, General Branch	
NAME AND ADDRESS OF DEPOSITORY Civil Archives Division The National Archives Washington, D. C. 20540 20409	

GSA FORM APR 68 6791A

DEPARTMENT OF COMMERCE

BUREAU OF MINES

Nº 81384

1932

U. S. GOVERNMENT PRINTING OFFICE: 1931

REPORT OF DUST INVESTIGATION OF THE
EAGLE PICHER ROCK WOOL PLANT
at
JOPLIN, MISSOURI

In September, 1931, at the request of the Safety Engineer of the Eagle Picher Mining and Smelting Company, an inspection was made of the company's rock wool plant at Joplin, Missouri. This plant is operated in connection with a lead smelter and the product is made from by-products of lead smelting. Inasmuch as the rock wool plant is only operated when there is a demand for the product, considerable delay was encountered in assembling and collecting all data on the process. It was desired to obtain information on the dust, its chemical analysis, and to examine the older men employed at the plant in order to draw conclusions as to possible harmfulness of the dust.

Rock Wool. Rock Wool is made from slag which is heated to a molten liquid and is blown out of a small orifice at considerable pressure into the stream, breaking the molten liquid into very fine hairlike particles. This is blown into a large room and after collecting in quantities it is shoveled into containers for transferring to another building for fabricating. The material is made into sheets, bricks, and is combined with asbestos and used for the purpose of insulating buildings, furnaces, etc. In both the buildings in which the furnace and the fabricating rooms were located, large amounts of dust were detected in the air.

Dust Count. Atmospheric samples were taken in the mixing room, fabricating department, granulator and furnace rooms. The sample in the furnace room shows 25,000,000 particles under 10 microns; in the mixing room No. 2 samples shows 23,000,000 particles; No. 1 sample 10,000,000 particles; the fabricating room shows 1,000,000 particles; and the granulator 4,000,000,000 particles. all under 10 microns. Two of these samples were forwarded to Pittsburgh, Pennsylvania, for analysis (furnace room and mixing room No. 2) and the figures given above are the figures obtained at Pittsburgh. Our own figures show a much higher count. It is possible that some of the particles have gone into solution.

Chemical Analysis. Samples of the rock wool were sent to Pittsburgh to Mr. W. A. Selvig for chemical analysis and the analyses are as follows:

#1	PARTIAL ANALYSIS	Per cent
Lead, Pb	- - - - -	1.6
Silica, SiO ₂	- - - - -	34.6
Aluminum oxide, Al ₂ O ₃	- - - - -	6.3
Ferric Oxide, Fe ₂ O ₃	- - - - -	34.4
Calcium oxide, CaO	- - - - -	13.3

#2		
Lead, Pb	- - - - -	0.5
Silica, SiO ₂	- - - - -	40.8
Aluminum oxide Al ₂ O ₃	- - - - -	5.9
Ferric oxide Fe ₂ O ₃	- - - - -	31.6
Calcium oxide CaO	- - - - -	13.3

#3		
Lead, Pb	- - - - -	0.7
Silica, SiO ₂	- - - - -	42.0
Aluminum oxide, Al ₂ O ₃	- - - - -	6.0
Ferric oxide, Fe ₂ O ₃	- - - - -	29.2
Calcium oxide, CaO	- - - - -	12.0

The concluding statement of Mr. Salvig's report is as follows:

"As mineral wool is a slag and has been thoroughly fused it may be quite irritating if breathed into the throat and lungs in the form of dust."

Physical examinations. On January 6, 1932, four of the employees working at the plant were examined at the clinic to determine whether or not they show evidence of lung involvement. Three out of the four men examined show a decidedly more fibrosis than normal, and one of the three shows an old tuberculosis. The other man was negative. The histories of the men show that they have not been employed steadily in this plant, but they have been engaged in this work for periods ranging from 9 months to 1½ years, probably at about half time. The man that shows no thickening in the bronchial tubes is the foreman who is probably exposed to the minimum amount of dust.

Conclusions drawn. Based on the chemical analysis, quantity of dust, and evidence of such peribronchial thickening in the men who have been exposed, according to the histories, only a relatively short period of time to the dust, it is very likely that the dust is harmful if breathed over a relatively long period of time. This is particularly true in the mixing room where it is stated by the employees that rock wool is mixed with asbestos in various mixtures ranging from 10 to 75 per cent. This is a particularly dusty place, and it is now known definitely that asbestos dust is one of the most dangerous dusts to which man is exposed. With the combination of asbestos and a fused silica dust, known to be irritating to the lungs, it is reasonable to

conclude that the man will get extensive fibrotic changes in a relatively short period of time. This is particularly true where the rock wool is mixed with asbestos. A study of the X-ray pictures of these men fails to reveal any silicosis at the present time, but to produce a decidedly more fibrosis than normal condition in the mines in the Picher field, the group shows an average working time of six years; in other words, apparently these men have contracted the same amount of fibrosis in 12 months or less that occurs in the mines of the Picher field in approximately six years. Assuming this to be correct, the evidence, while not complete, would lead to the conclusion that the dust encountered by these men is more dangerous and will produce lung involvement in a very much shorter period of time than the dust which is encountered in the Picher mines.

Dust Control. Machines should be introduced to control the amount of dust produced at this plant. In the furnace room, where the wool is blown into the room, a method of sucking the dust out of the room or an upward system of ventilation should be installed. In the fabricating room, it should be as open as possible, and a definite dust-controlling system installed. In the mixing room, it is suggested that a machine be installed to do this mixing, sacking, etc., similar to that used by cement industries, and it will not be necessary for the two men to be in the room. These machines are in common use and could be used here with economical results.