

MAY, 1954
Supersedes Issue July, 1953

Navy Control

BULLETIN
6900 A
PRICE LIST

A-c and D-c Brakes For Shipboard Service

Navy A Service

Bulletin 503 — D-c Magnet Operated — Type NM											
Brake Size	Max. Torque Ratings Lbs. Ft. Shunt-Wound		Prices								
			Brake with Standard Wheel*			Add for Special Wheel	Omission of Wheel †	Add for Bulkhead or Ceiling Mounting of Open Type (Horizontal Shaft)	Complete Set of Spare (Unboxed) Includes Navy Packaging	Master Plan	Ship Plan
	Navy A		Open Type	Drip- Proof O	Spray- tight Δ						
	Con- tinuous	Inter- mittent									
8	80	80	\$ 689.	\$ 784.	\$ 959.	\$ 49.	\$ 92.	\$ 45.	\$ 104.	\$ 213.	\$ 213.
10	135	180	873.	1028.	1336.	58.	115.	49.	151.	213.	213.
14	350.	470	1234.	1465.	1734.	73.	170.	49.	211.	213.	213.
18	600	800	1500.	1810.	2222.	82.	241.	67.	315.	213.	213.
21	1200	1600	2517.	2907.	3362.	96.	380.	67.	398.	213.	213.

Bulletin
6902

Bulletin 508 — A-c Torque Motor Operated — Type NTM — 550 Volts A-c Maximum											
Brake Size (Wheel Diam. Ins.)	Max. Torque Ratings in Lbs. Ft. at 50% Voltage		Prices								
			Brake with Standard Wheel*			Add for Special Wheel	Omission of Wheel †	Add for Bulkhead or Ceiling Mounting of Open Type (Horizontal Shaft)	Complete Set of Spares (Unboxed) (Includes Navy Packaging)	Master Plan	Ship Plan
	Open Type	Drip- Proof O	Spray- tight Δ								
10-	125	160	\$ 1268.	\$ 1160.	\$ 1340.	\$ 62.	\$ 83.	\$ 102.	\$ 102.	\$ 213.	\$ 213.
13	325	400	1819.	2069.	2369.	69.	158.	122.	136.	213.	213.
16	800	800	2435.	2845.	2973.	85.	229.	208.	178.	213.	213.
20	1500	1500	3513.	3827.	4303.	95.	414.	233.	242.	213.	213.
25	2400	3200	5804.	6214.	-----	107.	750.	276.	375.	213.	213.

Manual Across-the-Line Starter With Thermal Overload Protection

Navy A Service

Max. H-p		Voltage	Controller				Complete Set of Spares (Unboxed) Includes Navy Packaging		Master Plan	Ship Plan
1 Phase	3 Phase		Drip Proof		Spraytight		Price	Net Wt. Spares Unboxed		
			Price	Net Wt.	Price	Net Wt.				
A-C CONTROLLER WITH LOW VOLTAGE RELEASE EFFECT										
1½	3	110	\$ 65.	9½	---	---	\$ 10.25	2	No Charge	\$ 213.
3	5	220	65.	9½	---	---	10.25	2	No Charge	213.
5	7½	440	65.	9½	---	---	10.25	2	No Charge	213.
D-C CONTROLLER WITH LOW VOLTAGE RELEASE EFFECT										
1½	---	115	65.	9½	---	---	8.40	2	No Charge	213.
1½	---	230	65.	9½	---	---	8.40	2	No Charge	213.

Bulletin
6922

D-c Two Pole Magnetic Contactors

Size	Max. Amps. *	Contactor Open Type		Drip Proof Enclosure Only For Non-Reversing Contactor		Complete Set of Spares (Unboxed) Includes Navy Packaging		Mechanical Interlock	Master Plan	Ship Plan
		Price	Net Wt. Lbs.	Price	Net Wt. Lbs.	Price	Net Wt. Lbs.			
0	15	\$ 112.	5½	\$ 108.	15	\$ 27.	2	\$ 15.	No Charge	\$ 213.
1	25	132.	5½	108.	15	27.	2	15.		213.
2	50	162.	12¼	122.	15	34.	3	15.		213.
3	100	238.	20	136.	25	43.	4	15.		213.
4	150	284.	31¼	---	---	72.	6	15.		213.

Bulletin
6937

End of
Bulletin
6937

- † Do not use as selling price of separate wheel.
- * Dimensions of Standard Wheels are listed on page 2, Bulletin 6902.
- Δ Max. Torque at 85% Voltage.
- This addition does not apply when brake is to be ceiling mounted. For drip proof, ceiling mounting, prices on application.
- Δ Brake with spraytight enclosure requires removal of cover to operate hand release.
- * When contactor is enclosed, derate 10%.
- † Contactor does not provide its own coil protection, must be protected by succeeding contactor.

CUTLER 167/399
12/1/2006



CUTLER-HAMMER, INC.

All prices F. O. B. Milwaukee — Discount Schedule 16 CD
MILWAUKEE 1, WISCONSIN

PAGE 3

7-69