Registered 5-1-53

SUPER ONE COAT HOUSE PAINT

WHITE 338

FOR EXTERIOR OR INTERIOR WORK

A high hiding super one coat house paint white that combines ease of application with beauty of finish and excellent durability.

This paint is designed for use on previously primed or finished surfaces. All new or unpainted surfaces should have a first coat of High Standard Primer No. 260.

DIRECTIONS—It is essential that the surface be prepared carefully in order to obtain the best results. Clean the surface thoroughly. Remove all loose paint and other foreign matter. The surface must be dry; the paint should not be applied in damp, foggy or cold weather.

MIXING—Pour off liquid into another vessel. Stir remaining paste to uniform consistency. Return liquid gradually, stirring well between additions of the liquid.

APPLICATION—It brushes easily; therefore, apply it with a full brush and do not attempt to brush out over too wide an area, thereby reducing film thickness. This one coat paint is not recommended for application on poorly prepared surfaces or on structures with old coatings where the finish has deteriorated badly.

THINNING—It should be applied as it comes in the container. If thinning is essential, reduce with a small quantity Lowe Brothers Utility Thinner V-988, mineral spirits or turpentine.

Super One Coat House Paint is for the finish coat only. On dark colored surfaces, High Standard Primer should be followed with a single coat of Super One Coat House Paint.

Super One Coat House Paint White 338 (By Weight)	
Pigment	64.5%
Vehicle	35.5%
	100.0%
Pigment (By Weight)	
Titanium Dioxide	17.5%
Titanium Calcium	20.0%
Basic Lead Sulfate	16.0%
Zinc Oxide	29.0%
Magnesium Silicate	17.5%
	100.0%
Vehicle (By Weight)	
Raw Linseed Oil	32.0%
Heat Bodied Linseed Oil	45.5%
Mineral Spirits and Driers	22.5%
A-2	100.0%

U. S. STANDARD FIVE-GALLON NET

THE LOWE BROTHERS COMPANY
DAYTON FACTORIES TORONTO

N 18726

0032 SUP 016218