

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

81112-246
1- S.D. File
1- R. McCutchan

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 694-1000		
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS Mono Chlorobiphenyl			TRADE NAME AND SYNONYMS MCS 1109		
CHEMICAL FAMILY Chlorinated aromatic			FORMULA		
SECTION II HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (P.F.)	760 mm	255-290°C	SPECIFIC GRAVITY (H ₂ O=1) (25/15.5°C)	1.133	
VAPOR PRESSURE (mm Hg.)	118°C	10 mm	PERCENT VOLATILE BY VOLUME (%)	N.A.	
VAPOR DENSITY (AIR=1)	Not Avail		EVAPORATION RATE (BIIAC=1)	<1	
SOLUBILITY IN WATER	Not Avail				
APPEARANCE AND ODOR	colorless liquid aromatic odor				
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (Method used)	C.C.235°F		FLAMMABLE LIMITS	Let	Uet
EXTINGUISHING MEDIA	Water, foam, CO ₂ or dry chemical				
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.					
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.					

DSW 267522

THRESHOLD LIMIT VALUE	Not available.
EFFECTS OF OVEREXPOSURE Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.	
EMERGENCY AND FIRST AID PROCEDURES Remove contaminated clothing. Remove from exposure. Wash contact area with large amounts of water and soap. Refer to physician.	

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.	
WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.	

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Bureau of Mines approved respirator for organic			
VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL vapors.
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES rubber		EYE PROTECTION chemical goggles	
OTHER PROTECTIVE EQUIPMENT			

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Avoid skin and eye contact. Avoid inhalation of vapors.	
OTHER PRECAUTIONS	

DSW 267523

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/25/72