

56668

PART 173—SHIPPERS—GENERAL REQUIREMENTS FOR SHIPMENTS AND PACKAGINGS

2. Section 173.1090 is added preceding Subpart N to read as follows:

§ 173.1090 Asbestos.

(a) Asbestos includes any of the following hydrated mineral silicates: chrysotile, crocidolite, amosite, anthophyllite asbestos, tremolite asbestos, actinolite asbestos, and every product containing any of these minerals.

(b) Commercial asbestos is any material or product containing asbestos that has commercial value because of its asbestos content.

(c) Asbestos which is immersed or fixed in a natural or artificial binder material (such as cement, plastic, asphalt, resins or mineral ore) and manufactured products containing asbestos or any materials or products whose commercial value is not dependent on their asbestos content, are not subject to the requirements of this subchapter.

(d) Commercial asbestos must be offered for transportation and transported in—

(1) Rigid, airtight packagings such as metal or fiber drums, portable tanks, or

(2) Bags and other non-rigid packagings that are dust and sift proof. When transported by other than a private carrier by highway, bags and other non-rigid packagings containing asbestos must be palletized and unitized by methods such as shrink-wrapping in plastic film or wrapping in fiberboard secured by strapping.

PART 174—CARRIAGE BY RAIL

3. A Subpart M Heading is added immediately following § 174.812 to read as follows:

Subpart M—Detailed Requirements for Other Regulated Materials

4. Section 174.840 is added to read as follows:

§ 174.840 Special loading and handling requirements for asbestos.

Asbestos must be loaded, handled, and unloaded, and any asbestos contamination of rail cars removed, in a manner that will minimize occupational exposure to airborne asbestos particles released incident to transportation. (See § 173.1090 of this subchapter.)

PART 175—CARRIAGE BY AIRCRAFT

5. Section 175.640 is added to read as follows:

§ 175.640 Special requirements for other regulated materials.

Asbestos must be loaded, handled,

RULES AND REGULATIONS

and unloaded, and any asbestos contamination of aircraft removed, in a manner that will minimize occupational exposure to airborne asbestos particles released incident to transportation. (See § 173.1090 of this subchapter.)

PART 176—CARRIAGE BY VESSEL

6. Section 176.906 is added to read as follows:

§ 176.906 Stowage and handling of asbestos.

Asbestos must be stowed, handled, and unloaded, and any asbestos contamination of vessels removed, in a manner that will minimize occupational exposure to airborne asbestos particles released incident to transportation. (See § 173.1090 of this subchapter.)

PART 177—CARRIAGE BY PUBLIC HIGHWAY

7. Section 177.844 is added to read as follows:

§ 177.844 Other regulated materials.

Asbestos must be loaded, handled, and unloaded, and any asbestos contamination of transport vehicles removed, in a manner that will minimize occupational exposure to airborne asbestos particles released incident to transportation. (See § 173.1090 of this subchapter.)

(49 U.S.C. 1803, 1804, 1808; 49 CFR 1.53(e).)

NOTE.—The Materials Transportation Bureau has determined that these amendments do not require a regulatory analysis under the terms of Executive Order 12044 and DOT implementing procedures (43 FR 9582). A regulatory evaluation is available for review in the docket.

Issued in Washington, D.C., on November 27, 1978.

L. D. SANTMAN,
Director, Materials
Transportation Bureau.

(FR Doc. 78-33771 Filed 12-1-78; 8:45 am)

[4910-59-M]

CHAPTER V—NATIONAL HIGHWAY

TRAFFIC SAFETY ADMINISTRATION, DEPARTMENT OF TRANSPORTATION

[Docket No. 78-17; Notice 1]

PART 571—FEDERAL MOTOR VEHICLE SAFETY STANDARDS

New Pneumatic Tires—Passenger Cars

AGENCY: National Highway Traffic Safety Administration (NHTSA), Department of Transportation.

ACTION: Final rule.

SUMMARY: Pursuant to petitions by the Michelin Tire Corporation (Michelin) and by the Rubber Manufacturers Association (RMA), this notice amends Federal Motor Vehicle Safety Standard No. 109, *New Pneumatic Tires—Passenger Cars*, by adding four new tire size designations to Table I of Appendix A of the standard. The amendment permits the introduction into interstate commerce of the new tire sizes.

EFFECTIVE DATE: January 3, 1979. If objections are not received prior to that date.

ADDRESS: Comments should refer to the docket number and be submitted to Room 5108, Nassif Building, 400 Seventh Street SW., Washington, D.C. 20590.

FOR FURTHER INFORMATION CONTACT:

John Diehl, Office of Vehicle Safety Standards, National Highway Traffic Safety Administration, 400 Seventh Street SW., Washington, D.C. 20590 (202-426-1714).

SUPPLEMENTARY INFORMATION: According to agency practice, the National Highway Traffic Safety Administration responds to petitions for adding new tire sizes to Table I of Appendix A of Standard No. 109 by quarterly issuing final rules under an abbreviated rulemaking procedure for expediting such routine amendments.

On July 13, 1978, Michelin petitioned for the addition of two new tire size designations requested to be located in a new table, I-QQ within Appendix A of Standard No. 109. On July 13, 1978, and August 3, 1978, the RMA petitioned for the addition of two new tire size designations to existing tables within Table I of Appendix A of the standard. The bases for accepting or denying requests to add new tire size designations are set forth in introductory guidelines to the appendix (October 5, 1968, 33 FR 14964, as amended May 4, 1971, 36 FR 8298; July 22, 1971, 36 FR 13601; and August 13, 1974, 39 FR 28980). The four new tire size designations requested to be added to

1302597

DUP 0501726

DBE

DU 001447

RULES AND REGULATIONS

18673

(Sec. 205(c), 63 Stat. 390; 40 U.S.C. 486(c))

Dated: March 14, 1979.

PAUL E. GOULDING,
Acting Administrator of
General Services

(FR Doc. 79-9311 Filed 3-28-79; 8:45 am)

[4310-10-M]

CHAPTER 14—DEPARTMENT OF THE INTERIOR

PART 14-4—SPECIAL TYPES AND METHODS OF PROCUREMENT

Aircraft services

AGENCY: Department of the Interior,
Office of the Secretary.

ACTION: Final rule.

SUMMARY: This rule amends the Interior Procurement Regulations by adding a reference to the requirements of Part 353 of the Departmental Manual which covers the procurement of aircraft and aircraft-related services and maintenance.

EFFECTIVE DATE: This amendment is effective on April 30, 1979.

FOR FURTHER INFORMATION CONTACT:

William Opdyke, (202) 343-5914.

SUPPLEMENTARY INFORMATION: The primary author of this rule is William Opdyke, Division of Procurement and Grants, Office of Administrative and Management Policy, Department of Interior, (202) 343-5914.

NOTE—The Department of Interior has determined that this document is not a significant rule and does not require a regulatory analysis under Executive Order 12044 and 43 CFR Part 14.

It is the general policy of the Department of Interior to allow time for interested parties in the rulemaking process. However, the amendments contained herein are entirely administrative in nature. Therefore, the rulemaking process is waived.

Dated: March 21, 1979.

RICHARD R. HITE,
Deputy Assistant Secretary
of the Interior

Accordingly, pursuant to the authority of the Secretary of the Interior contained in 5 U.S.C. 301, 41 CFR is amended as stated below.

PART 14-4—SPECIAL TYPES AND METHODS OF PROCUREMENT

1. The Table of Contents for Part 14-4 is amended by adding new entries as follows:

Subpart 14-4.53—Aircraft Services

Sec. 14-4.5300 Requirements for acquiring aircraft services.

AUTHORITY: 5 U.S.C. 301

2. New Subpart 14-4.53 and § 14-4.5300 are added as follows:

Subpart 14-4.53—Aircraft Services

§ 14-4.5300 Requirements for acquiring aircraft services.

Procurement of aircraft and aircraft-related services and maintenance shall be performed by the Office of Aircraft Services in accordance with the procedures contained in Part 353 of the Department Manual (353 DM).

(FR Doc. 79-9507 Filed 3-28-79; 8:45 am)

[4910-60-M]

Title 49—Transportation

CHAPTER I—RESEARCH AND SPECIAL PROGRAMS ADMINISTRATION, MATERIALS TRANSPORTATION BUREAU, DEPARTMENT OF TRANSPORTATION

(Docket No. HM-160; Amdt. No. 173-47, 173-123, 174-33, 175-7, 176-6, 177-44)

PART 173—SHIPPERS—GENERAL RE- QUIREMENTS FOR SHIPMENTS AND PACKAGINGS

Transportation of Asbestos; Revision of Amendment No. 173-123; Effective Date Extension

AGENCY: Materials Transportation Bureau (MTB), Research and Special Programs Administration, DOT.

ACTION: Revision of previous Amendment No. 173-123 and extension of the effective date for all amendments.

SUMMARY: This revision of Amendment No. 173-123 regarding the transportation of asbestos as published on December 4, 1978, in the FEDERAL REGISTER (43 FR 56684) will allow shipments of asbestos when packaged in bags or other non-rigid packagings to be transported in closed freight containers, motor vehicles, or rail cars when loaded by the consignor and unloaded by the consignee; or in bags and other non-rigid packagings that are dust and sift proof which are palletized and unitized. Unitized loads in slings need not be palletized during

transportation by vessel. The effective date of the entire Docket HM-160 is revised from April 30, 1979 to August 20, 1979.

EFFECTIVE DATE: August 20, 1979.

ADDRESS: All written comments received in this rulemaking action are available for examination during regular business hours in the Docket Branch, Room 8500, TransPoint Building, 2100 Second Street, S.W., Washington, D.C.

FOR FURTHER INFORMATION CONTACT:

Delmer F. Billings, Standards Division, Materials Transportation Bureau, Research and Special Programs Administration, 2100 Second Street, S.W., Washington, D.C. 20590, phone 202-755-4902.

SUPPLEMENTARY INFORMATION: On December 4, 1978, the MTB published a final rule under Docket HM-160 in the FEDERAL REGISTER (43 FR 56684). Since this publication, the MTB has received several petitions for reconsideration in accordance with the provisions of 49 CFR 106.35. The petitions requested reconsideration of the provisions and/or extension of the effective date of the final rule. This document will incorporate methods of shipment which were identified in the notice of proposed rulemaking (43 FR 5662, March 2, 1978) and also those which were included in the final rule. These amendments represent minimum safety requirements and are intended to reduce the risks to public health associated with the generation of unacceptable airborne concentrations of asbestos that may result from packaging and handling of asbestos shipments in commercial transportation.

Two petitioners based their petitions on the fact that the final rule contained a provision requiring bags and other non-rigid containers of asbestos to be palletized and unitized by some method such as shrink-wrapping in plastic film or wrapping in fiberboard secured by strapping. It was noted that this requirement was not included in the notice of proposed rulemaking (43 FR 5662), thus making comments on this requirement impossible during the normal comment period for the proposed rulemaking. Petitioners also posed the question of whether or not freight containers, rail cars, etc., constituted rigid, airtight packagings as required in § 173.1090(d)(1). It was stated that if such containers were not included in this provision, all shipments of bags or non-rigid containers would be required to be palletized and unitized according to the provisions of § 173.1090(d)(2), and that this requirement would impose great hardship on the asbestos industry and on shippers

DUP 0501727

DBE

1302598

DU 001448

of large volumes of asbestos who normally ship using exclusive use vehicles and rail cars. It was also indicated that neither the equipment nor facilities exist at the present time to achieve compliance with the palletizing and unitizing requirement of the final rule by the published effective date. The MTB has determined that freight containers and, probably, motor vehicles and rail cars would not satisfy the requirements of § 173.1090(d)(1).

By allowing the use of unitized pallet loads as identified in the final rule, the MTB intended to recognize less restrictive handling requirements for bagged asbestos than those that would have been required by the "loading by consignor/unloading by consignee" approach. However, it was not the intent of the MTB to eliminate the more restrictive consignor/consignee approach. Therefore, § 173.1090(d) is being revised to allow the option of either the consignor/consignee approach as identified in the original proposed rulemaking with inclusion of an exclusive use provision or the unitized pallet approach using bags or other non-rigid packagings as required by the final rule.

One petitioner noted that a method of shipment of asbestos via water was the use of slings which are shrink-wrapped or stretch-wrapped and transported in the hold of a vessel without the use of pallets. It was the petitioner's contention that the use of pallets would increase the incidents of unintentional release of asbestos due to the interaction of the pallets against the bags which are unitized by the slings. It was noted that pallets were used in all instances except when placed in the hold of the transport vessel. Given the lack of detailed data on the amount of asbestos fibers released in transportation and the circumstances and cause for such release, the MTB is in general agreement that increased unintentional releases may be likely if pallets were used under the method identified in the petition. Therefore, § 173.1090(d) is being revised to allow slings in loads that are shrink-wrapped or stretch-wrapped to be transported by water without the use of pallets. Future monitoring of hazardous materials incident reports will assist the MTB in determining the safety and efficiency of this and other methods for shipment of asbestos.

One petitioner suggested that the terms "pallet" and "palletized" be defined in the rulemaking. The MTB does not intend to publish a definition of pallet or palletized. It is the MTB's opinion that any rigid platform or board upon which goods may be placed for transportation would meet the requirements when unitizing a load of bags or other non-rigid packagings.

Several petitioners cited a need for the MTB to define the term "dust and sift proof". For the purposes of this amendment, the MTB considers dust and sift proof to mean packagings which are constructed so as to prevent the release of their contents either through materials of construction, seams, or closures during conditions normally incident to transportation.

One petitioner requested that the use of gluing of bags into a unit be allowed as an alternative to the unitizing methods identified in the final rule. It is the MTB's opinion that the use of shrink-wrapping or other similar methods of enclosure assist not only in unitizing a pallet load of bags or other non-rigid packagings, but also assist in the prevention of airborne asbestos contamination of individuals involved in the transportation of asbestos. Simply gluing these packagings together to form a unit would not provide this added measure of safety to which the final rule addresses itself. Therefore, gluing of bags into a unit is not being included as an alternative unitizing method.

One petitioner requested that quantities of less than 2,000 pounds, net weight, per vehicle be exempted from the palletizing and unitizing requirement. It is MTB's opinion that the palletizing and unitizing requirement does not unreasonably restrict the shipment of asbestos in any quantity. This requirement is necessary to provide a minimum level of safety.

Several petitioners requested an extension of the effective date of the final rule. The effective date has been extended to allow five months for compliance as originally intended by the December 4, 1978 publication.

Primary drafters of this document are Delmer F. Billings, Standards Division, Office of Hazardous Materials Regulation, and Douglas A. Crockett, Standards Division, Office of Hazardous Materials Regulations.

In consideration of the foregoing, the effective date and paragraph (d) of § 173.1090 as they appeared in the FEDERAL REGISTER published on December 4, 1978 (43 FR 56664) are revised to read as follows:

1. The effective date of the final rule as it appeared in HM-180 on December 4, 1978, is revised to read as follows:

EFFECTIVE DATE: August 20, 1979.

2. In § 173.1090 paragraph (d) as it appeared at 43 FR 56669 is revised to read as follows:

§ 173.1090 Asbestos.

(d) Commercial asbestos must be offered for transportation and transported in—

(1) Rigid, airtight packagings such as metal or fiber drums, portable tanks;

(2) Bags or other non-rigid packagings in closed freight containers, motor vehicles, or rail cars that are loaded by and for the exclusive use of the consignor and unloaded by the consignee; or

(3) Bags or other non-rigid packagings which are dust and sift proof and which are palletized and unitized by methods such as shrink wrapping in plastic film or wrapping in fiberboard secured by strapping. Pallets need not be used during transportation by vessel for loads with slings that are unitized by methods such as shrink wrapping, if the slings adequately and evenly support the loads and the unitizing method prevents shifting of the bags or other non-rigid packagings during conditions normally incident to transportation.

(49 U.S.C. 1803, 1804, 1808; 49 CFR 1.53).

NOTE.—The Materials Transportation Bureau has determined that these amendments do not require a regulatory analysis under the terms of Executive Order 12044 and DOT implementing procedures (43 FR 9582). A regulatory evaluation is available for review in the Docket.

Issued in Washington, D.C. on March 22, 1979.

L.D. SANTMAN,
Director,

Materials Transportation Bureau.
(FR Doc. 79-9325 Filed 3-28-79; 8:45 am)

[4910-S9-M]

CHAPTER V—NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION, DEPARTMENT OF TRANSPORTATION

(Docket No. 73-3; Notice 13)

PART 571—FEDERAL MOTOR VEHICLE SAFETY STANDARDS

School Bus Passenger Seating and Crash Protection

AGENCY: National Highway Traffic Safety Administration (NHTSA).

ACTION: Final rule.

SUMMARY: This notice makes final an existing Interim Amendment to Standard No. 222, School Bus Passenger Seating and Crash Protection, increasing the maximum allowable seat spacing in school buses from 20 to 21 inches. In issuing the original standard, the agency intended that the seats be spaced approximately 20 inches apart (S5.2). However, because of manufacturing tolerances, some school bus manufacturers were spacing their seats at distances less than

$$f = \frac{1}{\sum_{i=1}^n \left[\frac{1}{n_i} + \frac{1}{n} \right]}$$

4. Results.
 4.1 If K_1 , K_2 , K_3 and K_4 are the official values of the coefficients in Table 1, then with 95% confidence the difference between K_1 and K_2 is significant, and so for the difference between K_3 and K_4 is significant, and so for the difference between K_1 and K_3 is significant, and so for the difference between K_2 and K_4 is significant.

TABLE 1

Degree of freedom (n, p-1)	f (95% confidence)
1	2.28
2	2.11
3	2.01
4	1.94
5	1.89
6	1.85
7	1.82
8	1.80
9	1.78
10	1.76
11	1.75
12	1.74
13	1.73
14	1.72
15	1.71
16	1.70
17	1.69
18	1.68
19	1.67
20	1.66
21	1.65
22	1.64
23	1.63
24	1.62
25	1.61
26	1.60
27	1.59
28	1.58
29	1.57
30	1.56
31	1.55
32	1.54
33	1.53
34	1.52
35	1.51
36	1.50
37	1.49
38	1.48
39	1.47
40	1.46
41	1.45
42	1.44
43	1.43
44	1.42
45	1.41
46	1.40
47	1.39
48	1.38
49	1.37
50	1.36
51	1.35
52	1.34
53	1.33
54	1.32
55	1.31
56	1.30
57	1.29
58	1.28
59	1.27
60	1.26
61	1.25
62	1.24
63	1.23
64	1.22
65	1.21
66	1.20
67	1.19
68	1.18
69	1.17
70	1.16
71	1.15
72	1.14
73	1.13
74	1.12
75	1.11
76	1.10
77	1.09
78	1.08
79	1.07
80	1.06
81	1.05
82	1.04
83	1.03
84	1.02
85	1.01
86	1.00
87	0.99
88	0.98
89	0.97
90	0.96
91	0.95
92	0.94
93	0.93
94	0.92
95	0.91
96	0.90
97	0.89
98	0.88
99	0.87
100	0.86
101	0.85
102	0.84
103	0.83
104	0.82
105	0.81
106	0.80
107	0.79
108	0.78
109	0.77
110	0.76
111	0.75
112	0.74
113	0.73
114	0.72
115	0.71
116	0.70
117	0.69
118	0.68
119	0.67
120	0.66
121	0.65
122	0.64
123	0.63
124	0.62
125	0.61
126	0.60
127	0.59
128	0.58
129	0.57
130	0.56
131	0.55
132	0.54
133	0.53
134	0.52
135	0.51
136	0.50
137	0.49
138	0.48
139	0.47
140	0.46
141	0.45
142	0.44
143	0.43
144	0.42
145	0.41
146	0.40
147	0.39
148	0.38
149	0.37
150	0.36
151	0.35
152	0.34
153	0.33
154	0.32
155	0.31
156	0.30
157	0.29
158	0.28
159	0.27
160	0.26
161	0.25
162	0.24
163	0.23
164	0.22
165	0.21
166	0.20
167	0.19
168	0.18
169	0.17
170	0.16
171	0.15
172	0.14
173	0.13
174	0.12
175	0.11
176	0.10
177	0.09
178	0.08
179	0.07
180	0.06
181	0.05
182	0.04
183	0.03
184	0.02
185	0.01
186	0.00
187	0.00
188	0.00
189	0.00
190	0.00
191	0.00
192	0.00
193	0.00
194	0.00
195	0.00
196	0.00
197	0.00
198	0.00
199	0.00
200	0.00

For each test the degrees of freedom, we may standardize the test statistic as follows:
 4.1 Assume the two performance tests produced the following results:
 Test 1
 Test 2
 4.2 The test statistic is:

$$T = \frac{100 + 95 + 110}{3} = 102$$

$$T_1 = \frac{115 + 120 + 125}{3} = 120$$

 4.3 Using Equation 1:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.4 Using Equation 2:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.5 Using Equation 3:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.6 Using Equation 4:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.7 Using Equation 5:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.8 Using Equation 6:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.9 Using Equation 7:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.10 Using Equation 8:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.11 Using Equation 9:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.12 Using Equation 10:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.13 Using Equation 11:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.14 Using Equation 12:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.15 Using Equation 13:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.16 Using Equation 14:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.17 Using Equation 15:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.18 Using Equation 16:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.19 Using Equation 17:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.20 Using Equation 18:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.21 Using Equation 19:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.22 Using Equation 20:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.23 Using Equation 21:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.24 Using Equation 22:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.25 Using Equation 23:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.26 Using Equation 24:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.27 Using Equation 25:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.28 Using Equation 26:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.29 Using Equation 27:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.30 Using Equation 28:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.31 Using Equation 29:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.32 Using Equation 30:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.33 Using Equation 31:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.34 Using Equation 32:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.35 Using Equation 33:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.36 Using Equation 34:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.37 Using Equation 35:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.38 Using Equation 36:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.39 Using Equation 37:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.40 Using Equation 38:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.41 Using Equation 39:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.42 Using Equation 40:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.43 Using Equation 41:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.44 Using Equation 42:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.45 Using Equation 43:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.46 Using Equation 44:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.47 Using Equation 45:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.48 Using Equation 46:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.49 Using Equation 47:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.50 Using Equation 48:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.51 Using Equation 49:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.52 Using Equation 50:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.53 Using Equation 51:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.54 Using Equation 52:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.55 Using Equation 53:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.56 Using Equation 54:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.57 Using Equation 55:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.58 Using Equation 56:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.59 Using Equation 57:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.60 Using Equation 58:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.61 Using Equation 59:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.62 Using Equation 60:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.63 Using Equation 61:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.64 Using Equation 62:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.65 Using Equation 63:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.66 Using Equation 64:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.67 Using Equation 65:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.68 Using Equation 66:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.69 Using Equation 67:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.70 Using Equation 68:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.71 Using Equation 69:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.72 Using Equation 70:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.73 Using Equation 71:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.74 Using Equation 72:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.75 Using Equation 73:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.76 Using Equation 74:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.77 Using Equation 75:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.78 Using Equation 76:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.79 Using Equation 77:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.80 Using Equation 78:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.81 Using Equation 79:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.82 Using Equation 80:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.83 Using Equation 81:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.84 Using Equation 82:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.85 Using Equation 83:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.86 Using Equation 84:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.87 Using Equation 85:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.88 Using Equation 86:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} = 25$$

 4.89 Using Equation 87:

$$F = \frac{(100 - 102)^2 + (95 - 102)^2 + (110 - 102)^2}{3 - 1} = 58.5$$

 4.90 Using Equation 88:

$$F = \frac{(115 - 120)^2 + (120 - 120)^2 + (125 - 120)^2}{3 - 1} =$$

§ 61.03

Title 40—Protection of Environment

- (i) "Existing source" means any stationary source which is not a new source.
- (j) "Modification" means any physical change in, or change in the method of operation of, a stationary source which increases the amount of any hazardous air pollutant emitted by such source or which results in the emission of any hazardous air pollutant not previously emitted.
- (k) "Routine maintenance, repair, and replacement" shall not be considered a change in the method of operation.
- (l) The following shall not be considered a change in the method of operation:
- (1) An increase in the production rate, if such increase does not exceed the operating design capacity of the stationary source;
- (2) An increase in hours of operation.
- (3) "New source" means any stationary source, the construction or modification of which is commenced after the publication in the Federal Register of proposed national emission standards for hazardous air pollutants which will be applicable to such source.
- (4) "Owner or operator" means any person who owns, leases, operates, controls, or supervises a stationary source.
- (m) "Reference method" means any method of sampling and analyzing for an air pollutant, as described in Appendix B to this part.
- (n) "Startup" means the setting in operation of a stationary source for any purpose.
- (o) "Standard" means a national emission standard for a hazardous air pollutant proposed or promulgated under this part.
- (p) "Stationary source" means any building, structure, facility, or installation which emits or may emit any air pollutant which has been designated as hazardous by the Administrator.
- 1st FR 1026, Apr. 8, 1973, as amended at 38 FR 1624, May 8, 1973
- § 61.03 Abbreviations.
- The abbreviations used in this part have the following meanings:
- "C"—Degrees Centigrade.
- "ft³"—Cubic feet per minute.
- "ft³"—Cubic feet.
- "P"—Pounds per hour.
- "in.—Inch.
- "mi.—Mile.
- "M"—Mole.
- "m³"—Cubic meter.

Chapter 1—Environmental Protection Agency

§ 61.05

- (b) Section 112(d) directs the Administrator to delegate to each State, when appropriate, the authority to implement and enforce the national emission standards for hazardous air pollutants for stationary sources located in such State. All information required to be submitted to EPA under paragraph (a) of this section, must also be submitted to the appropriate State Agency of any State to which this authority has been delegated (provided, that each specific delegation may exempt sources from a certain federal or State reporting requirements). The appropriate mailing addresses for those States whose delegation request has been approved is as follows:
- (A)-(C) [reserved].
- (D) California—
Bay Area Air Pollution Control District, 935 Ellis St., San Francisco, CA 94109.
Del Norte County Air Pollution Control District, Coos Bay, Crescent City, OR 95531.
Humboldt County Air Pollution Control District, 6800 S. Main St., Eureka, CA 95501.
Klamath County Air Pollution Control District, 1300 Pioneer Dr. (P.O. Box 907), Eureka, CA 95502.
Monterey Bay Unified Air Pollution Control District, 420 Church St. (P.O. Box 467), Eureka, CA 95501.
Northern Butte County Air Pollution Control District, 315 Casside St., Seattle, WA 98101.
Trinity County Air Pollution Control District, Box 41, Weaverville, CA 96093.
Ventura County Air Pollution Control District, 235 E. Santa Clara St., Ventura, CA 93001.
- (E)-(G) [reserved].
- (H)-(I) [reserved].
- (J)-(K) [reserved].
- (L)-(M) [reserved].
- (N)-(O) [reserved].
- (P)-(Q) [reserved].
- (R)-(S) [reserved].
- (T)-(U) [reserved].
- (V)-(W) [reserved].
- (X)-(Y) [reserved].
- (Z) [reserved].

- (EE) New Hampshire Air Pollution Control Agency, Department of Health and Welfare, State Laboratory Building, Room 1219, Concord, New Hampshire 03301.
- (FF) New York State Department of Environmental Conservation, 60 Wolf Road, Albany, New York 12242, attention: Division of Air Resources.
- (GG)-(II) [reserved].
- (JJ)-(LL) [reserved].
- (MM)-(NN) [reserved].
- (OO)-(PP) [reserved].
- (QQ)-(RR) [reserved].
- (SS)-(TT) [reserved].
- (UU)-(VV) [reserved].
- (WW)-(XX) [reserved].
- (YY)-(ZZ) [reserved].

- (1) Region I (Connecticut, Maine, New Hampshire, Massachusetts, Rhode Island, Vermont), John F. Kennedy Federal Building, Boston, MA 02203.
- (2) Region II (New York, New Jersey, Puerto Rico, Virgin Islands), Federal Office Building, 20 Federal Plaza (Paley Square), New York, N.Y. 10007.
- (3) Region III (Delaware, District of Columbia, Pennsylvania, Maryland, Virginia, West Virginia), Curtis Building, Sixth and Market Streets, Philadelphia, PA 19103.
- (4) Region IV (Alabama, Florida, Georgia, Mississippi, Kentucky, North Carolina, South Carolina, Tennessee), Suite 200, 141 Peachtree Street, Atlanta, Georgia 30309.
- (5) Region V (Illinois, Indiana, Minnesota, Michigan, Ohio, Wisconsin), 1 North Wacker Drive, Chicago, Illinois 60606.
- (6) Region VI (Arkansas, Louisiana, New Mexico, Oklahoma, Texas), 1000 Petroleum Square, Oklahoma City, Oklahoma 73101.
- (7) Region VII (Iowa, Kansas, Missouri, Nebraska), 1715 Baltimore Street, Kansas City, Missouri 64108.
- (8) Region VIII (Colorado, Montana, North Dakota, South Dakota, Utah, Wyoming), 196 Lincoln Tower, 1830 Lincoln Street, Denver, Colorado 80202.
- (9) Region IX (Arizona, California, Hawaii, Nevada, Guam, American Samoa, Northern Mariana Islands), 1000 California 94111.
- (10) Region X (Washington, Oregon, Idaho, Alaska), 1200 Sixth Avenue, Seattle, Washington 98101.

- (11) [reserved].
- (12) [reserved].
- (13) [reserved].
- (14) [reserved].
- (15) [reserved].
- (16) [reserved].
- (17) [reserved].
- (18) [reserved].
- (19) [reserved].
- (20) [reserved].
- (21) [reserved].
- (22) [reserved].
- (23) [reserved].
- (24) [reserved].
- (25) [reserved].
- (26) [reserved].
- (27) [reserved].
- (28) [reserved].
- (29) [reserved].
- (30) [reserved].
- (31) [reserved].
- (32) [reserved].
- (33) [reserved].
- (34) [reserved].
- (35) [reserved].
- (36) [reserved].
- (37) [reserved].
- (38) [reserved].
- (39) [reserved].
- (40) [reserved].
- (41) [reserved].
- (42) [reserved].
- (43) [reserved].
- (44) [reserved].
- (45) [reserved].
- (46) [reserved].
- (47) [reserved].
- (48) [reserved].
- (49) [reserved].
- (50) [reserved].
- (51) [reserved].
- (52) [reserved].
- (53) [reserved].
- (54) [reserved].
- (55) [reserved].
- (56) [reserved].
- (57) [reserved].
- (58) [reserved].
- (59) [reserved].
- (60) [reserved].
- (61) [reserved].
- (62) [reserved].
- (63) [reserved].
- (64) [reserved].
- (65) [reserved].
- (66) [reserved].
- (67) [reserved].
- (68) [reserved].
- (69) [reserved].
- (70) [reserved].
- (71) [reserved].
- (72) [reserved].
- (73) [reserved].
- (74) [reserved].
- (75) [reserved].
- (76) [reserved].
- (77) [reserved].
- (78) [reserved].
- (79) [reserved].
- (80) [reserved].
- (81) [reserved].
- (82) [reserved].
- (83) [reserved].
- (84) [reserved].
- (85) [reserved].
- (86) [reserved].
- (87) [reserved].
- (88) [reserved].
- (89) [reserved].
- (90) [reserved].
- (91) [reserved].
- (92) [reserved].
- (93) [reserved].
- (94) [reserved].
- (95) [reserved].
- (96) [reserved].
- (97) [reserved].
- (98) [reserved].
- (99) [reserved].
- (100) [reserved].

- (101) [reserved].
- (102) [reserved].
- (103) [reserved].
- (104) [reserved].
- (105) [reserved].
- (106) [reserved].
- (107) [reserved].
- (108) [reserved].
- (109) [reserved].
- (110) [reserved].
- (111) [reserved].
- (112) [reserved].
- (113) [reserved].
- (114) [reserved].
- (115) [reserved].
- (116) [reserved].
- (117) [reserved].
- (118) [reserved].
- (119) [reserved].
- (120) [reserved].
- (121) [reserved].
- (122) [reserved].
- (123) [reserved].
- (124) [reserved].
- (125) [reserved].
- (126) [reserved].
- (127) [reserved].
- (128) [reserved].
- (129) [reserved].
- (130) [reserved].
- (131) [reserved].
- (132) [reserved].
- (133) [reserved].
- (134) [reserved].
- (135) [reserved].
- (136) [reserved].
- (137) [reserved].
- (138) [reserved].
- (139) [reserved].
- (140) [reserved].
- (141) [reserved].
- (142) [reserved].
- (143) [reserved].
- (144) [reserved].
- (145) [reserved].
- (146) [reserved].
- (147) [reserved].
- (148) [reserved].
- (149) [reserved].
- (150) [reserved].
- (151) [reserved].
- (152) [reserved].
- (153) [reserved].
- (154) [reserved].
- (155) [reserved].
- (156) [reserved].
- (157) [reserved].
- (158) [reserved].
- (159) [reserved].
- (160) [reserved].
- (161) [reserved].
- (162) [reserved].
- (163) [reserved].
- (164) [reserved].
- (165) [reserved].
- (166) [reserved].
- (167) [reserved].
- (168) [reserved].
- (169) [reserved].
- (170) [reserved].
- (171) [reserved].
- (172) [reserved].
- (173) [reserved].
- (174) [reserved].
- (175) [reserved].
- (176) [reserved].
- (177) [reserved].
- (178) [reserved].
- (179) [reserved].
- (180) [reserved].
- (181) [reserved].
- (182) [reserved].
- (183) [reserved].
- (184) [reserved].
- (185) [reserved].
- (186) [reserved].
- (187) [reserved].
- (188) [reserved].
- (189) [reserved].
- (190) [reserved].
- (191) [reserved].
- (192) [reserved].
- (193) [reserved].
- (194) [reserved].
- (195) [reserved].
- (196) [reserved].
- (197) [reserved].
- (198) [reserved].
- (199) [reserved].
- (200) [reserved].

DBE

1302906

DU 001451

(2) A notification of the actual date of initial startup of the source within 15 days after such date.

§ 61.10 Source reporting and waiver request.

(a) The owner or operator of any stationary source, or any new source to which a standard prescribed under this part is applicable which has an initial startup which preceded the effective date of a standard prescribed under this part, shall, within 30 days after the effective date, provide the following information in writing to the Administrator:

(1) Name and address of the owner or operator.

(2) The location of the source.

(3) The type of stationary source.

(4) A brief description of the nature, size, design, and method of operation of the stationary source including the operating design capacity of such source.

(5) Identify each point of emission for each hazardous pollutant.

(6) The average weight per month of the hazardous materials being processed by the source over the last 12 months preceding the date of the report.

(7) A description of the existing control equipment for each emission point.

(8) Primary control device(s) for each hazardous pollutant.

(9) Secondary control device(s) for each hazardous pollutant.

(10) Estimated control efficiency (percent) for each control device.

(11) A statement by the owner or operator of the source as to whether he can comply with the standards prescribed in this part within 90 days of the effective date.

(12) The owner or operator of an existing source unable to comply with the standards within 90 days of the effective date of a standard prescribed under this part may request a waiver of compliance with such standard for a period not exceeding 2 years from the effective date. Any request shall be in writing and shall include the following information:

(i) A description of the controls to be installed to comply with the standard.

(ii) A compliance schedule, including the date each step toward compliance will be reached. Such list shall include as a minimum the following controls:

(i) Date by which contracts for emission control systems or process modifications will be awarded or data by which orders will be issued for the purchase of component parts to accomplish emission control or process modification;

(ii) Date by which such modifications will be completed.

(iii) Date by which such modifications will be completed.

(iv) Date by which such modifications will be completed.

(v) Date by which such modifications will be completed.

(vi) Date by which such modifications will be completed.

(vii) Date by which such modifications will be completed.

(viii) Date by which such modifications will be completed.

(ix) Date by which such modifications will be completed.

(x) Date by which such modifications will be completed.

(xi) Date by which such modifications will be completed.

(xii) Date by which such modifications will be completed.

(xiii) Date by which such modifications will be completed.

(xiv) Date by which such modifications will be completed.

(xv) Date by which such modifications will be completed.

(xvi) Date by which such modifications will be completed.

(xvii) Date by which such modifications will be completed.

(xviii) Date by which such modifications will be completed.

(xix) Date by which such modifications will be completed.

(xx) Date by which such modifications will be completed.

(xxi) Date by which such modifications will be completed.

(xxii) Date by which such modifications will be completed.

(xxiii) Date by which such modifications will be completed.

(xxiv) Date by which such modifications will be completed.

(xxv) Date by which such modifications will be completed.

(xxvi) Date by which such modifications will be completed.

(xxvii) Date by which such modifications will be completed.

(xxviii) Date by which such modifications will be completed.

(xxix) Date by which such modifications will be completed.

(xxx) Date by which such modifications will be completed.

(xxxi) Date by which such modifications will be completed.

(xxxii) Date by which such modifications will be completed.

(xxxiii) Date by which such modifications will be completed.

(xxxiv) Date by which such modifications will be completed.

(xxxv) Date by which such modifications will be completed.

(xxxvi) Date by which such modifications will be completed.

(xxxvii) Date by which such modifications will be completed.

(xxxviii) Date by which such modifications will be completed.

(xxxix) Date by which such modifications will be completed.

(xl) Date by which such modifications will be completed.

(xli) Date by which such modifications will be completed.

(xlii) Date by which such modifications will be completed.

(xliiii) Date by which such modifications will be completed.

(xliv) Date by which such modifications will be completed.

(xlv) Date by which such modifications will be completed.

(xlvi) Date by which such modifications will be completed.

(xlvii) Date by which such modifications will be completed.

(xlviii) Date by which such modifications will be completed.

(xlvix) Date by which such modifications will be completed.

(xli) Date by which such modifications will be completed.

(xlii) Date by which such modifications will be completed.

(xliiii) Date by which such modifications will be completed.

(xliiv) Date by which such modifications will be completed.

(xli) Date by which such modifications will be completed.

(xlii) Date by which such modifications will be completed.

(xliiii) Date by which such modifications will be completed.

(xliiv) Date by which such modifications will be completed.

(xli) Date by which such modifications will be completed.

(xlii) Date by which such modifications will be completed.

(xliiii) Date by which such modifications will be completed.

(xliiv) Date by which such modifications will be completed.

(xli) Date by which such modifications will be completed.

(xlii) Date by which such modifications will be completed.

(xliiii) Date by which such modifications will be completed.

(xliiv) Date by which such modifications will be completed.

Title 40—Protection of Environment

§ 61.06

owner or operator shall operate any new source in violation of such standard except under an exemption granted by the President under section 112(c)(2) of the act.

(c) Ninety days after the effective date of any standard prescribed under this part, no owner or operator shall operate any existing stationary source in violation of such standard, except under a waiver granted by the Administrator in accordance with this subject or under an exemption granted by the President under section 112(c)(2) of the act.

(d) No owner or operator subject to the provisions of this part shall fail to report, revise reports, or report source test results as required under this part.

§ 61.05 Determination of construction or modification.

Upon written application by an owner or operator, the Administrator will make a determination of whether such source is intended to be taken by such owner or operator to constitute construction or modification or the commencement thereof within the meaning of this part. The Administrator will within 30 days of receipt of sufficient information to evaluate an application, notify the owner or operator of this determination.

§ 61.07 Application for approval of construction or modification.

(a) The owner or operator of any new source to which a standard prescribed under this part is applicable shall, prior to the date on which construction or modification is planned to commence, or within 30 days after the effective date in the case of a new source that already has commenced construction or modification and has not begun operation, submit to the Administrator an application for approval of such construction or modification. A separate application shall be submitted for each stationary source.

(b) Each application shall include:

(1) The name and address of the applicant.

(2) The location or proposed location of the source.

(3) Technical information describing the proposed nature, size, design, operating design capacity, and method of operation of the source, including a description of any equipment to be used for control of emissions, such technical information shall include calculations of emission estimates in sufficient detail to permit assessment of the validity of such calculations.

§ 61.08 Approval by Administrator.

(a) The Administrator will, within 60 days of receipt of sufficient information to evaluate an application under § 61.07, notify the owner or operator of approval or intention to deny approval of construction or modification.

(b) If the Administrator determines that a stationary source for which an application pursuant to § 61.07 was submitted will, if properly operated, not cause emissions in violation of a standard, he will approve the construction or modification of such source.

(c) Prior to denying any application for approval of construction or modification pursuant to this section, the Administrator will notify the owner or operator making such application of the Administrator's intention to issue such denial, together with:

(1) Notice of the information and findings on which such intended denial is based, and

(2) Notice of opportunity for such owner or operator to present, within such time limit as the Administrator shall specify, additional information or arguments to the Administrator prior to final action on such application.

(d) A final determination to deny any application for approval will be in writing and will set forth the specific grounds on which such denial is based. Such final determination will be made within 90 days of presentation of additional information or arguments, or 60 days after the final date specified for presentation, if no presentation is made.

(e) Neither the submission of an application for approval nor the Administrator's granting of approval to construct or modify shall:

(1) Relieve an owner or operator of legal responsibility for compliance with any applicable provision of this part or of any other applicable Federal, State, or local requirement, or

(2) Prevent the Administrator from implementing or enforcing this part or taking any other action under the act.

§ 61.09 Notification of startup.

(a) Any owner or operator of a source which has an initial startup after the effective date of a standard prescribed under this part shall furnish the Administrator written notification as follows:

(1) A notification of the anticipated date of initial startup of the source not more than 60 days nor less than 30 days prior to such date.

(b) Date of initiation of on-site construction or installation of emission control equipment or process change;

(c) Date by which on-site construction or installation of emission control equipment or process modification is to be completed; and

(d) Date by which final compliance is to be achieved.

(e) A description of interim emission control steps which will be taken during the waiver period.

(f) Changes in the information provided under paragraph (a) of this section shall be provided to the Administrator within 30 days after such change, except that if changes will result from modification of the source, as defined in § 61.02 (f), the provisions of § 61.07 and § 61.08 are applicable.

(g) The format for reporting under this section is included as Appendix A of this part. Advice on reporting the status of compliance may be obtained from the Administrator.

§ 61.11 Waiver of compliance.

(a) Based on the information provided in any request under § 61.10, or other information, the Administrator may grant a waiver of compliance with a standard for a period not exceeding 2 years from the effective date of such standard.

(b) Such waiver will be in writing and will:

(1) Identify the stationary source covered.

(2) Specify the termination date of the waiver. The waiver may be terminated at an earlier date if the conditions specified under paragraph (b) (3) of this section are not met.

(3) Specify dates by which steps toward compliance are to be taken; and impose such additional conditions as the Administrator determines to be necessary to assure installation of the necessary controls within the waiver period, and to assure protection of the health of persons during the waiver period.

(c) Prior to denying any request for a waiver pursuant to this section, the Administrator will notify the owner or operator making such request of the Administrator's intention to issue such denial, together with:

(1) Notice of the information and findings on which such intended denial is based, and

(2) Notice of opportunity for such owner or operator to present, within such time limit as the Administrator specifies, additional information or arguments to the Administrator prior to final action on such application.

Chapter 1—Environmental Protection Agency

61.21

emission limiting regulation is not less stringent than the standards prescribed under this part.

(h) "Commercial asbestos" means any variety of asbestos which is produced by extracting asbestos from asbestos ore.

processing of this combination into a product as specified in § 61.27(c).

structural member and any related removing or stripping or friable asbestos materials.

be crumbled, pulverized, or reduced to powder, when dry, by hand pressure.

ing or substance of fabric; buttons made-
 tial used so, make of thread and

...tural members are blocked or taken out
...are excluded...

“(n) “Planned renovation” means a renovation operation, or a number of such operations, in which the amount

(b) "Emergency renovation" means a renovation operation that results from a sudden, unexpected, and unforeseen circumstance.

(q) "Removing" means taking out friable asbestos materials used to insulate

or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member from any building, structure, facility, or installation.

emission limiting regulation is not less stringent than the standards prescribed under this part.

(h) "Commercial asbestos" means any variety of asbestos which is produced by extracting asbestos from asbestos-bearing rocks.

... of commercial asbestos, or in the case of woven friction products the combining of textiles containing commercial asbestos with any other material.

(b) "Edible asbestos material" means

be crumbled, pulverized, or reduced to powder, when dry, by hand pressure.

means any asbestos-containing waste material that is collected in a pollution

ing or substance of fabric; buttons made-
 tial used so, make of thread and

“(n) “Planned renovation” means a renovation operation, or a number of such operations, in which the amount

in aqueous solution to prevent dual

(q) "Removing" means taking out of

reactor, turbine, furnace, or structural member from any building, structure, facility, or installation.

- (7) "Stripping" means taking off friable asbestos materials used for insulation or fireproofing from any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member.
- (8) "Fabricating" means any processing of a manufactured product containing commercial asbestos, with the exception of processing at temporary sites for the construction or restoration of buildings, structures, facilities or installations.
- (9) "Inert waste disposal site" means any disposal site or portion thereof where additional asbestos-containing waste material will not be deposited and where the surface is not disturbed by vehicular traffic.
- (10) "Active waste disposal site" means any disposal site other than an inactive site.
- (11) "Roadways" means surfaces on which motor vehicles travel including, but not limited to, highways, roads, streets, parking areas, and driveways.
- (12) "Asbestos-containing waste material" means any waste which contains commercial asbestos and is generated by a source subject to the provisions of this subpart, including asbestos mill tailings, industrial asbestos waste, friable asbestos waste material, and bays or containers that previously contained commercial asbestos.
- (13) "Asbestos mill tailings" means any waste material generated by an asbestos mill, as amended at 58 FR 422, Apr. 6, 1993, 60 FR 4229, Oct. 14, 1995, May 2, 1996, 60 FR 4229, Oct. 14, 1995.

§ 61.22

Asbestos standard.

- (a) Asbestos mills: There shall be no visible emissions to the outside air from any asbestos mill except as provided in paragraph (b) of this section.
- (b) Roadways: The surfacing of roadways with asbestos tailings or with asbestos-containing waste that is generated by any source subject to paragraph (a) of this section is prohibited, except for temporary roadways on an area of asbestos ore deposits. The deposition of asbestos tailings or asbestos-containing waste on roadways covered with snow or ice is considered "surfacing."
- (c) Manufacturing: There shall be no visible emissions to the outside air, except as provided in paragraph (f) of this section, from any of the following operations if they use commercial asbestos in or from any building or structure in which such operations are conducted:

- (1) The manufacture of cloth, cord, wicks, tubing, tape, rope, rope, thread, yarn, weaving, lag, or other textile materials.
- (2) The manufacture of cement products.
- (3) The manufacture of fireproofing and insulating materials.
- (4) The manufacture of friction products.
- (5) The manufacture of paper, millboard, and felt.
- (6) The manufacture of floor tile.
- (7) The manufacture of paints, coatings, caulks, adhesives, sealants.
- (8) The manufacture of plastics and rubber materials.
- (9) The manufacture of chlorine.
- (10) The manufacture of asbestos shells.
- (11) The manufacture of asphalt concrete.
- (12) Demolition and renovation: The requirements of this paragraph shall apply to any owner or operator of a building or structure who intends to demolish or renovate any institutional, commercial, or industrial building including apartment buildings having more than four dwelling units, a structure, facility, installation, or portion thereof, which contains any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member that is insulated or fireproofed with friable asbestos material, except as provided in paragraph (d) of this section; or who intends to renovate any institutional, commercial, or industrial building, structure, facility, installation, or portion thereof, which contains any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member that is insulated or fireproofed with friable asbestos material, except as provided in paragraph (d) of this section.

- (1) Name of owner or operator.
- (2) Address of the building, structure, facility, or installation to be demolished or renovated, including the size, age, and prior use of the structure, and the approximate amount of friable asbestos material used for insulation and fireproofing.
- (3) Address or location of the building, structure, facility, or installation.
- (4) Scheduled starting and completion dates of demolition or renovation.
- (5) Nature of planned demolition or renovation and methods to be employed.
- (6) Procedures to be employed to meet the requirements of this paragraph and paragraph (1) of this section.
- (7) The name and address or location of the waste disposal site where the friable asbestos waste will be deposited.
- (8) Name, title, and authority of the State or local governmental representative who has ordered a demolition which is subject to paragraph (d) of this section.
- (9) For purposes of determining whether a planned renovation operation constitutes a renovation within the meaning of this paragraph, the amount of this paragraph, the amount of friable asbestos material to be removed or stripped shall be the total amount of friable asbestos material that will be removed or stripped as a result of the sudden, unexpected event that necessitated the renovation.
- (10) The following procedures shall be used to prevent emissions of particulate asbestos material to outside air:

- (i) Friable asbestos materials, used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member, shall be removed from any building, structure, facility or installation subject to this paragraph. Such removal shall occur before wrecking or dismantling of any portion of such building, structure, facility or installation that would break up the friable asbestos materials and before wrecking or dismantling of any other portion of such building, structure, facility or installation that would preclude access to such materials for subsequent removal. Removal of friable asbestos materials used for insulation or fireproofing of any pipe, duct, or structural member which are encased in concrete or other similar structural material is not required prior to demolition, but such material shall be adequately wetted whenever exposed during demolition.
- (ii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (iii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (iv) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (v) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (vi) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (vii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (viii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (ix) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (x) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xi) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xiii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xiv) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xv) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xvi) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xvii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xviii) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xix) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.
- (xx) Friable asbestos materials used to insulate or fireproof pipe, duct, boiler, tank, reactor, turbine, furnace, or structural members shall be adequately wetted during stripping, except as provided in paragraph (d) of this section.

- (1) The notification requirements of paragraph (b) of this section shall be posted in the building, structure, facility or installation and shall include the information required by paragraphs (1) through (11) of this section.
- (2) Written notice of intention to demolish or renovate shall be provided to the Administrator by the owner or operator of the demolition or renovation operation. Such notice shall be postmarked 10 days prior to commencement of demolition, or as early as possible prior to commencement of emergency demolition, and as early as possible prior to commencement of renovation. Such notice shall include the following information:

- (i) Name of owner or operator.
- (ii) Address of the building, structure, facility, or installation to be demolished or renovated, including the size, age, and prior use of the structure, and the approximate amount of friable asbestos material used for insulation and fireproofing.
- (iii) Address or location of the building, structure, facility, or installation.
- (iv) Scheduled starting and completion dates of demolition or renovation.
- (v) Nature of planned demolition or renovation and methods to be employed.
- (vi) Procedures to be employed to meet the requirements of this paragraph and paragraph (1) of this section.
- (vii) The name and address or location of the waste disposal site where the friable asbestos waste will be deposited.
- (viii) Name, title, and authority of the State or local governmental representative who has ordered a demolition which is subject to paragraph (d) of this section.
- (ix) For purposes of determining whether a planned renovation operation constitutes a renovation within the meaning of this paragraph, the amount of this paragraph, the amount of friable asbestos material to be removed or stripped shall be the total amount of friable asbestos material that will be removed or stripped as a result of the sudden, unexpected event that necessitated the renovation.
- (x) The following procedures shall be used to prevent emissions of particulate asbestos material to outside air:

DBE

1302909

(iii) Pipes, ducts, boilers, tanks, reactors, turbines, furnaces, or structural members that are insulated materials provided with friable asbestos shall be removed or taken out of any building, structure, facility, or installation subject to this paragraph as units in sections as provided in paragraph (d) (4) (iii) of this section. The removal of such materials shall not be dropped or thrown to the ground, but shall be carefully lowered to ground level.

(iv) The stripping of friable asbestos materials used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace or structural member that has been removed as a unit or in sections as provided in paragraph (d) (4) (iii) of this section shall be performed in accordance with paragraph (d) (4) (iii) of this section. Rather than comply with the wetting requirement, a local exhaust ventilation and collection system may be used to prevent emissions to the outside air. Such local exhaust ventilation systems shall be designed and operated to capture the asbestos particles and remove them from the building. There shall be no visible emissions to the outside air from such local exhaust ventilation and collection systems, except as provided in paragraph (f) of this section.

(v) Sources subject to this paragraph are exempt from the requirements of § 61.05(a), § 61.07, and § 61.09.

(vi) The demolition of a building, structure, facility, or installation, pursuant to an order of an authorized representative of a State or local governmental agency, issued because that building is structurally unsound and in danger of imminent collapse is exempt from all but the following requirements of paragraph (d) of this section:

(i) The notification requirements specified by paragraph (d) (2) of this section;

(ii) The requirements on stripping of friable asbestos materials from previously removed units or sections as specified in paragraph (d) (4) (iv) of this section;

(iii) The wetting, as specified by paragraph (d) (4) (v) of this section, of friable asbestos materials that have been removed or stripped;

(iv) The portion of the structure being demolished that contains friable asbestos materials shall be adequately wetted during the wrecking operation.

(v) Stripping: There shall be no visible emissions to the outside air from the spray-on application of materials containing more than 1 percent asbestos, on a dry weight basis, used to insulate or fireproof equipment and machinery, except as provided in paragraph (f) of this section. Spray-on materials used to insulate or fireproof buildings, structures, pipes, and conduits shall contain less than 1 percent asbestos on a dry weight basis.

(1) Sources subject to this paragraph are exempt from the requirements of § 61.05(a), § 61.07, and § 61.09.

(2) Any owner or operator who intends to spray asbestos materials which contain more than 1 percent asbestos on a dry weight basis to insulate or fireproof equipment and machinery shall report such intention to the Administrator at least 20 days prior to the commencement of the spraying operation. Such report shall include the following information:

(i) Name of owner or operator.

(ii) Address of owner or operator.

(iii) Location of spraying operation.

(iv) Procedures to be followed to meet the requirements of this paragraph.

(v) Rather than meet the no-visible-emission requirements as specified by paragraphs (a), (c), (d), (e), (f), (g), and (h) of this section, an owner or operator may elect to use the methods specified by § 61.23 to clean emissions containing particulate asbestos material before such emissions escape to, or are vented to, the outside air.

(g) Where the presence of uncombined water is the sole reason for failure to meet the no-visible-emission requirements of paragraphs (a), (c), (d), (e), (f), (g), or (h) of this section, such failure shall not be a violation of such emission requirements.

(h) Enfranchising: There shall be no visible emissions to the outside air, except as provided in paragraph (f) of this section, from any of the following operations if they use commercial asbestos or from any building or structure in which such operations are conducted:

(1) The fabrication of cement building products.

(2) The fabrication of friction products, except those operations that primarily install asbestos friction materials on motor vehicles.

(3) The fabrication of cement or all-cast board for ventilation hoods; ovens; electrical panels; laboratory furniture; bulkheads, partitions and ceilings for marine construction; and flow control devices for the molten metal industry.

(4) Insulating: Molded insulating materials with a life friable and wet-applied insulating materials which are friable after drying, installed after the effective date of these regulations, shall contain no commercial asbestos. The provisions of this paragraph do not apply to insulating materials which are spray applied; such materials are regulated under § 61.22(c).

(1) Waste disposal for manufacturing, fabricating, demolition, renovation and spraying operations: The owner or operator of any source covered under the provisions of paragraphs (c), (d), (e), or (h) of this section shall meet the following standards:

(i) There shall be no visible emissions to the outside air, except as provided in paragraph (1) (2) of this section, during the collection, processing, including incineration; packaging; transporting; or deposition of any asbestos-containing waste material which is generated by such source.

(2) All asbestos-containing waste material shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.23.

(3) Rather than meet the requirement of paragraph (1) (i) of this section, an owner or operator may elect to use either of the disposal methods specified under (3) (i) and (ii) of this section, or an alternative disposal method which has received prior approval by the Administrator:

(i) Treatment of asbestos-containing waste material with water:

(A) Control device asbestos waste shall be thoroughly mixed with water into a slurry and other asbestos-containing waste material shall be adequately wetted. There shall be no visible emissions to the outside air from the collection, mixing and wetting operations except as provided in paragraph (1) of this section.

(B) After wetting, all asbestos-containing waste material shall be sealed into leak-tight containers while wet, and such containers shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.23.

(C) The containers specified under paragraph (1) (3) (i) (B) of this section shall be labeled with a warning label that states:

CONTAINS ASBESTOS
Avoid Opening or Breaching Container
Breathing Asbestos is Hazardous
to Your Health

Alternatively, warning labels specified by Occupational Safety and Health Standards of the Department of Labor, Occupational Safety and Health Administration (OSHA) under 29 CFR 1910.93a(g) (2) (ii) may be used.

DBE

1302910

DU 001455

DUP 0501739

(U) Processing of asbestos-containing waste material into non-friable forms:

(A) All asbestos-containing waste material shall be formed into non-friable pellets or other shapes and deposited at waste disposal sites which are operated in accordance with the provisions of § 61.35.

(B) There shall be no visible emissions to the outside air from the collection and processing of asbestos-containing waste material, except as specified in paragraph (f) of this section.

(C) For the purposes of this paragraph (f), the term all asbestos-containing waste material as applied to demolition and renovation work covered by paragraph (d) of this section includes only friable asbestos waste and control device asbestos waste.

(D) Waste disposal for asbestos miller: The owner or operator of any source covered under the provisions of paragraph (a) of this section shall meet the following standard:

(1) There shall be no visible emissions to the outside air, except as provided in paragraph (k)(3) of this section, during the collection, processing, packing, transporting or deposition of asbestos-containing waste material which is generated by such source.

(2) All asbestos-containing waste material shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.35.

(3) Rather than meet the requirement of paragraph (k)(1) of this section, an owner or operator may elect to meet the following requirements in paragraphs (k)(2) and (k)(3) of this section, or use an alternative disposal method which has received prior approval by the Administrator:

(i) There shall be no visible emissions to the outside air from the transfer of control device asbestos waste to the tailings conveyor, except as provided in paragraph (f) of this section. Such waste shall be subsequently processed either as specified in paragraph (k)(3) (ii) of this section or as specified in paragraph (i)(3) of this section.

(ii) All asbestos-containing waste material shall be adequately mixed, with a wetting agent recommended by the manufacturer of the agent to effectively wet dust and tailings, prior to deposition at a waste disposal site. Such agent shall be used as recommended for the particular dust by the manufacturer of the agent. There shall be no discharge of

visible emissions to the outside air from the wetting operation except as specified in paragraph (f) of this section. Wetting may be suspended when the ambient temperature at the waste disposal site is less than -9.3°C (ca. 15°F). The ambient air temperature shall be determined by an appropriate measurement method recorded at least at hourly intervals during the period that the operation of the wetting system is suspended. Records of such temperature measurements shall be retained at the source for a minimum of two years and made available for inspection by the Administrator.

(1) The owner of any inactive waste disposal site, which was operated by sources covered under § 61.22 (a), (c) or (f) and where asbestos-containing waste material produced by such source was deposited, shall meet the following standards:

(i) There shall be no visible emissions to the outside air from an inactive waste disposal site subject to this paragraph, except as provided in paragraph (i)(3) of this section.

(ii) Warning signs shall be displayed at all entrances, and along the perimeter of the site or along the perimeter of the sections of the site where asbestos-containing waste material was deposited, at intervals of 100 m (ca. 330 ft) or less, except as specified in paragraph (i)(4) of this section. Signs shall be posted in such a manner and location that a person may easily read the legend. The warning signs required by this paragraph shall conform to the requirements of 29 CFR 1910.146(c)(4) and this paragraph. The signs shall display the following legend in the lower panel, with letter size and style of a visibility at least equal to those specified in this paragraph.

LEGEND

Asbestos Waste Disposal Site

Do Not Enter Site

Breathing Asbestos is Hazardous to Your Health

NOTATION

1" Sans Serif, Outline or Block

¾" Sans Serif, Outline or Block

14 Point Outline

Spacing between lines shall be at least equal to the height of the upper of the two lines.

devices must be operated at a pressure drop of no more than 4 inches water gage, as measured across the filter fabric. The airflow permeability, as determined by ASTM method D727-69, must not exceed 30 ft³/min/ft² for woven fabrics or 38 ft³/min/ft² for felted fabrics, except that 40 ft³/min/ft² for woven and 46 ft³/min/ft² for felted fabrics is allowed for filtering air from asbestos ore dryers. Each square yard of felted fabric must weigh at least 14 ounces and be at least one-thirtieth inch thick throughout. Synthetic fabrics must not contain any yarn other than that which is spun.

(b) If the use of fabric filters creates a fire or explosion hazard, the administrator may authorize the use of wet collectors designed to operate with a unit contacting energy of at least 40 inches water gage pressure.

(c) The administrator may authorize the use of filtering equipment other than that described in paragraphs (a) and (b) of this section if the owner or operator demonstrates that the collection of the asbestos-containing material is equivalent to that of the described equipment.

(d) All air-cleaning equipment authorized by this section must be properly installed, used, operated and maintained. Bypass devices may be used only during upset or emergency conditions and then only for so long as it takes to shut down the operation generating the particulate asbestos material.

(e) 153 FR 6248, Apr. 4, 1973, as amended at 40 FR 4302, Oct. 14, 1975

§ 61.24 Reporting.

The owner or operator of any existing source to which this subpart is applicable shall, within 90 days after the effective date, provide the following information to the administrator:

(a) A description of the emission control equipment used for each process;

(b) If a fabric filter device is used to control emissions, the pressure drop across the fabric filter in inches water gage;

(c) If the fabric filter device utilizes a woven fabric, the airflow permeability in ft³/min/ft²; and, if the fabric is synthetic, indicate whether the all yarn is spun or not spun;

(d) If the fabric filter device utilizes a felted fabric, the density in oz/yd², the minimum thickness in inches, and the airflow permeability in ft³/min/ft².

(3) The perimeter of the site shall be fenced in a manner adequate to deter access by the general public, except as specified in paragraph (i)(4) of this section.

(4) Warning signs and fencing are not required where the requirements of paragraphs (1) (i) or (ii) of this section are met, or where a natural barrier adequately deters access by the general public. Upon request and supply of appropriate information, the Administrator will determine whether a fence or a natural barrier adequately deters access to the general public.

(5) Rather than meet the requirement of paragraph (1) (i) of this section, an owner may elect to meet the requirements of this paragraph or may use an alternative control method for emissions from inactive waste disposal sites which has received prior approval by the Administrator.

(i) The asbestos-containing waste material shall be covered with at least 15 centimeters (ca. 6 inches) of compacted non-asbestos-containing material, and a cover of vegetation shall be grown and maintained on the area adequate to prevent exposure of the asbestos-containing waste material;

(ii) The asbestos-containing waste material shall be covered with at least 60 centimeters (ca. 2 feet) of compacted non-asbestos-containing material and maintained to prevent exposure of the asbestos-containing waste; or

(iii) For inactive waste disposal sites for asbestos tailings, a reclamation or leach-based dust suppression agent which effectively binds dust and controls wind erosion shall be applied. Such agent shall be used as recommended for the particular asbestos tailings by the dust suppression agent manufacturer. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. For purposes of this paragraph, waste crankcase oil is not considered a dust suppression agent.

(38 FR 6426, Apr. 6, 1973, as amended at 38 FR 18308, May 3, 1976; 40 FR 40266, Oct. 14, 1975)

§ 61.23 Air-cleaning.

If air-cleaning is elected, as permitted by § 61.22 (f) and § 61.22 (d) (4) (iv), the requirements of this section must be met:

(a) Fabric filter collection devices must be used, except as noted in paragraphs (b) and (c) of this section. Such

(c) For sources subject to § 61.22(f) and § 61.22(h):
(1) A brief description of each process that generates asbestos-containing waste material.

(2) The average weight of asbestos-containing waste material disposed of, measured in kg/day.

(3) The emission control methods used in all stages of waste disposal.

(4) The type of disposal site or incineration site used for ultimate disposal, the name of the site operator, and the name and location of the disposal site.

(d) For sources subject to § 61.22(i):
(1) A brief description of the site.

(2) The method or methods used to comply with the standard, or alternative procedures to be used.

(e) Such information shall accompany the information required by § 61.10. The information described in this section shall be reported using the format of Appendix A of this part.

(3) FR 425, Apr. 4, 1972, as amended at 40 FR 4302, Oct. 14, 1975.

§ 61.25 Waste disposal sites.
In order to be an acceptable site for disposal of asbestos-containing waste material under § 61.22 (j) and (k), an active waste disposal site shall meet the requirements of this section.

(a) There shall be no visible emissions to the outside air from any active waste disposal site where asbestos-containing waste material has been deposited, except as provided in paragraph (e) of this section.

(b) Warning signs shall be displayed at all entrances, and along the property line of the site or along the perimeter of the sections of the site where asbestos-containing waste material is deposited, at intervals of 100 m (ca. 328 ft) or less except as specified in paragraph (d) of this section. Signs shall be posted in such a manner and location that a person may easily read the legend. The warning signs required by this paragraph shall conform to the requirements of 29 CFR 1910.120(d)(4) and this paragraph. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to those specified in this paragraph.

LEGEND
ASBESTOS WASTE DISPOSAL SITE
Do Not Create Dust
Breathing Apparatus
In Hazardous to Your Health
Notation
1" Base Bolt, Double or Bolt
14 Point Goggles

Spacing between lines shall be at least equal to the height of the upper of the two lines.

(c) The perimeter of the disposal site shall be fenced in order to adequately deter access to the general public except as specified in paragraph (d) of this section.

(d) Warning signs and fencing are not required where the requirements of paragraph (c)(1) of this section are met, or where a natural barrier adequately deters access to the general public. Upon request and supply of appropriate information, the Administrator will determine whether a fence or a natural barrier adequately deters access to the general public.

(e) Rather than meet the requirements of paragraph (a) of this section, an owner or operator may elect to meet the requirements of paragraph (a)(1) or (a)(2) of this section, or may use an alternative control method for emissions from active waste disposal sites which has received prior approval by the Administrator.

(1) At the end of each operating day, or at least once every 24-hour period while the site is in continuous operation, the asbestos-containing waste material which was deposited at the site during the operating day or previous 24-hour period shall be covered with at least 15 centimeters (ca. 6 inches) of compacted non-asbestos-containing material.

(2) At the end of each operating day, or at least once every 24-hour period while the disposal site is in continuous operation, the asbestos-containing waste material which was deposited at the site during the operating day or previous 24-hour period shall be covered with a resinous or petroleum-based dust suppressant which effectively binds dust and controls wind erosion. Such agent shall be used as recommended for the particular dust by the dust suppression

agent manufacturer. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. For purposes of this paragraph, waste crankcase oil is not considered a dust suppression agent.

(40 FR 4302, Oct. 14, 1975)

Subpart C—National Emission Standard for Beryllium

§ 61.30 Applicability.

The provisions of this subpart are applicable to the following stationary sources:

(a) Extraction plants, ceramic plants, foundries, incinerators, and propellant plants which process beryllium ore, beryllium, beryllium oxide, beryllium alloys, or beryllium-containing waste.

(b) Machine shops which process beryllium, beryllium oxides, or any alloy when such alloy contains more than 5 percent beryllium by weight.

§ 61.31 Definitions.

Terms used in this subpart are defined in the act, in subpart A of this part, or in this section as follows:

(a) "Beryllium" means the element beryllium. Where weights or concentrations are specified, such weights or concentrations apply to beryllium only, excluding the weight or concentration of any associated elements.

(b) "Extraction plant" means a facility chemically processing beryllium ore to beryllium metal, alloy, or oxide, or performing any of the intermediate steps in these processes.

(c) "Beryllium ore" means any naturally occurring material mined or gathered for its beryllium content.

(d) "Machine shop" means a facility performing cutting, grinding, turning, boring, milling, deburring, lapping, electrochemical machining, etching, or other similar operations.

(e) "Ceramic plant" means a manufacturing plant producing ceramic items.

(f) "Foundry" means a facility engaged in the melting or casting of beryllium metal or alloy.

(g) "Beryllium-containing waste" means material contaminated with beryllium and/or beryllium compounds used or generated during any process or operation performed by a source subject to this subpart.

(h) "Incinerator" means any furnace used in the process of burning waste for the primary purpose of reducing the volume of the waste by removing combustible matter.

(i) "Propellant" means a fuel and oxidizer physically or chemically combined which undergoes combustion to provide rocket propulsion.

(j) "Beryllium alloy" means any metal to which beryllium has been added in order to increase its beryllium content and which contains more than 0.1 percent beryllium by weight.

(k) "Propellant plant" means any facility engaged in the mixing, casting, or machining of propellant.

§ 61.32 Emission standard.

(a) Emissions to the atmosphere from stationary sources subject to the provisions of this subpart shall not exceed 10 grams of beryllium over a 24-hour period, except as provided in paragraph (b) of this section.

(b) Rather than meet the requirements of paragraph (a) of this section, an owner or operator may request approval from the Administrator to meet an ambient concentration of beryllium in the vicinity of the stationary source of 0.01 $\mu\text{g}/\text{m}^3$, averaged over a 30-day period.

(1) Approval of such requests may be granted by the Administrator provided that:

(i) At least 3 years of data is available which in the judgment of the Administrator demonstrates that the future ambient concentrations of beryllium in the vicinity of the stationary source will not exceed 0.01 $\mu\text{g}/\text{m}^3$, averaged over a 30-day period. Such 3-year period shall be the 3 years ending 30 days before the effective date of this standard.

(ii) The owner or operator requests such approval in writing within 30 days after the effective date of this standard.

(iii) The owner or operator submits a report to the Administrator within 45 days after the effective date of this standard which report includes the following information:

(a) Description of sampling method including the method and frequency of calibration.

(b) Method of sample analysis.

(c) Averaging technique for determining 30-day average concentrations.

DBE

1302912

§ 61.33 Title 40—Protection of Environment

- (d) Number, identity, and location (address, coordinates, or distance and bearing from plant) of sampling sites.
- (e) Ground elevations and height above ground of sampling sites.
- (f) Plant and sampling area plots showing emission points and sampling sites. Topographic features significantly affecting dispersion including plant building heights and locations shall be included.
- (g) Information necessary for estimating dispersion including stack height, inside diameter, exit gas temperature, exit velocity or flow rate, and beryllium concentration.
- (h) A description of data and procedures (methods or models) used to design the air sampling network (i.e., number and location of sampling sites).
- (i) Air sampling data indicating beryllium concentrations in the vicinity of the stationary source for the 3-year period specified in paragraph (b)(1) of this section. This data shall be presented chronologically and include the beryllium concentration and location of each individual sample taken by the network and the corresponding 30-day average beryllium concentrations.
- (j) Within 60 days after receiving such report, the Administrator will notify the owner or operator in writing whether approval is granted or denied. Prior to denying approval to comply with the provisions of paragraph (b) of this section, the Administrator will consult with representatives of the stationary source for which the demonstration report was submitted.
- (k) The burning of beryllium and/or beryllium-containing waste, except pyrotechnics, is prohibited except in incinerators, emissions from which must comply with the standard.
- § 61.33 Stack sampling.
 - (a) Unless a waiver of emission testing is obtained under § 61.12, each owner or operator required to comply with § 61.32(a) shall test emissions from his source.
 - (1) Within 90 days of the effective date in the case of an existing source or a new source which has an initial startup date preceding the effective date; or
 - (2) Within 90 days of startup in the case of a new source which did not have an initial startup date preceding the effective date.
 - (b) All monitoring sites shall be operated continuously except for a reasonable time allowance for instrument maintenance and calibration, for changing filters, or for replacement of equipment needing major repair.
 - (c) Filters shall be analyzed and concentrations calculated within 30 days after filters are collected. Records of concentrations at all sampling sites and data needed to determine such concentrations shall be retained at the source and made available, for inspection by the Administrator, for a minimum of 2 years.
- § 61.34 Air sampling.
 - (a) Stationary sources subject to § 61.32(b) shall locate air sampling sites in accordance with a plan approved by the Administrator. Such sites shall be located in such a manner as is calculated to detect maximum concentrations of beryllium in the ambient air.
 - (b) All monitoring sites shall be operated continuously except for a reasonable time allowance for instrument maintenance and calibration, for changing filters, or for replacement of equipment needing major repair.
 - (c) Filters shall be analyzed and concentrations calculated within 30 days after filters are collected. Records of concentrations at all sampling sites and data needed to determine such concentrations shall be retained at the source and made available, for inspection by the Administrator, for a minimum of 2 years.

Chapter I—Environmental Protection Agency

§ 61.51

- (d) Concentrations measured at all sampling sites shall be reported to the Administrator every 30 days by a registered letter.
- (e) The Administrator may at any time require changes in, or expansion of, the sampling network.
- Subpart D—National Emission Standard for Beryllium Rocket Motor Firing
- § 61.40 Applicability.

The provisions of this subpart are applicable to rocket motor test sites.
- § 61.41 Definitions.

Terms used in this subpart are defined in the Act, in Subpart A of this part, or in this section as follows:

 - (a) "Rocket motor test site" means any building, structure, facility, or installation where the static test firing of a beryllium rocket motor and/or the disposal of beryllium propellant is conducted.
 - (b) "Beryllium propellant" means any propellant incorporating beryllium.
- § 61.42 Emission standard.
 - (a) Emissions to the atmosphere from rocket-motor test sites shall not cause time-weighted atmospheric concentrations of beryllium to exceed 75 micrograms per cubic meter of air within the limits of 18 to 60 minutes, accumulated during any 3 consecutive weeks, in any area in which an effect adverse to public health could occur.
 - (b) If combustion products from the firing of beryllium propellant are collected in a closed tank, emissions from such tank shall not exceed 2 grams per hour and a maximum of 10 grams per day.
- § 61.43 Emission testing—rocket firing or propellant disposal.
 - (a) Ambient air concentrations shall be measured during and after firing of rocket motor or propellant disposal and in such a manner that the effect of these emissions can be compared with the standard. Such sampling techniques shall be approved by the Administrator.
 - (b) All samples shall be analyzed and results shall be calculated within 30 days after samples are taken and before any subsequent rocket motor firing or propellant disposal at the given site. All results shall be reported to the Administrator by a registered letter dispatched within 30 days after the test.
- § 61.44 Stack sampling.
 - (a) Sources subject to § 61.42(b) shall be continuously sampled, during release of combustion products from the tank in such a manner that compliance with the standards can be determined. The provisions of § 61.41 shall apply.
 - (b) All samples shall be analyzed, and beryllium emissions shall be determined within 30 days after samples are taken and before any subsequent rocket motor firing or propellant disposal at the given site. All determinations shall be reported to the Administrator by a registered letter dispatched before the close of the next business day following such determination.
 - (c) Records of emission test results and other data needed to determine total emissions shall be retained at the source and made available, for inspection by the Administrator, for a minimum of 2 years.
 - (d) The Administrator shall be notified at least 30 days prior to an emission test, so that he may at his option observe the test.
- § 61.45 Emission Standard

DUP 0501/42

DU 001458

DBE

1302913

§ 61.53

Title 40—Protection of Environment

(b) "Mercury ore" means a mineral mined specifically for its mercury content.

(c) "Mercury ore processing facility" means a facility processing mercury ore to obtain mercury.

(d) "Condenser stack gases" mean the gaseous effluent evolved from the stack of processes utilizing heat to extract mercury metal from mercury cell.

(e) "Mercury chlor-alkali cell" means a device which is electrically composed of an electrolytic action and a denuder (decomposer) section and utilizes mercury as product, chlorine gas, hydrogen gas, and chlorine gas byproduct.

(f) "Mercury chlor-alkali electrolyzer" means an electrolytic device which is part of a mercury chlor-alkali cell and utilizes a flowing mercury cathode to produce chlorine gas and chlorine metal amalgam.

(g) "Denuder" means a horizontal or vertical container which is part of a mercury chlor-alkali cell and in which water and alkali metal amalgam are converted to alkali metal hydroxide, mercury, and hydrogen gas in a short-circuited, electrolytic reaction.

(h) "Hydrogen gas stream" means a hydrogen stream formed in the chlor-alkali cell denuder.

(i) "End box" means a container located on one or both ends of a mercury chlor-alkali electrolyzer which serves as a connection between the electrolyzer and denuder for rich and stripped amalgam.

(j) "End box ventilation system" means a ventilation system which collects mercury emissions from the end boxes, the mercury pump sumps, and their water collection system.

(k) "Cell room" means a structure housing one or more mercury electrolytic chlor-alkali cells.

(l) "Sludge" means sludge produced by a treatment plant that processes industrial or municipal waste waters.

(m) "Sludge dryer" means a device used to reduce the moisture content of sludge by heating to temperatures above 45°C. 150°F directly with combustion gas.

(n) "Mercury chlor-alkali plant-by-product" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(o) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(p) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(q) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(r) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(s) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(t) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(u) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(v) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(w) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(x) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(y) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(z) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(aa) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ab) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ac) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ad) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ae) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(af) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ag) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ah) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ai) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(aj) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ak) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(al) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(am) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(an) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ao) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ap) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(aq) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ar) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(as) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(at) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(au) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(av) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(aw) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ax) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ay) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(az) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(ba) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(bb) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(bc) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(bd) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

(be) "Mercury chlor-alkali plant" means a stream of mercury, chlorine, and end-box ventilation gas stream.

Chapter I—Environmental Protection Agency

§ 61.53

(1) Within 90 days of the effective date in the case of an existing source or the source which has an initial startup date preceding the effective date; or

(2) Within 90 days of startup in the case of a new source which did not have an initial startup date preceding the effective date.

(3) The Administrator shall be notified at least 30 days prior to an emission test, so that he may at his option observe the test.

(4) Samples shall be taken over such a period or periods as are necessary to accurately determine the maximum emissions which will occur in a 24-hour period. No changes in the operation shall be made, which would potentially increase emissions above that determined by the most recent source test, until the new emission has been estimated by calculation and the results reported to the Administrator.

(5) All samples shall be analyzed and mercury emissions shall be determined within 30 days after the source test. All the determinations will be reported to the Administrator by a registered letter dispatched before the close of the next business day following such determination.

(6) Records of emission test results and other data needed to determine total emissions shall be retained at the source and made available for inspection by the Administrator, for a minimum of 2 years.

(7) Mercury chlor-alkali plants—cell room ventilation system.

(8) Stationary sources using mercury chlor-alkali cells may test cell room emissions in accordance with paragraph (c) (2) of this section or demonstrate compliance with paragraph (c) (4) of this section and assume ventilation emissions of 1,300 gms/day of mercury.

(9) Unless a waiver of emission testing is obtained under § 61.13, each owner or operator shall pass all cell room air in forced gas streams through stacks suitable for testing.

(10) Within 90 days of the effective date in the case of an existing source or a new source which has an initial startup date preceding the effective date; or

(11) Within 90 days of startup in the case of a new source which did not have an initial startup date preceding the effective date.

(12) The Administrator shall be notified at least 30 days prior to an emission test, so that he may at his option observe the test.

(13) Examples shall be taken over such a period or periods as are necessary to determine accurately the maximum emissions which will occur in a 24-hour period. No changes shall be made in the operation which would potentially increase emissions above that determined by the most recent stack test, until the new emission level has been estimated by calculation and the results reported to the Administrator.

(14) All samples shall be analyzed and mercury emissions shall be determined within 30 days after the stack test. Each determination shall be reported to the Administrator by a registered letter dispatched before the close of the next business day following such determination.

(15) Records of emission test results and other data needed to determine total

DU 001459

1302914

DBE

DUP 0501743

§ 61.54 Title 40—Protection of Environment

emissions shall be retained at the source and shall be made available, for inspection by the Administrator, for a minimum of 2 years.

(34 FR 824, Apr. 6, 1971, as amended at 43 FR 4352, Oct. 14, 1978)

§ 61.54 Sludge sampling.

(a) As an alternative means for demonstrating compliance with § 61.52 (b), an owner or operator may use Method 105 of Appendix B and the procedures specified in this section.

(1) Sludge test shall be conducted within 90 days of the effective date of these regulations in the case of an existing source or a new source which has an initial startup date preceding the effective date.

(2) Sludge test shall be conducted within 90 days of startup in the case of a new source which did not have an initial startup date preceding the effective date.

(b) The Administrator shall be notified at least 30 days prior to a sludge sampling test so that he may at his option observe the test.

(c) Sludge shall be sampled according to paragraph (c)(1) of this section. Sludge charging rate for the plant shall be determined according to paragraph (c)(2) of this section, and the sludge analysis shall be performed according to paragraph (c)(3) of this section.

(1) The sludge shall be sampled after dewatering and before incineration or drying, at a location that provides a representative sample of the sludge that is charged to the incinerator or dryer. Eight consecutive grab samples shall be obtained at intervals of between 15 and 60 minutes and thoroughly mixed into one sample. Each of the eight grab samples shall have a volume of at least 200 ml but not more than 400 ml. A total of three composite samples shall be obtained within an operating period of 24 hours. When the 24-hour operating period is not continuous, the total sampling period shall not exceed 72 hours after the first grab sample is obtained. Samples shall not be exposed to any condition that may result in mercury contamination or loss.

(2) The maximum 24-hour period sludge incineration or drying rate shall be determined by use of a flow rate measuring device that can measure the mass rate of sludge charged to the in-

cinerator or dryer with an accuracy of ± 5 percent over its operating range. Other methods of measuring sludge mass charging rates may be used if they have received prior approval by the Administrator.

(3) The handling, preparation, and analysis of sludge samples shall be accomplished according to Method 105 in Appendix B of this part.

(d) The mercury emissions shall be determined by use of the following equation:

$$E_{\text{Hg}} = 1 \times 10^{-4} \times Q$$

where

E_{Hg} —Mercury emissions, g/day.

Q —Mercury concentration of sludge on a dry solids basis, g/g (ppm).

Q —Sludge charging rate, kg/day.

(e) No changes in the operation of a plant shall be made after a sludge test has been conducted which would potentially increase emissions above the level determined by the most recent sludge test until the new emission level has been estimated by calculation and the results reported to the Administrator.

(f) All sludge samples shall be analyzed for mercury content within 30 days after the sludge sample is collected. Each determination shall be reported to the Administrator by a registered letter dispatched before the close of the next business day following such determination.

(g) Records of sludge sampling, charging rate determination and other data needed to determine mercury content of wastewater treatment plant sludges shall be retained at the source and made available, for inspection by the Administrator, for a minimum of 2 years.

(40 FR 4803, Oct. 14, 1975)

§ 61.55 Emission monitoring.

(a) Wastewater treatment plant sludge incineration and drying plants. All such sources for which mercury emissions exceed 1600 g/day, demonstrated either by stack sampling according to § 61.53 or sludge sampling according to § 61.54, shall monitor mercury emissions at intervals of at least once per year by use of Method 105 of Appendix B or the procedures specified in § 61.54(c) and (d). The results of monitoring shall be reported and retained according to § 61.53(d) (8) and (9), or § 61.54(f) and (g).

(40 FR 4202, Oct. 14, 1975)

Chapter 1—Environmental Protection Agency

App. A

APPENDIX A

National Emission Standards for Hazardous Air Pollutants

Compliance Status Information

1. SOURCE REPORT

INSTRUCTIONS: Owners or operators of sources of hazardous pollutants subject to the National Emission Standards for Hazardous Air Pollutants are required to submit the information contained in Section 1 to the appropriate U.S. Environmental Protection Agency Regional Office prior to 90 days after the effective date of any standards or amendments which require the submission of such information.

A list of regional offices is provided in 61.09.

A. SOURCE INFORMATION

1. **Identification/Location** - Indicate the name and address of each source.

1-2 Region 3-4 State 5-8 County 9-13 Source Number 14-16 17-19 NA 20-22 City Code 23-24 Source Name 25-26 City Code 27-28 State Address (Location of Plant) 29-30 State 31-32 City Name 33-34 State 35-36 State 37-38 State 39-40 State 41-42 State 43-44 State 45-46 State 47-48 State 49-50 State 51-52 State 53-54 State 55-56 State 57-58 State 59-60 State 61-62 State 63-64 State 65-66 State 67-68 State 69-70 State 71-72 State 73-74 State 75-76 State 77-78 State 79-80 State 81-82 State 83-84 State 85-86 State 87-88 State 89-90 State 91-92 State 93-94 State 95-96 State 97-98 State 99-100 State

Dep 1-10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

Dep 1-10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

2. **Contact** - Indicate the name and telephone number of the owner or operator or other responsible official whom EPA may contact concerning this report.

DUP 0501744

DU 001460

130291