

PLAINTIFF'S
EXHIBIT

07079.00

PROCEEDINGS
of
All Ohio Safety Congress

Held under the auspices of
THE INDUSTRIAL COMMISSION OF OHIO
and the direct management of
THE DIVISION OF SAFETY AND HYGIENE

Published under the authority
of
The Industrial Commission of Ohio

Deshler-Wallick Hotel
Columbus, Ohio
May 10, 11, 12
1938

THE F. J. HEER PRINTING CO.
Columbus, Ohio
1938

PLAINTIFF'S
EXHIBIT

WV-002429

LIST OF HONORARY VICE-PRESIDENTS

O. B. CHAPMAN, Director, Department of Industrial Relations, State of Ohio.
 JOHN E. RYDER, President, Columbus Chamber of Commerce, Columbus, Ohio.
 DON K. MARTIN, Secretary, Ohio Manufacturers' Association, Columbus, Ohio.
 THOS. J. DONNELLY, Secretary, Ohio Federation of Labor, Columbus, Ohio.
 THOS. J. DUFFY, former Chairman, Industrial Commission of Ohio, Columbus, Ohio.
 JUDGE LEE E. SKEEL, President, Cleveland Safety Council, Cleveland, Ohio.
 FRANK A. PURNELL, President, The Youngstown Sheet and Tube Company, Youngstown, Ohio.
 CHARLES R. HOOK, President, The American Rolling Mill Company, Middletown, O.
 MAJOR NORMAN A. IMRIE, President, Columbus Safety Council, Columbus, Ohio.
 BEN W. MARR, President and General Manager, Col. and So. Ohio Electric Co., Columbus, Ohio.
 S. P. BUSH, Columbus, Ohio.
 C. C. SLUSSER, Vice President, Goodyear Tire and Rubber Company, Akron, Ohio.
 LEWIS M. CROSLY, Vice President and General Manager, The Crosley Radio Corporation, Cincinnati, Ohio.
 CHARLES L. KELLER, Vice President, The Richardson Company, Lockland, Ohio.
 J. A. VOSS, Vice President in charge of Industrial Relations, Republic Steel Corporation, Youngstown, Ohio.
 E. M. BLAND, President, Zanesville Industrial Safety Council, Zanesville, Ohio.
 GEORGE W. SMITH, JR., Vice President, White Motor Company, Cleveland, Ohio.
 C. E. TORREY, General Manager, Ohio Power Company, Canton, Ohio.
 DONALD P. HESS, Assistant to the President, Timken Roller Bearing Company, Canton, Ohio.
 DR. O. P. GEIER, Director of Employee Relations, The Cincinnati Milling Machine Company, Cincinnati, Ohio.

C. H. PIPPERT, President, Middletown Safety Council, Middletown, Ohio.

C. R. STEINER, President, Lancaster Safety Council, Lancaster, Ohio.

HARRY EHRLICH, President, Marion Safety Council, Marion, Ohio.

D. S. LUNTZ, President, Scrap Iron and Steel Institute, Canton, Ohio.

C. A. HELSER, President, Newark Safety Council, Newark, Ohio.

EARL TROLL, President, Mansfield Safety Council, Mansfield, Ohio.

*D. M. CROVIN, President, Crovin China Co., Minerva, Ohio.

*Deceased

Chairman: TH
 dustrial Co:
 P. A. ALBERTY,
 WILLIAM ATTEL
 ERNEST AUGUST
 CLAUDE BAWDE
 FRED G. BENNE
 ARNOLD BILL, S
 America, N
 GEORGE V. BOLA
 C. S. BOWDEN,
 JOHN BREIDENB
 F. G. BRUCKLA
 W. S. BUCKLEY
 JAMES R. BYRU
 HARRY E. CAM
 Ohio.
 A. CLARK, The
 R. J. CLARK, C.
 S. H. CLOUSE, S
 A. C. COOK, Suy
 town, Ohio.
 H. E. CRAIN, S.
 DAVID CROOKS,
 R. J. DEATER, S
 THOS. J. DONN
 H. G. EHRET, I
 Relations, C
 E. A. ELLIS, Di
 L. L. EVERT, Ot
 ROBERT FEATHE
 R. H. FERGUSO:
 W. T. FILMER,
 Ohio.
 D. K. FINLEY,
 bus, Ohio.
 HARLEY J. GOU
 E. E. GRANT, V
 D. H. GROTHAU
 E. E. GROVER, C
 G. E. HART, Na
 R. T. HENDERSO
 H. H. HENRY,
 DON C. HUNTER
 Ohio.
 JOHN W. JOCKE
 land, Ohio.
 J. T. KIDNEY, M
 Akron, Ohio
 R. H. KRONE, S
 O. S. LEGG, Fed

COMMITTEES

Arrangements

Chairman: THOS. P. KEARNS, Superintendent, Division of Safety and Hygiene, Industrial Commission of Ohio, Columbus, Ohio.

P. A. ALBERTY, Secretary, Ohio Fuel Gas Co., Columbus, Ohio.

WILLIAM ATKINSON, Wheeling Steel Corp., Portsmouth, Ohio.

ERNEST AUGUSTUS, Safety Director, Mead Corp., Chillicothe, Ohio.

CLAUDE BAWDEN, Underwriters Laboratories, Youngstown, Ohio.

FRED G. BENNETT, Safety Director, Buckeye Steel Castings Co., Columbus, Ohio.

ARNOLD BILL, Secretary-Treasurer, Ohio State Council of Carpenters and Joiners of America, North Olmsted, Ohio.

GEORGE V. BOLGER, Cleveland Plain Dealer, Cleveland, Ohio.

C. S. BOWDEN, Ohio Public Service Co., Alliance, Ohio.

JOHN BREIDENBACH, City Commissioner, Dayton, Ohio.

F. G. BRUCKLACHER, Ohio Oil Co., Findlay, Ohio.

W. S. BUCKLEW, Chief, Upper Arlington Fire Department, Columbus, Ohio.

JAMES R. BYRUM, Safety Advisor, American Rolling Mill Co., Middletown, Ohio.

HARRY E. CAMERON, General Superintendent, Cambridge Collieries Co., Cambridge, Ohio.

A. CLARK, The Safety Clothing Co., Cleveland, Ohio.

R. J. CLARK, Crosley Radio Corp., Cincinnati, Ohio.

S. H. CLOUSE, Springfield Purity Dairy, Springfield, Ohio.

A. C. COOK, Superintendent, Safety, Welfare and Claims, Carnegie Steel Co., Youngstown, Ohio.

H. E. CRAIN, Safety Director, Ohio Power Co., Canton, Ohio.

DAVID CROOKS, Kroger Grocery & Baking Co., Cincinnati, Ohio.

R. J. DEAYER, Safety Inspector, Pittsburgh Plate Glass Co., Zanesville, Ohio.

THOS. J. DONNELLY, Secretary, Ohio Federation of Labor, Columbus, Ohio.

H. G. EHRET, Division of Factory & Building Inspection, Department of Industrial Relations, Columbus, Ohio.

E. A. ELLIS, Director of Welfare, Wheeling Steel Corp., Wheeling, W. Va.

L. L. EVERT, Ohio Bell Telephone Co., Cleveland, Ohio.

ROBERT FEATHERINGHAM, Warner Collieries Co., Wolf Run, Ohio.

R. H. FERGUSON, Manager of Safety, Republic Steel Corp., Cleveland, Ohio.

W. T. FILMER, Supervisor of Safety, Youngstown Sheet & Tube Co., Youngstown, Ohio.

D. K. FINLEY, Secretary, Columbus Safety Council, Chamber of Commerce, Columbus, Ohio.

HARLEY J. GOULD, Ferro Concrete Construction Co., Cincinnati, Ohio.

E. E. GRANT, Vice President, Crystal Tissue Co., Middletown, Ohio.

D. H. GROTHAUS, Subscription Manager, The McCall Co., Dayton, Ohio.

E. E. GROVER, Columbus & Southern Ohio Electric Co., Columbus, Ohio.

G. E. HART, National Refining Co., Findlay, Ohio.

R. T. HENDERSON, Safety Engineer, Standard Oil Co., Cleveland, Ohio.

H. H. HENRY, Safety Director, Otis Steel Co., Cleveland, Ohio.

DON C. HUNTER, Personnel Department, Oxford Miami Paper Co., West Carrollton, Ohio.

JOHN W. JOCKEL, Ohio Conference of Bricklayers, Masons & P. I. U., East Cleveland, Ohio.

J. T. KIDNEY, Manager, Employees Service Division, Goodyear Tire & Rubber Co., Akron, Ohio.

R. H. KRONE, Safety Director, Union Gas & Electric Co., Cincinnati, Ohio.

O. S. LEGG, Federal Printing Co., Columbus, Ohio.

GEORGE J. LEROUX, Assistant Manager, National Malleable & Steel Castings Co., Cleveland, Ohio.
 J. D. LYLE, Personnel Director, Fisher Body Cleveland Division, Cleveland, Ohio.
 DON K. MARTIN, Secretary, Ohio Manufacturers Association, Columbus, Ohio.
 W. J. MCCARTER, Superintendent of Employment & Training, Cleveland Railways Co., Cleveland, Ohio.
 J. M. MCCLOY, James B. Clow & Sons, Newcomerstown, Ohio.
 GEORGE H. MCCONAHY, American Steel Foundries, Alliance, Ohio.
 F. R. MCLEAN, Safety & Insurance Department, Socony-Vacuum Oil Co., Detroit, Mich.
 E. E. MCPHERSON, Pure Oil Co., Heath Refinery, Newark, Ohio.
 RAY S. METZGER, Director of Claims & Safety, Toledo Edison Co., Toledo, Ohio.
 URBAN L. MOLER, Inland Manufacturing Co., Dayton, Ohio.
 R. W. MORSE, Firestone Tire & Rubber Co., Akron, Ohio.
 BUELL W. NUTT, President, Safety Equipment Service Co., Cleveland, Ohio.
 S. R. OLSEN, Champion Paper & Fiber Co., Hamilton, Ohio.
 A. W. OLVEY, Fairfield Paper Co., Baltimore, Ohio.
 JOHN OWENS, President, District No. 8, United Mine Workers of America, Columbus, Ohio.
 H. W. PAINTE, Director, Vocational Teacher Improvement Service, University of Toledo, Toledo, Ohio.
 J. G. POLM, Safety Director, Goodyear Tire & Rubber Co., Akron, Ohio.
 F. S. POPE, The Mead Corp., Chillicothe, Ohio.
 W. W. REIS, Ohio Fuel Gas Co., Springfield, Ohio.
 KATHRYN B. REYNOLDS, American Education Press, Columbus, Ohio.
 GILBERT M. RICKETTS, Valet Cleaners & Storage, Columbus, Ohio.
 FRED I. ROWE, W. L. Johnson Construction Co., Hicksville, Ohio.
 WILLIAM ROY, Safety Director, Hanna Coal Co., St. Clairsville, Ohio.
 W. M. SALLE, New Method Laundry Co., Columbus, Ohio.
 W. L. SCHNEIDER, Safety Engineer, B. F. Goodrich Co., Akron, Ohio.
 J. L. SIVARD, Safety Director, Wheeling Steel Corp., Steubenville, Ohio.
 E. C. SKOTTOWE, H. H. Meyer Packing Co., Cincinnati, Ohio.
 U. S. SLEMMER, American Telephone & Telegraph Co., Cleveland, Ohio.
 CARL L. SMITH, Managing Director, Cleveland Safety Council, Cleveland, Ohio.
 FRANK G. SMITH, Asst. General Superintendent, Sunday Creek Coal Co., Nelsonville, Ohio.
 RUSSELL D. SQUIBB, Y & O Coal Co., Martins Ferry, Ohio.
 J. P. SUTTON, Manager of Industrial Relations, Ohio Oil Co., Findlay, Ohio.
 B. H. TAYLOR, Personnel Director, Diamond Alkali Co., Painesville, Ohio.
 W. S. TAYLOR, Franklin-American Laundry & Zoric Dry Cleaning Co., Columbus, Ohio.
 S. TRAINER, Sebring Fire Department, Sebring, Ohio.
 R. REID VANCE, Secretary, Graphic Arts Federation, Columbus, Ohio.
 J. A. VOSS, Vice President in Charge of Industrial Relations, Republic Steel Corp., Youngstown, Ohio.
 CABLE WAGNER, Secretary, Wagner Manufacturing Co., Sidney, Ohio.
 F. W. WEBER, Standard Lime & Stone Co., Woodville, Ohio.
 R. M. WEIMER, Dayton Rubber Mfg. Co., Dayton, Ohio.
 HOMER J. WEEKS, Manager, Safety, Sanitation & Welfare, American Steel & Wire Co., Cleveland, Ohio.
 S. F. WHITESSEL, Franklin Board & Paper Co., Franklin, Ohio.
 O. W. WISWELL, Executive Secretary, Ohio Coal Conference, Inc., Columbus, Ohio.
 FREDERICK D. WITMER, JR., Ohio Hydrate & Supply Co., Woodville, Ohio.
 JOSEPH H. ZUCKER, Cleveland Plain Dealer, Cleveland, Ohio.

Chairman: CARL L. SMITH

Chairman: BUELL W. NUTT
land, Ohio.

Chairman: H. G. EURE
Inspection, Department

Chairman: H. M. PAUL,
and Hygiene, Industri

Chairman: A. L. ROSE,
Industrial Commissio

Chairman: C. C. BEASLY
Commission of Ohio.

Industrial C

BUREAU

Chairman: GEORGE P. M
Staff of

C. G. BARTHE.....
 H. P. HEYNE.....
 MACKIN KELLY.....
 P. B. MARTENS.....
 R. M. ANDERSON.....
 GEORGE P. MEEHAN.....
 Lewis C. Lewis.....
 D. M. RYAN.....
 H. L. SAIN.....
 W. E. OBETZ.....
 P. V. WADDELL.....
 JAMES FLUKER.....
 ODE J. GRUBB.....
 R. C. JONES.....
 JAMES P. SCANLON.....
 SIDNEY SMITH.....
 A. R. TAUBMAN.....
 BEN T. GODFREY.....

ROBT. W. NOTT, Su

Cable & Steel Castings Co.

Division, Cleveland, Ohio.
 Division, Columbus, Ohio.
 Division, Cleveland Railways.

Ohio.
 Division, Ohio.
 Vacuum Oil Co., Detroit.

Ohio.
 Division Co., Toledo, Ohio.

Ohio.
 Cleveland, Ohio.

Division of America, Columbus.

Division Service, University of
 Akron, Ohio.

Ohio.
 Ohio.
 Ohio.
 Ohio, Ohio.

Ohio.
 Ohio, Ohio.

Ohio.
 Ohio, Cleveland, Ohio.
 Ohio Coal Co., Nelsonville.

Findlay, Ohio.
 Ohio, Ohio.
 Ohio, Columbus.

Ohio.
 Republic Steel Corp.

Ohio.

American Steel & Wire

Inc., Columbus, Ohio.
 Ohio, Ohio.

Program

Chairman: CARL L. SMITH, Managing Director, Cleveland Safety Council.

Exhibits

Chairman: BUZZ W. NUTT, President, Safety Equipment Service Company, Cleveland, Ohio.

Entertainment

Chairman: H. G. EHRET, Safety Director, Division of Factory and Building and Inspection, Department of Industrial Relations of Ohio.

Publicity

Chairman: H. M. PAUL, Supervisor of Printing and Publications, Division of Safety and Hygiene, Industrial Commission of Ohio.

Reception

Chairman: A. L. ROSE, Assistant Superintendent, Division of Safety and Hygiene, Industrial Commission of Ohio.

Registration

Chairman: C. C. BEASOR, Statistician, Division of Safety and Hygiene, Industrial Commission of Ohio.

Industrial Commission Booths 4 and 5 in Safety Exhibit

BUREAU OF INFORMATION ON SAFETY, COMPENSATION AND CLAIMS SAFETY

Chairman: GEORGE P. MEEHAN, Mechanical Engineer.

Staff of the Division of Safety and Hygiene of the Industrial Commission of Ohio

C. G. BARTH.....	Safety Engineer
H. P. HEYNE.....	Safety Engineer
MACKIN KELLY	Safety Engineer
P. B. MARTENS.....	Safety Engineer
R. M. ANDERSON.....	Structural Engineer
GEORGE P. MEEHAN.....	Mechanical Engineer
Lewis C. Lewis.....	Mining Engineer
D. M. RYAN.....	Mining Engineer
H. L. SAIN.....	Special Representative
W. E. OBETZ.....	Medical Director
P. V. WADDELL.....	Examiner (Professional)
JAMES FLUKER.....	Special Investigator
ODE J. GRUBB.....	Special Investigator
R. C. JONES.....	Special Investigator
JAMES P. SCANLON.....	Special Investigator
SIDNEY SMITH.....	Special Investigator
A. R. TAUDMAN.....	Special Investigator
BEN T. GODFREY.....	Special Investigator

COMPENSATION

ROBT. W. NOTT, Supervisor of Information, Industrial Commission of Ohio.

EXHIBITORS

Ninth All Ohio Safety Congress

Deshler-Wallick Hotel

Columbus, Ohio

May 10, 11, 12, 1938

Porter Cable Machine Co., Syracuse,
New York

Safway Steel Scaffold of Ohio, Fostoria,
Ohio.

C. H. Dockson Co., Detroit, Mich.

The Kimball Safety Products Co., Cleve-
land, Ohio.

The Industrial Commission of Ohio, Di-
vision of Safety and Hygiene.

Safety Engineering Magazine, Division
of Alfred M. Best Co., Inc., New York,
N. Y.

Chicago Eye Shield Co., Chicago, Ill.

The Geo. L. Williams Co., Cleveland,
Ohio.

M. E. Cunningham Co., Pittsburgh, Pa.

The Strauss Co., Pittsburgh, Pa.

Willson Products, Inc., Reading, Pa.

Acme Safety Products Co., Akron, Ohio.

Safety First Shoe Co., Holliston, Mass.

Mine Safety Appliances Co., Pittsburgh,
Pa.

American Optical Co., Cleveland, Ohio.

Burroughs Wellcome & Co., Inc., New
York, N. Y.

Harry L. Morgan Co., Columbus, Ohio.

Pulmosan Safety Equipment Corp.,
Brooklyn, N. Y.

Industrial Gloves Co., Danville, Ill.

Davis Emergency Equipment Co., Inc.,
New York, N. Y.

The Safety Clothing Co., Cleveland,
Ohio.

Wiesman Mfg. Co., Dayton, Ohio.

W. S. Schuyler Mfg. Co., Springfield,
Ohio.

Safety Equipment Service Co., Cleveland,
Ohio.

Elliott Service Co., New York, N. Y.

The Governor's Safety Coordinating Bu-
reau, Columbus, Ohio.

Melflex Products Co., Akron, Ohio.

Panther-Panco Co., Chelsea, Mass.

H. W. Peters Co., Columbus, Ohio.

The M. F. Murdock Co., Akron, Ohio.

Pyrene Mfg. Co., Chicago, Ill.

Bauer Mfg. Co., Wooster, Ohio.

Lehigh Safety Shoe Co., Allentown, Pa.

Safeguard Electric Co., Inc., Brooklyn,
N. Y.

Brown Shoe Co., St. Louis, Mo.

Burroughs Adding Machine Co., Detroit,
Mich.

The Positive Safety Mfg. Co., Cleveland,
Ohio.

Surty Mfg. Co., Chicago, Ill.

The Fyr-Fyter Co., Dayton, Ohio.

Keystone View Co., Meadville, Pa.

Flohr Mfg. Co., Buffalo, N. Y.

H. Childs & Co., Inc., Pittsburgh, Pa.

The Dayton Safety Ladder Co., Cincin-
nati, Ohio.

Chas. B. Timmons, Middletown, Ohio.

Shepherd Safety Shoe Corp., Chicago, Ill.

ClerSite Co., New York, N. Y.

Sugar Beet Products Co., Saginaw, Mich.

A. Schrader's Son, Brooklyn, N. Y.

International Shoe Co., St. Louis, Mo.

Columbus Glove Mfg. Co., Columbus,
Ohio.

Guardian Chemicals, Inc., Columbus,
Ohio.

Youngstown Safety Supply Co., Youngs-
town, Ohio.

Williams & Co., Inc., Pittsburgh, Pa.

Metropolitan Life Insurance Co., New
York, N. Y.

The Surety Rubber Co., Carrollton, Ohio.

Standard Safety Equipment Co., Chi-
cago, Ill.

Thos. W. Ruff & Co., Columbus, Ohio.

Cyril Ainsworth

H. W. Arlin....

Ernest Augustus

L. E. Bailey....

Charles G. Bart

Claude Bawden

J. W. Beall....

Ernest W. Beck

R. H. Bennett.

Thomas Bentley

James Berry ..

George Biechler

Arnold Bill ...

Col. Lynn Blac

Will T. Blake.

Walter J. Bloo

W. R. Botkins.

C. B. Boulet..

Otto W. Brac

H. A. Bradley

John Breidenb

Arthur F. Bri

James R. Byru

James G. Caff

Harry J. Calla

Charles J. Cas

O. B. Chapma

J. Leo Child..

William P. C.

S. H. Clouse.

O. R. Corneli

David Crooks

Al. Dalton ..

Governor Ma

Homer A. De

Kenneth L. E.

W. R. Elliot.

H. S. Ernst.

L. L. Evert..

Joseph E. Fa

Kenneth L. :

W. L. Faulke

Robert Feath

R. Fenner ...

R. H. Fergus

W. T. Filmer

D. Knight F

Glenn Gardin

INSURANCE SOCIETY OF NEW YORK, INC.

PAGE
318

PAGE

PUBLIC UTILITIES

<i>Chairman:</i> W. W. REIS, The Ohio Fuel Gas Co., Springfield, Ohio.....	385
<i>Vice Chairman:</i> C. S. BOWDEN, Ohio Public Service Co., Alliance, Ohio.	
"DO BARRICADES BARRICADE?":.....	383
Robert Radbone, The Ohio Fuel Gas Co., Toledo, Ohio.	
DISCUSSION:	387
"DOG BITES MAN":.....	389
C. N. Rakestraw, The Cleveland Electric Illuminating Co., Cleveland, Ohio.	
DISCUSSION:	393
"INTANGIBLES TO SAFETY":.....	397
Paul C. Martin, Attorney at Law, Springfield, Ohio.	

RUBBER

<i>Chairman:</i> R. M. WEIMER, Dayton Rubber Manufacturing Co., Dayton, Ohio...	408
<i>Vice Chairman:</i> R. W. MORSE, Firestone Tire & Rubber Co., Akron, Ohio.	
<i>Secretary:</i> URBAN L. MOLER, Inland Manufacturing Co., Dayton, Ohio.	
REPORT OF NOMINATING COMMITTEE:.....	408
"SAFEGUARDING THE WORKER'S HEALTH":.....	409
E. H. Gilman, Manager, Health Laboratory, Goodyear Tire and Rubber Co., Akron, Ohio.	
DISCUSSION OF PREVIOUS ADDRESS:.....	413
Led by J. G. Polm, Safety Director, Goodyear Tire & Rubber Co., Akron, Ohio.	
"SAFETY PROGRESS IN THE RUBBER INDUSTRY DURING THE PAST TWENTY YEARS":	422
E. W. Beck, Safety Supervisor, United States Rubber Products, Inc., New York, N. Y.	

QUARRIES, CEMENT AND LIME

<i>Chairman:</i> FREDERICK D. WITMER, JR., Ohio Hydrate & Supply Co., Woodville Ohio	429
"HAZARDS AND THE PREVENTION OF ACCIDENTS IN QUARRY OPERATIONS":.....	429
G. H. Rutherford, Personnel Manager, Basic Dolomite, Inc., Maple Grove, Ohio.	
"INHALATION OF DUST AND CONTROL OF DUST HAZARDS".....	432
William C. James, Safety Engineer, Portland Cement Association, Chicago, Ill.	
ROUND TABLE DISCUSSION:	437
"Our Most Serious Accident Hazards."	

PETROLEUM

<i>Chairman:</i> F. R. McLEAN, Socony-Vacuum Oil Co., Detroit, Mich.....	441
<i>Vice Chairman:</i> E. E. McPHERSON, Pure Oil Co., Heath, Ohio.	
<i>Secretary:</i> G. E. HART, National Refining Co., Findlay, Ohio.	

INHALATION OF DUST AND CONTROL OF DUST HAZARDS

MR. WILLIAM C. JAMES,

Safety Engineer, Portland Cement Association, Chicago, Ill.

Mr. Chairman, gentlemen:

Confusion still seems to be the dominant keynote outside the research laboratory in this question of occupational "dusty-lung" diseases. Terms such as pneumoconiosis, silicosis, siderosis, chalicosis and even silicatosi are bandied about indiscriminately and often without meaning. Usually, the mere mention of dust in a conversation inspires visions of high mortality, high sickness rates and a long trail of serious hazards.

The term "pneumoconiosis" is often interpreted to mean a disease of the lungs, resulting from dust inhalation. Actually, it means simply "dusty lung." In the early history of lung disease it was thought that all dusts caused the same disease reaction and this term was applied to that disease. Modern research has demonstrated that most dusts are harmless. The term "pneumoconiosis" therefore should assume its primary meaning and when applied to an individual can rightly be interpreted only as indicating that the person has inhaled dust. Dr. Leroy U. Gardner, referring to non-specific pneumoconiosis says, "Such changes have no clinical significance and produce neither symptoms nor interference with working capacity. They are of no more importance than the callouses on the palms of the hands." Any person in any environment may develop this condition. Even office workers in large industrial communities may show X-ray evidence of having inhaled dust, but such evidence is meaningless as far as health is concerned.

Of the various strictly industrial dusts, coal and iron ore are perhaps most spectacular in their appearance in the lung. Early investigators, and by this I mean investigators in the first 16 or 17 centuries of the Christian era, were so impressed by the lung pigmentation of workers in iron ore and coal that they credited these substances with a prominent part in the development of lung disease. Modern research has demonstrated that this coloring of the lung tissue is, in itself, of no significance.

Only two substances are now known to cause a definite lung disease, namely, asbestos and uncombined silica. Research men who have dealt specifically with dust diseases have long recognized that dusts with a low silica content are free from health hazards. Compensation insurance actuaries are also accepting the fact, as is demonstrated by the rates they have set for the cement industry. Cement quarries contain mostly limestone, in which quartz constitutes less than 10% of the total rock formation. In California, cement plants and quarries have been entirely excluded from the occupational disease rate schedule. Indiana and Illinois both have all-inclusive occupational disease laws. In these states, a rate of only five cents has been set for both cement mills and quarry operations. That this rate is based on a known absence of hazard is evident when it is considered that quarries other than cement quarries have been assigned a rate of \$1.14 in Indiana and \$1.20, which is 24 times the cement rate, in Illinois.

In Michigan, which has a schedule type law, the cement industry's rate is two cents. Other quarries have been assessed at the rate of forty cents in this state. New York State, which has a liberal combined schedule, and all-inclusive law, has set a rate of seven cents for the cement quarries. Quarries other than cement have been given a rate of \$1.07.

Inhalation of free silicon dioxide (usually quartz) in excessive quantities over a long period of time causes the disease, silicosis. You will note particularly that three factors are necessary to the causation of this disease:

1. Fre
- gre
2. Ex
3. Lor

Particu
con dioxide.
says—not c
(which is c
confusion h
honored pr
oxides of t
cement will
this silica is
been conclus
exposure to
of free silic
common for
and chert, n
be less severe

The lim
this do not
terial will v
at Saranac
per cent qua
cent quartz v

Dr. Gar
does not fra
clusions as t
dence on an
ing zone of

The sec
quartz that
easily determ
quartz conter

Dr. A. J
Company, an
mary of wha
fore The Ar
1937. He sa

In the
limits of dus
dust content
working conc
industry if th
with the help
and applicable
right direction

This rec

The Nat
million partic
siliceous dusts
by different i
recommended

ARDS

h laboratory
neumoconio-
discriminately
conversation
of serious

of the lungs,
g." In the
same disease
has demon-
efore should
tly be inter-
U. Gardner,
nical signifi-
acity. They
ands." Any
workers in
ed dust, but

erhaps most
this I mean
so impressed
redited these
Modern re-
tself, of no

ase, namely,
ly with dust
e free from
e fact, as is
ent quarries
e total rock
cluded from
all-inclusive
been set for
n a known
than cement
is 24 times

rate is two
this state
ve law, has
than cement

unities over
cularly that

1. Free silicon dioxide (usually quartz), in particles less than 10 microns in greatest diameter.
2. Excessive concentration.
3. Long period of exposure.

Particular emphasis should be given to these limiting factors: First, "free silicon dioxide, less than 10 microns in greatest diameter." This means exactly what it says—not calcium carbonates, not iron oxides, not silicates, not even silicon carbide (which is carborundum) but free silicon dioxide. It seems probable that no little confusion has arisen in the minds of plant superintendents and engineers of the time-honored practice by industrial chemists of reporting an analysis in terms of the oxides of the components. For example, a typical reported analysis of Portland cement will show a total silica content of about twenty per cent. Actually, all of this silica is combined in the form of entirely harmless calcium silicates, and it has been conclusively demonstrated that it is utterly impossible to acquire silicosis from exposure to cement dust. It should be mentioned that quartz is not the only form of free silica, though it is apparently the most dangerous and certainly the most common form. The various amorphous forms of the compound, such as flint, tripoli and chert, may also produce the silicotic reaction in the lung, but they are known to be less severe in their effect.

The limiting size of ten microns is also of importance. Particles larger than this do not reach the lungs. Furthermore, the percentage of quartz in a given material will vary greatly with the particle size. A petrographic examination of shale at Saranac Laboratory under Dr. L. U. Gardner's direction, recently revealed 20 per cent quartz. In a special fraction containing only large particles, 40 to 50 per cent quartz was found.

Dr. Gardner writes, "this is obviously due to the fact that quartz is so hard it does not fracture into fine particles." It must, therefore, be emphasized that conclusions as to the hazard existent in a dusty operation cannot be based with confidence on an analysis of the parent rock. Only an analysis of the dust in the breathing zone of the operator will give an accurate picture of conditions.

The second limiting factor is concentration. The exact amount of air-borne quartz that constitutes a dangerous concentration in any particular industry is not easily determined, nor is there as yet any substantial agreement as to what limits of quartz content should be observed.

Dr. A. J. Lanza, Assistant Medical Director of the Metropolitan Life Insurance Company, an outstanding authority on the silicosis problem, gave an excellent summary of what needs to be known about dust concentration in his paper presented before The American Institute of Mining and Metallurgical Engineers, in February, 1937. He said:

"In the present state of our knowledge, it is not possible to establish permissible limits of dustiness for all dusty industries or processes as the variation both in the dust content and in external modifying conditions is so extreme. In mining, however, working conditions are fairly constant and it would be extremely valuable to the industry if the various mining companies that face a silica hazard would establish, with the help of the proper governmental authorities, tentative standards practicable and applicable for their own mines. Some have done so and it is a long step in the right direction."

This recommendation might well be extended to other industries.

The National Silicosis Conference tentatively established a maximum of five million particles per cubic foot as a safe quartz concentration in the case of highly siliceous dusts. This standard is subject to modification as more data are developed by different industries. The National Silicosis Conference report also says, "It is recommended that clinical and engineering studies be carried out as rapidly as pos-

sible to establish the necessary scientific data upon which we may base practical and effective regulatory standards." The report then states that knowledge of three factors is necessary for establishing safe concentration of atmospheric dust:

1. The relative number and size of the free silica and the other particles suspended at breathing levels in the different parts of the industrial atmosphere.

2. The proportion of the workmen's time actually spent in the various dust concentrations.

3. The effects of exposure to environment, as revealed by the occupational and medical histories of old employees, by physical examination and by the roentgenological appearances of their lungs.

Through a knowledge of these three factors, any industry can discover what, if any, hazard it has and what preventive measures are needed. For the past two years, under the direction of Dr. Leroy U. Gardner of the Saranac Laboratory for the Study of Tuberculosis, the cement industry has been making a careful estimate of the health of its workers, according to the plan just outlined. Many of the statements in this paper regarding the effect of mixed or non-siliceous dusts have been based on the findings of these studies.

One of the outstanding conclusions a student of these researches in the cement industry will reach is that concentrations of free silica appreciably higher than the maximum specified by the Silicosis Conference are safe if the silica constitutes a moderate proportion of the total dust. Apparently, a mixture of silica with other minerals, if the other minerals are predominant, tends to inhibit the effect of the silica in the lung. It is not yet possible to recommend, without reservation, the dilution of silica with other dusts as a protective measure. It is far better to remove the dust from the atmosphere. Nevertheless, it is significant that in the Portland cement industry, where a high concentration of raw material dust containing up to 10 per cent of free silica is sometimes found, the X-rays and physical examinations reveal no pathological lung condition attributable to dust.

Although no agreement has been reached as to the maximum safe concentration of free silica in the presence of harmless dusts, agreement as to good housekeeping limits is practically unanimous. Industries with a dusty process, even though dusts are harmless, should endeavor to reach a concentration in the neighborhood of 100 million particles per cubic foot of air in the breathing zone of the workers, in the interests of comfort and increased efficiency.

The third factor in the development of silicosis is duration of exposure. The problem of exposure resolves itself into two parts. First, what proportion of the workers' time is actually spent in the dusty atmosphere? It is evident that a hazardous dust will not affect a man unless he is actually exposed to it and will not have as great an effect on a man who is exposed to it one hour a day as on a man continuously exposed.

The United States Public Health Service has developed a formula for calculating the actual exposure in terms of particle hours. They recommend, in Bulletin 217, "The Determination and Control of Industrial Dust," that the particle concentration in any area be multiplied by the number of hours an employee works in that area; that this product be calculated for each hour of the working day and that the total of these products be divided by the number of working hours to give the equivalent of continuous exposure during the day.

For example, a man may spend two hours a day in a concentration of 200 million particles per cubic foot; three hours in a concentration of 10 million particles; one and three-quarter hours in a concentration of 40 million particles and 15 minutes in concentration 1,200 million particles. The man's exposure would be calculated:

Hours
per day
2
2
3
2 1/4
1/4

Total Hours 8

800 particle hours in 8

8 ho

The application of from a study of conc plant atmospheric dust by the P. H. S. meth greatest.

How long does it be equivocal. Much respiratory passages usual protective me normal nasal and bro by pneumonia or tub all familiar with the resistance against tu dentally, suggests one other dusts. Medica lung resemble the les tuberculosis and, at The seriousness of significant quantities nostic symptoms are reveal the presence o the Metals Sections c from silicosis is not silicosis, uncomplica seldom pronounced e deprived of an oppo shows some signs o neering methods, of simply because of a fied out of all prop do not produce the t to tuberculosis. In 1700 employees reve or quiescent. Studi of mills in the inc tuberculosis of 0.0 mortality rate of 0 culosis' Association The various fa silicosis, if we may

Hours per day	Dust Concentration	Particle-hours (millions)
a	b	a and b
2	200	400
3	10	30
24	40	110
1	1040	260
Total Hours 8		800

800 particle hours in millions per cubic foot

8 hours

= 100 million particles per cubic foot
daily exposure

The application of this formula in a practical problem is apparent. If you find, from a study of concentration and silica content, that in two or three areas in your plant atmospheric dust exceeds safe limits, you will make an analysis of the exposure by the P. H. S. method and attack first that point where employee exposure is the greatest.

How long does it take silicosis to develop? The answer to such a question must be equivocal. Much depends on the physical condition of the worker. A man whose respiratory passages have been damaged so that dust is not readily excluded by the usual protective mechanism, may contract silicosis more readily than a man with normal nasal and bronchial passages. Also a man whose lungs have been damaged by pneumonia or tuberculosis may develop silicosis more quickly. We are probably all familiar with the reverse of this; i.e., that the man with silicosis has much less resistance against tuberculosis than a man with unaffected lungs. This fact, incidentally, suggests one of the outstanding differences between the action of silica and other dusts. Medical authorities state that not only does the silicotic lesion in the lung resemble the lesion in tuberculosis, the silica actually stimulates the activity of tuberculosis and, at the same time, conceals its symptoms until it is far advanced. The seriousness of such a condition may readily be imagined. A tubercular with significant quantities of silica in his lungs may be rapidly getting worse, yet diagnostic symptoms are often lacking. Frequently only a careful X-ray examination can reveal the presence of tuberculosis in a silicotic. Mr. P. N. Bushnell, speaking before the Metals Sections of this Congress last year, emphasized the fact that the real danger from silicosis is not silicosis at all, but tuberculosis. First or even second degree silicosis, uncomplicated by tuberculosis, usually causes relatively slight disability, seldom pronounced enough to interfere with working capacity. No worker should be deprived of an opportunity to earn a living at his regular job just because his X-ray shows some signs of nodulation. The job should be cleaned up by approved engineering methods, of course, but discharge of workers who are perfectly capable, simply because of a non-symptomatic condition which hysterical opinion has magnified out of all proportion, is certainly not the solution of the problem. Inert dusts do not produce the typical nodular lesion, nor do they cause any increased susceptibility to tuberculosis. In the cement industry, for example, only 4% of the X-rays of 1700 employees revealed old tuberculosis lesions and 96% of these lesions were healed or quiescent. Studies of absenteeism over a two-year period, covering the majority of mills in the industry, confirms the X-ray evidence. The mortality rate from tuberculosis of 0.07 per 1000 employees in 1937 is only 8% of the tuberculosis mortality rate of 0.87 per 1000 employed males established by the National Tuberculosis Association in a comprehensive survey in 1930.

The various factors which may influence the length of time required to develop silicosis, if we may recapitulate, are (1) intensity of dust concentration, (2) pro-

portion of free silica in the dust, (3) proportion of working time employees spend in the dusty atmosphere, (4) condition of employee's upper respiratory tract, and (5) condition of employee's lungs.

In any case, it is extremely doubtful that first-stage silicosis will develop in less than seven years, except in the presence of active tuberculosis. Dr. Gardner says that for silicosis to develop in five years, the exposure must be intense. The National Silicosis Conference report, to which we have previously referred, says with admirable skepticism, "There are reports of a few cases of the disease developing in as short a period as one and one-half years. In these instances, the individuals were exposed to excessive concentrations of extremely fine silica in almost a pure state." The report then states that exposures to low concentrations of silica may sometimes continue for thirty years before the condition develops to the stage where it can be called silicosis. In such cases, possibly another 15 or 20 years would be needed before any disability would be noticed. A great majority of the cases have had at least seven years' exposure. Thus it will be seen that silicosis is a very slowly developing disease, which, in the absence of infection, is not especially dangerous. In the presence of infection, however, the picture may be different.

No attempt has been made to separate the two sections of this paper, as indicated by the title, since the discussion of the problem is too intimately bound up with the methods of solving it. There are, however, some details of prevention which, for the sake of completeness, should be mentioned.

It might be worth while to think about the methods of determining dust concentrations. The quick sampling, easy counting devices on the market now probably fill a definite need, but their use is not altogether an unmixed blessing. The standards mentioned in this paper are all based on the United States Public Health Service's impinger technique with light field count. It is a complex technique requiring skill and experience to operate successfully, but it is the standard counting method in the United States and results of short-cut methods have not been shown to be correlative with it. After dust control has been instituted and the impinger technique has shown that concentrations are within safe limits, a simpler technique might be permitted for periodic checks on the efficiency of the control system. But don't be surprised if your counts with the simplified technique soar way above the impinger counts. The dark field illumination will uncover a large number of particles, apparently too small to have any effect, that are screened out by light field methods. The result is similar to the effect of a strong beam of light in a dark room. This difficulty can be overcome to some extent by taking impinger samples and samples by the other technique simultaneously, as soon as dust control equipment is installed, thus getting as much correlation as possible between the two techniques at the beginning.

A general paper of this type is not a suitable place to discuss the relative merits of different types of dust control systems. There are, though, a few principles which can be properly mentioned. Wherever possible, dust should be removed at its source, before it reaches the workroom atmosphere. Methods of accomplishing this vary with the process and should be decided upon by competent engineers after a careful study. In milling processes, closed, dust-tight systems with adequate separators and collectors may be adequate. Water sprays are sometimes effective where they can be used. In the quarry wet drilling is often all that is necessary to bring concentrations down to safe limits. Sometimes more elaborate dust traps are needed, either independently or conjunctly with wet drills.

Some processes are not amenable to control at the source. In such cases employees should be required to use respirators or masks of approved type. All of these methods have their place. The right one for each location must be determined by a thorough engineering survey.

The importance of good housekeeping cannot be too strongly emphasized. Much

of the dust nuisance can be eliminated by good housekeeping programs. The advantage, in addition, the atmosphere

Medical control is not available in the case of employment examination applicants.

In this paper we have pointed out the problem. We have, first, diseases, silicosis and a

We have pointed out three must be present:

1. Uncombined silica, usually quartz.

2. Sufficiently high concentration is set at five microns in greatest diameter. Studies in materials, appreciably higher concentrations of limestone, are interesting.

3. Exposure by inhalation of silica of the

The influence of dust on this disease. The stages, usually results of the working environment as long as he is free from

Methods of control examinations, removal of dust and the use of respirators in the atmosphere is not possible.

It should be emphasized that silicosis is a hazard to the physician who is interested in

Dr. A. R. Riddell, of the fields of Ontario has squared up to the engineering in importance. Exclusively through the elimination of dust by the engineer. Engineers have that the occurrence of silicosis cease entirely during the (Applause.)

CHAIRMAN WITMER: Will you please take over

Dr. OBETZ: Medical anything to add to the questions that may be hazards that are present

Mr. NIEMAN: I

of the dust nuisance can be eliminated by systematic routine and thorough clean-up programs. The advantages are obvious. The plant is much better looking and, in addition, the atmospheric dust is reduced.

Medical control is equally important. The only sure way to know that a hazard does not exist is the careful observation of the workers over a period of years. Pre-employment examinations are, of course, also important for proper placement of applicants.

In this paper we have presented some of the salient features of the silicosis problem. We have, first of all, emphasized that only two pneumoconioses are actual diseases, silicosis and asbestosis.

We have pointed out that there are three causative factors of silicosis and all three must be present simultaneously to produce the disease.

1. Uncombined silica in small particles, of which the most dangerous is probably quartz.

2. Sufficiently intense concentrations of the dust to be hazardous. This concentration is set at five million particles (light field count) of quartz less than ten microns in greatest diameter, if the quartz constitutes a high percentage of the material. Studies in the cement industry have demonstrated that, in many cases, appreciably higher concentrations of quartz can be tolerated when inert dusts, as clay or limestone, are intermixed with the silica.

3. Exposure by the employees over a sufficiently long period to high concentrations of silica of the necessary fineness.

The influence of silica on tuberculosis is strong, whereas inert dusts have no effect on this disease. Serious disability from silicosis, especially in the first two stages, usually results from infection, rather than from the uncomplicated disease. If the working environment is adequately clean, a silicotic need not be denied work as long as he is free from infection and is capable of doing his job.

Methods of control of the disease include pre-employment and periodic medical examinations, removal of dust at point of origin, emphasis on good housekeeping and the use of respiratory protective equipment where removal of dust from the atmosphere is not possible.

It should be emphasized that control, especially engineering control, of the silicosis hazard is the phase of the problem that is of greatest importance to those of us who are interested in the practical methods of eradicating the disease.

Dr. A. R. Riddell of the Ontario Department of Health, whose work in the gold fields of Ontario has won for him an international reputation, put the problem squarely up to the engineers when he said: "Silicosis is an occupational disease declining in importance. Its prevention is not a medical problem. As it occurs exclusively through the inhalation of dust containing silica, its prevention depends on the elimination of dusts industrially produced. This is a problem for the industrial engineer. Engineers have met the problem so energetically and with such intelligence that the occurrence of silicosis in many operations now considered hazardous will cease entirely during the next fifteen or twenty years."

(Applause.)

CHAIRMAN WITMER: Has anyone any questions to ask Mr. James? Dr. Obetz, will you please take over the meeting now to discuss this subject?

Dr. OBETZ, Medical Director, Industrial Commission: I don't know that I have anything to add or discuss. I would like to have anyone here ask Mr. James any questions that they may have in mind in order that they may fully understand the hazards that are present in the quarry industry.

Mr. NIEMAN: I understood the speaker to say something about asbestosis.

MR. JAMES: As I understand it, asbestosis in magnesium silicate—it has been developed that the appearance, as I understand it of a lung affected with asbestosis isn't quite the same as silicosis, but at the same time it has been definitely shown to be a progressive disease in case of magnesium silicate, and that is the only one that has been established as being harmful. Its effect is not as great as silica.

MR. NIEMAN: It struck me particularly, it not being harmful.

MR. JAMES: It is a surprise to a great many people, I believe. Do you care to discuss that any further, Dr. Obetz?

DR. OBETZ: No, I can't, I can't give the reason for it, but I know that it is true.

CHAIRMAN WITMER: Anyone else have any questions at this time? If not we will go on to the next subject which is a round table discussion of our most serious accident hazards. Anyone here going to open the subject in an informal round table discussion? Mr. Adams, do you have anything to say on that subject?

MR. ADAMS: I don't think so.

CHAIRMAN WITMER: Well of course we have been talking all along here about serious things like the handling of dynamite, transportation, and so forth, but from reports sent out by the Industrial Commission I note that the major accident rate and the index to the accident figures for the industry, all three of these industries, lime, cement and quarries, has been in the handling of small tools, and that's true in almost every industry, I think. I know last year the subject of small tools was not discussed very fully and I think that some suggestions along those lines in the prevention of that class of accident should be discussed. Has anyone any comments to make? Dr. Obetz, probably you can give us some of those industrial figures on that.

DR. OBETZ: I am sorry, but Mr. Meehan was to be here and conduct that part of the meeting, he was called to another section. Anyone have any thoughts along that line?

MR. RUTHERFORD: I might say that I had missed that in one of the hazards that I had listed there, but in my excitement I overlooked it. We have had some, in talking of small tools, especially in the quarry, from claw bars and mallets, spawls flying off of those striking the men working, and we have eliminated that to a great extent by tool inspection and repair, in other words keep the spike maul so it isn't flattened out and corners breaking off; the same way with the claw bar, where you are driving a claw bar under the head of a spike, you have some trouble there. I think tool inspection goes a long ways in eliminating hand tool injuries.

MR. ADAMS: I might ask one question, if I may. Some of our accident reports read for particle in left eye, or for a particle in right eye. I wonder if we are an exception or whether we are more careless than someone else in the wearing of goggles, or do the rest of the people have the same thing?

MR. L. C. LEWIS, of the Industrial Commission, Division of Safety and Hygiene: I think about every industry I have come in contact with has the same complaint that you have just mentioned, particularly the coal mining industry. They take a pick, strike a piece of coal, piece of steel, the first thing you know something in the eye, and the proper wearing of goggles, that is the proper kind of goggles, naturally would eliminate that condition. There is no question about it. Some mines now are one hundred per cent in the reports of their accidents that they have been sending in to the Industrial Commission; one-fourth or twenty-five per cent of the accidents occurred were from the eye. That one firm has totally eliminated the eye accidents.

that's the Akron Co are quite a number Rutherford suggest t and with the hand men would take it; drive a nail; I hav hold it with their h: an injured finger. I your hand tools are frost, picked up by take his gloves off, know what happene thawed free. I saw moved his cigarette in there, that man v on his upper lip bec were put in the pro you would eliminat the eye trouble, tha a rigid enforcement

CHAIRMAN WITMER: but I would like to regard to the frequ experience?

MR. F. W. WE had quite a few acc was a lost eye, and course we tried to gram that all gogg of goggles, and I work out very sati of rim glasses with don't think we hav wear them. Of co blowing a lot, but to wear goggles, e on. I have a pair t glasses are permis got that a hundred shoes, when they : put a piece of iron out different, just if they didn't fit y We finally got ar have got so many such as respirator: our dust as much but we are a whol

MR. LEWIS: outside, if they ha the head that will

ite—it has been
with asbestosis
nitely shown to
e only one that
ilica.

Do you care to

now that it is

ie? If not we
ur most serious
ual round table
??

ng here about
orth, but from
accident rate
ese industries,
nd that's true
all tools was
e lines in the
e any com-
ese industrial

uct that part
oughts along

the hazards
e had some,
and mallets,
minated that
: spike maul
ie claw bar,
ome trouble
ool injuries.

dent reports
we are
wearing of

d Hygiene
e complaint
hey take a
hing in the
s, naturally
ts now are
en sending
e accidents
accidents,

that's the Akron Coal Company over in Guernsey County. Now, hand tools, there are quite a number of injuries come from hand tools, and I am glad to hear Mr. Rutherford suggest that proper inspection of tools. I have gone into different plants, and with the hand tools, even the hammer, the hatchet was loose on the handle, men would take it; I have seen the hatchet fly right off when they were trying to drive a nail; I have seen it move sufficiently when they were driving a nail and hold it with their hand, the hammer would hit the wrong nail, consequently it was an injured finger. I think one of the best suggestions that you made is to see that our hand tools are inspected. I have seen crow bars set out in the winter, full of frost, picked up by a man, and to my surprise one day I saw a man, he wanted to take his gloves off, change his gloves, he put the small bar right in his mouth, you know what happened, his tongue was stuck on the bar, he had to wait until it thawed free. I saw another man putting his bar up to his mouth, just that way, moved his cigarette or cigar, whatever it was, and the bar touched; infection set in there, that man was laid up for six weeks just because of an infection that came on his upper lip because of the contact with the frosted steel bar. So if the tools were put in the proper place, kept in the right condition, properly inspected, I think you would eliminate many injuries. Using the goggles, naturally would eliminate the eye trouble, that is at least ninety per cent of it, and I think there should be a rigid enforcement of the proper use of goggles.

CHAIRMAN WITMER: I think Mr. Lewis has very ably answered your question, but I would like to call on Mr. Weber to give you a little more detailed answer with regard to the frequency of that same accident. Mr. Weber, what has been your experience?

MR. F. W. WEBER (Standard Lime & Stone Co., Woodville, Ohio): We have had quite a few accidents, in fact we had our last one about seven years ago, which was a lost eye, and since that we gradually got the men to wear goggles, and of course we tried to make them wear them at first, and we found out during the program that all goggles didn't fit everybody alike, but we finally got the right kind of goggles, and I think we have about four kinds that we use, and they seem to work out very satisfactorily. Some of these goggles are just ordinary large pairs of rim glasses with a shatter-proof glass in it, where they are using the lime, and I don't think we have had any trouble of anybody getting lime in his eye where they wear them. Of course they wouldn't be much good out doors where the wind was blowing a lot, but I must say we have eliminated our eye accidents. Everybody has to wear goggles, even myself, when I get in a bad place I have got to put them on. I have a pair to fit over these glasses, although I wear them lots of places where glasses are permissible. And that also applies to safety shoes, although we haven't got that a hundred per cent, we hope to have before the year is over. Take safety shoes, when they first came out you thought you had to build a pair of shoes and put a piece of iron in the foot and everybody could wear them, but they soon found out different, just like you go in a shop and buy a pair of shoes for Sunday wear, if they didn't fit you didn't take them. That was the same way with safety shoes. We finally got around where we could fit most of the men very nicely now, they have got so many good shoes on the market. The same way with other equipment such as respirators, although we don't use those so much any more. We eliminate our dust as much as we can. We don't say we are a hundred per cent free of dust, but we are a whole lot different than we used to be.

MR. LEWIS: Just one question. You mention about the goggles not being used outside, if they have the wire gauze protection from the helmet back to the side of the head that will protect all right.

Mr. WEBER: The wire gauze is all right, we have men who wear them now. They wear them under their helmet and then they use them for chipping only, they are not much protection for dust, I wouldn't rely on them.

Mr. LEWIS: They don't protect from the wind.

Mr. WEBER: Not where you have dust around a cement or lime plant.

Mr. LEWIS: That question was discussed by a goggle salesman the other day.

Mr. WEBER: The reason we use that one kind for the welder, he used to have a burning goggles and welding helmet, and also another pair for chipping, he was not going to stop to put them on so we got this other type which fits on just like a pair of glasses does, and the minute he tips his helmet back those chipping goggles are right on hand, he goes right on with his work.

Mr. CORNELIUS, Southwestern Cement Company: We use a sun-right shade on our goggles. It is a transparent material something like celluloid, otherwise no opening there whatever, we find it very effective and helpful under dust conditions.

Mr. LEWIS: That protects against the wind dust?

Mr. CORNELIUS: Oh yes. They are open around the inside here, but the sides are closed up entirely, that gives a little ventilation around the nose, but it closes up and protects very well against winds blowing dust around like that. We went through a stage a couple of years ago of eye injuries. In one year I think our eye injuries were about seventy-five per cent of our medical cases, foreign particles in the eye. We went through what we call education or the conscious movement, we tried to make all the fellows feel that the eyes were important enough to protect and did everything we could do to make them wear their goggles and follow their helpers, where they had been doing work that there might not be the least requirement for goggles, put them on, there might be a remote chance of having something get in their eye, give themselves the benefit of the doubt and put their goggles on. For the last year and a half or two years our eye cases have been practically nothing. I don't think we had a case last year, a medical case of something in the eye.

Mr. LEWIS: And yet prior to the use of goggles it ran as high as seventy per cent.

Mr. CORNELIUS: We had goggles at that time, but the fellows didn't use them, but we had to get them to see it, that they absolutely needed the goggles, and we furnished them to them and all they had to do was go to the storeroom and get them and put them on, we made them available at all points where there wouldn't be any excuse that they couldn't get goggles, we eliminated that part of it, then we put it up to them. We got good results from that. So far we have got our eye condition under control.

Mr. LEWIS:—One statement I would like to make about John Rigby, show you how he went about to enforce the use of goggles in mines. They had been wearing them one hundred per cent. He went away on a coal sales trip with the sales manager, he came back, he saw the goggles piled in the office, 310 pairs of them. The next morning he met the men at the mine. He says, "What is the matter with these goggles?" "We are not going to wear them any more," "Aren't you? All right, it is up to you." They walked over to the gate to go down the shaft, they said: "When are you going to open the gates?" "The gates are not going to be opened, not until those goggles are in you men's possession, and you agree to wear them. You men are going to be technical, so am I. Your eyes are getting hurt, not mine. If you haven't got judgment enough to protect your own eyes, I don't feel you

have got judgment enough and the next morning before he came. So some

CHAIRMAN WITMER: minor injuries? If not for next year. We have time, might as well get it. Thereupon Mr. Rud

Mr. CORNELIUS: I r

CHAIRMAN WITMER: closed. In view of that next year signify by say Motion carried.

CHAIRMAN WITMER: In past years it has been he passes the buck onto for the important office, Vice Chairman?

Mr. RUTHERFORD: I

Mr. WEAVER: I bel

CHAIRMAN WITMER: tions for Vice Chairman Thereupon Mr. Cor

Mr. WEAVER: I mo Motion seconded and

CHAIRMAN WITMER: my gratitude to Mr. Ru here today, and I am su business to come before

Mr. LEWIS: I would There are quite a number would make a suggestion division of Safety and we possibly can. Mr. K list, your President, Sec the Industrial Commission it sent out if you wish, quarrymen of the State you can't make this one are bigger here today than can get more next year

Mr. WEBER: I think

Mr. LEWIS: Don't Industrial Commission work except type the le

Mr. WEBER: We h here at these meetings, unless you drag them in

have got judgment enough to work for the Akron Coal Company." They went home and the next morning they came back and all the glasses were out of the office before he came. So sometimes it takes discipline to handle the problem.

CHAIRMAN WITMER: Any more comments on this problem of small-tools and minor injuries? If not I will call for nominations for chairman for the committee for next year. We have got to nominate a chairman for next years' session sometime, might as well get up and nominate a chairman.

Thereupon Mr. Rutherford was nominated as chairman.

MR. CORNELIUS: I move to close the nomination.

CHAIRMAN WITMER: It is moved by Mr. Cornelius that the nomination is closed. In view of that fact all those in favor of Mr. Rutherford for chairman of next year signify by saying "Aye".

Motion carried.

CHAIRMAN WITMER: Mr. Rutherford has been elected chairman for next year. In past years it has been the experience that the Chairman never acts as chairman, he passes the buck onto the Vice Chairman. Therefore we now hold nominations for the important office, that of Vice Chairman. Do I hear any nominations for Vice Chairman?

MR. RUTHERFORD: I nominate J. R. Weaver.

MR. WEAVER: I believe I will decline to accept that nomination.

CHAIRMAN WITMER: It is still open for nomination. Do I hear any nominations for Vice Chairman?

Thereupon Mr. Cornelius was nominated as Vice Chairman.

MR. WEAVER: I move the nomination be closed and Mr. Cornelius be elected.

Motion seconded and carried.

CHAIRMAN WITMER: Mr. Cornelius elected Vice Chairman. I again express my gratitude to Mr. Rutherford and Mr. James who gave us such wonderful talks here today, and I am sure that we all profited measurably by it. Is there any more business to come before the meeting, or any other remarks?

MR. LEWIS: I would like to say something before the new president takes office. There are quite a number of quarries in Ohio that never send anyone here. I would make a suggestion, it is only a suggestion, I want you to understand that our division of Safety and Hygiene is instructed to help and assist in every way that we possibly can. Mr. Kearns gave me this order, I would suggest that you get a list, your President, Secretary and Vice President get a list of the quarries from the Industrial Commission and write a letter, and if you write a letter we will have it sent out if you wish, mimeographed and sent out from our office to the different quarrymen of the State of Ohio requesting them to get into this section and see if you can't make this one of the real big sections. I compliment you here today, you are bigger here today than you were last year. Now if you go after it right you can get more next year than you have this year.

MR. WEBER: I think so.

MR. LEWIS: Don't you think it would be? In order to get that list from the Industrial Commission and have them type the letter, they wouldn't have to do the work except type the letter.

MR. WEBER: We have a man four miles from us, still we don't see anybody here at these meetings. I have been over to see them, but I can't get them to come unless you drag them in here.

CHAIRMAN WITMER: I might explain that this week the National Lime Convention was held down at Cincinnati and it is still in progress today, in fact at ten o'clock this morning there was a safety meeting down there, and many of the men were attending that convention and stayed down there for the meeting this morning rather than come up here. That's one reason why there are so many of the lime manufacturers there.

MR. LEWIS: Can you tell me if the Alpha Portland Cement Company had representatives down there from Ironton?

CHAIRMAN WITMER: I don't know. If there is no other business the meeting is adjourned.

The Petroleum Se
at nine o'clock A. M.,
pany, Detroit, Michiga

CHAIRMAN McLE
to order, and I would
certainly very pleasing
Marketing problems a
interest, I think, to th

Before we really
hame-Graham is in th
experience, we found
the stories they told a
speakers to be embarr
tain on that point befo

I think those of
greater appreciation c
analogy in our own i
grasp some of the lar
know when we are se
pound of grease, but
vehicle transportation.
thing goes wrong wit
page occurs, there is
facilities, and possibl
with the efficiency and
while, as you know,
placed, the stopping c
accidents are sympto
only the fact that th
entire organization o
let-down of efficiency,
ployee has to be repl

Investigation by
penses through stopp
four times as expens
the little analogy wit
Safety, in fact, what
modity that keeps ou
do for the machinery

It is very fitting
thing of the sales
unnecessary to intro
first place, I am a
casual visitor now a
in this town, went
Business Administra
an accountant, he be
tion, in Philadelphia

©ClB 391433

Charter Member



Associated Business Papers

CONCRETE, with which has been combined Cement Age, New York, and Concrete Engineering, Cleveland, is devoted to the Proper Use of Concrete and the Manufacture of Cement.

Published Monthly by

CONCRETE PUBLISHING CORPORATION
400 West Madison Street
Chicago, Illinois
Telephone CENTral 8822

Louis Brookman, Jr., Business Manager
L. Moeller, Circulation Manager
Harold O. Hayes, Promotion Manager

Representatives

New York City
E. Macdonald Bacon
17 West 45th—Room 909
Longacre 3-5260

Detroit
Parker & Tarbell
419 Curtis Bldg., 2842 W. Grand Blvd.
Madison 1540

San Francisco: Don Harway
Room 1009, 155 Montgomery St.
Exbrook 6029

Los Angeles: Don Harway & Co.
318 West Ninth Street
Tucker 9706

The Cement Mill Edition of Concrete

The Cement Mill Edition of CONCRETE is edited exclusively for those interested in the manufacture of portland cement and related products.

Its pages are devoted to discussions of plant design, management, operation, production efficiency, chemical research and control, quarry operation, progress and news of the industry.

The Cement Mill Edition also contains all the material published in the corresponding Regular Edition and so provides news of the uses and merchandising of the materials whose manufacture is discussed in the Mill Edition.

The Regular Section furnishes mill operating officials and mill executives valuable points of contact with the users of the materials they produce.

The subscription price is \$4.00 a year in the United States and its possessions, and Mexico. One dollar additional for postage in all other countries. Current copies, 50 cents each.

Charter Member



Audit Bureau of Circulations

CONCRETE—Cement Mill Section—July, 1938

CEMENT MILL SECTION of

Concrete

Established 1904

Volume 46

July, 1938

Number 7

NORMAN M. STINEMAN, Editor

J. C. WITT, Consulting Editor

A. C. BAMBERGER, Assistant Editor

CONTENTS

Direct Firing of Rotary Kilns	198
High-Alumina Cement in Japan	198
Inhalation of Dust and Control of Dust Hazards—By W. C. James	200
How Japanese Cement Manufacturers Diversify Their Activities —By Kanichi Moroi	202
Lehigh to Complete Rehabilitation of Two Eastern Plants	204
Combine Cement and Quarry Sections of Safety Council	204
Methods of Protection Against Silicosis	205
Editorial	207
June Campaigns Do Pay More Diversified Production Then the Accident Curve Dropped	208
No Bids on Federal Cement for Ohio, West Virginia and New Jersey	209
Find High Degree of Accuracy in Wagner Turbidimeter	209
Argentina's Cement Production Expanded Beyond Nation's Needs	210
Mill Equipment	211
Men and Mills	212

Copyright, 1938, by Concrete Publishing Corp.

CONCRETE is indexed in INDUSTRIAL ARTS INDEX, which may be consulted in any Technical or Public Library.

INHALATION OF DUST and Control of Dust Hazards

By W. C. JAMES
Safety Engineer
Portland Cement Association



W. C. JAMES

CONFUSION still seems to be the dominant keynote outside the research laboratory in this question of occupational "dusty-lung" diseases. Terms such as pneumoconiosis, silicosis, siderosis, chalcosis and even silicatosis are bandied about indiscriminately and often without meaning. Usually, the mere mention of dust in a conversation inspires visions of high mortality, high sickness rates and a long trail of serious hazards.

Confusion of Terms

The term "pneumoconiosis" is often interpreted to mean a disease of the lungs, resulting from dust inhalation. Actually, it means simply "dusty lung." In the early history of lung disease it was thought that all dusts caused the same disease reaction, and this term was applied to that disease. Modern research has demonstrated that most dusts are harmless. The term "pneumoconiosis" therefore should assume its primary meaning, and when applied to an individual it can rightly be interpreted only as indicating that the person has inhaled dust. Dr. Leroy U. Gardner, referring to non-specific pneumoconiosis says, "Such changes have no clinical significance and produce neither symptoms nor interference with working capacity. They are of no more importance than the callouses on the palms of the hands." Any person in any environment may develop this condition. Even office workers in large industrial communities may show X-ray evidence of having inhaled dust, but such evidence is meaningless as far as health is concerned.

Of the various strictly industrial dusts, coal and iron ore are perhaps the most spectacular in their appearance in the lung. Early investigators—and by this I mean investigators in the first 16 or 17 centuries of the Christian era—were so

impressed by the lung pigmentation of workers in iron ore and coal that they credited these substances with a prominent part in the development of lung disease. Modern research has demonstrated that this coloring of the lung tissue is, in itself, of no significance. Only two substances are now known to cause a definite lung disease—namely, asbestos and uncombined silica.

Inhalation of free silicon dioxide (usually quartz) in excessive quantities over a long period of time causes the disease, silicosis. You will note particularly that three factors are necessary to the causation of this disease:

1. Free silicon dioxide (usually quartz), in particles less than 10 microns in greatest diameter.
2. Excessive concentrations.
3. Long period of exposure.

No Silicosis from Cement Dust

Particular emphasis should be given to these limiting factors. First, "free silicon dioxide, less than 10 microns in greatest diameter." This means exactly what it says—not calcium carbonates, not iron oxides, not silicates, not even silicon carbide (which is carborundum), but free silicon dioxide. It seems probable that no little confusion has arisen in the minds of plant superintendents and engineers because of the time-honored practice by industrial chemists of reporting an analysis in terms of the oxides of the components. For example, a typical reported analysis of portland cement will show a total silica content of about 20 per cent. Actually, all of this silica is combined in the forms of entirely harmless calcium silicates; and it has been conclusively demonstrated that it is utterly impossible to acquire silicosis from exposure to cement dust. It should be mentioned that quartz is not the only form of free silica, though it is apparently the most dangerous, and certainly the most common, form. The various

amorphous forms of the compound, such as flint, tripoli and thert, may also produce the silicotic reaction in the lung, but they are known to be less severe in their effect.

The limiting size of ten microns is also of importance. Particles larger than this do not reach the lungs. Furthermore the percentage of quartz in a given material will vary greatly with the particle size. A petrographic examination of shale at Saranac Laboratory under Dr. L. U. Gardner's direction, recently revealed 20 per cent quartz. In a special fraction containing only large particles, 40 to 50 per cent quartz was found.

Dr. Gardner writes, "this is obviously due to the fact that quartz is so hard it does not fracture into fine particles." It must, therefore, be emphasized that conclusions as to the hazard existent in a dusty operation can not be based with confidence on an analysis of the parent rock. Only an analysis of the dust in the breathing zone of the operator will give an accurate picture of conditions.

Question of Concentration

The second limiting factor is concentration. The exact amount of air-borne quartz that constitutes a dangerous concentration in any particular industry is not easily determined, nor is there as yet any substantial agreement as to what limits of quartz content should be observed.

Dr. A. J. Lanza, assistant medical director of the Metropolitan Life Insurance Company, an outstanding authority on the silicosis problem, gave an excellent summary of what needs to be known about dust concentration in his paper presented before The American Institute

Paper read before the Quarry Section of the All-Ohio Safety Congress, May 11, 1938.

of Mining and Metallurgical Engineers, in February, 1937. He said:

"In the present state of our knowledge, it is not possible to establish permissible limits of dustiness for all dusty industries or processes, as the variation both in the dust content and in external modifying conditions is so extreme. In mining, however, working conditions are fairly constant and it would be extremely valuable to the industry if the various mining companies that face a silica hazard would establish, with the help of the proper governmental authorities, tentative standards practicable and applicable for their own mines. Some have done so and it is a long step in the right direction."


This recommendation might well be extended to other industries.

More Knowledge Is Needed

The National Silicosis Conference tentatively established a maximum of five million particles per cubic foot as a safe quartz concentration in the case of highly siliceous dusts. This standard is subject to modification as more data are developed by different industries. The National Silicosis Conference report also says, "It is recommended that clinical and engineering studies be carried out as rapidly as possible to establish the necessary scientific data upon which we may base practical and effective regulatory standards." The report then states that knowledge of three factors is necessary for establishing safe concentrations of atmospheric dust:

1. The relative number and size of the free silica and the other particles suspended at breathing levels in the different parts of the industrial atmosphere.
2. The proportion of the workmen's time actually spent in the various dust concentrations.
3. The effects of exposure to environment, as revealed by the occupational and medical histories of old employees, by physical examination and by the roentgenological appearance of their lungs.

Through a knowledge of these three factors, any industry can discover what, if any, hazard it has and what preventive measures are needed. For the past two years, under the direction of Dr. Leroy U. Gardner of the Saranac Laboratory for the Study of Tuberculosis, the cement industry has been making a careful estimate of the health of its workers, according to the plan just outlined. Many of the statements in this paper regarding



Dust sampling at hammer mills—raw end

the effect of mixed or non-siliceous dusts have been based on the findings of these studies.

One of the outstanding conclusions a student of these researches in the cement industry will reach is that concentrations of free silica appreciably higher than the maximum specified by the Silicosis Conference are safe if the silica constitutes a moderate proportion of the total dust. Apparently a mixture of silica with other minerals, if the other minerals are predominant, tends to inhibit the effect of the silica in the lung. It is not yet possible to recommend, without reservation, the dilution of silica with other dusts as a protective measure. It is far better to remove the dust from the atmosphere. Nevertheless, it is significant that in the portland cement industry, where a high concentration of raw material dust containing up to 10 per cent of free silica is sometimes found, the X-rays and physical examinations reveal no pathological lung condition attributable to dust.

The Practical Limit

Although no agreement has been reached as to the maximum safe concentration of free silica in the presence of harmless dusts, agreement as to good housekeeping limits is practically unanimous. Industries with a dusty process, even though dusts are harmless, should endeavor to reach a concentration in the neighborhood of 100 million particles per cubic foot of air in the breathing zone of the workers, in the interests of comfort and increased efficiency.

The third factor in the development of silicosis is duration of exposure. The

problem of exposure resolves itself into two parts. First, what proportion of the workers' time is actually spent in the dusty atmosphere? It is evident that a hazardous dust will not affect a man unless he is actually exposed to it and will not have as great an effect on a man who is exposed to it one hour a day as on a man continuously exposed.

[The remaining part of this paper will discuss the effect of duration of exposure, followed by a discussion of preventive measures.—Editor.]

Plan New Cement Plant for Turkey

ACCORDING to a report to the U. S. Bureau of Foreign and Domestic Commerce from the office of the American Commercial Attache at Istanbul, the Turkish Government has awarded a contract to a European equipment manufacturer for cement mill machinery to be installed in a new plant at Sivas.

Installation of the machinery is expected to start in October of this year, and the plant should enter into operation in July, 1939, with a daily production capacity of 300 tons, or 90,000 tons per year. In view of the abundance of raw material in the surrounding district, it is hoped that the factory will soon be able to double its production. The quarries will be connected with the plant by an aerial line of 3,100 meters. It is anticipated that when this factory enters into production the Eastern Vilayets and Central Anatolia will be supplied with cement at considerably lower prices.

Aug -5 1938
 8891 2- 374 ©Cl: 8 381434

Charter Member



Associated Business Papers

CONCRETE, with which has been combined Cement Age, New York, and Concrete Engineering, Cleveland, is devoted to the Proper Use of Concrete and the Manufacture of Cement.

Published Monthly by

CONCRETE PUBLISHING CORPORATION
 400 West Madison Street
 Chicago, Illinois
 Telephone CENtral 8822

Louis Brookman, Jr., Business Manager
 L. Moeller, Circulation Manager
 Harold O. Hayes, Promotion Manager

Representatives

New York City
 E. Macdonald Bacon
 17 West 45th—Room 909
 Longacre 3-5269

Detroit
 Parker & Tarbell
 419 Curtis Bldg., 2842 W. Grand Blvd.
 Madison 1540

San Francisco: Don Harway
 Room 1009, 155 Montgomery St.
 EXbrook 6029

Los Angeles: Don Harway & Co.
 313 West Ninth Street
 TuckeR 9706

The Cement Mill Edition of Concrete

The Cement Mill Edition of CONCRETE is edited exclusively for those interested in the manufacture of portland cement and related products.

Its pages are devoted to discussions of plant design, management, operation, production efficiency, chemical research and control, quarry operation, progress and news of the industry.

The Cement Mill Edition also contains all the material published in the corresponding Regular Edition and so provides news of the uses and merchandising of the materials whose manufacture is discussed in the Mill Edition.

The Regular Section furnishes mill operating officials and mill executives valuable points of contact with the users of the materials they produce.

The subscription price is \$4.00 a year in the United States and its possessions, and Mexico. One dollar additional for postage in all other countries. Current copies, 50 cents each.

Charter Member



Audit Bureau of Circulations

CONCRETE—Cement Mill Section—August, 1938

CEMENT MILL SECTION of

Concrete

Established 1904

Volume 46 August, 1938 Number 8

NORMAN M. STINEMAN, Editor

J. C. WITT, Consulting Editor

A. C. BAMBERGER, Assistant Editor

CONTENTS

Handling and Processing Raw Materials at Peerless' Detroit Plant	214
How a Texas Pioneer Produced Cement	215
Inhalation of Dust and Control of Dust Hazards—By W. C. James	216
Cebu Plant in Philippines to Double Its Capacity	218
Relation of Cement Composition to Quality of Concrete	218
Preventing Silicosis—Some Results of Recent Research	219
P. C. A. Holds Spring Meeting in Atlantic City	220
June Sees Few Accidents—But Four Are Fatal	221
Big Expansion of Producing Capacity in India in 1938	221
Huron Establishes Distributing Plant at Green Bay	222
Andreasen's Method for Determination of Fineness	222
Heats of Hydration and Transition of Calcium Sulfate	222
Editorial	223
The June Campaign	
Direct Firing of Rotary Kilns	
Dust and Machinery	
How Welding Is Applied to Plant Maintenance and Repairs	224
Award Jury Selecting Winning Papers	226
MIS Equipment	227
Men and Mills	228

Copyright, 1938, Concrete Publishing Corp.

CONCRETE is indexed in INDUSTRIAL ARTS INDEX, which may be consulted in any Technical or Public Library.

INHALATION OF DUST and Control of Dust Hazards

By W. C. JAMES

Safety Engineer
Portland Cement Association
Chicago, Illinois

THE first part of this article, published in the July issue, discusses the concentration of industrial dusts and points out the harmless character of cement dust; but the need for more knowledge about dust is emphasized. The present concluding part takes up matters such as the effect of duration of exposure, and the adoption of preventive measures.—*Editor.*

THE United States Public Health Service has developed a formula for calculating the actual exposure in terms of particle hours. They recommend in Bulletin 217, "The Determination and Control of Industrial Dust," that the particle concentration in any area be multiplied by the number of hours an employee works in that area; that this product be calculated for each hour of the working day and that the total of these products be divided by the number of working hours to give the equivalent of continuous exposure during the day.

Equivalent Exposure

For example, a man may spend two hours a day in a concentration of 200 million particles per cubic foot; three hours in a concentration of 10 million particles; one and three-quarter hours in a concentration of 40 million particles and 15 minutes in concentration of 1200 million particles. The man's exposure would be calculated:

Hours per day a	Dust Concentration b	Particle-hours (millions) a and b
2	200	400
3	10	30
1 3/4	40	110
1/4	1200	260
8		800
Total Hours		
800 particle hours in millions per cubic foot =		
8 hours		
100 million particles per cu. ft. daily exposure.		

Paper read before the Quarry Section of the All-Ohio Safety Congress, May 11, 1933.


The application of this formula in a practical problem is apparent. If you find, from a study of concentration and silica content, that in two or three areas in your plant atmospheric dust exceeds safe limits, you will make an analysis of the exposure by the P.H.S. method and attack that point where employee exposure is the greatest.

How Long in Developing

How long does it take silicosis to develop? The answer to such a question must be equivocal. Much depends on the physical condition of the worker. A man whose respiratory passages have been damaged so that dust is not readily excluded by the usual protective mechanism, may contract silicosis more readily than a man with normal nasal and bronchial passages. Also a man whose lungs

have been damaged by pneumonia or tuberculosis may develop silicosis more quickly. We are probably all familiar with the reverse of this; i.e., that a man with silicosis has much less resistance against tuberculosis than a man with unaffected lungs. This fact, incidentally, suggests one of the outstanding differences between the action of silica and other dusts. Medical authorities state that not only does the silicotic lesion in the lung resemble the lesion in tuberculosis, the silica actually stimulates the activity of tuberculosis and, at the same time, conceals its symptoms until it is far advanced. The seriousness of such a condition may readily be imagined. A tubercular with significant quantities of silica in his lungs may be rapidly getting worse, yet diagnostic symptoms are often lacking. Frequently only a careful X-ray examination can reveal the presence of tuberculosis in a silicotic. Mr. P. N. Bushnell, speaking before the Metals Sections of this Congress last year, emphasized the fact that the real danger from silicosis is not silicosis at all, but tuberculosis. First or even second degree silicosis, uncomplicated by tuberculosis, usually causes relatively slight disability, seldom pronounced enough to interfere with working capacity. No worker should be deprived of an opportunity to earn a living at his regular job because his X-ray shows some signs of nodulation. The job should be cleaned up by approved engineering methods, of course, but discharge of workers who are perfectly capable, simply because of a non-symptomatic condition which hysterical opinion has magnified out of all proportion, is certainly not the solution of the problem. Inert dusts do not produce the typical nodular lesion, nor do they cause any increased susceptibility to tuberculosis. In the cement industry, for exam-

The dragline conveyor is a prolific source of dust



ple. only 4 per cent of the X-rays of 1700 employees revealed old tuberculosis lesions and 96 per cent of these lesions were healed or quiescent. Studies of absenteeism over a two-year period, covering the majority of mills in the industry, confirms the X-ray evidence. The mortality rate from tuberculosis of 0.07 per 1000 employees in 1937 is only 8 per cent of the tuberculosis mortality rate of 0.87 per 1,000 employed males established by the National Tuberculosis Association in a comprehensive survey in 1930.

Factors That Control

The various factors which may influence the length of time required to develop silicosis, if we may recapitulate, are: (1) intensity of dust concentration, (2) proportion of free silica in the dust, (3) proportion of working time employees spend in the dusty atmosphere, (4) condition of employee's upper respiratory tract, and (5) condition of employee's lungs.

In any case, it is extremely doubtful that first-stage silicosis will develop in less than seven years, except in the presence of active tuberculosis. Dr. Gardner says that for silicosis to develop in five years, the exposure must be intense. The National Silicosis Conference report, to which we have previously referred, says with admirable skepticism, "There are reports of a few cases of the disease developing in as short a period as one and one-half years. In these instances, the individuals were exposed to excessive concentrations of extremely fine silica in almost a pure state." The report then states that exposure to low concentrations of silica may sometimes continue for thirty years before the condition develops to the stage where it can be called silicosis. In such cases, possibly another 15 or 20 years would be needed before any disability would be noticed. A great majority of the cases have had at least seven years' exposure. Thus it will be seen that silicosis is a very slowly developing disease, which, in the absence of infection, is not especially dangerous. In the presence of infection, however, the picture may be different.

Control of Dust Hazards

No attempt has been made to separate the two sections of this paper, as indicated by the title, since the discussion of the problem is too intimately bound up with the methods of solving it. There are, however, some details of prevention which should be mentioned.

It might be worth while to think about the methods of determining dust concentrations. The quick sampling, easy counting devices on the market now probably fill a definite need, but their use is not altogether an unmixed blessing. The standards mentioned in this paper are all based on the United States Public Health Service's impinger technique with light field count. It is a complex technique requiring skill and experience to operate successfully, but it is the standard counting method in the United States and results of short-cut methods have not been shown to be correlative with it. After dust control has been instituted and the impinger technique has shown that concentrations are within safe limits, a simpler technique might be permitted for periodic checks on the efficiency of the control system. But don't be surprised if your counts with the simplified technique soar way above the impinger counts. The dark field illumination will uncover a large number of particles, apparently too small to have any effect, that are screened out by light field methods. The result is similar to the effect of a strong beam of light in a dark room. This difficulty can be overcome to some extent by taking impinger samples and samples by the other technique simultaneously, as soon as dust control equipment is installed, thus getting as much correlation as possible between two techniques at the beginning.

Remove Dust at Source

A general paper of this type is not a suitable place to discuss the relative merits of different types of dust control systems. There are, though, a few principles which can be properly mentioned. Wherever possible, dust should be removed at its source, before it reaches the workroom atmosphere. Methods of accomplishing this vary with the process and should be decided upon by competent engineers after a careful study. In milling processes, closed, dust-tight systems with adequate separators and collectors may be adequate. Water sprays are sometimes effective where they can be used. In the quarry wet drilling is often all that is necessary to bring concentrations down to safe limits. Sometimes more elaborate dust traps are needed, either independently or conjunctly with wet drills.

Some processes are not amenable to control at the source. In such cases employees should be required to use respirators or masks of approved type. All of these methods have their place. The right one for each location must be determined by a thorough engineering survey.

The importance of good housekeeping can not be too strongly emphasized. Much of the dust nuisance can be eliminated by systematic, routine and thorough clean-up programs. The advantages are obvious. The plant is much better looking and, in addition, the atmospheric dust is reduced.

Medical control is equally important. The only sure way to know that a hazard does not exist is the careful observation of the workers over a period of years. Pre-employment examinations are, of course, also important for proper placement of applicants.

Salient Features of Problem

In this paper we have presented some of the salient features of the silicosis problem. We have, first of all, emphasized that only two pneumoconioses are actual diseases, silicosis and asbestosis.

We have pointed out that there are three causative factors of silicosis and all three must be present simultaneously to produce the disease.

1. Uncombined silica in small particles, of which the most dangerous is probably quartz.
2. Sufficiently intense concentrations of the dust to be hazardous. This concentration is set at five million particles (light field count) of quartz less than ten microns in greatest diameter, if the quartz constitutes a high percentage of the material. Studies in the cement industry have demonstrated that, in cases, appreciably higher concentrations of quartz can be tolerated when inert dusts, as clay or limestone, are intermixed with silica.
3. Exposure by the employees over a sufficiently long period to high concentrations of silica of the necessary fineness.

The influence of silica on tuberculosis is strong, whereas inert dusts have no effect on this disease. Serious disability from silicosis, especially in the first two stages, usually results from infection, rather than from the uncomplicated disease. If the working environment is adequately clean, a silicotic need not be denied work as long as he is free from infection and is capable of doing his job.

Medical Control Is Important

Methods of control of the disease include pre-employment and periodic medical examinations, removal of dust at point of origin, emphasis on good housekeeping and the use of respiratory protection. (Continued on page 222)

Huron Establishes Distributing Plant at Green Bay

HURON Portland Cement Company has put into operation that company's twelfth packing and distributing plant at the Leicht dock at Green Bay, Wisconsin. Previously-built distributing plants owned by Huron are located at Detroit, Oswego, Buffalo, Cleveland, Toledo, Wyandotte, Saginaw, Alpena, Muskegon, Milwaukee, and Duluth.

Cement for the Green Bay packing and distributing plant is brought from the Huron's Alpena cement plant in the company's own bulk-cement lake steamers, the largest of which has a cargo capacity of 40,000 bbl.

At Green Bay the bulk cement is transferred to the cement company's boat *Samuel Mitchell*, which is lashed to the dock and will serve temporarily as a "warehouse" until the necessary construction and installations on shore can be completed. The *Samuel Mitchell* brought the first cargo of bulk cement totalling 15,000 bbl. Dredging operations are enlarging the slip in which this boat is docked, and when this phase of

the work is completed the floating "warehouse" can be moved further in, thereby enabling other boats to dock directly back of it, to unload their cargo.

A cement packing machine having a capacity of 1,000 sacks an hour has been installed on the dock alongside the *Samuel Mitchell*. From the hold of the ship, cement is pumped into a steel bin over the packing machine, and is fed to the packer for sacking as required, to fill orders from the trade, the cement being forwarded either by rail or by motor truck. Cement can also be shipped from the Green Bay distributing plant in bulk-cement railway hopper cars, although this type of railway rolling stock is not, as yet, generally available. Only a few railways have supplied themselves with such rolling stock, and they have only a small number of these special cars.

With twelve packing and distributing plants operating at ports on the Great Lakes, the cement company's bulk-cement carriers will make regular stops and unload whatever cement is required.

Andreasen's Method for Determination of Fineness

IN a report presented to the Twenty-Second General Meeting of the Association of Japanese Portland Cement Engineers, Prof. Toosaku Yoshioka, of the Imperial University at Kyoto, gave confirmation to the correctness of results from the use of Andreasen's pipette method for the determination of fineness of powdered materials.

From his experience in the fineness determination of Japanese clayey materials for the last three years, he has come to recognize the value of Prof. Andreasen's pipette method as one of the best of present methods for scientific as well as technical determination of fineness of powdered materials.

He tried to introduce this method to the field of cement research and factory

control, and explained about the principles, apparatus and manipulation, and concluded that this method would be worth attention for cement chemists because of the simplicity of the apparatus, easiness of manipulation and correctness.

He also mentioned a few points necessary to get fair results; i.e. complete elimination of bubbles adhering to the particles, by placing the suspension in a vacuum vessel, placing the whole apparatus into a thermostat to prevent temperature fluctuations and avoid convection disturbances, and recovery of solvents when ethyleneglycol, alcohol, etc. are used.

The Association of Japanese Portland Cement Engineers has its offices in the Teikoku Building, in Osaka, Japan.

INHALATION OF DUST

(Continued from page 217)

protective equipment where removal of dust from the atmosphere is not possible.

It should be emphasized that control, especially engineering control, of the silicosis hazard is the phase of the problem that is of greater importance to those of us who are interested in the practical methods of eradicating the disease.

Dr. A. A. Riddell of the Ontario Department of Health, whose work in the gold fields of Ontario has won for him an international reputation, put the problem squarely up to the engineers when he said: "Silicosis is an occupational disease declining in importance. Its prevention is not a medical problem. As it occurs exclusively through the inhalation of dust containing silica, its prevention depends on the elimination of dusts industrially produced. This is a problem for the industrial engineer. Engineers have met the problem so energetically and with such intelligence that the occurrence of silicosis in many operations now considered hazardous will cease entirely during the next fifteen or twenty years."

Heats of Hydration and Transition of Calcium Sulfate

HEATS of hydration and transition of calcium sulfate are discussed in a detailed report by Edwin S. Newman and Lansing S. Wells, published by the National Bureau of Standards as Research Paper RP-1107, and appearing also in the June (1938) issue of the *Journal of Research* of the National Bureau of Standards.

The heats evolved in the hydration to $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ at 25° C. of $\text{CaSO}_4 \cdot 1/2\text{H}_2\text{O}$ prepared by treating gypsum with steam in the autoclave, and of CaSO_4 prepared by heating gypsum at 1,000° C., have been determined and found to be 4,100 plus or minus 30 and 3,900 plus or minus 20 cal/mole, respectively. The heat evolved in the hydration to $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ of soluble anhydrite prepared by dehydrating gypsum at 75° C. is not less than 6,990 cal/mole. During the progress of this work no indications were found of more than two anhydrous forms of calcium sulfate; soluble anhydrite, and a modification formed rapidly at high temperatures, the latter being identical with natural anhydrite. The heat evolved in the transition of soluble anhydrite to natural anhydrite is not less than 3,000 cal/mole.