NOTICE: If the text below is less clear than this notice, it is due to the quality of the document being filmed.

CONFIDENTIAL

51

#8407

DOCUMENT REPRODUCED 3/18/82 DALLAS COUNTY CASES

MATERIAL 8407 (Stating Dash Number) (Spec.3500) June 5, 1946
CEMENT,HEAT INSULATING (PLASTIC INSULATION) X
SPECIAL MATERIAL FOR SOUTH PHILADELPHIA ONLY
FURNISHED BY -
(For 8407-1)(A)Baldwin-Hill Co, 900 Klagg Ave,Trenton (2), N.J.
(B)Eagle Picher Sales Co,American Bldg,Cincinnati(1),
ORDER FROM SUPPLIER AS
(For 8407-1 (A) Baldwin-Hill #1 Insulating Cement.
(B) Eagle-Picher Super 66 Plastic Insulation.
CHARACTERISTICS (8407-1) A loose fibrous heat insulating cement, composed of black mineral wool derived from slag, asbestos fiber and clay binder, applied by mixing with water and throwing into position by hand, and spreading smooth as desired. Serviceable to about 1200 F, and is 100% reclaimable for reapplication when temperature of 648 C (1200 F) has not been exceeded.

APPLICATION Plastic heat insulating cement for steam turbines and steam lines.
SPECIFY AS CEMENT 8407-1

Issued by Mfg Engrg Sec, Eng Labs & Stds Dept, Kent Sqr, Pa.
Supersedes data 8407. Dated (-20-)
Printed in U.S.A.

PLAINTIFF'S EXHIBIT WH-57