

self-cleaning

Extremely durable, this house paint is self-cleaning. The white stays white . . . the colors stay clear and bright.

**also ideal
for all
masonry
surfaces**

**SELF-CLEANING
house paint**

**MILDEW & FUME
RESISTANT
OUTSIDE WHITE**

ea

For on
on the
garage
Use
wood,
crete

GLD018206

It's so **FAST** and **EASY**

with GRANTS SELF-CLEANING HOUSE PAINT

1 Sand or wire-brush areas that are scaled, blistered, or chipped and corroded metal. Remove dust, dirt and foreign matter. Coat knots and sappy places with shellac. Caulk window frames and crevices before painting. Between coats, putty cracks and nail holes. If one coat is to be applied, putty before painting. Surface must be dry. Open can, pour off liquid into another container. Stir remaining paste with lifting motion, gradually returning liquid.

2 Pour from container to container several times after thoroughly stirring. Stir occasionally while using. Spot prime bare areas. Brush paint well into surface. Painting a similar color over a previously painted surface usually requires only one coat. If two coats are to be used, thin first coat with one pint paint thinner or turpentine to the gallon. Allow 4 days or more between coats. Apply final coat without thinning.

3 On unpainted or hard worn surfaces, apply one coat GRANTS PRIME COAT, then apply one or two finish coats of GRANTS HOUSE PAINT. If only one coat of GRANTS HOUSE PAINT is to be applied, do not thin it — if two coats, follow directions under No. 2. If PRIME COAT is not used, at least two coats of HOUSE PAINT should be applied—thinning first coat with one pint of paint thinner or turpentine to the gallon. Apply second coat full body. Allow 3 or 4 days drying time between coats.

659

sy to apply

one or two-coat application exterior of houses, barns, fences and trellises. on outside surfaces of metal, brick, stone, concrete and stucco.

SHINGLE STAIN GRANTS HOUSE PAINT may be used to re-coat wood shingles by adding one gallon paint thinner and 1/2 gallon raw linseed oil to a gallon of the desired color.

WARNING-FLAMMABLE Keep away from heat, sparks and open flame. Use with adequate ventilation. Keep container closed when not in use. May contain lead compound. Avoid prolonged or repeated breathing of vapors, spray mist, and dust when wire brushing or sanding, also prolonged or repeated contact with skin. Do not take internally. Before smoking or eating and after using, cleanse hands thoroughly.

ANALYSIS—OUTSIDE WHITE HOUSE PAINT
 Titanium Calcium 19.4% Mineral Spirits 11.4% dew fungi growing in or
 Titanium Dioxide 5.9% and Drier 11.4% on the paint
 Zinc Oxide 19.4% 101.0% di (Phenyl-Mercury)
 Magnesium Silicate 11.9% Contains added fungicide dodecyl succinate
 Treated Linseed Oil 21.7% to make this paint resistant
 Bodied Linseed Oil 7.7% tant to the action of mil- Inert Ingredients .10%
 88.9 100.0%

Satisfaction Guaranteed W. T. GRANT CO.

NEW YORK 18, N. Y.

1/4 U.S. GALLON OR 32 LIQUID OUNCES

CAUTION—DO NOT TINT GRANTS SELF-CLEANING OUTSIDE WHITE HOUSE PAINT. AS TINTING MAY CAUSE IT TO STREAK OR FADE AS IT WEATHERS. USE GRANTS TRIM WHITE HOUSE PAINT AS A BASE FOR TINTING.

GLD018207