CONFIDENTIAL

(File 46110BJ) Feb. 20, 1962
MATERIAL 46110B
CEMENT, HEAT INSULATING (PLASTIC INSULATION)
FURNISHED BY -
(A)Baldwin Ehret-Hill, Inc, 500 Klagg Ave, Trenton 2, N J
(B)Philip Carey Mfg Co, Wayne at Cooper, Cincinnati 15, Ohio
(C)Eagle Picher Sales Co, 1356 American Bldg, Cincinnati 1, Ohio
(D)Johns-Manville, 22 E 40th St, N Y C 16
(E)Owens-Corning Fiberglas Corp, 717 5th Ave, N Y C 22

ORDER FROM SUPPLIER AS -
(A)Baldwin-Hill #1 Insulating Cement
(B)MW50 Insulation Cement
(C)Eagle-Picher Super 66 Plastic Insulation
(D)J-M 460 Insulating Cement
(E)OCF 660 Insulating Cement

CHARACTERISTICS - (Previous 3407-1)(User:PH)Loose fibrous heat insulating cement, composed of black mineral wool derived from slag, asbestos fiber and clay binder. Apply by mixing with water,

Printed in U.S.A. (Over)

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

PLAINTIFF'S EXHIBIT WK-74

F

throwing into position by hand and troweling smooth as desired. Serviceable to 816 C (1500 F) and is 100% reclaimable for reapplication when a temperature of 649 C (1200 F) has not been exceeded.

APPLICATION - Plastic heat insulating cement for steam turbines and steam piping.

SPECIFY AS - CEMENT 461XCBJ

Issued by Std Dept, Matl Labs, E Pgh,

DOCUMENTS PROJECTED DALLAS COUNTY CASES 2/18/92

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92