

BUSWAYS




High Performance—Low Impedance UNI-BUS® Duct and Fittings

WHEN ORDERING SPECIFY

- Complete layout of the system including all dimensional information and labeled parts.
- Computations from which the final list price was established. (See page 31 for pricing procedures.)

FEEDER DUCT AND FITTINGS—TYPE HF—VENTILATED

System	Amps.	Duct Price ① per Foot		Forming Price					Complete Device Price				
		Alumi- num Bus Type HFA	Copper Bus Type HFC	Elbow	Flexible Con- nector	Tee	Cross	Expan- sion Joint	End Box	Cable Tap Box	Switch- board adapter Box	Switch- board Stub	Trans- former Tap Fitting
2 POLE—600 VOLTS (6 INCH FACE)													
	800	\$18.	\$23.	\$102.	\$102. ②	\$122.	\$144.	\$102.	\$14.	\$92.	\$12.	\$110.	\$50.
	1000	23.	29.	102.		122.	144.	102.	14.	100.	12.	130.	60.
	1350	34.	41.	136.		170.	202.	204.	28.	178.	24.	220.	100.
	1600	40.	50.	136.		170.	202.	204.	28.	206.	24.	220.	100.
	2000	50.	62.	136.		170.	202.	204.	30.	214.	24.	260.	120.
	2500	63.	77.	136.		170.	202.	204.	42.	240.	---	330.	150.
	3000	75.	93.	170.		202.	236.	408.	45.	268.	---	390.	180.
4000	100.	124.	170.		202.	236.	408.	60.	420.	---	520.	240.	
3 POLE—600 VOLTS (6 INCH FACE)													
	800	\$26.	\$31.	\$102.	\$102. ②	\$122.	\$144.	\$102.	\$14.	\$92.	\$12.	\$110.	\$80.
	1000	31.	39.	102.		122.	144.	102.	14.	100.	12.	130.	100.
	1350	47.	54.	136.		170.	202.	204.	28.	178.	24.	220.	160.
	1600	56.	66.	136.		170.	202.	204.	28.	206.	24.	220.	160.
	2000	66.	82.	136.		170.	202.	204.	30.	214.	24.	260.	200.
	2500	83.	102.	136.		170.	202.	204.	42.	240.	---	330.	240.
	3000	99.	123.	170.		202.	236.	408.	45.	268.	---	390.	300.
4000	132.	164.	170.		202.	236.	408.	60.	420.	---	520.	400.	
4 POLE—HALF NEUTRAL—277/480 VOLTS (7 1/2 INCH FACE)													
	800	\$31.	\$38.	\$122.	\$122. ②	\$144.	\$168.	\$122.	\$14.	\$100.	\$14.	\$130.	\$130.
	1000	39.	47.	122.		144.	168.	122.	14.	116.	14.	150.	160.
	1350	55.	66.	170.		202.	236.	244.	28.	214.	28.	260.	260.
	1600	66.	80.	170.		202.	236.	244.	28.	246.	28.	260.	260.
	2000	82.	98.	170.		202.	236.	244.	30.	262.	28.	300.	320.
	2500	102.	123.	170.		202.	236.	244.	42.	284.	---	390.	390.
	3000	123.	147.	202.		236.	270.	488.	45.	312.	---	450.	480.
4000	164.	196.	202.		236.	270.	488.	60.	448.	---	600.	640.	
4 POLE—FULL NEUTRAL—277/480 VOLTS (7 1/2 INCH FACE)													
	800	\$36.	\$44.	\$122.	\$122. ②	\$144.	\$168.	\$122.	\$14.	\$100.	\$14.	\$130.	\$130.
	1000	44.	55.	122.		144.	168.	122.	14.	116.	14.	150.	160.
	1350	62.	77.	170.		202.	236.	244.	28.	214.	28.	260.	260.
	1600	76.	92.	170.		202.	236.	244.	28.	246.	28.	260.	260.
	2000	92.	114.	170.		202.	236.	244.	30.	262.	28.	300.	320.
	2500	115.	143.	170.		202.	236.	244.	42.	284.	---	390.	390.
	3000	138.	171.	202.		236.	270.	488.	45.	312.	---	450.	480.
4000	184.	228.	202.		236.	270.	488.	60.	448.	---	600.	640.	

① Duct price includes sufficient hangers for proper mounting (2 per 10 feet of duct). U.L. approved for 10 foot support spacing.
For weatherproof construction, add 20% to footage price only.

For Feeder Duct as risers requiring a limited number of plug-in outlets per floor, add \$10 for each outlet, 3 or 4 pole.

② For flexible connectors above 800 amperes, consult factory.