UNITED STATES REGISTER COMPANY

Battle Creek, Michigan, U.S.A.

AIR CONDITIONING REGISTERS—GRILLES—DIFFUSERS—EXHAUST and BACK PRESSURE DAMPERS—ACCESSORIES



NO. 153 U.S. AIR CONDITIONING *SINGLE VALVE REGISTER, Lever-Operated.* ¼ in. Bar Spacing 22 deg. affords Non-Vision. With Rubber Sealing Gaskets. Tie-Bars Stop Vibratory Noises—Increase Strength.



NO. 256 U.S. AIR CONDITIONING MULTIPLE-VALVE REGISTER, Lever-Operated. ¼ in. Bar Spacing 22 deg Right and 22 deg Left gives 4-Way Diffusion and Non-Vision.



NO. 249 U.S. AIR CONDITIONING MULTIPLE-VALVE REGISTER, Lever-Operated Valves. Vertical Grille Bars Completely Adjustable to 45 deg Right or Left Flow and Two-Way Flow.



NO. 153-VVL U.S. AIR CONDITIONING MULTIPLE-VALVE REGISTER. Horizontal ¼ in. Bar Design. Two-Group Lever Operated, Vertical Rear Valves which afford Right and Left Flow or Two-Way Flow.



NO. 190 U.S. MULTI-FLEX REGISTER, VERTICAL STREAMLINED FRONT GRILLE BARS, HORIZONTAL REAR BARS, INDIVIDUALLY ADJUSTABLE, SCREWDRIVER OPERATED OPPOSED REAR VALVES.



NO. 191 U.S. MULTI-FLEX REGISTER, HORIZONTAL STREAMLINED FRONT GRILLE BARS, VERTICAL REAR BARS INDIVIDUALLY ADJUSTABLE. SCREWDRIVER OPERATED OPPOSED REAR VALVES.



NO. 192-L MULTI-FLEX REGISTER, VERTICAL STREAMLINED GRILLE BARS INDIVIDUALLY ADJUSTABLE. LEVER-OPERATED PARALLEL MULTIPLE VALVES. NO. 192 SAME, BUT SCREWDRIVER OPERATED OPPOSED VALVES.



NO. 201 NON-FLEX REGISTER, RETURN AIR—FIXED HORIZONTAL BARS. NO. 200—FIXED VERTICAL BARS. FOR MULTI-FLEX GRILLES AND NON-FLEX RETURN AIR FIXED BAR REGISTERS AND GRILLES, see Complete New Catalog A.

UNITED STATES REGISTER COMPANY—A-C REGISTERS—GRILLES—DIFFUSERS—DAMPERS—ACCESSORIES



NO. 1500 ROUND STEP-DOWN CEILING DIFFUSER. Also made in No. 1501 FLUSH-TYPE



NO. 1500 Round Ceiling Diffuser Cross Section



NO. 1800 ROUND CEILING DAMPER, REMOVABLE KNOB CONTROL



NO. 2500 SQUARE STEP-DOWN CEILING DIFFUSER. Also made in No. 2501 FLUSH-TYPE



NO. 2500—Cross-Section



NO. 2800 SQUARE CEILING DAMPER, REMOVABLE KNOB CONTROL

Request your copy of New Engineering CATALOG "A"



NO. 500 SERIES—U.S. ROUND CEILING DIFFUSER will be continued. Fine for Sound Outlets—also Residential.



NO. 105 U.S. DIFFUSER A-C REGISTER. 180 deg Perimeter Diffusion. Three Sizes Only—10 x 6—12 x 6—14 x 6.



NO. 410 DIFFUSER FLOOR REGISTER for Perimeter Systems. Made in Nine Sizes

2¼ x 10	4 x 10	6 x 10
2¼ x 12	4 x 12	6 x 12
2¼ x 14	4 x 14	6 x 14



NO. 400 U.S. TRUSSTEEL FLOOR REGISTER, Grid-Bar Face 2 x ½ in. O.C. spacing of Bars.



NO. 600 U.S. SANI-STEEL REGISTER, 13/16 in. Square Mesh 3/16 in. Bars. Valve and body construction same as No. 400; *Lever Operation No. 600. Key Lock Operation* specify No. 625. Key-Operation specify No. 620. Pole-Operation specify No. 650.