

The Hazards of Asbestos for Brake Mechanics

BARRY CASTLEMAN, LUCILLE A. CAMAROTA, ALBERT J. FRITSCH,
SUSAN MAZZOCCHI, and ROBERT G. CRAWLEY

ASBESTOS is the generic name of a group of hydrated magnesium silicate mineral fibers. There are two groups of these minerals—serpentine (chrysotile) and amphibole (amosite, crocidolite, anthophyllite, tremolite, and actinolite). Ninety-five percent of the world's asbestos production is chrysotile.

Reports of epidemiologic and pathological studies (1-4) reveal that occupational exposure to commercial asbestos minerals enhances the likelihood of a number of diseases—asbestosis and cancers of the lung, pleura, peritoneum, larynx, and gastrointestinal tract. The time from onset of exposure to the time of clinically apparent disease is usually more than 20 years. Cancer from asbestos is not limited to workers who handle the material. There are also reports of pleural and peritoneal mesothelioma (tumors rarely seen in the general population) in persons with family, or neighborhood, or indirect occupational exposure to asbestos (4-7).

Mesothelioma was the cause of death of a man who had regularly sanded vinyl asbestos floor tile (8). Under simulated conditions of this man's work, a maximum asbestos dust concentration of 1.3 fibers per ml (fibers longer than 5 microns) was found in air samples passed through membrane filters worn by a person sanding vinyl asbestos (8). The type of asbestos now used in domestic floor tile is chrysotile—the same as that used in brake friction materials, according to the Asbestos Information Association. A case of mesothelioma in a brake mechanic has been reported (9).

Commercial friction materials used in the United States for braking passenger cars and trucks contain an average composition of 50 percent chrysotile by weight (10). Asbestos has been used for brake drum linings,


disk pads, and clutch facings for the past 50 years. Jacko and DuCharme (11) estimated that the United States annually uses 103 million pounds of asbestos for brake friction materials and 4.5 million pounds in automotive clutch friction materials.

In 1968 Lynch reported that because of the heat of friction caused by braking, almost all of the asbestos in brake linings is transformed to a nonfibrous mineral, and a small fraction of asbestos escapes as free fiber (12). Jacko and co-workers determined that vehicles in this country emit 158,000 pounds of asbestos per year, of which 11.2 percent is retained in the brake and disposed of during service (13).

Brake mechanics have low and intermittent exposure to asbestos. This exposure has been reported to be 0.79 fiber per ml time-weighted average (fibers longer than 5 microns), with peaks up to 7 fibers per ml when brake parts are being cleaned (14). The standard method for removing dust from brake parts is to blow it out with a

□ Mr. Castleman, an environmental engineer, was with the Center for Science in the Public Interest when this paper was prepared; he is now with the Maryland Public Interest Research Group. Dr. Fritsch is director of the Center for Science in the Public Interest. Ms. Camarota is an occupational health nurse, District of Columbia Department of Human Resources. Ms. Mazzocchi was a research associate, Environmental Cancer Research Project, Environmental Sciences Laboratory, Mount Sinai School of Medicine, New York City. Mr. Crawley is a sanitarian, Baltimore County Department of Health.

Teasheet requests to Barry Castleman, Maryland Public Interest Research Group, 3110 New Main Dining Hall, University of Maryland, College Park, Md. 20742.



foot of air to 2 fibers per ml (fibers longer than 5 microns). For asbestos textile plants, this reduction is about 15-fold (22). Present and scheduled standards claim only to protect workers against asbestosis, the disease for which the dose-response relationship is most quantitatively known. The British standards for chrysotile and amosite asbestos, which are comparable to the asbestos standard scheduled to take effect in the United States in 1976, do not purport to provide protection against increased risk of cancer (23,24).

Previously studied cohorts of asbestos workers were exposed to time-averaged concentrations greater than 2 fibers per ml (fibers longer than 5 microns). Current studies of cohorts with time-averaged exposure on the order of 1 fiber per ml (greater than 5 microns in length) may provide evidence of hazard at that level. In view of alarming preliminary findings of pulmonary fibrosis in such a cohort, the National Institute of Occupational Safety and Health has suggested to the Department of Labor that consideration be given to further lowering of the asbestos standard (25).

The average brake mechanic is not aware of the potential hazard of airborne brake dust. Nor is he quick to change time-hardened habits when warned of dangers if he cannot feel their effects. Nonetheless, substantial reduction in asbestos exposures during brake repair can be achieved by simple changes in technique, with the use of equipment already available in most brake service establishments.

In view of the tendency of the accumulating literature to reveal cancer induction from asbestos at progressively lower levels of exposure, mechanics should be advised not to blow out brake parts and to use instead methods which create less airborne dust. The manufacturers of automotive friction materials could easily attach a clear hazard warning to every item sold.

The limited success of both the Baltimore and Washington studies shows the limited efficacy of voluntary compliance with health warnings—the shop managers and the mechanics simply do not have the same regard for a warning that they have for a regulation. The margin of safety, if any, provided by the current asbestos standards has been sharply criticized as insufficient (26). While it is advisable that brake mechanics at least be warned of the potential hazard of their work, it is also apparent that blowing out brakes will be a common practice so long as health regulations permit it.

References

- Cooper, W. C., et al.: Asbestos—the need for and feasibility of air pollution controls. National Academy of Sciences, Washington, D.C., 1971.
- Selikoff, I. J., Hammond, E. C., and Churg, J.: Mortality experiences of asbestos insulation workers. In *Proceedings of the International Conference on Pneumoconiosis*, Johannesburg, 1969, edited by H. A. Shapiro. Oxford University Press, Capetown, South Africa, 1970, pp. 180–186.
- Stell, P. M., and McGill, T.: Asbestos and laryngeal carcinoma. *Lancet* 2: 416–417, Aug. 25, 1973.
- Newhouse, M. L., and Thompson, H.: Mesothelioma of the pleura and peritoneum following exposure to asbestos in the London area. *Br J Ind Med* 22: 261–269 (1965).
- Lichen, J., and Pistawka, H.: Mesothelioma and asbestos exposure. *Arch Environ Health* 14: 559–563 (1967).
- Wagner, J. C., Sleight, C. A., and Marchand, P.: Diffuse pleural mesothelioma and asbestos exposure in the North Western Cape Province. *Br J Ind Med* 17: 250–271 (1960).
- Dalquen, P., Dabbert, A. F., and Hinz, L.: Epidemiologie der Pleuramesothelioma. Vorläufiger Bericht über 119 Fälle aus dem Hamburger Raum. *Prax Pneumol* 23: 547–558 (1969).
- Murphy, R. L., et al.: Floor tile installation as a source of asbestos exposure. *Am Rev Respir Dis* 104: 576–580, October 1971.
- Sullivan, R. J., and Athanassiadis, Y. C.: Preliminary air pollution survey of asbestos. National Air Pollution Control Administration, APTD 69–27, Raleigh, N.C., 1969, p. 32.
- Harwood, C.: Asbestos air pollution from the wear of brake linings. Illinois Institute of Technology Research Institute, Chicago, April 1972.
- Jacko, M. G., and DuCharme, R. T.: Brake emissions: emission measurements from brake and clutch linings from selected mobile sources. Environmental Protection Agency Report 68-04-0020, Ann Arbor, 1973.
- Lynch, J.: Brake lining decomposition products. *J Air Pollut Control Assoc* 18: 824–826 (1968).
- Jacko, M. G., DuCharme, R. T., and Somers, J. H.: Brake and clutch emissions during vehicle operation. Paper presented at Society of Automotive Engineers Meeting, Detroit, May 1973.
- Hickish, D. E., and Knight, K. L.: Exposure to asbestos during brake maintenance. *Ann Occup Hyg* 13: 17–21 (1970).
- Hatch, D.: Possible alternatives to asbestos as a friction material. *Ann Occup Hyg* 13: 25–29 (1970).
- Knight, K. L., and Hickish, D. E.: Investigations into alternative forms of control for dust generated during the cleaning of brake assemblies and drums. *Ann Occup Hyg* 13: 37–39 (1970).
- Lee, G. L.: Removing dusts from brake assemblies during vehicle servicing—alternative cleaning methods. *Ann Occup Hyg* 13: 33–36 (1970).
- Bentley, M. L.: Control of the use of asbestos-containing friction materials. *Ann Occup Hyg* 13: 31–32 (1970).
- U.S. Senate, Committee on Commerce: Toxic Substances Control Act of 1973. Hearings before the Environment Subcommittee. Statement of B. Castleman. 93d Cong. U.S. Government Printing Office, Washington, D.C., 1973, pp. 117, 349–350.
- Guenther, G. C.: Emergency standard for exposure to asbestos dust. *Federal Register*, vol. 36, No. 234, Dec. 7, 1971, pp. 23207–23208.
- Guenther, G. C.: Standard for exposure to asbestos dust. *Federal Register*, vol. 37, No. 110, June 7, 1972, pp. 11318–11322.
- Lynch, J. R., Ayer, H. E., and Johnson, D. L.: The interrelationship of selected asbestos exposure indices. *Am Ind Hyg Assoc J* 12: 598–604 (1970).
- Hygiene standard for chrysotile asbestos dust. *Ann Occup Hyg* 11: 47–49 (1968).
- Hygiene standards for airborne amosite asbestos dust. *Ann Occup Hyg* 16: 1–5 (1973).
- Key, M. M.: Reopening of asbestos standard. Memorandum to J. Stender, Assistant Secretary of Labor, Occupational Safety and Health Administration. Office of Technical Publications, National Institute for Occupational Safety and Health, Rockville, Md., March 28, 1974.
- Gee, B., and Bouhuys, A.: Action on asbestos. *N Engl J Med* 285: 1317–1318, Dec. 2, 1971.

