

DIXIE MADE FOR DIXIE TRADE

*Climatic*

**DIXIE-LAC**

QUICK-DRYING

ENAMEL

1250 DELPHINIUM

**THE AMERICAN PAINT WORKS**

DIVISION

**THE GLIDDEN COMPANY**

\* NEW ORLEANS, LOUISIANA \*

GL031592

*Handwritten notes:*  
Pigment 25.5%  
Volatile 50.5%  
Solids 24.0%



# TIME TESTED

PAINTS • VARNISHES • LACQUERS • ENAMELS

## DIXIE-LAC Quick-Drying ENAMEL

For use on furniture, kitchen and bathroom walls; woodwork; toys, boats, autos, porch and lawn furniture; vehicles, implements, or wherever a hard, smooth, gloss finish is desired. Dries dust-free in two hours and hard in 4 to 6 hours, depending on weather conditions. Dixie-Lac may be used for any interior or exterior enameling.

### DIRECTIONS

Stir enamel thoroughly before using.

**OLD PAINTED SURFACES**—Remove loose paint and rough spots by sanding lightly with fine sandpaper. Then wipe off with mild soap and water; let dry well. One coat of Dixie-Lac usually is sufficient. Two coats may be applied if desirable. Let first coat dry overnight. If a distinct change in color from dark to light is planned, clean the surface carefully and proceed as suggested for new wood.

**NEW UNPAINTED SURFACES**—Apply Dixie-Lac Flat White as a first coat. For second coat, mix equal parts of Dixie-Lac Flat White and Dixie-Lac Enamel. Final coat should be Dixie-Lac Enamel as it comes from the can. Sand lightly between coats.

**PLASTER WALLS**—New plaster should be primed with Interior Base Coat. Finish with one or two coats of Dixie-Lac. On old painted surfaces Dixie-Lac may be applied without undercoat. However, if old surface is porous or worn from repeated washings, a coat of Interior Base Coat should be applied. (Dixie-Lac will cover about 600 square feet per gallon depending upon nature of surface.)

64

WHEN DIXIE-LAC IS FOUND TOO HEAVY, THIN WITH TURPENTINE