

GASOLINE

TEXACO INC.
INDUSTRIAL HYGIENE, TOXICOLOGY, AND MATERIAL
SAFETY DATA SHEET



NOTE: NO REPRESENTATION IS MADE AS TO THE ACCURACY OF THE INFORMATION
 HEREIN. SEE PAGE 7 FOR CONDITIONS UNDER WHICH DATA ARE FURNISHED.

Trade Name and Synonyms	
00360 TEXACO SUPER UNLEADED	
Manufacturer's Name	Emergency Telephone No.
Texaco Inc.	(914) 831-3400 ext. 204
Address	
P.O. Box 509 Beacon, NY 12508	
Chemical Name and/or Family or Description	
Automotive Lead-Free Gasoline	
THIS PRODUCT IS CLASSIFIED AS: _____ NOT HAZARDOUS:	
☒ HAZARDOUS BY DEFINITION NO(S) 1,2,5,10,12 _____ ON ATTACHED EXPLANATION SHEETS	
WARNING STATEMENT: DANGER! EXTREMELY FLAMMABLE HARMFUL OR FATAL IF SWALLOWED MAY BE HARMFUL IF INHALED; MAY CAUSE IRRITATION MAY BE HARMFUL IF ABSORBED THROUGH SKIN	
OCCUPATIONAL CONTROL PROCEDURES	
Protective Equipment (Type)	
Eyes	Chemical type goggles or face shield optional.
Skin	Protective clothing such as uniforms, coveralls or lab coats should be worn. Launder or dry clean when soiled. Gloves resistant to chemicals and petroleum distillates required.
Inhalation	SCBA or supplied air respiratory protection required for entry into tanks, vessels, or other confined spaces containing gasoline.
Ventilation	Adequate to meet permissible concentrations.
Permissible Concentrations:	
Air	The ACGIH (1984-85) TWA for gasoline is 300ppm; Texaco recommends a TWA of 100ppm.
EMERGENCY AND FIRST AID PROCEDURES	
First Aid	
Eyes	Flush with water for fifteen minutes.
Skin	Wash exposed areas with soap and water.
Ingestion	Do NOT induce vomiting. May cause chemical pneumonitis. Call a physician.
Inhalation	Should symptoms noted under physiological effects occur, remove to fresh air. If not breathing, apply artificial respiration.
Other Instructions	Remove gasoline-soaked clothing.

DO A 061861
 CONFIDENTIAL

**ENVIRONMENTAL PROTECTION**Code
No.

00360

Waste Disposal Method

Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures and processes may change classification to non-hazardous or hazardous for reasons other than, or in addition to, ignitability. (See Remarks for Waste Classification.)

Procedures in Case of Breakage or Leakage

(Transportation Spills Call CHEMTREC (800) 424-9300)
Eliminate all ignition sources including internal combustion engines and power tools. Ventilate area. Avoid breathing vapor. Use SCBA or supplied-air mask for large spills in confined areas. Contain spill if possible. Remove with inert absorbent.

Remarks:

Waste Classification: Product (as presently constituted) has the RCRA characteristic of ignitability and if discarded in its purchased form would have the hazardous waste number D001.

PRECAUTIONS

DANGER! EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
MAY BE HARMFUL IF INHALED; MAY CAUSE IRRITATION
MAY BE HARMFUL IF ABSORBED THROUGH SKIN
Long term exposure to vapors has caused cancer in laboratory animals. Keep away from heat, sparks and flame.
Avoid breathing vapor. Use only in well-ventilated locations.
Avoid contact with eyes and prolonged contact with skin.
Keep container closed. Wash thoroughly after handling.
FOR USE AS MOTOR FUEL ONLY

Requirements for Transportation, Handling and Storage:

Transport, handle and store in accordance with OSHA Regulation 1910.106, and applicable D.O.T. regulations.

DOT Proper Shipping Name: Gasoline

DOT Hazard Class (if applicable): Flammable liquid, UN 1203

CHEMICAL AND PHYSICAL PROPERTIESBoiling Point (PF) >90 Vapor Pressure >-350 (mmHg)Specific Gravity 0.7-0.77 (H₂O=1) Vapor Density 3-4.0 (Air=1)Appearance and Odor Light straw to light red liquidpH of undiluted product N.A.Solubility slightPercent Volatile by Volume 100Evaporation N.D. () - 1Viscosity <1.4 cSt @ 100FOther -Hazardous Polymerizations Occur X Do not occur

The Material Reacts Violently With: (If others is checked below, see additional comments on page 6 for further details)

Air	Water	Heat	Strong Oxidizers	Others	None of These
		X	X		

ND - Not Determined
< - Less ThanN.A. - Not Applicable
> - Greater Than



PRODUCT SHIPPING LABEL

Code
No.

00360

00360 TEXACO SUPER UNLEADED

DANGER! EXTREMELY FLAMMABLE

HARMFUL OR FATAL IF SWALLOWED

MAY BE HARMFUL IF INHALED; MAY CAUSE IRRITATION

MAY BE HARMFUL IF ABSORBED THROUGH SKIN

Long term exposure to vapors has caused cancer in laboratory animals. Keep away from heat, sparks and flame.

Avoid breathing vapor. Use only in well-ventilated locations.

Avoid contact with eyes and prolonged contact with skin.

Keep container closed. Wash thoroughly after handling.

FOR USE AS MOTOR FUEL ONLY

If swallowed, do not induce vomiting. Call a physician immediately. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Wash skin with soap and plenty of water. Gasoline-soaked clothing should be removed and laundered before reuse.

In case of fire use water spray, foam, dry chemical or CO2.

Chemical/Common Name	CAS No.	Range in %
Gasoline consists mainly of straight chain and branched paraffinic hydrocarbons, olefins, cycloparaffins and aromatics. The benzene content normally varies from 0.2-3.5% with a typical value of 1.4%.	MIXTURE	100.00

Hazardous according to OSHA (1910.1200) or one or more state Right-To-Know lists.

HMIS

Health : 2 Reactivity : 0
Flammability: 4 Special :

Proper Shipping Name: Gasoline
Hazardous Class : Flammable liquid, UN 1203

CAUTION Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

HEALTH EMERGENCY TELEPHONE: (914) 831-3400 (EXT. 204)

Texaco Inc.
2000 Westchester Avenue
White Plains, New York 10650

For Additional Information Concerning:

Fuels/Lubricants/Antifreezes
call (914) 831-3400 (EXT.204)

Chemicals
call (512) 459-6543

Transportation Spills
call CHEMTREC (800) 424-9300