ALLIED CHEMICAL CORPORATION

RECEIVED

FEB 7 1972

LEGAL DEPT.

February 4, 1972

Mr. John R. Taylor
Specialty Chemicals Division
Morristown - DAB-1

Subject: Revised Labeling
for Vinyl Chloride

The MCA is reviewing Chemical Safety Data Sheet SD-56 and it is expected that a revised sheet will be issued in the near future. An announcement on its availability will appear in the MCA General Bulletin.

For your information and guidance you will find attached the revised precautionary labeling for vinyl chloride, approved by the MCA Lapi Committee at their January 25-26, 1972 meetings, which will appear in revised SD-56 when it is issued.

EDWARD HOGAN
Labeling Specialist

cc: Mr. Lloyd Flanner
Mr. Wm. A. Knapp
Mr. Stanley R. Stevinson

ASI-PR 0003145

MANUFACTURING CHEMISTS ASSOCIATION
1872 A CENTURY OF SERVICE 1972
1825 CONNECTICUT AVENUE, N.W. WASHINGTON, D.C. 20009 (202) 483-6126

January 31, 1972

TO: LABELS AND PRECAUTIONARY INFORMATION COMMITTEE

Subject: Label for SD-56 (Vinyl Chloride)

Gentlemen:

Attached is a copy of the subject label as approved at the January 25-26, 1972 LAPIC meeting, except that "foam" has been deleted from the fire statement. Mr. Stephenson explains that mention of foam has been deleted from the data sheet, since it is ineffective.

Sincerely yours,

M. M. Hoover, Secretary
Labels and Precautionary
Information Committee

MMH:ckm

Attachment

Distribution "C"

cc: Mr. F. G. Stephenson

ASI-PR 0003146

VINYL CHLORIDE

DANGER! EXTREMELY FLAMMABLE LIQUID
AND GAS UNDER PRESSURE
HARMFUL IF INHALED
MAY POLYMERIZE VIOLENTLY UNDER FIRE
CONDITIONS OR LOSS OR REMOVAL OF INHIBITOR

Keep away from heat, sparks, and open flame.
Keep container closed.
Use with adequate ventilation.
Avoid breathing vapor.
Avoid contact with skin.
Keep cylinder out of sun and away from heat.
Container should be grounded when being emptied.
Never drop cylinder.

FIRST AID: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

In case of:
Fire - Use water spray, dry chemical, or CO_2.
Spill or Leak - For small spills, evacuate area and permit to evaporate. For large spills or leaks, evacuate area. Dike or flush to ground and let evaporate. Do not flush to sewer because of explosion hazard.

MCA Chemical Safety Data Sheet SD-56 available.