

FILE NAME: Raybestos-Manhattan (RBM)

DATE: 1937 May

DOC#: RBM118

DOCUMENT DESCRIPTION: US Public Health Report - A Study of Dust Control Methods in an Asbestos Fabricating Plant with Cover Letter from RBM

COPY

General Asbestos & Rubber Division

of Raybestos-Manhattan, Inc.

North Charleston, S. C.

May 23, 1937

Dr. R. R. Mayers, Senior Surgeon,
Chief, Division of Industrial Hygiene,
National Institute of Health,
U. S. Public Health Service,
Washington, D. C.

Dear Doctor:-

I have received yours of the 20th enclosing a copy of the paper showing the results of the study conducted at our plant during the month of March of this year. I delayed acknowledging this paper immediately as I wished to read same very carefully, and after having read this report I feel that Messrs. Page and Bloomfield have made a very careful study of the conditions existing at this plant. Also, I wish to thank you for the opinion expressed as per the last sentence of the first paragraph of your letter of the 20th.

In regard to the statement as made in the second paragraph of your letter as to your desiring to publish this report in the official organ of the Public Health Service (Public Health Reports), I would like to advise that when Dr. Wilson of the South Carolina State Health Department first approached me in regard to this matter, I advised Dr. Wilson that I would have to first take the matter up with our President, Mr. Sumner Simpson, before I could grant his request as to making a study of this plant. After taking the matter up with Mr. Simpson, it was agreed with Dr. Wilson that no publicity would be given as to the results of the inspection by the U. S. Health Department in cooperation with the South Carolina State Department of Health until after your report had been submitted to us and we could pass on same. I am, therefore, in accordance with that understanding, forwarding today to Dr. Simpson the report which you submitted, along with your letter, and requesting Dr. Simpson to give consideration to your request as to the publishing of the report. Just as soon as I hear from him, I will advise you.

I might also state that I have made a copy of this report and have turned it over to Mr. Julian Mitchell for his consideration. Thanking you for having sent me this report and also for your letter of the 20th, and with kindest personal regards to you and also to Messrs. Page and Bloomfield, I remain,

Yours very truly,

GENERAL ASBESTOS & RUBBER DIVISION
of Raybestos-Manhattan, Inc.

E. H. Jefforis, Gen. Mgr.

EHJ:je

cc: Mr. Mitchell

Mr. Simpson ✓

Chase

A STUDY OF DUST CONTROL METHODS IN AN ASBESTOS FABRICATING PLANT

By

Richard T. Page, Assistant Public Health Engineer, and
J. J. Bloomfield, P. A. Sanitary Engineer,
United States Public Health Service.

An extensive medical and engineering study of the health of asbestos workers has been conducted by the United States Public Health Service⁵. The material contained in this paper supplements the general study with a detailed study of the dust control methods used in an asbestos fabricating plant.

The following report on present conditions and how they have been obtained is presented as an example of the results of the application of scientific methods of dust control. These data should be interesting not only to the asbestos industry but also to other industries having similar dusty processes. The plant studied has only partly completed an extensive dust control program and conditions are being improved continually and, consequently, these results should not be interpreted as representing the maximum possible efficiency in the control of asbestos dust, but it is believed that they are representative of the best practice in this country at this time. The dust control systems in use with the various processes in each department are described. An occupational analysis of employees is presented with a comparison of the atmospheric dust concentrations associated with controlled and similar uncontrolled processes.

FABRICATION OF ASBESTOS TEXTILES

Asbestos is the class name for several different fibrous minerals but the asbestos of commerce¹ is mainly the fibrous form of serpentine

known as chrysotile*. Due to its fibrous nature, flexibility, and heat resistant properties, asbestos fiber finds many practical applications. One of its important industrial uses is in the manufacture of fire resistant textiles.

In the plant studied, practically all raw material was crude Canadian or South African Asbestos. Some imported short fiber was used, as well as some of the short fiber salvaged in the recovery process, but most of the short recovered fiber was shipped to other plants. Significant variations in atmospheric dust concentrations due to the grade of fiber being processed were not evident in controlled processes in this plant. Consequently, the type of fiber used has not been considered in the analysis of the data. Each dust controlled process tended to decrease the amount of dust generated in subsequent processes. These factors must be considered when comparing dust concentrations reported in this plant with the data which have been reported for other plants.

Approximately three hundred persons were employed in this plant, of whom one hundred and eighty worked in departments having a potential asbestos dust hazard. This study was confined to these departments, namely: preparation; carding; spinning; twisting and winding; and weaving. The occupational distribution of exposed workers is shown in Table I.

(Take in Table I)

* Chrysotile is a hydrous magnesium silicate ($H_4Mg_3Si_2O_9$ or $2H_2O.3MgO.2SiO_2$) containing 44.1% silica, 43.0% magnesia and 12.9% water. Other types of asbestos often contain silicates of iron, calcium and aluminum as well as magnesium.^{2/}

METHOD OF STUDY

This investigation included a study of atmospheric dust concentrations in the factory workrooms, and a study of the exhaust systems used to remove asbestos dust.

Eighty-two atmospheric dust samples were collected at the workers' breathing level with the impinger dust sampling apparatus^{3/}. Sixty-nine of these represented present working conditions and thirteen represented conditions while exhaust apparatus had been turned off for one hour. A collecting medium containing twenty-five percent ethyl alcohol in distilled water was found to prevent flocculation without causing excessive evaporation in either the sampling flasks or the counting cells. All samples were counted the day after collection. Due to the low dust concentrations encountered, most of the samples represented the dust in from twenty to thirty cubic feet of air. Samples were diluted with distilled water and counted according to the light field technic described by Bloomfield and DallaValle^{3/}. A micrometer eyepiece having an engraved square equivalent to one-fourth the standard Whipple square was used in counting. Since it is customary to count only one quadrant of the Whipple field, the same volume of sample (0.25 cu.mm.) per field was counted.

The quantities of air removed through the various exhaust systems were calculated from Pitot tube measurements of center line velocities in the pipe lines^{4/}. Average exhaust rates per process are listed in Table II and discussed below in the description of exhaust systems. Entrance velocities at open hoods were measured with an Alnor Velometer and checked with a vane anemometer. Most of the hoods were of the enclosed type designed to exhaust only enough air to prevent the escape of

asbestos dust into the workroom. Where individual measurements were impractical, air volumes exhausted through each hood were calculated from measurements of main line velocities. Whenever differences in exhaust volumes were noted between similar hoods on the same operation, the average value is given.

DESCRIPTION OF PROCESSES AND DUST CONTROL MEASURES

Asbestos is received in burlap bags containing one hundred pounds of fiber. Cotton is received in standard bales. These are the only raw materials used in the preparation of asbestos yarn at this plant. Unloading, storage and transportation of the packed raw materials were not hazardous occupations. The progress of the material from raw fiber to completed fabric is shown by means of a flow sheet (Figure I) Individual processes and the measures for dust control are described below.

(Take in Figure I)

Preparation Department.

Crushing. Some of the asbestos fiber arrives at the plant as "precrushed" fiber but most of the crude fiber has received no treatment other than mining, sorting and screening. This latter type is hand dumped from the bags into rim-wheel crushers and crushed from five to fifteen minutes. These crushers have two heavy rollers attached to a radial axle, and revolve on a smooth surfaced tray in which the asbestos is placed. The asbestos fiber is constantly stirred during crushing by revolving scrapers. After crushing, the fiber is replaced in the bags and carried to the asbestos opener. Crushers were not enclosed or exhausted in any way but the general ventilation in the preparation department was sufficient to prevent high concentrations of dust near this operation. Crusher men

had respirators** and usually wore them while loading or unloading the crushers. The average exposure of a crusherman tending three crushers was 3.5 M.P.P.C.F.

Asbestos Opening and Screening. The crushed fiber is dumped from bags to the floor beside the asbestos openers and lifted into the feed lattice hopper with wooden hand forks. Two openers of different design were in operation but the method of exhaust hooding was the same on both (See Schematic Design - Figure II). The feed lattice hopper was partially enclosed and exhausted at the top. (Hood A). A second hood exhausted the bottom fly and settled dust from the bottom of the opener (Hood B). The opened fiber was packed up by hood C and pneumatically transported to a cyclone separator where the fibers were removed and dropped onto an enclosed vibrating screen. A large portion of the dust and fine fibers entering the asbestos opener was removed by hoods A and B. Clumps of unopened fibers and pieces of rock too heavy to be lifted by the pneumatic fiber conveyor, fall onto an enclosed belt conveyor serving both openers, and were carried to the recovery process. (Belt conveyor not shown in Figure II). Exhaust volumes through the hoods were: hood A- 400 cfm, hood B- 400cfm, hood C- (pneumatic conveyor) 1800 cfm, conveyor velocity 2730 ft./minute.

(Take in Figure II)

Each opener had its own cyclone separator and enclosed and exhausted, vibrating screen. One screen had two exhaust hoods, one beside

**All employees in the preparation department and all repair men and jaintors were provided with respirators of a type approved by the U. S. Bureau of Mines against high concentrations of fine silica dust.

the charging hopper drawing 400 cfm and one over the discharge end of the screen and the stock car, drawing 770 cfm. The second screen had one hood only, over the discharge end, drawing 615 cfm. Short fibers and rock particles passing the screens fell through a chute to the enclosed recovery conveyor. Fiber failing to pass these screens dropped into a stock car. Full stock cars were pushed to a platform scale and then to the mixing beds.

The same men charged the openers and filled the stock cars. The average dust exposure of asbestos-opener operators was 3.6 M.P.P.C.F.

Cotton Openers. The best grades of insulation contain very small amounts of cotton if any, but in all other cases, cotton fiber is mixed with asbestos fiber to improve its spinning qualities. At this plant the batch seldom contained more than 15% cotton by weight but as high as 20% cotton were used in lower grade yarns. The two stage, Saco-Howell, cotton opener was exhausted at three points. 770 cfm of air were exhausted through a canopy hood over the feed lattice, 270 cfm from the bottom of the primary opener and 1120 cfm from the bottom of the secondary opener. Opened cotton fiber was discharged into stock cars. No samples were taken at the cotton openers but the operators average exposure was about 2.4 M.P.P.C.F. (General air - preparation department).

Mixing. Weighed quantities of asbestos and cotton were placed in alternate layers in the mixing beds. Occasionally, layers of roving waste from the carding room were reopened and added to the bed. Mixing was done in six exhausted booths, each 10'-2" deep by 6'-10" wide by 6' high. Sides of the booths were permanent while the back consisted

of a removable wood and canvas section. Each booth was covered by a pyramid hood 32" high through which approximately 1025 cu. ft. air per minute per hood were exhausted. The velocity of air motion into these booths averaged 50 ft. per minute during bed making and about 30 ft. per minute during picker loading. Dust concentrations averaged 5.4 M.P.P.C.F. for the bed making operation.

After a bed was placed, the picker operator removed the rear partition of the booth and forked the hatch into the charging hopper of a picker (Figure III). The picker machine mixes the fibers in revolving beaters. The four machines represented three different operations and two different types of exhaust systems. The first machine, not in operation during this study discharged mixed fiber into a stock car. This material was then passed through a second picker for remixing. The second and third machines discharged mixed fiber onto a belt conveyor which transported it to bins in the carding room. The product of the fourth picker was carried to the carding room by a pneumatic conveyor. Each of the first three machines had a hood over the charging lattice exhausting approximately 500 cfm, a pipe exhausting about 1650 cfm from the bottom-fly settling chambers under the main picker drum, and a hood over the end of the discharge lattice exhausting about 400 cfm. The fourth picker had the same hood arrangement over the charging lattice but had no bottom-fly exhaust and the mixed fiber was removed by a pneumatic conveyor exhausting approximately 2000 cfm of air at a velocity of 2550 ft. per minute. The picker operators wear respirators during the charging operation. Dust concentrations during picker charging varied from 4.0 to 9.5 M.P.P.C.F. averaging about 6.7 M.P.P.C.F.

(Take in Figure III)

Recovery Processes. Waste roving from the card room was returned to the preparation department for reopening. The roving reopener was exhausted only from the pit below the last beater, but the 1780 cfm of air drawn through this hood were sufficient to prevent the escape of dust through the discharge lattice.

The dusty air collected by the exhaust systems in the preparation and carding department was blown into a large settling chamber occupying two stories in the end of a separate building. Air was displaced from this room to a bag house occupying the second floor on the other end of this building. Dust was filtered out by burlap filters stretched on "A" frames. The filters were beaten down by hand daily during the noon rest period. The collected dust was removed during the weekend shutdown, and stored in bins in the preparation department. Bag house dust was screened on a completely enclosed and exhausted vibrating screen (Background - Figure IV) and the long fibers were removed to a cyclone collector by a pneumatic conveyor. The dust from the settling chamber, the long fibers from the bag house dust, and fibers separated by cyclones on the exhaust lines from the spooling operation and the weaving department were passed through a fly-willower and vibrating screen (Figure IV). Approximately 250 cfm of air were exhausted from the top of the charging lattice and 620 cfm from the discharge side of the opening drum. Dirt passing the screen dropped onto an inclined tray and was removed by an exhaust hood drawing 730 cfm. Fibers which did not fall through the screen were removed by the hood at the lower end of the screen (1710 cfm) and pneumatically conveyed to a cyclone collector. Rock and other impurities not picked up by the pneumatic conveyor fell into a waste box below the end of the screen. The market for recovered fiber is limited and such

fiber is usually too soiled for use in high grade textiles. Consequently only part of the collected dust was passed through this process.

Average exposure of operators was estimated at between 3 and 5 M.P.P.C.F.

(Take in Figure IV)

As a measure of the effectiveness of the dust control system in the preparation department, the exhaust fans were shutt off for one hour. Pneumatic conveyors remained in operation. Dust concentrations increased steadily to about 50 M.P.P.C.F. at which time the exhaust fans were turned on. The samples taken during this period were only a partial measure of uncontrolled conditions since the hoods and enclosures had a definite control value.

While the location and design of hoods were the most important factors in dust control in the preparation department, general ventilation helped prevent high dust concentrations. This department occupied approximately 320,000 cu. ft. of space, from which approximately 34,650 cfm of air were exhausted. Consequently 6.5 air changes per hour were produced by mechanical ventilation which was supplemented by natural ventilation through doors, windows, and roof ventilators. Fortunately heating was not a problem in this plant.

Carding Department. Mixed fiber from the preparation department was dropped from pneumatic or mechanical conveyors into bins in the carding department. A total volume of 6850 cfm was exhausted from four bins, the major portion of this air being drawn through the one or two bin doors left open during the loading of carding room stock cars. Dust concentrations as high as 40.4 M.P.P.C.F. were measured inside an active bin while the dust concentration just outside the door of the same bin was only 4.6 M.P.P.C.F. Workers, classed as stock rollers,

fork the mixed fiber from the bin into stock cars. This operation is supposed to be performed with both stock car and stock roller outside the bin door. This rule of keeping out of the bins should be strictly enforced. However, stock rollers, wearing respirators, like to push their cars under the chute and then climb into the car and "tread-down" the stock.

The cards are machines having a series of revolving cylinders wound diagonally with strips of leather set with fine, sharp, steel bristles. Carding removes remaining small bits of rock and combs the fibers into a more or less papalled condition to facilitate spinning. At the time of this study, thirty-one roving card units and two wicking cards were being operated. A roving card unit (Figure V) consisted of two cards, a breaker or primary card and a finisher or roving card.

(Take in Figure V)

The mixed fiber was fed by hand from the stock car to the feed hopper of the breaker card. The stock-roller wore a respirator during this operation. The fiber passed through the breaker card emerging as a loose blanket or web. It was carried to the finishing card by a lattice conveyor, or camel back. The fiber was stripped from the last cylinder of the finisher onto a moving leather apron where a set of reciprocating rubbers condenses it into loose rovings of unspun yarn. These rovings are wound on long "Jack" spools to be taken to the spinning department. The rovings at the extreme ends of the cards cannot be used for spinning because they lack uniform thickness. These rovings are collected by two small hoods and pneumatically conveyed to a collection bin for return to the preparation department. The exhaust system applied to roving cards is shown schematically in Figure Vi. The quantity of air

exhausted varied from 1100 cfm to 1800 cfm on different carding units with an average exhaust of 1440 cfm per unit. Cards are partially enclosed and only sufficient air is exhausted to prevent the escape of dust.

(Take in Figure VI)

Each breaker card is exhausted at three points. Hood "B" exhausts from the top of the feed hopper over the feed apron. This hopper was enclosed and covered, the cover being lifted during filling. About 160 cfm of air were exhausted through the hood. Hood "A" exhausted the top-fly from the enclosure covering the main carding cylinder. Hood "C" exhausted the bottom-fly from the settling chamber under the carding cylinders. Approximately 285 cfm were exhausted through each of these hoods.

The finishing card had four exhaust connections besides the two small hoods (G) which removed the waste roving. Hoods "E" and "F" correspond to hoods "A" and "C" respectively on the breaker card exhausting approximately 285 cfm. each. The doffer card cylinder, doffer combs and roving apron were exhausted from below through hoods "D₁" and "D₂" at 70 cfm each. About 40 cfm was exhausted through each roving collector.

The volumes of air exhausted through each hood were estimated on the basis of pipe areas. Actual volumes showed wide variations on different units.

Single cards were used in the manufacture of asbestos wick and ropesince a thick roving was desired. The wick or rope was twisted from the unspun roving. The wicking cards were exhausted at three points. Approximately 380 cfm of air were drawn from under the feed

lattice, 490 cfm were exhausted from the top of the main cylinder cover to remove the top-fly and 550 cfm were exhausted from the bottom-fly settling chamber.

Dust concentrations during carding averaged 1.7 M.P.P.C.F. This was also the average exposure of wicking card operators and wick and rope twisters. Samples taken near the carding department weight scales showed less than 0.5 M.P.P.C.F.

Card rolls were cleaned and ground at night except in cases of emergency. Cleaning was done with hand scrapers made of strips of card cloth and the card cylinder was turned by hand. Grinding was done with the usual type of card grinders. The large roll was ground in place in the carding machine. Slightly greater quantities of air were exhausted during grinding due to the decreased loss of head resulting from removal of the wooden card covers. The small card cylinders were ground in a grinding frame. These frames were partially enclosed and covered with a canopy hood exhausting 2330 cfm per grinder. Dust concentrations averaged 0.65 M.P.P.C.F. during grinding.

A special run of a group of carding machines made with all exhaust ventilation turned off and windows closed showed that dust concentrations steadily increased. At the end of one hour the concentration was 62.4 M.P.P.C.F. in the air. Under normal operating conditions about 64,000 cfm of air are exhausted from the carding department. This is equivalent to about 5.5 air changes per hour disregarding natural ventilation through windows on all four sides of the room.

Spinning, Twisting and Winding. The yarn as roving is twisted, or spun, into compact threads on either gule or ring spinning frames. In this plant most of the spinning was done on mule-spinners. The spun thread was transferred from the spinning spindles to spools, on Foster Winding

machines (spoolers). Spooled thread to be used as filler (or woof) in woven cloth was rewound on a cop winder into cops which will fit into the loom shuttles. The remaining spooled thread was respooled on twisters which twist several threads into a yarn. The number of strands used determined the size of yarn. Both plain and metallic yarn were twisted. Metallic yarn contains one or more strands of fine wire. Part of the twisted yarn was used in cloth weaving while the remaining yarn was rewound on Universal Winding frames for the market.

Mule spinning was separated from other operations in this department by partial partitions. Natural ventilation was good and no exhaust systems were used. The average dust concentration was 0.85 M.P.P.C.F. with a maximum of 1.3 M.P.P.C.F. recorded.

Ring spinning, cop winding and universal winding machines were located in the same room with the twisting machines. Average exposures in the first three operations, which were not themselves especially dusty, were due to dust from the twisting operation. With the exception of a trial exhaust system on one twister, the remaining machines were unexhausted. The trial system was reported to be satisfactory and is to be installed on all twisting machines. In this system, the bottom of the twisting frame was enclosed and a total of 1700 cfm of air per machine was drawn downward past the twisting yarns and through five conical hoods distributed along a central exhaust duct.

Average dust concentrations at the various operations in this room were ring spinning - 5.0 M.P.P.C.F.; cop winding - 6.9 M.P.P.C.F., universal winding 2.8 M.P.P.C.F. and twisting 11.0 M.P.P.C.F. with a maximum of 18.8 M.P.P.C.F. recorded beside a twisting frame. No accurate measurements of the efficiency of the exhaust system on the single exhausted twister

could be secured, but simultaneous samples on both sides of this frame showed a dust concentration of 18.0 M.P.P.C.F. on the side toward the unexhausted twisting frames and a concentration of 6.3 M.P.P.C.F. on the other side.

Four Foster Winders (spoolers) were partially separated from the other operations by partitions (Figure VII). The exhaust system consisted of an individual conical hood around each spindle holder (Figure VIII). Approximately 46.5 cfm were exhausted through each hood or a total of 9270 cfm through the 200 hoods on the four spooling frames. Dust concentrations at the spoolers averaged 2.9 M.P.P.C.F. and increased to 9.6 M.P.P.C.F. within 30 minutes after the ventilation was shut off.

(Take in Figure VII & Figure VIII)

Weaving and Inspection. Cloth, tape, listing and brake bands were woven on different types of looms. In this plant, exhaust systems had been applied to the dry cloth looms since these were considered to be the most important source of dust. The dust control program calls for installation of exhaust system on dry tape, listing and brake band looms. At present these operations are mainly performed wet or partially wet. Brake band looms were not in operation during this study. Significant differences could not be noted between dust samples collected around the various tape and listing looms. Dust concentrations ranged from 1.2 to 4.0 M.P.P.C.F. and averaged 3.0 M.P.P.C.F.

Nineteen cloth looms were in operation in this department. One of these was a wet loom and unexhausted, four were dry looms and exhausted and the other fourteen were exhausted but could be operated either wet or dry. An unexhausted loom is shown in Figure IX. The exhaust system

is shown schematically in Figure X. A double exhaust hood drew air from

(Take in Figure IX & Figure X)

under the warp while a second hood was attached to the top of the loom-lay with exhaust ducts running down the side of each picker arm to an air tight swing joint at the bottom. The openings in the loom lay hood consisted of four slots nine inches long by 1 inch wide extending over a space of four feet across the woven fabric at right angles to the warp. A total volume of approximately 10,500 cfm of air was exhausted from the eighteen hooded looms. This averaged about 580 cfm per loom, but since it was seldom necessary to operate more than ten dry looms at one time, the average quantity of air exhausted was close to 1000 cfm per loom. Exhaust dampers were provided on all looms and sufficient dampers to balance the system are closed on wet or idle looms. The average dust exposure of a weaver operating an exhausted dry loom was 0.7 M.P.P.C.F. while the average exposure in unexhausted wet weaving was 2.6 M.P.P.C.F. Samples taken beside a dry, unexhausted loom showed dust concentrations of 9.6 M.P.P.C.F. after forty-five minutes. Average dust concentrations during dry weaving have been shown as 49.7 M.P.P.C.F.^{5/}

Woven cloth was inspected, brushed and calendered on the inspection table shown in Figure XI. Each of the power driven brushes was partially enclosed and exhausted. Approximately 750 cfm of air were drawn through each of the two hoods at the front of the table and about 200 cfm was drawn through the cleaning hood at the back of the table. Dust concentrations during inspection averaged 0.5 M.P.P.C.F. A sample taken while a roll of fabric was passed across the table without benefit of exhaust showed a dust concentration of 11.8 M.P.P.C.F.

(Take in Figure XI)

Doffing, inspection and calendering of tape and listing were hand operations and were not exhausted. Dust concentrations of 5.0 M.P.P.C.F. were recorded during these operations but the exposure was intermittent.

Greelers had an average exposure of about 1.3 M.P.P.C.F. while placing spools and threading looms.

A total of 12200 cfm of air was exhausted from the weaving department corresponding to approximately 3 air changes per hour. In cold weather, warm air was distributed through the department from a plenum system while in warm weather natural ventilation was secured through use of windows on all four sides of the department.

Other Operations. Other operations in this plant consisted of processes in which the yarn was chemically treated and fabricated, or processes for chemically treating or rubberizing fabricated cloth. No potential asbestos hazard was associated with these processes with the exception of one braiding machine used to make large diameter asbestos tubing. This machine was covered with a conical canopy hood about six feet in diameter through which approximately 200 cfm of air were exhausted. A sample taken beside this machine showed a dust concentration of 0.4 M.P.P.C.F. at the operators breathing level.

Summary. Table II gives a summary of the exhausted operations, listing the number of exhaust ducts and rate of ventilation per machine, as well as the average dust concentrations to which operators are exposed. Average dust concentrations measured near corresponding unexhausted operations are tabulated to show the effectiveness of the control methods which have been described.

(Take in Table II)

Conclusion: This study of actual results secured by a dust control program in an asbestos fabricating plant is presented as an example of engineering control of an industrial hazard. Adequate data have not yet been published to justify the determination of threshold limits of dustiness which will produce asbestosis in any definite period of time. In the absence of such threshold values it is not possible to determine permissible limits of dustiness on a medical basis. Nevertheless, any appreciable decrease in the amount of asbestos dust will cause a decrease in the incidence and severity of the resulting asbestosis. The elimination of all the dust in an industrial workroom is rarely necessary from a physiological standpoint and usually economically impractical. Consequently, actual atmospheric conditions in an industry resulting from the application of practical methods of dust control, can be used as temporary standards by that industry.^{6/}

REFERENCES

- 1/ Rice, H., and Watson, T. L.; "Engineering Geology"; John Wiley & Sons, Inc.; New York; (1937)
- 2/ Fulton, W. B., Dooley, A., Matthews, J. L., and Houtz, R. I.; "Asbestosis. Part II. The Nature and Amount of Dust Encountered in Asbestos Fabricating Plants"; Spec. Bull. No. 42; Penna. Dept. of Labor and Industry; Sept. 20, 1933.
- 3/ Bloomfield, J. J., and DalleValle, J. M.; "The Determination and Control of Industrial Dust"; Pub. Health Bull. No. 217, April 1933.
- 4/ Harding, L. A., and Willard, A. C., "Heating, Ventilation and Air Conditioning"; John Wiley and Sons., Inc.; New York; 1932.
- 5/ Unpublished Data, U.S.P.H.S.
- 6/ Higgins, E., Lanza, A. J., Laney, F. B. and Rice, G. S. "Siliceous Dust in Relation to Pulmonary Disease Among Miners in the Joplin District, Missouri"; Bull. 132; U. S. Bureau of Mines, 1917.

Table I. - Occupations and Dust Exposures of Workers
in an Asbestos Textile Plant.

		Average Dust Conc. M.F.P.C.F.	
Occupation	No. of Workers	Normal	Without Exhaust Ventilation
Preparation			
Crusherman	2	3.5	59.6 (a)
Cotton Openers	1	-	
Asbestos openers	2	3.5*	
Bed Builders	2	5.4*	
Pickersmen	2	3.7*	
Others	5	2.4*	
Carding			
Carders	6	1.7*	62.4 (a)
Stock Rollers	10	4.6*	40.4 (b)
Card Tenders	8	0.7*	-
Tick, rope & cord	6	1.7	-
Others	6	0.3	
Spinning, Twisting & Winding			
Mule Spinners & Helpers	52	0.9	9.6 (a)
Ring Spinners	6	5.0	
Spoolers	16	2.9*	
Cop Winders	4	6.9	
Twisters	13	11.0	
Universal Winders	7	2.8	
Others	16	5.0	
Weaving			
Weavers-Dry Cloth	19	0.7*	9.6 (a)
" Wet Cloth		2.7	
" Tape & Listing		3.0	
Creelers	7	1.3	11.8 (a)
Inspectors - Cloth	2	0.5*	
Inspectors - Tape	2	3.1	
Others	7	1.3	

(a) Sample after one hours operations without exhaust.

(b) Sample taken inside bin during loading.

* Dust Exhaust system for this operation.

Table II.--Volumes of Air Exhausted per Machine
In Various Operations in an Asbestos Textile Plant.

Operation	Connections	Total Volume of Air Exhausts per minute (cu.ft./min.)	Dust Conc. with Exhaust P.P.T.P.	Dust Conc. without Exhaust P.P.T.P.
Asbestos Opener	2 (*)	625-1000	3.5	11.1-55.0
Vib. Screen	1	700		
Cotton Opener	3	2160	-	-
Mixing Beds	1	1025	5.4	3.1-10.6
Picker	3	2570	6.7	34.3-74.3
Roving Reopener	1	1780	2	-
Fly Willower & Screen	3 (*)	1600	-	-
Roving Cards	3	1420	1.7	62.4
Breaker (Primary)		1440		
Finisher		1420		
Wicking Card	3	1420		
Card Grinders	1	2330	0.7	-
Foster Winders† (Spoolers)	1 (+)	2225	2.9	13.1a/
Twisters	1	1700	-	11.0
Weaving (Broad Looms)	2	1500	0.7	49.7a/
Brusher - Calendar	3	1650	0.5	11.8'

* Equipped with pneumatic conveyor - exhaust thru conveyor not included

† Individual cone for each spindle connected to exhaust manifold.

a/ Unpublished data - other plants (J. M. DallaValle - U.S.P.H.S.)

b/ Fulton, et al. ref. 2/