



MATERIAL SAFETY DATA SHEET

Date of Preparation

November 12, 1985

Emergency Telephone Number

"CHEMTREC" - 1-800/424-9300

SECTION I -- PRODUCT IDENTIFICATION

Chemical Name & Synonyms: Chrysotile Asbestos

Trade Name & Synonyms: Asbestos

Chemical Family: Fibrous Mineral Silicates

Typical Formula: $Mg_3(Si_2O_5)(OH)_4$

SECTION II -- HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>Percent</u>	<u>Occupational Exposure Limits</u>		<u>Vapor Pressure</u>
		<u>PEL</u>	<u>TLV</u>	
Chrysotile Asbestos	Approx. 100%	2 fibres/cc 8 hr. TWA	Chrysotile- 2.0 fibres/cc	N.A.
C.A.S. Number: #12001-29-5		Ceiling Con- centration 10 fibres/cc	ACGIH, Documentation of TLVs at 27	
U.N. Shipping Number: 2590 (white asbestos)		OSHA Standard at 29 CFR 1910.1001		
H.M. I.S. Rating Numbers: Health-*(Possible Chronic Effects) Flammability-0 Reactivity-0		Fibres measured are those longer than 5 microns.		

SECTION III -- PHYSICAL DATA

Boiling Range: N/A	Vapor Density: N/A
Volatile Volume: N/A	Evaporation Rate Faster/Slower than Ether: N/A
Specific Gravity ($H_2O=1$): 2.4-2.6	Wt/Gal: Variable
Appearance and Odor: White fibrous dry material-no odor	

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: OSHA: N/A
(Non-flammable) DOT: N/A
Flash Point: N/A LEL: N/A
Extinguishing Media: (Use that which is appropriate for surrounding fire)
Foam "Alcohol" Foam CO₂ Dry Chemical Water Fog Other
Unusual Fire and Explosion Hazards: None
Special Firefighting Procedures: None

Section V -- HEALTH HAZARD DATA

Effects of Overexposure:

Acute - May cause eye and/or skin irritation.

Chronic - Overexposure to asbestos can cause asbestosis, a scarring of the lungs. Pleural thickening, effusion, and plaques are nondisabling conditions, seen separately or together, that have been associated with asbestos exposure. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of asbestos in humans.

Signs and Symptoms of Overexposure:

Asbestosis is associated with symptoms of labored breathing, chest pain, weakness and chest tightness. Symptoms are not usually manifest until 15-20 years after exposure.

Primary Route(s) of Entry: Dermal Inhalation Ingestion

Emergency and First Aid Procedures:

Remove asbestos slivers from skin promptly. In case of eye irritation, gently rinse with water. If irritation persists, get medical help.

Special Note: A medical surveillance program must be established for asbestos-exposed persons in accordance with the requirements of the Occupational Safety and Health Administration's standard for asbestos (29 CFR Part 1910.1001).

SECTION VI -- REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Decomposition Products: None

Conditions to Avoid: Avoid creating and breathing dust.

Incompatibility (Materials to Avoid): None

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Avoid creating dust. Collect dust by HEPA vacuum or in the wet state (wet sweeping, wet wiping) to prevent emission of airborne fibres.

Waste Disposal Method: Found at 40 CFR

§ 61.152 Standard for waste disposal for manufacturing demolition, renovation, spraying, and fabricating operations.

Each owner or operator of any source covered under the provisions of §§ 61.144-61.149 shall:

(a) Deposit all asbestos-containing waste material at waste disposal sites operated in accordance with the provisions of § 61.156; and

(b) Discharge no visible emissions to the outside air during the collection, processing (including incineration), packaging, transporting, or deposition of any asbestos-containing waste material generated by the source, or use one of the disposal methods specified in paragraphs (b)(1), (2), or (3) of this section, as follows:

(1) Treat asbestos-containing waste material with water:

(i) Mix asbestos waste from control devices with water to form a slurry; adequately wet other asbestos-containing waste material; and

(ii) Discharge no visible emissions to the outside air from collection, mixing, and wetting operations, or use the methods specified by § 61.154 to clean emissions containing particulate asbestos material before they escape to, or are vented to, the outside air; and

(iii) After wetting, seal all asbestos-containing waste material in leak-tight containers while wet; and

(iv) Label the containers specified in paragraph (b)(1)(iii) as follows:

CAUTION

Contains Asbestos.

Avoid Opening or

Breaking Container

Breathing Asbestos is hazardous
to Your Health

Alternatively, use warning labels specified by Occupational Safety and Health Standards or the Department of Labor, Occupational Safety and Health Administration (OSHA) under 29 CFR 1910.1001(g)(2)(ii).

(2) Process asbestos-containing waste material into nonfriable forms:

(i) Form all asbestos-containing waste material into nonfriable pellets or other shapes; and

(ii) Discharge no visible emissions to the outside air from collection and processing operations, or use the methods specified by § 61.154 to clean emissions containing particulate asbestos material before they escape to, or are vented to, the outside air.

(3) Use an alternative disposal method that has received prior approval by the Administrator.

§ 61.156 Active waste disposal sites.

To be an acceptable site for disposal of asbestos-containing waste material under §§ 61.151 and 61.152, an active waste disposal site must meet the requirements of this section.

(a) Either there must be no visible emissions to the outside air from any active waste disposal site where asbestos-containing waste material has been deposited, or the requirements of paragraph (c) or (d) of this section must be met.

(b) Unless a natural barrier adequately deters access by the general public, either warning signs and fencing must be installed and maintained as follows, or the requirements of paragraph (c)(1) of this section must be met.

(1) Warning signs must be displayed at all entrances and at intervals of 100 m (330 ft) or less along the property line of the site or along the perimeter of the sections of the site where asbestos-containing waste material is deposited. The warning signs must:

(i) Be posted in such a manner and location that a person can easily read the legend; and

(ii) Conform to the requirements of 31 cm x 36 cm (20" x 14") upright format signs specified in 29 CFR 1910.145(d)(4) and this paragraph; and

(iii) Display the following legend in the lower panel with letter sizes and styles of a visibility at least equal to those specified in this paragraph.

Legend	Message
Asbestos Waste Disposal Site Do Not Create Dust	2.5 cm (1 inch) Sans Serif Green or Black 1.8 cm (¾ inch) Sans Serif Green or Black 1.6 Point Green
Breathing Asbestos is hazardous to Your Health	

Spacing between any two lines must be at least equal to the height of the upper of the two lines.

(2) The perimeter of the disposal site must be fenced in a manner adequate to deter access by the general public.

(3) Upon request and supply of appropriate information, the Administrator will determine whether a fence or a natural barrier adequately deters access by the general public.

(c) Rather than meet the no visible emission requirement of paragraph (a) of this section, an active waste disposal site would be an acceptable site if at the end of each operating day, or at least once every 24-hour period while the site is in continuous operation, the asbestos-containing waste material which was deposited at the site during the operating day or previous 24-hour period is covered with either:

(1) At least 15 centimeters (6 inches) of compacted nonasbestos-containing material, or

(2) A resinous or petroleum-based dust suppression agent that effectively binds dust and controls wind erosion. This agent must be used as recommended for the particular dust by the manufacturer of the dust suppression agent. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. For purposes of this paragraph, waste crankcase oil is not considered a dust suppression agent.

(d) Rather than meet the no visible emission requirement of paragraph (a) of this section, an active waste disposal site would be an acceptable site if an alternative control method for emissions that has received prior approval by the Administrator is used.

(Secs. 112 and 301(e) of the Clean Air Act as amended (42 U.S.C. 7412, 7601(e)))

FR Doc. 86-0288 Filed 6-4-86; 9:45 am

GILLING CODE 0000-00-00

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection:

Reusable or single-use air purifying respirator -- for exposures which do not exceed the PEL by more than 10X.

Powered air-purifying respirator -- for exposures more than 10X, but less than 100X, the PEL.

Type "C" continuous flow or pressure-demand, supplied-air respirator -- for exposures more than 100X the PEL.

All respirators must be NIOSH/MSHA approved.

Ventilation: Local ventilation if engineering controls are inadequate.

Protective Gloves: (See "Other Protective Equipment")

Eye Protection: (See "Other Protective Equipment")

Other Protective Equipment:

If the ceiling concentration limit is exceeded, clothing providing whole body covering shall be supplied and its use required.

Hygienic Practices:

Do not create or breathe dust.
Do not dry sweep or use air hose for cleaning.
Do not take protective equipment or clothing home.
(See attached pamphlet, "Recommended Practices for Handling Asbestos Fiber".)

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing:

Use no hooks in loading and unloading.

Protect containers from damage.

Do not open containers in a manner that can release dust without providing proper enclosure or control measures.

Use dust suppression control measures, such as ventilation or wet-working, at all stages of asbestos handling, use and disposal.

Follow good housekeeping practices, such as wet-wiping dusty surfaces, to prevent accumulation of asbestos-containing dust.

Avoid inhalation of asbestos.

Other Precautions: Smoking greatly increases risk to health.

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, CALAVERAS ASBESTOS, LTD. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Recommended Practices for Handling Asbestos Fiber

protection of heat from friction,
a reinforcing material, resis-
tance to heat, cold and
properties of asbestos that
are of industrial applications

Asbestos is a group of hydrated
minerals characterized by fibrous
properties. Asbestos is fairly common to
many deposits and is of commercial
value. Asbestos is fibrous and, in a certain
amount, it is harmful to the lungs, maximum care
must be taken to avoid asbestos dust
exposure to asbestos dust
can result.

Packaging, transporting,
moving —asbestos
carefully and in such a
manner as to avoid the
release of bags and the
dust.

Immediately repaired, re-
packed. Any spillage of
asbestos should be cleaned up immediately —
after thoroughly
cleaned, it should be deposited in
a container for disposal.

Regulations governing
asbestos on discharge
codes, rules or
and use of

UNLOADING

Unitized loads should be lifted intact to and from
holds of ships, and off and on land transport by
forklift trucks or other suitable handling equipment.

Care should be taken to avoid puncturing the
asbestos fiber bags during unloading from ships, rail-
road cars, trucks or other modes of transportation.
Hooks or other sharp instruments should not be
used. Loose fiber accumulated during transit should
be picked up by vacuum cleaner before unloading.

STORAGE

For storage, fiber bags should be stacked and moved
with care to avoid breakage; protected from
puncture by moving vehicles; and, if possible, should
be isolated from traffic in the warehouse and covered
to prevent dust generation. To prevent deterioration
of stored bags, the principle of first-in, first-out
should be followed.

HANDLING

Maximum possible enclosure and fully effective dust
control systems should be provided at all stages of
in-plant handling where dust is created, such as in
bag opening, fiber dumping and bag disposal oper-
ations. Loose fiber should be cleaned from work
areas by vacuum cleaner, or after thoroughly wetting,
by sweeping, and then deposited in covered recep-
tacles.

PROTECTIVE EQUIPMENT

Wearing of respiratory equipment approved for pro-
tection against asbestos dust should be required at
all stages of asbestos fiber handling where quantities
of dust are generated which cannot be kept within
the permissible exposure limits by dust control equip-
ment or other methods.

TRANSPORT

Where the use of asbestos requires the transport of
loose fiber in open carts or buggies, covers should
be used to prevent spilling and dust generation.

WASTE MATERIALS

Waste materials, such as collected dust and empty
fiber bags, should be placed in special closed
receptacles and disposed of in such a manner as to
prevent the release of dust. Safety practices outlined
above in the **HANDLING** and **PROTECTIVE EQUIP-
MENT** sections should be followed during these
operations.

All dust from exhaust systems should be collected
and safely disposed of, being careful not to release
dust into the outside air. Particular attention should
be paid to the protection of employees whose job it
is to dispose of collected dust from fabric filter dust
collection and similar cleaning operations.

D 004155



November 21, 1985

Mr. E. E. Wang
J-M A/C Pipe Corporation
1051 Sperry Road
Stockton, CA 95206

Dear Mr. Wang,

Enclosed you will find a copy of our revised Material Safety Data Sheet. As per instructions on your purchase order, when this form is revised, you need a copy.

Thank you for your continued business.

Yours,

CALAVERAS NATURAL RESOURCES, INC.
General Partner

Terri Cantrell
Executive Secretary & Sales

enclosure

NOV. 22 1985

D 004156