


SIZES 1/4" thru 2"

Outside Screw And Yoke

■ GLOBE AND ANGLE

■ BOLTED BONNET

Screwed and Socket Weld Valves: For all pressures up to 600 psi at 910°F. W.S.P. 2000 psi-100°F. O.W.G. Flanged Valves: For all pressures up to 600 psi at 850°F. W.S.P. 1440 psi-100°F. O.W.G.
Renewable hard faced seat.




TYPE 5525 - GLOBE

ALSO FURNISHED WITH
2-V PORT DISCS

SIZES: 1/4" THROUGH 1"

TYPE 5526 - GLOBE


TYPE 5536 - ANGLE



TYPE 5525W - GLOBE
TYPE 5535W - ANGLE
SOCKET WELD ENDS
To ASA B16.11

TYPE 5525S - GLOBE
TYPE 5535S - ANGLE
SCREWED ENDS
To ASA B2.1

1" Size



TYPE 5525F - GLOBE
TYPE 5535F - ANGLE
FLANGED ENDS
To ASA B16.5
FACE TO FACE
To ASA B16.10

Flanges drilled unless otherwise stated on order.

Continuous Blowdown Valve
RMCoult.

SEP 3 1970

R. M. COULTER

CHEV B8 5936

HANCOCK 600# FORGED STEEL FLOCONTROL VALVES

GLOBE AND ANGLE
SCREWED, SOCKET WELD AND FLANGED ENDS

TYPES
5525
and
5535

DIMENSIONS—Screwed and Socket Weld Valves—Types 5525S and 5535W

NOMINAL PIPE SIZES	TYPE NUMBERS				A	AA	AB	B	C	D	E	F	I	K	L	M	WEIGHTS	
	SCREWED ENDS		SOCKET ENDS														GLOBE	ANGLE
	GLOBE	ANGLE	GLOBE	ANGLE														
1/4	5525S	5535S	5525W	5535W	7/8	1 5/16	1 5/16	1/4	3 5/16	3	5 15/16	5 3/4	12 1/32	.555	5/16	3/8	4	4
3/8					1 1/32	1 5/16	1 5/16	3/8	3 5/16	3	5 15/16	5 3/4	12 1/32	.690	3/8	3/8	4	4
1/2					1 5/16	1 5/16	1 5/16	1/2	3 5/16	3	5 15/16	5 3/4	12 1/32	.855	3/8	3/8	4	4
3/4					1 1/2	1 1/2	1 5/8	3/4	3 9/16	3 1/2	6 3/8	6 1/8	12 5/32	1.065	3/4	1/2	4 1/2	4 1/2
					1 7/8	1 7/8	1 7/8	1	4 3/8	4	7 3/4	7 3/8	23 1/16	1.330	1	1/2	8	8
					2 1/4	2 1/4	2 1/4	1 1/4	5 1/4	4 1/2	8 7/8	8 3/8	25 3/8	1.675	1 1/4	1/2	12	12
1					2 1/2	2 1/2	2 1/2	1 1/2	6 1/2	5 1/2	9 11/16	9 1/32	3 1/4	1.915	1 1/2	1/2	16 1/2	16 1/2
1 1/2					3 3/8	3 3/8	3 3/8	2	7	6 1/2	11 1/16	10 5/16	3 1/2	2.406	1 5/16	5/8	25	25

DIMENSIONS—Flanged Valves—Types 5525F and 5535F

PIPE SIZES INCHES	TYPE NUMBERS		D	G	H	N	P	Q	R	S	T	BOLT CIR.	HOLES		WEIGHTS	
	GLOBE	ANGLE											NO.	SIZE	GLOBE	ANGLE
1/2	5525F	5535F	3 1/2	6 3/4	6 1/2	3 3/4	1 5/8	1/2	3/16	6 1/2	3 1/4	2 5/8	4	5/8	9	8
3/4			4	8 5/16	7 15/16	4 5/8	1 11/16	3/4	5/8	7 1/2	3 3/4	3 1/4	4	3/4	14 1/2	13 1/2
			4 1/2	9 1/2	9	4 7/8	2	1	1 1/16	8 1/2	4 1/4	3 1/2	4	3/4	17	16
1			5 1/2	11 5/16	10 9/16	5 1/4	2 1/2	1 1/4	1 3/16	9	—	3 7/8	4	3/4	34 1/2	33
1 1/4			6 1/2	11 5/8	10 9/16	6 1/8	2 7/8	1 1/2	7/8	9 1/2	4 3/4	4 1/2	4	7/8	39	37
1 1/2			8 1/2	13 1/16	12 1/16	6 1/2	3 5/8	2	1	11 1/2	5 3/4	5	8	3/4	55 1/2	53

MATERIAL SPECIFICATIONS—Types 5525 and 5535

RT NO.	PART NAME	MATERIAL
1	BODY (GLOBE)	FORGED CARBON STEEL, ASTM A-105 GR. 2
2	BODY (ANGLE FLANGED)	CAST STEEL, ASTM A-216 GR. WCB
3	BONNET	FORGED CARBON STEEL, ASTM A-105 GR. 2
4	STEM	STAINLESS STEEL, AISI 416, H. T. 300 BRINELL
5	SEAT	STAINLESS STEEL, AISI 410
6	DISC	STAINLESS STEEL, AISI 420, H. T. 500 BRINELL
7	DISC NUT	CARBON STEEL, AISI B-1113
8	LOCK RING	STAINLESS STEEL, AISI 410, H. T. 250 BRINELL
9	THREAD BUSHING	STAINLESS STEEL, AISI 416, H. T. 400 BRINELL
10	PACKING GLAND FLANGE	FORGED STEEL, ASTM A-105 GR. 2
11	PACKING GLAND	STAINLESS STEEL, AISI 416, H. T. 400 BRINELL
12	PACKING GLAND BOLTS	STAINLESS STEEL, AISI 410, H. T. 300 BRINELL
13	PACKING GLAND NUTS	CARBON STEEL, CADMIUM PLATED
14	PINS	STAINLESS STEEL, AISI 416
15	PACKING RING	BRAIDED ASBESTOS WITH INCONEL WIRE, GRAPHITED & CORROSION INHIBITED
16	BONNET BOLTS	ALLOY STEEL, ASTM A-193 GR. B-7
17	GASKET	STAINLESS STEEL & ASBESTOS SPIRAL WOUND LAMINATED
18	HANDWHEEL	MALLEABLE IRON, ASTM A197
19	HANDWHEEL NUT	LOCK TYPE, CARBON STEEL
20	MARKER PLATE	ETCHED ALUMINUM
21	DIAL	BRASS
22	DIAL PLATE	BRASS
23	INDICATOR	BRASS
24	INDICATOR BRACKET	BRASS
25	INDICATOR PLATE	ETCHED BRASS
26	INDICATOR PLATE SCREWS	BRASS
27	SEAT FACING	STELLITE OR EQUAL

Page 40 for pressure and temperature ratings. See Bulletin 205 for Hancock Bronze Flocontrol Valves.

CHEV B8 5937

1300 # 2500 # 5000 #
STEEL VALVES

INSTRUMENTED VALVES


STEEL GATE VALVES

HANCOCK 600# FLOCONTROL VALVES

■ AIR, STEAM, WATER, BLOWDOWN CHARTS

AIR FLOW CHART

600# STEEL— TYPES 5525S, 5525W, 5535S & 5535W




For air at 70° F. only. For other gases, divide capacity by square root of specific gravity.

Note: If outlet pressure is greater than 55% of the inlet pressure, multiply capacity by the correction factor on Page 32, Chart #1.

4 V-Port valves only. 2 V-Port valves have half capacity.

STEAM FLOW CHART

600# STEEL— TYPES 5525S, 5525W, 5535S & 5535W




Note: If outlet pressure is greater than 55% of the inlet pressure, multiply capacity by the correction factor on Page 32, Chart #1. For superheated steam multiply by correction factor on Page 32, Chart #2.

4 V-Port valves. 2 V-Port valves have half capacity.

WATER FLOW CHART


600# STEEL— TYPES 5525S, 5525W, 5535S & 5535W



4 V-Port valves. 2 V-Port valves have half capacity.

BOILER BLOWDOWN CHART

600# STEEL— TYPES 5535S & 5535W



CHEV B8 5939

STEEL VALVES

Valway - Unit Tandem, Blow-off Valve

300# RF Flanged

Rated in service to 515 psi Boiler Blowoff pressure.

One piece forged tandem body

Inside - hard seat blowing valve

Outside - seatless seating valve

Fig. T-3948 - 3928 Series 30

2" - 300# flg Price = \$519⁰⁰ (GSTH 6/18/70)

Should be cheaper than 2-individually flanged
valves which are bolted together to make a tandem
unit (usually an angle to a straight way)

I have asked Bob Field what he thinks about it
from a maint standpoint. No answer as of 9/3/70.

Intermittent Blowdown Valve

RMC 8/21/70