Residential air conditioning (*continued*)
central systems, 652
equipment capacity, 651
equipment location, 653
equipment types, 652
gas-fired, 653
noise, 653
operating costs, 654
Resistance thermometers, 628
Resistivity, thermal, 5
Resistors, 231
electric, 5

Return
dry, 5
grille, 237, 279
mains, 5, 355, 367
openings, 279
wet, 5
Reversed return system, 5, 397
Ringelmann chart, 76, 635

Roof, roofs
heat flow through, 114–118, 121, 178–181, 184
time lag of solar radiation, 191
ventilators, 145

Room
air conditioners, 226, 652
air motion, 268, 274
control, 618
coolers, 225, 228
cross transmission noise, 352
latent heat, 197, 198
noise level, 341, 347
operating, 86
sensible heat, 197
Rotary dryer, 722
Rotary oil burner, 488, 491

S

Sabin, 5

Sanitary ventilation, 83
Saturated air, 1, 14
Saturation, 5
degree of, 5, 14, 17
pressure, 4

Scale, 735
cause and prevention, 733, 735
closed systems, 738
heating systems, 739
high temperature, 739
open systems, 738
temperature, 5

School Systems, 657
air supply, 659
control, 662
cooling, 660–662
design, 657
considerations, 658
criteria, 657
mechanical plant, 659
general considerations, 657
gravity exhaust, 660
heating, 660–662
maintenance, 662
mechanical exhaust, 660
operation, 662
types, 659–662
ventilating, 659
Secondary air, 470, 478, 495
Sensible cooling, 265
Sensible heat, 161, 167
gain, 167, 197
loss, 161

Shading of glass areas, 190, 195
Shading screen, 195
Sheet metal gages, 298, 299

Ship heating, ventilation, air conditioning, 668
air conditioning, 668, 669
design conditions, 668
factors affecting design, 668
general consideration, 668
heating, 668
insulation of ducts, 668
refrigeration, 669
requirements for space, 668
cargo, 669
living, 668
machinery, 668
storeroom, 669
systems, typical, 669
ventilating, 668

Silica gel, 601, 603
Single phase motors, 644
Skylights, 145
Slime, 734, 739
cause and prevention, 739
formers, 734
Slotted outlets, 275
Sludge, 733, 735
cause and prevention, 735
Smog, 76, 83
Smoke, 5, 73, 75
abatement, 75, 470
density measurements, 635
Smokeless arch, 5
Smokeless combustion, 470

Snow melting, 671
antifreeze characteristics, 676
circulating medium, 677
control, 679
effect of viscosity, 677
design, 671, 680
draining, 679
drifting snow, 680
heat from slab, 671, 674
heating requirements, 671
hydraulic requirements, 677
installation, 679
internal corrosion, 679
operating data, 675
pumping head, 677
safety, 679
slab construction, 673, 679
snowfall, 672, 673
testing installation, 679
thermal stresses, 679
Soil specific heat, 95

Solar constant, 5, 169

Solar heat, 169
absorbed by glass, 185
altitude, 169
calculation tables, 177, 178, 180–194
through shaded windows, 190, 195
time lag, 191
transmission of, 169
through glass, 184
through glass block, 188
through roofs, 178
through walls, 178

Solar heat gain, 169
basic principles, 169
design for figured rolled glass, 187
design for flat glass, 187
design for glass block, 188
deviation from design, 190
shading glass, 190, 195

Solar radiation, 169
absorption of, 169
magnitude, 169
Solar water heater, 760
Sol-Air temperature, 178
Solid adsorption, 602

Soot, 73, 470, 483
Sorbents, 601
absorbents, 601, 602
adsorbents, 601
Sorption, 5, 606

Sound (see *Noise*), 335
absorbers, 344–347
apparatus for measuring, 336, 636
attenuation, 336
control, 335
cross transmission between rooms, 352
general problems, 335
duct absorbers, 344–347
intensity, 336
levels, 335, 341
measurements, 336, 636
outlet absorbers, 346
pressure, 335
unit, 335, 336
Space heaters, 512–514
design, 513, 514
rating, 512–514
Specific gravity, 3
Split systems, 5
Splitter dampers, 278

Spray
apparatus, 579
booths, 706
cooling, 580
cooling ponds, 580
cooling towers, 581–589
dehumidifier, 261, 264, 594
dryer, 723
equipment, 580–582
humidifiers, 591–594
unit air conditioner, 225
Spread, air distribution, 267, 268, 273
Square foot of heating surface, 5
Squirrel-cage induction motor, 641, 642, 646

Stack, stacks, 139, 146, 515
height, 5, 147

Standard, standards (see also *Codes*), 763
air, 1
air distribution, 267
atmosphere, 33
Standard air, 1
Static
electricity elimination, 689
pressure, 4, 283, 303
regain, 294
Steady flow, energy equation, 13, 35

Steam, 5
coils, 314, 318
distribution piping, 361, 385–389
estimating consumption, 384, 385, 536, 537
flow, 362, 364, 365
flow measurement, 40, 389
heated equipment, 201, 384
heating systems, 5, 356
condensate return, 355, 388
connections to units, 380
control valves, 382
corrosion, 744
drips, 379

Index to Technical Data Section

Steam (*continued*)
flash leg, 380
gravity one-pipe air-vent, 356, 357
gravity return, 355
Hartford return, 374
high pressure steam, 364–369
low pressure steam, 364–366
mechanical return, 355
one-pipe, 355, 356
orifice, 360
piping for, 361
subatmospheric, 360
two pipe, 357
vacuum, 359
vapor, 358
jet type system, 551
meters, 40, 389
panel heating, 419
pipe capacities, 364–369
properties, 17, 26
reducing valves, 371
requirements, 383, 537
risers, 355, 366, 367
runout, 356
superheated, 5
tables, 18, 26
traps, 5, 376
valves, 382
velocity, 363, 365, 385
Steel boilers, 501
Sterilization of air, 83

Stoker, stokers, 485
classification of, 485
combustion adjustments, 486
combustion process, 486
controls, 498, 499
furnace design, 487
mechanical, 485
overfeed flat grate, 485
overfeed inclined grate, 485
sizing and ratings, 487
underfeed, 485
Subatmospheric systems, 360
Summer air-conditioning systems, 167, 651
Summer climatic conditions, 170–175
Summer comfort, 70, 71

Superheated steam, 5
Supply mains, 5
Supply openings, 237, 267, 275, 277
measurement of velocities, 632
Supports, pipe, 448

Surface
condensation, 127, 132, 134, 464
conductance, 2, 95, 98
coefficients, 98
external pipe, 438–438, 457
heating, 5
extended, 5
temperature, 124, 423, 512, 628
Suspended unit heater, 218

Symbols, 7, 8
air conditioning, 9–12
for drawings, 9
heating, 9, 10
piping, 9, 10
ventilating, 10, 11

T

Tables
air changes, 142
air-conditioning temperatures and humidities, 681–689
air leakage, 140–142
air requirements, 61
air, volume of, 18–21
air and water mixture, 14
allowable concentration
dust, fumes, 79
gases, vapors, 77, 80
altitude, pressure and temperature, 33
aluminum ducts, 299
analytical solutions for heat conduction, 58–60
anthracite size, 468, 469
antifreeze, solutions, 676
atmosphere, standard for altitudes, 33
atmospheric gas, 735
atmospheric impurities, 74, 735
attenuation
data, lining board, 346
in straight ducts, 344
of branches, 345
of plate absorber, 346
attic ventilation, 122, 136
azimuth angle, 178
black body radiation, 52
boiler ratings, 503–505
bonnet pressure, 258
bonnet temperature, 253, 254
building load factors, 539
calorific value, 368, 473, 475, 478
capture velocities, 701
carbon dioxide maximum, 480
cast-iron boiler rating, 505
ceiling temperature, 159
chimney damage survey, 524
chimney draft, 522
chimney efficiency, 520
circular equivalents of rectangular ducts, 288–289
classification of
coals, 468
motors, 642
water, 734
climatic conditions, 152, 170
coal analyses, 468
coal classification, 468
codes, 763
coil heat emission, 209
combustible elements and compounds, 478
combustion rates, 507
comfort ranges, 67
condenser design data, 585, 586
conductance, 49, 99–101
air space, 98
conduction problem solution, 54, 58–60
conductivity materials, 48, 99–101, 454
contaminant, allowable in water, 745
contaminant exhaust, 701
convection conductances, 49
conversion equations, 8
conveying velocity, 704–706, 711
cooling tower performance, 584
cooling tower pipe size, 753
copper elbow equivalents, 396
copper sheets, 300
copper tube dimensions, 438
copper tube surface, 438
correction factors
steam radiator, 211
water radiator, 211
corrosion resistance, 712, 713
cost of air conditioning, 728
degree days for cities, 529–533, 538, 539
design dry- and wet-bulb temperatures, 152–157, 168, 170–175, 668, 681
design humidity, 681–689
dew point, fuels, 482
draft in chimneys, 522
draft requirements of appliances, 522
duct attenuation, 344–346
duct combinations, 248, 249
duct gages, 238, 298, 299
duct joints, 298, 299

Tables (*continued*)
duct pressure drop, 257
duct sizing, 239, 242–252
duct velocity, 293
duct weight, 299, 300
dust concentration, 75, 79
dust particle size, 74, 75
efficiency, utilization, 528
elbow equivalent, 290, 363, 396, 416, 752
electric heating systems, 232
electric water heaters, 756
emissivity factors, 52, 98
end reflection, 346
environmental conditions, limits, 65
equivalent length of fittings, 248, 249, 363, 416, 752
equivalent temperature differentials, 180, 182
exhaust, engines, 149
exhaust pipes for machines, 704–706
exhaust velocities, 701, 704–706
fabric filters, 332
fan outlet velocity, 309
fan speed, 309
fitting allowance, 248, 249, 363, 396, 416, 752
fitting dimensions, 450–451
fixture flow, 747
fixture units, 748
flammability of gases and vapors, 80
flanged fittings surface, 457
flue gas dew point, 482
fluids, compressible, 39
free convection, 50
friction loss, pipe, 362, 365, 367, 395, 496
friction, valves and fittings, 363, 396, 416, 752
fuel combustion, 478
fuel consumption, 536
fuel oil properties, 472
fumes, concentration, 79
gas analysis, 475
gas piping capacity, 496
gaseous fuel properties, 475
glass block transfer, 123
glass sheet transfer, 123
graphical symbols, 9
grille area correction, 343
heat absorbed, cooling water, 585
heat conductance, 49, 54, 99–101
heat equivalents, 163
heat flow walls and roofs, 102–121, 182
heat gain
appliances, 200
coil heat emission, 209
glass, 186–189
glass blocks, 190–194
insulated cold pipes, 462
occupants, 198, 692
heat loss
bare copper pipe, 457
bare steel pipe, 209, 456
basement, 160
floor, 160, 161
pipe coils, 209
radiation, 52
residence, 164–166
room, 164
heat pump
heat storage materials, 576, 577
operating cost, 572
sources and sinks, 568
types, 566
heat stress evaluation, 694
heat transmission coefficients, 102–121
building construction, 102–121, 184
doors, 124
glass, 123
roofs, 114–118, 184
walls, 102–109
water heaters, 759