

BRAKE SHOE SPECIFICATIONS

APPLICATION SECTION 11
TRUCK

MODEL	LOC.	AXLE CAPACITY	BRAKE SIZE	AIR or HYD.	SHOE & LINING PART NUMBER	TRUCK
					PRIMARY	SECONDARY
1967 - continued						
F SERIES - continued						
F850/1000	R	22M, 23M	15" x 7"	A	C5TZ 2218-J	C5TZ 2218-J
F800/950	R	21M, 22M	16" x 6"	H	*C5TZ 2218-E r/b C8TZ 2218-F	*C5TZ 2218-E r/b C8TZ 2218-F
F600/800 (Eaton)	R	17M	16 1/2" x 4 1/2"	A	*C6TZ 2218-E r/b C8TZ 2218-A	*C5TZ 2219-B r/b C8TZ 2219-A
F600/800-Rockwell (Timken)	R	17M	16 1/2" x 4 1/2"	A	C6TZ 2218-D	C6TZ 2219-A
F700/850 (Eaton)	R	18M, 18.5M, 22M	16 1/2" x 6"	A	C1TZ 2218-B	C1TZ 2218-B
F700/850-Rockwell (Timken)	R	18M, 18.5M, 22M	16 1/2" x 6"	A	C1TT 2218-C	C1TT 2218-C
F800/1000 (Eaton)	R	18M, 18.5M, 22M, 23M	16 1/2" x 7"	A	C1TZ 2218-C	C1TZ 2218-C
F800/1000-Rockwell (Timken)	R	18.5M, 22M, 23M	16 1/2" x 7"	A	C1TT 2218-A	C1TT 2218-A
N-MT SERIES						
N500/750	F	5M, 5.5M, 6M	14" x 2 1/2"	H	C3TZ 2018-A	C3TZ 2019-A
N600/950, NT850	F	6M, 7M, 9M, 12M	15" x 3"	H	C4TZ 2018-B	C4TZ 2018-B
N600/1000, NT850/950	F	6M, 7M, 9M	15" x 3"	A	C5TZ 2018-E	C5TZ 2019-C
N-NT850/1000 (Bendix)	F	9M, 12M	15" x 3 1/2"	A	C5TZ 2018-F	C5TZ 2019-D
N-NT850/1000-Rockwell (Timken)	F	12M with C/P/S	15" x 3 1/2"	A	C5TZ 2018-B	C5TZ 2018-B
N-NT800/1000	F	6M, 7M, 9M	16" x 2 1/2"	A	C6TZ 2018-B	C6TZ 2019-B
NT750/1000, NT850/950	F	9M, (12M w/o C/P/S)	16 1/4" x 3 1/2"	A	C1TT 2018-E	C1TT 2018-E
N850/1000, NT850/950	F	12M with C/P/S	16 1/4" x 3 1/2"	A	C4TZ 2018-A	C4TZ 2018-A
N1000, NT850/950	F	15M	17 1/4" x 3 1/2"	A	B6QH 2018-A	B6QH 2019-A
N500/600 (Bendix)	R	11M, 13M, 15M	15" x 4"	H	C6TZ 2218-A	C6TZ 2218-A
N500/600 (Kelsey)	R	11M, 13M, 15M	15" x 4"	H	C4TZ 2218-A	C4TZ 2218-A
N600 (Bendix)	R	15M	15" x 4 1/2"	H	C6TZ 2218-C	C6TZ 2218-C
N600/750, NT850 (Wagner)	R	15M, 17M, 32M	15" x 5"	H	C5TZ 2218-B	C5TZ 2218-B
N600/750, NT850	R	17M, 32M	15" x 5"	A	C5TZ 2218-F	C5TZ 2218-F
N600/850, NT850	R	17M, 18.5M, 32M, 34M	15" x 6"	H	C5TZ 2218-D	C5TZ 2218-D
N600/1000, NT850 (Bendix)	R	17M, 18M, 18.5M, 32M, 34M	15" x 6"	A	C5TZ 2218-G	C5TZ 2218-G
NT850/950 (Bendix)	R	38M	15" x 6"	A	C7TZ 2218-B	C7TZ 2218-B
NT850-Rockwell (Timken)	R	18M dead axle	15" x 6"	A	C3TZ 2218-A	C3TZ 2218-A
N700/850, NT850	R	18.5M, 34M	15" x 7"	H	C5TZ 2218-C	C5TZ 2218-C
N700/850, NT850	R	18.5M, 34M	15" x 7"	A	C5TZ 2218-H	C5TZ 2218-H
N850/1000, NT850/950	R	22M, 23M, 38M	15" x 7"	A	C5TZ 2218-J	C5TZ 2218-J
N850/950	R	22M	16" x 6"	H	*C5TZ 2218-E r/b C8TZ 2218-F	*C5TZ 2218-E r/b C8TZ 2218-F
N600/750, NT850 (Eaton)	R	17M, 32M	16 1/2" x 4 1/2"	A	*C6TZ 2218-E r/b C8TZ 2218-A	*C6TZ 2219-B r/b C8TZ 2219-A
N600/750, NT850-Rockwell (Timken)	R	17M, 32M	16 1/2" x 4 1/2"	A	C6TZ 2218-D	C6TZ 2219-A
N700/1000, NT850/950 (Eaton)	R	18M, 18.5M, 22M, 34M, 38M	16 1/2" x 6"	A	C1TZ 2218-B	C1TZ 2218-B
N-NT700/1000-Rockwell (Timken)	R	18M, 18.5M, 22M, 34M, 38M	16 1/2" x 6"	A	C1TT 2218-C	C1TT 2218-C
N-NT850/1000 (Eaton)	R	18.5M, 22M, 23M, 34M, 38M	16 1/2" x 7"	A	C1TZ 2218-C	C1TZ 2218-C
N-NT850/1000-Rockwell (Timken)	R	18.5M, 22M, 23M, 34M, 38M	16 1/2" x 7"	A	C1TT 2218-A	C1TT 2218-A
P SERIES						
P100	F	2.6M	11" x 2"	H	C6TZ 2001-L	NOTE 1
P350/400-"Before Ser. A84,001"	F	3.8M	12 1/8" x 2"	H	*C5TZ 2001-A r/b C6TZ 2001-K	NOTE 1
P350/400-"From Ser. A84,001"	F	3.8M	12 1/8" x 2"	H	*C7TZ 2001-F r/b C7TZ 2001-J	NOTE 1
P500	F	4.7M	13" x 2 1/4"	H	TDAA 2018-B	TDAA 2019-B
P350	R	5.2M	12" x 2 1/2"	H	*C7TZ 2001-B r/b C9TZ 2001-A	NOTE 1
P350/400	R	7.4M	12" x 3"	H	*C7TZ 2001-A r/b D1TZ 2001-B	NOTE 1
P500	R	11M, 13M	14 1/8" x 3 1/2"	H	*B7J 2218-A r/b C6TZ 2218-L	*B7J 2218-A r/b C6TZ 2218-L

CONTINUED ON NEXT PAGE

F-front R-rear

NOTE 1 - 8001 or 2200 kit contains 2 primary, 2 secondary shoe and lining assays.

8008 0667

PRODUCED BY FORD