


Sarco Co., Inc.

183 Madison Ave., New York

BALTIMORE BOSTON BUFFALO CHICAGO CLEVELAND DETROIT PHILADELPHIA
PITTSBURGH RADIATOR, BLAST AND STEAM TRAPS.
PACKLESS INLET VALVES, TEMPERATURE REGULATORS AND STRAINERS



For Steam Pressure from 0 to 30 lb. Fig. 9-1 can be used. It has the same capacities as Fig. 9-2 but is furnished with brass composition valve heads and seats.

SARCO STEAM TRAP No. 9

For pressures 0 to 100 lb.

For industrial purposes, hospitals, laundry and kitchen equipment. Sarco Steam Trap No. 9 consists of a heavy bronze body with a powerful motor element of helical seamless bronze tubing containing an expansion fluid.

Is of the balanced pressure type, suitable for any steam pressure from 0 to 100 lb. *without readjustment.*

Has unusually great capacity, large valve area and quick, high lift when discharging. Cannot air bind.

Write for Booklet No. HV-261.

Size In.	Price, Each Type No. 9-2	Price, Each Type No. 9-1	Dimensions Inlet to Outlet	Capacity Lb. per Hour
1/2"	\$78.50	\$ 7.50	1 1/2"	500
3/4"	11.50	10.50	1 3/4"	600
1"	14.50	13.50	2"	800


SARCO HIGH AND LOW PRESSURE BLAST TRAPS

No. 9-3 and 9-4 (entirely Thermostatic)

This Heavy-Surface or Blast Trap is for draining steam coils of hot-water tanks, vent stacks and main drip lines; also where a large capacity trap is required such as for draining coils in dryers, vacuum pans, heating coils, cooking vessels, etc.

Will handle great flows of condensation without loss of steam. Is entirely thermostatic, so removes the air as well as water.

Operates on the same principle as the Sarco Steam Trap No. 9-2.



No. 9-3, PRESSURES 0-30 Lb.
Brass Composition Valve Head and Seat

List Prices F. O. B. Bethlehem, Pa.	Capacities Lb. per Hour
1"	1,000
1 1/2"	1,000
2"	1,500
2 1/2"	2,000

Can be furnished in offset patterns at same prices.

No. 9-4, PRESSURES 0-100 Lb.
Monel Valve Head and Seat

List Prices F. O. B. Bethlehem, Pa.	Capacities Lb. per Hour
1"	1,250
1 1/2"	1,250
2"	3,250

Write for Blast Trap and Heavy Service Booklet.



F.T. 1 (Float and Thermostatic)

Recommended for live drips, large heating units, vent stacks, hot water tanks, etc. Two inlet and two discharge connections tapped 1 1/4 in. are provided and can be adjusted to the size specified. The thermostatic by-pass releases air. The under-lying valve head insures large capacity and reduces wear.


Capacity in pounds of water per hour at pressure differential per square inch.

1/2 lb.	550	5 lb.	1600
1 lb.	725	7 1/2 lb.	1800
2 lb.	1000	10 lb.	2000

List Price: 3/4 in. 1 in. 1 1/4 in. \$25.00
F. O. B. Bethlehem, Pa. Weight: 15 lb.




SARCO RADIATOR TRAPS



Type E

For vacuum, vapor and low-pressure heating systems. The Sarco is of the thermostatic type, using Seamless Helical Bellows and a volatile liquid filling. Its positive action keeps radiators thoroughly drained, preventing water hammer and air binding.




Type H

Helical Bellows is phosphor bronze. It has a high lift, insuring free discharge, a maximum closing pressure and an unusually long life. Body is heavy brass, nickel plated. Can be used on all pressures up to 25 lb. without adjusting. Write for Booklet HV-125.

List Prices F.O.B. Bethlehem, Pa.		Dimensions		Capacity—Direct Radiation	
		Center Inlet to Outlet	Center Outlet to Face of Outlet	Vapor System Sq. Ft.	Vacuum System Sq. Ft.
Type E	1/2"	3/4"	1 1/2"	200	250
Type E	3/4"	3/4"	1 1/2"	600	800
Type E	1"	3/4"	2"	1500	1800
Type H	1/2"	3/4"	1 1/2"	125	150

Angle, straightway and offset types are furnished at same prices.

SARCO PACKLESS INLET VALVE



For use on vapor and vacuum heating systems.

This valve cannot leak as it is of the true Packless type.

By the use of the Sarco Helical Tubing it eliminates the necessity

regular. Easy to turn. Dial is distinctly marked.

Has heavy brass, well-nickled body. Furnished with lever or round moulded handles.

Write for Booklet HV-151.

List Prices F. O. B. Bethlehem, Pa.	Center Inlet to Outlet	CAPACITIES Feet Direct Radiation
1/2"	3"	up to 40 sq. ft.
3/4"	3"	41 to 75 sq. ft.
1"	3 1/2"	76 to 125 sq. ft.
1 1/4"	3 1/2"	126 to 200 sq. ft.

for packing of any kind.

Valve opens or closes with a three-quarter turn and the pressure is always even, smooth and

SARCO TEMPERATURE REGULATORS

Sarco Temperature Regulators are self-contained and self-operating. No auxiliaries such as air, water or electricity are required. They operate thermostatically by the expansion of a heavy hydro-carbon oil and are positive in action. Will operate steam, gas or water valves and can also be supplied to open with rise in temperature.

They can be used for hot water tanks, cold storage plants, dry room or kiln control and for any specified temperature from 30 to 300 deg. fahr.

Sarco Regulators can also be furnished to meet special conditions. Inquiries are invited.


Write for Booklet HV-55.

SARCO SELF-CLEANING STRAINER

For Steam, Water and Oil Lines. Write for Booklet HV-225.

SARCO AIR ELIMINATOR

Has a capacity of 15,000 sq. ft. of Direct Radiation based on one ounce pressure. Has 3/4 in. port area and is fitted with union connection.



Type TR-21