

Produced in camera under seal by order of
Judges Paul Riley and Gordon Maag,
October 18, 1989, in Jamison v. A. P. Green
et al. 87-L1230

OC-42-1-OC 8498



PURCHASE ACCEPTANCE STANDARDS

No. CRM.59.1.467

Date 6/15/62

Supersedes 6/30/61

MATERIAL - Roofing Cement (Flintkote #224 Cutback Asphalt)

SCOPE

This specification covers the necessary data for ordering a lightly fabricated cut-back cement for use as an adhesive between plies and to deck.

A. DESCRIPTION

Roofing Cement is composed of lightly fibrated cutback of 25 penetration asphalt designed primarily for spray application.

B. PROPERTIES

	<u>Rutherford</u>	<u>New Orleans</u>	<u>Chicago Heights</u>
Asphalt %	48.6-52.6	47.5-51.5	47.1-51.0
Asbestos %	11.4-12.6	10.0-11.0	10.4-11.4
Ash %	9.4-11.0	8.2-9.6	8.6-10.0
Volatiles %	35.1-39.7	37.6-42.6	37.6-42.4
Weight/Gal., Lbs.	7.9-8.2	7.5-8.3	7.4-7.7

C. CONTAINER SIZES


1 gallon - 6 per carton
5 gallon container
30 gallon drum
55 gallon drum

D. LABELS

Each container shall be neatly labeled with OCF Label No. L.1.214.

E. WARRANTIES

Manufacturer to warrant material meets these specifications and will replace material not in accordance with specification.



01 061 1194