

SL 006111

WRITTEN BY: S.L.
WRITTEN BY: S.L.
APPROVED BY: J.D.P.
DATE: 10/08/91

SOP = 6904-038.SOP
PROPER HS FILTER ELEMENT
DISPOSAL, "FLAMMABLE DERIVATIVES
FILTERS" ---SATELLITE AREA
NORTH OF THE HS

OPERATOR'S NAME: _____ DATE: _____

- 1. JOB SAFETY INSTRUCTIONS REVIEWED.
- 2. INSURE THAT YOU ARE WEARING PROPER SAFETY EQUIPMENT.
- 3. FOR PROPER CONTAINMENT OF SPENT FILTER ELEMENTS, THE SPENT FILTER ELEMENT MUST BE PLACED IN A BLUE DRUM LOCATED IN THE PROPER SATELLITE AREA.
 - a. The drum must be labeled as to its contents and labeled "HAZARDOUS WASTE".
 - b. The metal clamp on the drum must be closed and wired shut after dumping the filter element.
- 4. ONCE THE DRUM IS FULL, A "Hazardous Waste" STICKER MUST BE PLACED ON THE BLUE DRUM.
 - a. The contents of the drum and the unit identification must be written on the corner of the sticker.
 - b. The proper D.O.T. shipping name-- Waste Flammable Liquid, n.o.s., Flammable Liquid, UN1993, RQ (ETHYLENE DICHLORIDE, 1,1,2-TRICHLOROETHANE) --must be written on the sticker.
 - c. The EPA Waste Numbers F025 and (D001, D007, D008, D028, D039) must be written on the sticker.
 - d. The accumulation start date (the date the drum is full and sealed) must be written on the sticker.
- 5. A "FLAMMABLE LIQUID" STICKER MUST BE PLACED ON THE DRUM OR BE STENCILED ON THE DRUM WHEN ACCUMULATION STARTS.
- 6. THE TE II MAINTENANCE FOREMAN MUST BE CONTACTED SO THAT THE DRUM CAN BE REMOVED.
 - a. The drum must be removed from the area within 3 days after the accumulation start date.
 - b. When a drum becomes full and is labeled with an accumulation start date, a second

drum

may be used to collect waste at the same location. The second drum may not become full until the first drum has been removed.

7. IN CASE OF SPILLS OR RELEASES the reporting requirements for drums are the same as for other types of spills or releases.
- follow those guidelines described in the derivatives yellow book;
 - spills should be cleaned up immediately;
 - insure that the hazardous waste does not get into waste water trmt sustem;
 - liquids must be transported to the WTU classifier for recovery and solids should be returned to the container.

APPROVED BY: J.D.R.
DATE: 10/08/91

SOP # 6904-038.SOP
PROPER HS FILTER ELEMENT
DISPOSAL, "FLAMMABLE DERIVATIVES
FILTERS" --- SATELLITE AREA
NORTH OF THE HS

OPERATOR'S NAME: _____

DATE: _____

- 1. JOB SAFETY INSTRUCTIONS REVIEWED.
- 2. INSURE THAT YOU ARE WEARING PROPER SAFETY EQUIPMENT.
- 3. FOR PROPER CONTAINMENT OF SPENT FILTER ELEMENTS, THE SPENT FILTER ELEMENT MUST BE PLACED IN A BLUE DRUM LOCATED IN THE PROPER SATELLITE AREA.
 - The drum must be labeled as to its contents and labeled "HAZARDOUS WASTE".
 - The metal clamp on the drum must be closed and wired shut after dumping the filter element.
- 4. ONCE THE DRUM IS FULL, A "Hazardous Waste" STICKER MUST BE PLACED ON THE BLUE DRUM.
 - The contents of the drum and the unit identification must be written on the corner of the sticker.
 - The proper D.O.T. shipping name-- Waste Flammable Liquid, n.o.s., Flammable Liquid, UN1993, RQ (ETHYLENE DICHLORIDE, 1,1,2-TRICHLOROETHANE) --must be written on the sticker.
 - The EPA Waste Numbers F025 and (D001, D007, D008, D028, D039) must be written on the sticker.
 - The accumulation start date (the date the

SL 006112