EQUIPMENT		PAGE 02 OF 2 CG 01 CODE YC-016-B	USE LBS	N-CODE	ACCT LBS
	26	RUN V-358 AT 67-69*F THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV AT 67-69*F IN 17-19 MIN			
		RECORD: START 8:15 PM M & TOTAL MIN 19			
		NOTE: V-358 STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS MT			
SV 6 (CONT)	27	WHEN S 26 COMPLETED AND BEFORE WASHING IN V-358, DUMP IN N-4-A FROM S-4			
	28	RUN IN USING WEIGHT AND FLOW CONTROL PANEL			
		OPTR _____, MK 1, 29.89 %	14	28-D	22
		OPTR _____, MK _____, _____ %	_____	28-D	_____
	29	DURING S'S 27 AND 28 (IF ALONE, AFTER S'S 27 & 28) WASH IN V-358			
	30	STIR 2 MIN			
	31	RECORD: PH 11.7 (2.2-2.5) & PB XS + (+)			
	32	STIR TOTAL OF 15 MIN FROM COMPLETION OF S 26 RECORD: START 8:31 TOTAL MIN 15			
	33	DUMP IN N-3-A FROM S 1			
	34	STIR 3 MIN			
	35	RUN IN N-131-B FROM S 3 IN 7 MIN			
	36	STIR 3 MIN			
	37	POUR IN N-32-D FROM S-3			
	38	STIR 2 MIN			
	39	RUN IN USING BADGER METER	450	115-A	225
	40	STIR 3 MIN & FLUSH ALUM LINES WITH WATER			
	41	DUMP IN N-3-A FROM S 2			
	42	STIR 3 MIN			
	43	RECORD: PH 5.4 (5.8-6.0)			
	44	IF NECESSARY, ADJ TO PH 5.8-6.0 ASSUME 50%	40	7-D	20
		RECORD: PH 6.0 ASSUME 66%	_____	33-D	_____
	45	FLOOD TO 153" (7298 G)			
	46	STOP AGITATOR			

START	FINISH	OPTR
4:30 PM	9:30 PM	SL

S.V. 240, 241, 242, 245, 246 DATE PRINTED: 1/25/82

CG 01 CODE YC-016-B PQ 93 PROCESSES APPROVED BY FWP

DATE MAY 28 1982 LOT: F2H85 (A) YC-016-B ( ) FWP 10/28/81

ESTIMATED WEIGHT: 3098* LBS. COMTYP JOB NAME: 01YC016BMA

EQUIPMENT		NAME: MOLYBDATE ORANGE	USE LBS	N-CODE (RMCON)	ACCT LBS
PREP 1	1	WEIGH FOR S 33	90.	3-A	90
	2	WEIGH FOR S-41	80	3-A	80
	3	WEIGH IN DRUM FOR S-37	145	32-D	145
	4	WEIGH FOR S-27	250	4-A	250
356 2	5	RUN 25* (451 G) WATER INTO V-356			
	6	TURN ON AGITATOR AND STEAM			
	7	WEIGH AND SIFT IN	270	131-B	270
	8	HEAT TO AND MAINTAIN 60-66* C FOR S 35			
359 3	9	WEIGH IN. OPTR ____, MK 31, T-360 31.30%	684	423-D	214
		OPTR ____, MK ___, T-___, _____%			
351 4 4	10	WEIGH IN OPTR _____, MK 172, 37.84%	3015	10-D	1141
		OPTR _____, MK ____, _____%			
	11	RUN IN V-359			
358 5	12	RUN 10* (473 G) WATER INTO V-358			
	13	PUMP V-351 INTO V-358			
	14	ADJ TO 68* (3216 G) AT 67-69*F. RECORD: ___*			
	15	STIR 3 MIN. RECORD: 67 *F & PH 9.1			
	16	IF NECESSARY, ADJ TO PH 9.8-9.9 ASSUME 50%	1	7-D	1
		RECORD: PH 9.9 ASSUME 66%		33-D	
	17	RECORD: G/ML 1.047 (1.044-1.047)			
SV 6	18	RUN 40* (1908 G) WATER INTO V-241			
	19	RUN IN FROM V-354			
		OPTR 101, MK 310, 84*F, 27.56%	1056	41-D	3047
		OPTR _____, MK ____, _____*F, _____%			
	20	ADJ TO 3148 G AT 67-69*F (64* IN V-240 & V-246; 66* IN V-241, V-242, & V-245)	JUN 1 1982		
	21	STIR 3 MIN RECORD: 68*F		57-A	
	22	RECORD: PH 3.2 (2.8-3.6)			
	23	ADJ TO PH 4.0-4.1 ASSUME 66%		33-D	
		RECORD: PH 4.0 & VOL 66* ASSUME 50%	1	7-D	2
		NOTE: DILUTE N-7-D 10:1 WITH WATER			
	24	RECORD: G/ML 1.097 (1.097-1.100)			
	25	OBTAIN 1 QT SAMPLES OF S-17 & S-24 SOLUTIONS & TITRATE TWICE			
		RECORD: LOWEST PH _____ & ML N-10-D _____			
		LOWEST PH _____ & ML N-10-D _____			
		NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 8.0-8.6 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.1 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS)			
		DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE			

PROCEED TO PAGE 2

N37653

DUP050046140