

REMOVAL AND INSTALLATION (Continued)**Removal and Installation**

⚠ WARNING: Use of any other than approved DOT 3 motor vehicle brake fluid will cause permanent damage to brake components and will render the brakes inoperative. Failure to follow these instructions may result in personal injury.

⚠ WARNING: Brake fluid contains polyglycol ethers and polyglycols. Avoid contact with eyes. Wash hands thoroughly after handling. If brake fluid contacts eyes, flush eyes with running water for 15 minutes. Get medical attention if irritation persists. If taken internally, drink water and induce vomiting. Get medical attention immediately. Failure to follow these instructions may result in personal injury.

⚠ CAUTION: Brake fluid is harmful to painted and plastic surfaces. If brake fluid is spilled onto a painted or plastic surface, immediately wash it with water.

1. Remove the brake shoes and linings. For additional information, refer to Brake Shoes in this section.
2. Disconnect the brake tube-to-wheel cylinder fitting.
 - To install, tighten to 18 Nm (13 lb-ft).
3. Remove the 2 wheel cylinder bolts and the wheel cylinder.
 - To install, tighten to 15 Nm (11 lb-ft).
4. To install, reverse the removal procedure.
 - Bleed the brake system; for additional information, refer to Section 206-00.

DISASSEMBLY AND ASSEMBLY**Wheel Cylinder****Material**

Item	Specification
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1)	ESA-M6C25-A