

**APPENDIX A**  
**29 CFR PART 1910.134**

# **federal register**

**WEDNESDAY, OCTOBER 18, 1972**  
**WASHINGTON, D.C.**

**Volume 37 ■ Number 202**

**PART II**



---

## **DEPARTMENT OF LABOR**

■

### **OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION**

■

### **OCCUPATIONAL SAFETY AND HEALTH STANDARDS**

## Title 29—LABOR

### Chapter XVII—Occupational Safety and Health Administration, Department of Labor

#### PART 1910—OCCUPATIONAL SAFETY AND HEALTH STANDARDS

Pursuant to authority in sections 6 and 8(g) of the Williams-Steiger Occupational Safety and Health Act of 1970 (84 Stat. 1593, 1600; 29 U.S.C. 655, 657) and in Secretary of Labor's Order No. 12-71 (36 F.R. 8764), Part 1910 of Title 29 of the Code of Federal Regulations is hereby revised to read as set forth below. This revision includes amendments through Sept. 22, 1972. The purpose of the revision is (1) to publish fully in one place the present occupational safety and health standards contained therein in order to reflect many changes made during the current year and thereby to improve their usefulness and facilitate their enforcement; (2) to correct a number of typographical and clerical errors in the text of the standards; and (3) to publish indexes with the standards, which are intended to permit quicker access to pertinent standards.

Since this revision does not make any substantive changes in the standards, it is not necessary to provide notice of proposed rulemaking, opportunity for public participation therein, nor any delay in effective date. For the same reason, good cause is found for not following the regular procedure for rulemaking provided in 5 U.S.C. 553 and for making this revision effective immediately.

Signed at Washington, D.C. this 4 day of October 1972.

G. C. GUENTHER,  
Assistant Secretary of Labor.

##### Subject A—General

- 1910.1 Purpose and scope.
- 1910.2 Definitions.
- 1910.3 Petitions for the issuance, amendment, or repeal of a standard.
- 1910.4 Amendments to this part.
- 1910.5 Applicability of standards.
- 1910.6 Incorporation by reference.

##### Subject B—Adoption and Extension of Established Federal Standards

- 1910.11 Scope and purpose.
- 1910.12 Construction work.
- 1910.13 Ship repairing.
- 1910.14 Shipbuilding.
- 1910.15 Shipbreaking.
- 1910.16 Longshoring.
- 1910.17 Effective dates.
- 1910.18 Changes in established Federal standards.
- 1910.19 Abestos dust.

##### Subject C—(Reserved)

##### Subject D—Walking—Working Surfaces

- 1910.21 Definitions.
- 1910.22 General requirements.
- 1910.23 Guarding floor and wall openings and holes.
- 1910.24 Fixed industrial stairs.
- 1910.25 Portable wood ladders.
- 1910.26 Portable metal ladders.

- 1910.27 Fixed ladders.
- 1910.28 Safety requirements for scaffolding.
- 1910.29 Manually propelled mobile ladder stands and scaffolds (towers).
- 1910.30 Other working surfaces.
- 1910.31 Sources of standards.
- 1910.32 Standards organizations.

##### Subject E—Means of Egress

- 1910.33 Definitions.
- 1910.34 General requirements.
- 1910.35 Means of egress, general.
- 1910.36 Specific means of egress requirements by occupancy. [Reserved]
- 1910.37 Sources of standards.
- 1910.38 Standards organizations.

##### Subject F—Powered Platforms, Manlifts and Vehicle-Mounted Work Platforms

- 1910.66 Power platforms for exterior building maintenance.
- 1910.67 Vehicle-mounted elevating and rotating work platforms.
- 1910.68 Manlifts.
- 1910.69 Sources of standards.
- 1910.70 Standards organizations.

##### Subject G—Occupational Health and Environmental Control

- 1910.93 Air contaminants.
- 1910.93a Asbestos.
- 1910.94 Ventilation.
- 1910.95 Occupational noise exposure.
- 1910.96 Ionizing radiation.
- 1910.97 Nonionizing radiation.
- 1910.98 Effective dates.
- 1910.99 Sources of standards.
- 1910.100 Standards organizations.

##### Subject H—Hazardous Materials

- 1910.101 Compressed gases (general requirements).
- 1910.102 Acetylene.
- 1910.103 Hydrogen.
- 1910.104 Oxygen.
- 1910.105 Nitrous oxide.
- 1910.106 Flammable and combustible liquids.
- 1910.107 Spray finishing using flammable and combustible materials.
- 1910.108 Dip tanks containing flammable or combustible liquids.
- 1910.109 Explosives and blasting agents.
- 1910.110 Storage and handling of liquefied petroleum gases.
- 1910.111 Storage and handling of anhydrous ammonia.
- 1910.112 [Reserved]
- 1910.113 [Reserved]
- 1910.114 Effective dates.
- 1910.115 Sources of standards.
- 1910.116 Standards organizations.

##### Subject I—Personal Protective Equipment

- 1910.132 General requirements.
- 1910.133 Eye and face protection.
- 1910.134 Respiratory protection.
- 1910.135 Occupational head protection.
- 1910.136 Occupational foot protection.
- 1910.137 Electrical protective devices.
- 1910.138 Effective dates.
- 1910.139 Sources of standards.
- 1910.140 Standards organizations.

##### Subject J—General Environmental Controls

- 1910.141 Sanitation.
- 1910.142 Temporary labor camps.
- 1910.143 Nonwater carriage disposal systems.
- 1910.144 Safety color code for marking physical hazards.
- 1910.145 Specifications for accident prevention signs and tags.
- 1910.146 [Reserved]
- 1910.147 Sources of standards.

- 1910.148 Standards organizations.
- 1910.149 Effective dates.

##### Subject K—Medical and First Aid

- 1910.151 Medical services and first aid.
- 1910.152 [Reserved]
- 1910.153 Sources of standards.

##### Subject L—Fire Protection

- 1910.156 Definitions applicable to this subpart.

##### PORTABLE FIRE SUPPRESSION EQUIPMENT

- 1910.157 Portable fire extinguishers.
- 1910.158 Standpipes and hose systems.

##### FIXED FIRE SUPPRESSION EQUIPMENT

- 1910.159 Automatic sprinkler systems.
- 1910.160 Fixed dry chemical extinguishing systems.
- 1910.161 Carbon dioxide extinguishing systems.
- 1910.162 Other special fixed extinguishing systems. [Reserved]

##### OTHER FIRE PROTECTION SYSTEMS

- 1910.163 Local fire alarm signaling systems.
- 1910.164 Fire brigades. [Reserved]
- 1910.165 Effective dates.
- 1910.165a Sources of standards.
- 1910.165b Standards organizations.

##### Subject M—Compressed Gas and Compressed Air Equipment

- 1910.166 Inspection of compressed gas cylinders.
- 1910.167 Safety relief devices for compressed gas cylinders.
- 1910.168 Safety relief devices for cargo and portable tanks storing compressed gases.
- 1910.169 Air receivers.
- 1910.170 Sources of standards.
- 1910.171 Standards organizations.

##### Subject N—Materials Handling and Storage

- 1910.176 Handling materials—general.
- 1910.177 Indoor general storage.
- 1910.178 Powered industrial trucks.
- 1910.179 Overhead and gantry cranes.
- 1910.180 Crawler, locomotive, and truck cranes.
- 1910.181 Derricks.
- 1910.182 Effective dates.
- 1910.183 Sources of standards.
- 1910.184 Standards organizations.

##### Subject O—Machinery and Machine Guarding

- 1910.211 Definitions.
- 1910.212 General requirements for all machines.
- 1910.213 Woodworking machinery requirements.
- 1910.214 Coopers machinery.
- 1910.215 Abrasive wheel machinery.
- 1910.216 Mills and calendars in the rubber and plastics industries.
- 1910.217 Mechanical power presses.
- 1910.218 Forging machines.
- 1910.219 Mechanical power-transmission apparatus.
- 1910.220 Effective dates.
- 1910.221 Sources of standards.
- 1910.222 Standards organizations.

##### Subject P—Hand and Portable Powered Tools and Other Hand-Held Equipment

- 1910.241 Definitions.
- 1910.242 Hand and portable powered tools and equipment, general.
- 1910.243 Guarding of portable powered tools.
- 1910.244 Other portable tools and equipment.
- 1910.245 Effective dates.
- 1910.246 Sources of standards.
- 1910.247 Standards organizations.

- § 1910.107 (b) (1), (b) (2), (b) (3), (b) (4), (b) (5) (i), (b) (5) (ii), (b) (5) (iv), (b) (6), (b) (7), (b) (8), (b) (10), (c) (1), (c) (4), (c) (5), (c) (6), (c) (7), (d), (e) (7), (e) (8), (f) (1), (f) (2), (h), (i), (j), (l) (2), (l) (3), (l) (5), (l) (6), (l) (7), and (m) (1).  
 § 1910.108 (b), (c), (e) (1), (c) (2), (g) (3), (g) (4), and (g) (5).  
 § 1910.109 (g) (4) and (h).  
 § 1910.110.  
 § 1910.111.

(c) Notwithstanding anything in paragraph (a), (b), or (d) of this section, any provision in any other section of this subpart which contains in itself a specific effective date or time limitation shall become effective on such date or shall apply in accordance with such limitation.

(d) Notwithstanding anything in paragraph (a), or (b) of this section, if any standard in 41 CFR Part 50-204, other than a national consensus standard incorporated by reference in § 50-204.2(a) (1), is or becomes applicable at any time to any employment and place of employment, by virtue of the Walsh-Healey Public Contracts Act, or the Service Contract Act of 1965, or the National Foundation on Arts and Humanities Act of 1965, any corresponding established Federal standard in this Subpart H which is derived from 41 CFR Part 50-204 shall also become effective, and shall be applicable to such employment and place of employment, on the same date.

§ 1910.115 Sources of standards.

| Sec.          | Source                                                                                                      |
|---------------|-------------------------------------------------------------------------------------------------------------|
| 1910.101----- | 41 CFR 50-204.67, 70, and 71.                                                                               |
| 1910.102----- | 41 CFR 50-204.68.                                                                                           |
| 1910.103----- | NFPA No. 50M-1968, Standard for Liquefied Hydrogen Systems at Consumer Sites.                               |
| 1910.104----- | NFPA No. 50B-1968, Standard for the Installation of Bulk Oxygen Systems at Consumer Sites.                  |
| 1910.105----- | NFPA No. 30-1969, Flammable and Combustible Liquids Code.                                                   |
| 1910.107----- | NFPA No. 33-1969, Standard for Spray Finishing using Flammable and Combustible Materials.                   |
| 1910.108----- | NFPA No. 34-1968, Standard for Dip Tanks Containing Flammable or Combustible Liquids.                       |
| 1910.109----- | NFPA No. 400-1970, Code for Manufacture, Transportation, Storage and Use of Explosives and Blasting Agents. |
| 1910.110----- | NFPA 55-69, Standard for the Handling of Liquefied Petroleum Gases.                                         |
| 1910.111----- | ANSI Z39.1-1968, Storage and Handling of Anhydrous Ammonia.                                                 |

§ 1910.116 Standards organizations.

National Fire Protection Association (NFPA), 60 Battery March Street, Boston, MA 02110.  
 National Plant Food Institute, 1700 K Street NW., Washington, DC 20006.

Compressed Gas Association, Inc., 500 Fifth Avenue, New York, NY 10036.  
 American Society of Mechanical Engineers Inc., United Engineering Center, 345 East 47th Street, New York, NY 10017.  
 American Petroleum Institute, 1801 K Street NW., Washington, DC 20006.  
 National Board of Boiler and Pressure Vessel Inspectors, 1155 North High Street, Columbus, OH 43201.  
 American National Standards Institute, 1430 Broadway, New York, NY 10018.  
 American Society for Testing and Materials (ASTM), 1916 Race Street Philadelphia, PA 19103.  
 Underwriters Laboratories, Inc. (UL), 207 East Ohio Street, Chicago, IL 60611.

Subpart I—Personal Protective Equipment

§ 1910.132 General requirements.

(a) *Application.* Protective equipment, including personal protective equipment for eyes, face, head, and extremities, protective clothing, respiratory devices, and protective shields and barriers, shall be provided, used, and maintained in a sanitary and reliable condition wherever it is necessary by reason of hazards of processes or environment, chemical hazards, radiological hazards, or mechanical irritants encountered in a manner capable of causing injury or impairment in the function of any part of the body through absorption, inhalation or physical contact.

(b) *Employee-owned equipment.* Where employees provide their own protective equipment, the employer shall be responsible to assure its adequacy, including proper maintenance, and sanitation of such equipment.

(c) *Design.* All personal protective equipment shall be of safe design and construction for the work to be performed.

§ 1910.133 Eye and face protection.

(a) *General.* (1) Protective eye and face equipment shall be required where there is a reasonable probability of injury that can be prevented by such equipment. In such cases, employers shall make conveniently available a type of protector suitable for the work to be performed, and employees shall use such protectors. No unprotected person shall knowingly be subjected to a hazardous environmental condition. Suitable eye protectors shall be provided where machines or operations present the hazard of flying objects, glare, liquids, injurious radiation, or a combination of these hazards.

(2) Protectors shall meet the following minimum requirements:

(i) They shall provide adequate protection against the particular hazards for which they are designed.

(ii) They shall be reasonably comfortable when worn under the designated conditions.

(iii) They shall fit snugly and shall not unduly interfere with the movements of the wearer.

(iv) They shall be durable.

(v) They shall be capable of being disinfected.

(vi) They shall be easily cleanable.

(vii) Protectors should be kept clean and in good repair.

(3) Persons whose vision requires the use of corrective lenses in spectacles, and who are required by this standard to wear eye protection, shall wear goggles or spectacles of one of the following types:

(i) Spectacles whose protective lenses provide optical correction.

(ii) Goggles that can be worn over corrective spectacles without disturbing the adjustment of the spectacles.

(iii) Goggles that incorporate corrective lenses mounted behind the protective lenses.

(4) Every protector shall be distinctly marked to facilitate identification only of the manufacturer.

(5) When limitations or precautions are indicated by the manufacturer, they shall be transmitted to the user and care taken to see that such limitations and precautions are strictly observed.

(6) Design, construction, testing, and use of device, for eye and face protection shall be in accordance with American National Standard for Occupational and Educational Eye and Face Protection, Z87.1-1968.

§ 1910.134 Respiratory protection.

(a) *Permissible practice.* (1) In the control of those occupational diseases caused by breathing air contaminated with harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors, the primary objective shall be to prevent atmospheric contamination. This shall be accomplished as far as feasible by accepted engineering control measures (for example, enclosure or confinement of the operation, general and local ventilation and substitution of less toxic materials). When effective engineering controls are not feasible, or while they are being instituted, appropriate respirators shall be used pursuant to the following requirements.

(2) Respirators shall be provided by the employer when such equipment is necessary to protect the health of the employee. The employer shall provide the respirators which are applicable and suitable for the purpose intended. The employer shall be responsible for the establishment and maintenance of a respiratory protective program which shall include the requirements outlined in paragraph (b) of this section.

(3) The employee shall use the provided respiratory protection in accordance with instructions and training received.

(b) *Requirements for a minimal acceptable program.* (1) Written standard operating procedures governing the selection and use of respirators shall be established.

(2) Respirators shall be selected on the basis of hazards to which the work is exposed.

(3) The user shall be instructed and trained in the proper use of respirators and their limitations.

(4) Where practicable, the respirator should be assigned to individual workers for their exclusive use.

(5) Respirators shall be regularly cleaned and disinfected. Those issued to

the exclusive use of one worker should be cleaned after each day's use, or more often if necessary. Those used by more than one worker shall be thoroughly cleaned and disinfected after each use.

(6) Respirators shall be stored in a convenient, clean, and sanitary location.

(7) Respirators used routinely shall be inspected during cleaning. Worn or deteriorated parts shall be replaced. Respirators for emergency use such as self-contained devices shall be thoroughly inspected at least once a month and after each use.

(8) Appropriate surveillance of work area conditions and degree of employee exposure or stress shall be maintained.

(9) There shall be regular inspection and evaluation to determine the continued effectiveness of the program.

(10) Persons should not be assigned to tasks requiring use of respirators unless it has been determined that they are physically able to perform the work and use the equipment. The local physician shall determine what health and physical conditions are pertinent. The respirator user's medical status should be reviewed periodically (for instance, annually).

(11) Approved or accepted respirators shall be used when they are available. The respirator furnished shall provide adequate respiratory protection against the particular hazard for which it is designed in accordance with standards established by competent authorities. The U.S. Department of Interior, Bureau of Mines, and the U.S. Department of Agriculture are recognized as such authorities. Although respirators listed by the U.S. Department of Agriculture continue to be acceptable for protection against specified pesticides, the U.S. Department of the Interior, Bureau of Mines, is the agency now responsible for testing and approving pesticide respirators.

(c) *Selection of respirators.* Proper selection of respirators shall be made according to the guidance of American National Standard Practices for Respiratory Protection Z88.2-1969.

(d) *Air quality.* (1) Compressed air, compressed oxygen, liquid air, and liquid oxygen used for respiration shall be of high purity. Oxygen shall meet the requirements of the United States Pharmacopoeia for medical or breathing oxygen. Breathing air shall meet at least the requirements of the specification for Grade D breathing air as described in Compressed Gas Association Commodity Specification G-7.1-1964. Compressed oxygen shall not be used in supplied-air respirators or in open circuit self-contained breathing apparatus that have previously used compressed air. Oxygen must never be used with air line respirators.

(2) Breathing air may be supplied to respirators from cylinders or air compressors.

(i) Cylinders shall be tested and maintained as prescribed in the Shipping Container Specification Regulations of the Department of Transportation (49 CFR Part 179).

(ii) The compressor for supplying air shall be equipped with necessary safety and standby devices. A breathing air-

type compressor shall be used. Compressors shall be constructed and situated so as to avoid entry of contaminated air into the system and suitable in-line air purifying sorbent beds and filters installed to further assure breathing air quality. A receiver of sufficient capacity to enable the respirator wearer to escape from a contaminated atmosphere in event of compressor failure, and alarms to indicate compressor failure and overheating shall be installed in the system. If an oil-lubricated compressor is used, it shall have a high-temperature or carbon monoxide alarm, or both. If only a high-temperature alarm is used, the air from the compressor shall be frequently tested for carbon monoxide to insure that it meets the specifications in subparagraph (1) of this paragraph.

(3) Air line couplings shall be incompatible with outlets for other gas systems to prevent inadvertent servicing of air line respirators with nonrespirable gases or oxygen.

(4) Breathing gas containers shall be marked in accordance with American National Standard Method of Marking Portable Compressed Gas Containers to Identify the Material Contained, Z48.1-1954; Federal Specification BB-A-1034a, June 21, 1960, Air, Compressed for Breathing Purposes; or Interim Federal Specification GG-B-00675b, April 27, 1965, Breathing Apparatus, Self-Contained.

(e) *Use of respirators.* (1) Standard procedures shall be developed for respirator use. These should include all information and guidance necessary for their proper selection, use, and care. Possible emergency and routine uses of respirators should be anticipated and planned for.

(2) The correct respirator shall be specified for each job. The respirator type is usually specified in the work procedures by a qualified individual supervising the respiratory protective program. The individual issuing them shall be adequately instructed to insure that the correct respirator is issued. Each respirator permanently assigned to an individual should be durably marked to indicate to whom it was assigned. This mark shall not affect the respirator performance in any way. The date of issuance should be recorded.

(3) Written procedures shall be prepared covering safe use of respirators in dangerous atmospheres that might be encountered in normal operations or in emergencies. Personnel shall be familiar with these procedures and the available respirators.

(i) In areas where the wearer, with failure of the respirator, could be overcome by a toxic or oxygen-deficient atmosphere, at least one additional man shall be present. Communications (visual, voice, or signal line) shall be maintained between both or all individuals present. Planning shall be such that one individual will be unaffected by any likely incident and have the proper rescue equipment to be able to assist the other(s) in case of emergency.

(ii) When self-contained breathing apparatus or hose masks with blowers

are used in atmospheres immediately dangerous to life or health, standby men must be present with suitable rescue equipment.

(iii) Persons using air line respirators in atmospheres immediately hazardous to life or health shall be equipped with safety harnesses and safety lines for lifting or removing persons from hazardous atmospheres or other and equivalent provisions for the rescue of persons from hazardous atmospheres shall be used. A standby man or men with suitable self-contained breathing apparatus shall be at the nearest fresh air base for emergency rescue.

(4) Respiratory protection is no better than the respirator in use, even though it is worn conscientiously. Frequent random inspections shall be conducted by a qualified individual to assure that respirators are properly selected, used, cleaned, and maintained.

(5) For safe use of any respirator, it is essential that the user be properly instructed in its selection, use, and maintenance. Both supervisors and workers shall be so instructed by competent persons. Training shall provide the men an opportunity to handle the respirator, have it fitted properly, test its facepiece-to-face seal, wear it in normal air for a long familiarity period, and, finally, to wear it in a test atmosphere.

(i) Every respirator wearer shall receive fitting instructions including demonstrations and practice in how the respirator should be worn, how to adjust it, and how to determine if it fits properly. Respirators shall not be worn when conditions prevent a good face seal. Such conditions may be a growth of beard, sideburns, a skull cap that projects under the facepiece, or temple pieces on glasses. Also, the absence of one or both dentures can seriously affect the fit of a facepiece. The worker's diligence in observing these factors shall be evaluated by periodic check. To assure proper protection, the facepiece fit shall be checked by the wearer each time he puts on the respirator. This may be done by following the manufacturer's facepiece fitting instructions.

(ii) Providing respiratory protection for individuals wearing corrective glasses is a serious problem. A proper seal cannot be established if the temple bars of eye glasses extend through the sealing edge of the full facepiece. As a temporary measure, glasses with short temple bars or without temple bars may be taped to the wearer's head. Wearing of contact lenses in contaminated atmospheres with a respirator shall not be allowed. Systems have been developed for mounting corrective lenses inside full facepieces. When a workman must wear corrective lenses as part of the facepiece, the facepiece and lenses shall be fitted by qualified individuals to provide good vision, comfort, and a gas-tight seal.

(iii) If corrective spectacles or goggles are required, they shall be worn so as not to affect the fit of the facepiece. Proper selection of equipment will minimize or avoid this problem.

(f) *Maintenance and care of respirators.* (1) A program for maintenance and

# RULES AND REGULATIONS

22213

care of respirators shall be adjusted to the type of plant, working conditions, and hazards involved, and shall include the following basic services:

- (i) Inspection for defects (including a leak check).
- (ii) Cleaning and disinfecting.
- (iii) Repair.
- (iv) Storage

Equipment shall be properly maintained to retain its original effectiveness.

(2) (i) All respirators shall be inspected routinely before and after each use. A respirator that is not routinely used but is kept ready for emergency use shall be inspected after each use and at least monthly to assure that it is in satisfactory working condition.

(ii) Self-contained breathing apparatus shall be inspected monthly. Air and oxygen cylinders shall be fully charged according to the manufacturer's instructions. It shall be determined that the regulator and warning devices function properly.

(iii) Respirator inspection shall include a check of the tightness of connections and the condition of the facepiece, headbands, valves, connecting tube, and canisters. Rubber or elastomer parts shall be inspected for pliability and signs of deterioration. Stretching and manipulating rubber or elastomer parts with a massaging action will keep them pliable and flexible and prevent them from taking a set during storage.

(iv) A record shall be kept of inspection dates and findings for respirators maintained for emergency use.

(3) Routinely used respirators shall be collected, cleaned, and disinfected as frequently as necessary to insure that proper protection is provided for the wearer. Each worker should be briefed on the cleaning procedure and be assured that he will always receive a clean and disinfected respirator. Such assurances are of greatest significance when respirators are not individually assigned to workers. Respirators maintained for emergency use shall be cleaned and disinfected after each use.

(4) Replacement or repairs shall be done only by experienced persons with parts designed for the respirator. No attempt shall be made to replace components or to make adjustment or repairs beyond the manufacturer's recommendations. Reducing or admission valves or regulators shall be returned to the manufacturer or to a trained technician for adjustment or repair.

(5) (i) After inspection, cleaning, and necessary repair, respirators shall be stored to protect against dust, sunlight, heat, extreme cold, excessive moisture, or damaging chemicals. Respirators placed at stations and work areas for emergency use should be quickly accessible at all times and should be stored in compartments built for the purpose. The compartments should be clearly marked. Routinely

used respirators, such as dust respirators, may be placed in plastic bags. Respirators should not be stored in such places as lockers or tool boxes unless they are in carrying cases or cartons.

(ii) Respirators should be packed or stored so that the facepiece and exhalation valve will rest in a normal position and function will not be impaired by the elastomer setting in an abnormal position.

(iii) Instructions for proper storage of emergency respirators, such as gas masks and self-contained breathing apparatus, are found in "use and care" instructions usually mounted inside the carrying case lid.

(g) Identification of gas mask canisters. (i) The primary means of identifying a gas mask canister shall be by means of properly worded labels. The secondary means of identifying a gas mask canister shall be by a color code.

(2) All who issue or use gas masks falling within the scope of this section shall see that all gas mask canisters purchased or used by them are properly labeled and colored in accordance with these requirements before they are placed in service and that the labels and colors are properly maintained at all times thereafter until the canisters have completely served their purpose.

(3) On each canister shall appear in bold letters the following:

(i) —  
Canister for .....  
(Name for atmospheric contaminant)  
or  
Type N Gas Mask Canister

(ii) In addition, essentially the following wording shall appear beneath the appropriate phrase on the canister

label: "For respiratory protection in atmospheres containing not more than ..... percent by volume of ....."

(Name of atmospheric contaminant)

(iii) All of the markings specified above should be placed on the most conspicuous surface or surfaces of the canister.

(4) Canisters having a special high-efficiency filter for protection against radionuclides and other highly toxic particulates shall be labeled with a statement of the type and degree of protection afforded by the filter. The label shall be affixed to the neck end of, or to the gray stripe which is around and near the top of, the canister. The degree of protection shall be marked as the percent of penetration of the canister by a 0.3-micron-diameter dioctyl phthalate (DOP) smoke at a flow rate of 85 liters per minute.

(5) Each canister shall have a label warning that gas masks should be used only in atmospheres containing sufficient oxygen to support life (at least 16 percent by volume), since gas mask canisters are only designed to neutralize or remove contaminants from the air.

(6) Each gas mask canister shall be painted a distinctive color or combination of colors indicated in Table I-1. All colors used shall be such that they are clearly identifiable by the user and clearly distinguishable from one another. The color coating used shall offer a high degree of resistance to chipping, scaling, peeling, blistering, fading, and the effects of the ordinary atmospheres to which they may be exposed under normal conditions of storage and use. Appropriately colored pressure sensitive tape may be used for the stripes.

TABLE I-1

| Atmospheric contaminants to be protected against                                                              | Colors assigned*                                                                                                            |
|---------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Acid gases.....                                                                                               | White.                                                                                                                      |
| Hydrocyanic acid gas.....                                                                                     | White with 1/4-inch green stripe completely around the canister near the bottom.                                            |
| Chlorine gas.....                                                                                             | White with 1/4-inch yellow stripe completely around the canister near the bottom.                                           |
| Organic vapors.....                                                                                           | Black.                                                                                                                      |
| Ammonia gas.....                                                                                              | Green.                                                                                                                      |
| Acid gases and ammonia gas.....                                                                               | Green with 1/4-inch white stripe completely around the canister near the bottom.                                            |
| Carbon monoxide.....                                                                                          | Blue.                                                                                                                       |
| Acid gases and organic vapors.....                                                                            | Yellow.                                                                                                                     |
| Hydrocyanic acid gas and chloroacetylene vapor.....                                                           | Yellow with 1/4-inch blue stripe completely around the canister near the bottom.                                            |
| Acid gases, organic vapors, and ammonia gas.....                                                              | Brown.                                                                                                                      |
| Radioactive materials, excepting tritium and noble gases.....                                                 | Purple (Magenta).                                                                                                           |
| Particulates (dusts, fumes, mists, fogs, or smokes) in combination with any of the above gases or vapors..... | Canister color for contaminant, as designated above, with 1/4-inch gray stripe completely around the canister near the top. |
| All of the above atmospheric contaminants.....                                                                | Red with 1/4-inch gray stripe completely around the canister near the top.                                                  |

\*Gray shall not be assigned as the main color for a canister designed to remove acids or vapors.

Note: Orange shall be used as a complete body, or stripe color to represent gases not included in this table. The user will need to refer to the canister label to determine the degree of protection the canister will afford.