Condensation (*continued*)
control, 413
vapor barrier, 413
ventilation, 413
cooled structures, 415
heated structures, 411
visible, 411

Condensers, 683
air-cooled, 691
application, 693
control, 694
installation, 697
maintenance, 697
rating, 693
types, 692
evaporative, 697
accessory coils, 699
air flow, 698
capacity modulation, 700
coil wetting means, 697
coils, 697
heat transfer, 698
location, 700
ratings, 699
water treatment, 700
water-cooled, 683
ammonia, shell-and-tube, 687
city water hardness, 684
city water temperatures, 684
construction codes, 691
double-pipe, 690
fouling factors, 685
halocarbon, shell-and-tube, 690
heat removed, 683
noncondensable gases, 691
overall heat transfer, 683
shell-and-coil, 690
shell-and-U-tube, 690

Condensing, 62
dropwise, 62
film, 62, 64
inside horizontal tubes, 63
inside vertical tubes, 63
outside horizontal tubes, 63
outside vertical tubes, 63

Conductance, 417
air space, 422, 423
materials, 424–427
still air, 421
surface, 384, 417
Conduction, 49

Conductivity
building materials, 382, 424–427
factors affecting, 382
gases, 977
insulation, 382, 383, 424–427, 449
liquids, 978
moist air, 46
refrigerants, 284
soils, 417, 418
solids, 979, 980
vapors, 977

Contaminants, 765
control in refrigerant systems, 767
design conditions, 767
hermetic motor insulation, 772
lubricants, 771
motor burnouts, 773
operating conditions, 767
refrigerants, 769
tests for material evaluation, 768
refrigerant systems, 765
acid, 765
antifreeze agents, 767
copper plating, 765, 801
dirt, 766

Contaminants (*continued*)
flux, 766
metal, 766
moisture, 758–760, 765, 775
noncondensable gases, 766
sludge, 765
solvents, 766, 773

Contaminants, air, 147
air pollution, 151
bacteria, 159
classification, 147, 148
dusts, 147
fogs, 149
fumes, 147
gases, 149
mists, 149
smokes, 147
vapors, 149
combustible dusts, 151
fallout, 158
flammable gases and vapors, 150
limits, 156
industrial, 150
measurement, 149
pollen, 159
radioactive, 158
sizes, 149
threshold limit values, 152–155

Control
contaminants (refrigerant system), 767
design conditions, 767
hermetic motor insulation, 772
lubricants, 771
motor burnouts, 773
operating conditions, 767
refrigerants, 769
tests for material evaluation, 768
cooling coils, 605
fuel-burning, 815
draft, 817
electric overload releases, 817
firing rate, 815
flame failure, 816
fuses, 817
interlocks, 817
limit, 815
operating, 815
programming, 816
motor, 870
central air conditioning, 874
commercial refrigeration, 876
domestic refrigeration, 872
room air conditioners, 873
sound, 191
unit heaters, 855
unit ventilators, 849
vibration, 212

Control applications, 182
central fan systems, 182
compressor capacity, 185
cooling, 184
dehumidification, 184
heating coil, 183
humidity, 186
outdoor-air damper control, 182
preheater coil, 183
static-pressure, 186
typical system, 187
hot water systems, 188
temperature control, 188
zone control, 188
steam systems, 188
zone control, 188
terminal equipment, 190

Control, automatic, 171
application limitations, 181

Control, automatic (*continued*)
applications, 182
central fan systems, 182
hot water systems, 188
steam systems, 188
terminal equipment, 190
auxiliary devices, 176
controlled devices, 175
controllers, 171, 174
design coordination, 176
equipment selection, 177
flow, 178
air, 180
steam, 178
water, 179
fundamentals, 171
individual room, 181
precautions, 181
system components, 172
controllers, 172
indicating, 174
recording, 174
sensing elements, 173
transducers, 173
types of control action, 172
types of systems, 171
zone, 180, 188

Control, refrigerant, 715
capillary tubes, 734
basic rating curves, 738
capacity balance, 735
critical correction factor, 740
critical pressure chart, 740
flow factor chart, 739
inspection, 736
optimum refrigerant charge, 736
optimum selection, 736
preliminary selection, 737
processing, 736
simplified calculation procedure, 737–742
special applications, 736
system design factors, 734
theory, 734
control valves, 717
check, 731
condenser pressure regulators, 725
condensing water regulators, 730
constant pressure expansion, 722
evaporator pressure regulators, 723
high-side float, 725
low-side float, 726
refrigerant reversing, 729
relief, 732
solenoid, 726
suction pressure regulators, 724
thermostatic expansion, 717
controllers, 715
differential, 715
float switches, 716
pressure, 715
temperature, 715

Control valves, 717
check, 731
applications, 732
seat materials, 731
condenser pressure regulators, 725
condensing water regulators, 730
application, 731
operation, 730
selection, 730
three-way, 731
two-way, 730
constant pressure expansion, 722
application, 722
operation, 722
selection, 722
evaporator pressure regulators, 723
application, 723

Index to Technical Section

Control valves (*continued*)
operation, 723
selection, 723
high-side float, 725
application, 726
operation, 725
selection, 725
low-side float, 726
application, 726
selection, 726
refrigerant reversing, 729
operation, 729
relief devices, 732
discharge capacity, 733
functional valves, 733
fusible plug, 732
pressure setting, 733
rupture member, 732
safety valve, 732
solenoid, 726
application, 728
operation, 727
pilot application, 727
selection, 728
suction pressure regulators, 724
application, 725
operation, 725
selection, 725
superheat, 718
factory setting, 718
gradient, 718
operating, 718
static, 718
thermostatic expansion, 717
application, 720
capacity, 718
charge, 719
desuperheating, 722
flooded system, 721
operation, 717

Controllers, 172, 715
differential, 715
float switches, 716
application, 716
operation, 716
selection, 716
humidistats, 174
indicating and recording, 174
pressure, 174, 715
sensing elements, 173
temperature, 715
thermostats, 174
transducers, 173

Convectors, 857
application, 861
enclosure, paint, humidity effect, 862
heat emission, 857
non-standard conditions, 860
ratings, 860

Conversion factors, 983
acceleration, 985
areas, 983
capacity, 983
centigrade, 987
conductivity, thermal, 986
density, 984
energy, 985
enthalpy, 986
entropy, 986
Fahrenheit, 987
heat, 985
heat transfer coefficients, 986
lengths, 983
masses, 984
power, 985
pressure, 984
specific weight, 984
surface, 983
temperature, 987

Conversion factors (*continued*)
velocity, 985
viscosity, 986
volume, 983
weight, 984
work, 985

Coolants, secondary (brines), 371
brines, 371
calcium chloride, 371–375
corrosion, 375, 376
ethylene glycol, 375
halocarbons, 379
propylene glycol, 375
sodium chloride, 371–375

Coolers, 593, 911, 917
bottled beverage, 917
design considerations, 918
horizontal dry (cold wall), 917
horizontal forced-air, 917
refrigeration calculations, 920
vertical-forced air, 918
drinking water, 914
ratings, 916
refrigeration systems, 915
standards, 916
stream regulators, 916
types, 914
evaporative, 593, 598
air washers, 593
equipment, 598
principles, 593
rotary unit, 599
slinger unit, 598
wetted-pad unit, 598
water chillers, 911
components, 913
construction standards, 912
design, 911
rating, 914
selection requirements, 911
testing, 914

Coolers, liquid, 703
design criteria, 705
chemical requirements, 706
mechanical requirements, 705
performance requirements, 706
friction loss, 706
refrigerant pressure drop, 707
heat transfer, 707
analysis of test results, 708
chilled liquid film coefficient, 708
fouling factors, 709
overall rates, 709
refrigerant film coefficient, 707
Wilson plot, 708
types, 703
Baudelot, 704
centrifugal system, 705
double-pipe, 704
dry expansion, 704
flooded shell-and-tube, 703
flooded tank-and-agitator, 705
shell-and-coil, 705
spray, 703

Cooling
coils, 603
applications, 606
arrangement, 603, 606
construction, 603
control, 605
dehumidifying, 608, 611
direct-expansion, 604
dry, 608, 610
flow resistance, 609
heat transfer, 609
performance of dehumidifying coils, 611
performance of dry coils, 610

Cooling (*continued*)
refrigeration load determination, 611
selection, 607
uses, 603
water, 604
evaporative, 593, 598
air washers, 593
equipment, 598
principles, 593
rotary unit, 599
slinger unit, 598
wetted-pad unit, 598

Cooling load, 487
commercial and industrial, 487
air quantity required, 522
apparatus dew point, 522
appliances, 519–521
ceilings, 518
examples, 523
fenestration (glass), 500, 525
floors, 516
indoor conditions, 487, 494
infiltration, 517
instantaneous heat load, 496, 514
interior partitions, 516
lights, 518
minimum entering air temperature, 523
moisture transfer, 519
motors, 518
occupants, 518
outdoor air, 516
outdoor air requirement, 495, 496
outdoor conditions, 488–495
shading coefficients, 506–514
shading devices, 510–514
solar gain through roofs and walls, 498–505
solar gain through windows, 500–515
solar heat gain factors, 505–515
solar radiation, 496–515
ventilation, 516
residential, 525
appliances, 528
ceilings, 527
design temperatures, 525
equivalent temperature differentials, 526
floors, 527
infiltration, 528
latent, 528
occupants, 528
sensible, 526, 528
sensible heat gain, 524
total, 528
ventilation, 528
walls, 527
windows, 527

Cooling, thermoelectric, 21
advantages, 26
applications, 26
couple performance, 22
Figure of Merit, 23
design of devices, 27
effects, 21
modules, 27
refrigerating system analogies, 25

Cooling towers, 743
atmospheric, 744
blow-down, 755
characteristic, 750
film resistance, 751
heat balance, 751
coefficients, 749
available, 750
required, 750
design conditions, 752
drift loss, 745, 748, 755
evaluation, 754