




The State of Wisconsin

WISCONSIN STATE BOARD OF HEALTH
INDUSTRIAL HYGIENE DIVISION
STATE OFFICE BUILDING
1 WEST WILSON STREET
MADISON 2



October 18, 1956

Mr. G. R. Mercer, Superintendent
Algoma Plywood and Veneer Company
Algoma, Wisconsin

Dear Mr. Mercer:

Enclosed are two copies of the report of the
dust study made at your plant on June 18th.

We are missing a velometer which is packed in a
flat black case approximately 1 1/2 x 2 1/2 feet. We may
have used this instrument in your plant during the course
of the study and we are wondering if we could have possibly
left it in one of the departments.

I would appreciate it very much if you would let
us know if we did leave the instrument at your plant.

Sincerely yours,

William L. Lea

William L. Lea, Ph.D.
Director

WLL:vs
Encl

See attached

132

Insulation Hygiene Progress Reports

Vol. 7 No. 2 Summer 1975

from the
Insulation Industry Hygiene Research
Program

Editor: W. J. Nierthman, Ph.D., Published at
the Environmental Sciences Laboratory (Irving J.
Selikoff, M.D., Director), Mount Sinai School
of Medicine of the City University of New York,
N.Y. 10029

Advisory Council of IHRP

Irving J. Selikoff, M.D., Program Director and
Chairman

E. Cuyler Hammond, Sc.D., Vice President,
American Cancer Society, New York, N.Y.

Andrew Haas, General President, International
Association of Heat and Frost Insulators and As-
bestos Workers, Washington, D.C.

PURPOSES OF THE INSULATION INDUSTRY HYGIENE RESEARCH PROGRAM

1. To develop improved methods for minimizing exposure of insulation workers to dusts and fumes encountered in their work.
2. To disseminate knowledge of these improved methods of dust control wherever they may be applied advantageously and to offer cooperation, advice and assistance toward their universal adoption.

Self-Contained Supplied-Air Respirator Available

The removal of old asbestos-containing material continues to be a major source of exposure to insulation workers. While rip-out is only done occasionally, the dust concentrations during this procedure can be so high that special respiratory protection must be used. Often, asbestos fiber concentrations exceed 100 fibers per milliliter, 20 times the current standard.

According to the OSHA Asbestos Standard, employees engaged in the removal or demolition of pipes, structures, or equipment covered or insulated with asbestos must use type "C" continuous flow or pressure-demand supplied-air respirators. In addition, special coveralls, gloves, and shoe coverings are to be employed to prevent contamination of clothing by asbestos fibers.

On jobs where externally supplied air from tanks or compressors is available, a variety of hoods may be obtained for connection to the air source. Often, however, a supply of breathable air is not readily available, or the use of a long air hose may give rise to safety risks.

Battery-Powered Unit Available

Additionally, if air is supplied by compressors, provisions must be made to remove oil and water mists and to insure that carbon monoxide does not get into the system through improper placement of the air intake.

In such circumstances, a battery-powered air cleaner and hood have special utility. One model, available in the

last year and manufactured by the 3M Occupational Health and Safety Products Division, will operate for over four hours and provide protection in the dustiest of environments during removal of asbestos material. The respirator weighs only 10 pounds. There is no resistance to breathing, no condensation of moisture, and face fit is not of particular importance.

Maintenance Important


The respirator should, however, be checked periodically by personnel familiar with its operation. Any replacement parts required should be those of the manufacturer, and their instructions for servicing and repair should be followed carefully.

Other supplied-air breathing devices are available in which cylinders of oxygen or of compressed air are carried by the worker. Several approved types exist but they are more complicated to use and more cumbersome than the previously described battery-powered air filtering unit. Moreover, those using compressed air have a maximum use time of only 30 minutes before a new cylinder must be obtained. Those using oxygen have a longer operating time, but require chemical filtering of exhaled air.

The half-face dust respirators commonly available on job sites are not suitable for use during removal of asbestos insulation materials. The use of such respirators is limited to conditions in which dust concentrations are less than ten times the existing standard.



The face piece of a self-contained supplied-air respirator. It will operate for four hours using a rechargeable battery.



A diagram of the battery pack, fan motor, and filter of the respirator. It weighs 10 pounds.



The State of Wisconsin

WISCONSIN STATE BOARD OF HEALTH

INDUSTRIAL HYGIENE DIVISION

STATE OFFICE BUILDING

1 WEST WILSON STREET

MADISON 2

WELDRACK DUST STUDY

Plant: Algoma Flywood and Tenner Company

Location: Algoma, Wisconsin (Plant No. 2)

Date of Study: June 18, 1956

Officials Contacted: Mr. G. R. Marcer, Superintendent
Mrs. Gertrude C. Brice, R.N., Plant Nurse

A study was made March 19, 1956, in this plant with the assumption that the air-borne dust contained less than 50% free silica, resulting in a "Medium" free silica dust. "Medium", according to Threshold Limit Values, refers to dusts containing from 5% to 50% free silica. "Low" is less than 5% and "High" is over 50%.

To specifically determine the free silica content of air-borne dust around weldrock operations, a gross air sample was taken on the second floor of Plant No. 2 in the vicinity of the Tenner. The gross air sample represented a continuous sampling of the air for 3 hours, at the rate of about 20 cubic feet per minute. The dust was collected on a layer of salicylic acid crystals and sent to the U. S. Public Health Service for analysis. The result of the analysis is shown in Table I.

Table I

COMPOSITION OF AIR-BORNE DUST AT WELDRACK OPERATIONS

Free Silica	9.3%
Asbestos	20.3%

Wigdet impingers were used in collecting atmospheric dust samples for the purpose of determining the number of dust particles in the air around various operations on Weldrock in Plant 2. Normal propyl alcohol was the collecting medium and dust counts were made using the light-field microscopic technique. Summer conditions existed during the course of air sampling, in that an appreciable amount of natural ventilation was provided through open windows.

The results of the dust counts are given in Table II.

Table II

ATMOSPHERIC DUST CONCENTRATIONS

Sample No.	Location and Description	Millions of Particles Per Cubic Foot of Air
<u>FIRST FLOOR, 1:45 to 2:45 P.M.</u>		
1.	B.Z. (Breathing Zone) Drum Sander operator. Feed end. North side.	4.2
2.	B.Z. Drum Sander operator. Feed end. South side.	1.7
3.	B.Z. Drum Sander operator. Feed end. East side.	4.3
4.	G.A. (General Atmosphere) 10' from feed end of drum sander.	2.8
5.	B.Z. Drum Sander operator. Off-bearing end. North side	3.6
6.	B.Z. Drum Sander operator. Off-bearing end. West side.	6.5
7.	B.Z. Drum Sander operator. Off-bearing end. North side.	8.1
8.	G.A. 20' Northwest of belt sander.	2.7
<u>SECOND FLOOR, 3:00 to 4:00 P.M.</u>		
9.	B.Z. Straight line rip saw. Feed end.	1.7
10.	" " " " " Off-bearing end.	2.0
11.	B.Z. Tenoner. Off-bearing end.	1.6
12.	B.Z. Tenoner. Off-bearing end.	3.6
13.	B.Z. Tenoner. Feed end.	5.3
14.	B.Z. Tenoner. Feed end.	2.5
15.	G.A. End of room occupied by Tenoner	2.0
16.	G.A. " " " " " " "	0.6

134

SUMMARY

From the results of the analysis of the gross air sample (Table I), it was decided to use 20 million particles per cubic foot of air as the M.A.C. (Maximum Allowable Concentration) for the air-borne dust in the vicinity of weldrock operations. This value is the same as the value that was assumed in the March, 1956 study, from information on a previous analysis made on Kale dust in the collector system.

From the free silica content standpoint, it is seen that the 5.3% value is on the conservative end of the 5% to 50% free silica content range assigned to "Medium" silica dusts. In other words, the "Medium" and "High" ranges are very broad (5% to 50% and 50% to 100% respectively). Thus a dust containing 30% free silica would still be classed as a "Medium" silica dust, the same as a dust containing 5.3% free silica. It stands to reason, however, that in equal concentrations the 5.3% free silica dust would present less of a health hazard than the 30% free silica dust. Technically, a 4.7% free silica dust would have an M.A.C. of 50 m.p.p.e.f. (50 million particles per cubic foot of air) although physiologically there would probably be no difference between 4.7% and 5.3%. We would conservatively give the 4.7% free silica dust an M.A.C. of 20 m.p.p.e.f., since these ranges are not treated as sharp lines of distinction.

By the same token, the M.A.C. value for asbestos dust is 5 m.p.p.e.f. The analysis shows 10.3% asbestos in the air-borne dust. An M.A.C. value of 20 m.p.p.e.f. is again on the conservative side.

The atmospheric dust concentrations listed in Table II, range from a high of 8.1 m.p.p.e.f. to a low of 0.6 m.p.p.e.f., and are all under the M.A.C. value of 20 m.p.p.e.f. It should be remembered, however, that this study was made under summer conditions. When natural ventilation is at a minimum, an occasional operation will tend to produce atmospheric dust concentrations which are above the 20 m.p.p.e.f. threshold limit (See March, 1956 study).

LOCAL EXHAUST VENTILATION SYSTEMS

Each machine operating on weldrock is equipped with local exhaust ventilation hoods of varying design. These hoods appear to be doing a satisfactory job. It should be remembered, however, that an exhaust system having a bag collector becomes less efficient as the collected material in the bag offers more and more resistance to air flow into the hood. Thus, unless the bag collectors are automatically cleaned or "rapped", they should be cleaned before air flow is appreciably diminished.

In observing the performance of the exhaust hoods, it was felt that high atmospheric dust concentrations around an operation would in most cases not be as much a reflection upon the exhaust hood as upon the material handling before and after processing. Piling of finished panels on hand trucks and other similar operations appeared to be as much, if not more, of a dust source than the actual sanding or sawing.

RECOMMENDATIONS

The following recommendations are made on the basis of conditions existing during the March and June 1956 studies.

1.) It is recommended that the local exhaust systems be maintained in such a manner that maximum efficiency is realized. It is felt that the low atmospheric dust concentrations under summer conditions, and fairly low dust concentrations under winter conditions are due primarily to the local exhaust systems.

2.) Some consideration should be given to the handling of the weld-rock panels, as well as scrap handling and sweeping, to keep the dust dispersion at a minimum.

INDUSTRIAL HYGIENE DIVISION

Edward J. Otterson

Edward J. Otterson
Engineer

William L. Lea

William L. Lea, Ph.D.
Director

EJO:dm
10/10/56

1 000 000 000