Activated Sludge Primary Biodegradation of Polychlorinated Biphenyls

by E. Scott Tucker, Victor W. Saeger and Orville Hicks

Monsanto Company
St. Louis, Mo 63166
March 28, 1975

Since the identification of polychlorinated biphenyl (PCB) residues in the environment in Sweden (Jensen, 1966) an effort has been made to determine the level and distribution of these materials as well as their effects upon living organisms. The widespread distribution of low but detectable levels of some PCBs in the environment is now well documented and a substantial amount of data have been accumulated regarding their acute, subacute, and chronic toxicity (Peakall and Linder, 1970; Edwards, 1970).

While much is known about the effects of PCBs on living organisms, there is relatively little information available regarding the effects that living organisms have upon PCBs, i.e. their biodegradability.

The biodegradability or susceptibility of an organic compound to biological degradation, especially by bacteria, is a prime determinant of its environmental residence time. The finding of PCB residues in the environment suggests to many that PCBs as a class of compounds are resistant to microbial degradation. However, in order to fairly evaluate the persistence of PCBs it must be understood that PCBs are not a single entity, but complex mixtures made up of many entities which may undergo biological degradation at different rates.

Chlorinated biphenyls are commercially produced by the direct chlorination of biphenyl. The resultant mixtures can theoretically have as many as 210 different components containing 0-10 chlorine atoms per biphenyl molecule. Of the possible isomers, 103 are considered most probable (Widmark, 1968). The complexity of the PCBs, therefore, complicates the determination of both environmental levels and their impact on the biota.

Environmental monitoring programs have demonstrated that, with the exception of direct high level controllable contamination near points of manufacture or use,

Bulletin of Environmental Contamination & Toxicology, Vol. 14, No. 6 © 1975 by Springer-Verlag New York Inc.

MONS 004007

the PCBs generally found in the environment are the more highly chlorinated biphenyls, i.e., those containing 5 or more chlorine atoms per biphenyl molecule (Jensen and Widmark, 1967; Holmes, et al, 1967; Koeman, et al, 1969). This is true even though the more highly chlorinated biphenyls constitute only about 35% of all the PCBs manufactured over the years (Monsanto Company, 1971). This is strong evidence that the less chlorinated materials degrade more rapidly than the more highly chlorinated ones. It also suggests that even under conditions of unrestricted use and without special precautions to prevent entry into the environment that the less chlorinated materials degraded rapidly enough to prevent accumulation.

It is obvious, therefore, that to obtain a more complete understanding of the environmental behavior of PCBs that information concerning their susceptibility to microbial degradation is needed.

It has been shown that biphenyl can be degraded by gram-negative bacteria through 2,3-dihydro -2,3-dihydroxybiphenyl, α-hydroxy-β-phenylmuconic semi-aldehyde and phenyl pyruvate (Lunt and Evans, 1970), and it has been reported that Pseudomonas putida oxidizes biphenyl through 2,3-dihydro - 2,3-dihydroxybiphenyl and benzoic acid (Catelani, et al, 1971). More recently Gibson and co-workers isolated a bacterium, tentatively identified as a Beijerinckia species from a polluted stream, capable of utilizing biphenyl as a sole source of carbon and energy for growth (Gibson, et al, 1973) and organisms capable of oxidizing biphenyl and p-chloro biphenyl have been shown to be widely distributed in the natural environment (Ohmori, et al, 1973).

Degradation studies have also been carried out on some selected PCB isomers with two species of Achromobacter isolated from sewage (Ahmed and Focht, 1973a,b) and with Arocior 1242 (Kaiser and Wong, 1974). To date, no work has been reported on the biodegradation of commercial PCB mixtures by activated sludge.

In the study reported here, the susceptibility of commercial polychlorinated biphenyl mixtures to primary degradation by activated sludge microorganisms was investigated.

MONS 004008

METHODS AND MATERIALS

Polychlorinated Biphenyl Mixtures

The following polychlorinated biphenyl mixtures manufactured by Monsanto Company were studied: Aroclor[1] 1254, Aroclor 1242, Aroclor 1016, MCS 1043 (not a commercial mixture), and Aroclor 1221. In Table I, the typical per cent composition of the mixtures studied is given in terms of the number of chlorine atoms per biphenyl.

TABLE I
TYPICAL % COMPOSITION OF POLYCHLORINATED BIPHENYL PRODUCTS*

# Cl Bi-phenyl	Aroclor 1221 (21% Cl)	MCS 1043 (30% Cl)	Aroclor 1016 (41% Cl)	Aroclor 1242 (42% Cl)	Aroclor 1254 (54% Cl)
0	11	0.1	<0.1	<0.1	<0.1
1	51	22	1	1	<0.1
2	32	72	20	16	<0.5
3	4	6	57	49	1
4	2	ND	21	25	21
5	<0.5	ND	1	8	48
6	ND	ND	<0.1	1	23
7	ND	ND	ND	<0.1	6
8	ND	ND	ND	ND	ND

*Per cent (w/w) by GC/Mass using area correction factors.

ND - None Detected, <0.01%

Biodegradation Method

The primary degradation rate of the PCB mixtures was determined using the Soap and Detergent Association semi-continuous activated sludge (SCAS) procedure and modified feed (S.D.A., 1965, 1969). The sludge unit used was a cylindrical glass chamber (85 mm O.D.) of 1500 ml working volume with provisions for aeration, magnetic stirring, sampling and draining. The activated sludge culture was obtained from a local municipal sewage treatment plant and acclimated on synthetic sewage (300 mg of glucose + 200 mg nutrient broth + 130 mg KH_2PO_4 per liter) for several weeks prior to the start of actual feeding of the polychlorinated biphenyl mixtures. The mixed liquor (sludge + aqueous phase)

[1]Registered trademark of Monsanto Company

MONS 004009

was initially adjusted in each sludge unit to a suspended solids concentration of about 2500 mg/liter and during the course of the tests readjusted to this value on a weekly basis.

Each cycle was initiated by the addition of synthetic sewage and the PCB being studied.

Because of their low water solubility, the PCB mixtures being tested were fed via syringe injection of 200 µl of an ethanol solution. In this manner, homogeneous dispersions of the PCBs on the bacterial sludge were obtained.

After about 30 minutes of aeration, a 20 ml aliquot of the mixed liquor was withdrawn and analyzed for the PCB mixture in question. Aeration was continued until the end of the cycle when a second 20 ml sample of mixed liquor was withdrawn for analysis. At this point, the aeration was stopped and the sludge allowed to settle. After noting the sludge volume, two-thirds (1000 ml) of the supernatant was withdrawn and replaced with tap water. Monitoring of the sludge volume and supernatant pH provided some indication of satisfactory operation of the unit. The units were generally operated on two 48-hour and one 72-hour cycle per week.

Analytical Methods

The PCBs in the mixed liquor samples were isolated from the sample matrix by solvent extraction using either nanograde or spectrograde hexane. After concentrating in a Kuderna-Danish evaporative concentrator, the extracts were analyzed for PCBs by either electron-capture gas chromatography (EC/GC) or ultraviolet (UV) spectrophotometry. The UV analyses were made with a Cary Model 14 recording spectrophotometer and matched 2.0 cm quartz cells. The gas chromatographic analyses were carried out with a Hewlett-Packard 5750 chromatograph equipped with a Ni^{63} electron-capture detector. A 2 m X 4 mm glass column packed with 4% XE-60 on 80/100 mesh Chromosorb W, H.P., wes employed. The temperatures of the injection port, column and detector were 220°C, 170°-220°C, and 300°C, respectively. Calibration curves were prepared using standard solutions of the appropriate PCB mixture.

In Table II, the wavelength of the absorption maxima and absorptivities employed in the UV analyses are given. Aroclor 1254 did not have sufficient UV absorption for analytical purposes.

MONS 004010

TABLE II
ULTRAVIOLET ABSORPTION AND RECOVERY DATA FOR BIPHENYL AND POLYCHLORINATED BIPHENYL MIXTURES

Material	λ Max.,nm	Absorptivity Liters/g-cm	Per Cent Recovery
Biphenyl	246	110.9	93 ± 3
Aroclor 1221	245	66.4	96 ± 1
MCS 1043	244	48.9	95 ± 1
Aroclor 1016	246	36.1	92 ± 1
Aroclor 1242	245	37.0	84 ± 1
Aroclor 1254*	-	-	76 ± 2

*Analyzed by EC/GC

In order to demonstrate the efficiency of the extraction procedure, samples of activated sludge were spiked in duplicate at two levels, 2.5 and 5 ppm, with each of the materials and then carried through the entire analytical procedure. The recovery data for each PCB fluid studied are given in Table II. No isomer distribution changes were observed upon comparison of the electron-capture chromatograms of the PCB reference materials to those of the spiked sludge extracts.

In order to show that the PCBswere not irreversibly adsorbed on and/or stored within the bacterial cells of the activated sludge end therefore not recovered via extraction, a sample of acclimated Aroclor 1016 mixed liquor was homogenized with a Polytron Sonic Homogenizer to lyse the bacterial cells and then extracted. A 100 ml sample of homogenized mixed liquor gave a PCB level of 0.51 mg compared to 0.58 mg for an identical mixed liquor sample treated in the normal manner.

RESULTS AND DISCUSSION

In Figure 1, the per cent degradation rates and 95% confidence limits obtained in this study are given for biphenyl and the PCB fluids. It is apparent from the plot of degradation rate vs weight per cent chlorine that the level of chlorination of the mixture is the most significant factor in the relative degradability of the PCBs.

The degradation rates reported here were obtained after the sludge units had been acclimated for about 5 months to the appropriate PCB. Initially the PCB mixtures were fed at a rate of 1 mg per 24-hour cycle, but because of the relatively slow rate of degradation observed in spot checks, the cycle time was increased to 48 hours.

MONS 004011




Figure 1. SCAS primary biodegradation rates of commercial PCBs as a function of the weight per cent chlorine.

Since Aroclor 1221 was found to be quite degradable, the effects of both time cycle and feed level were studied briefly. In Table III disappearance rate data obtained for 24 and 48-hour time cycles at 1 and 5 mg feed levels are given. It is apparent that for Aroclor 1221, most of the degradation occurs during the first 24 hours. This can be explained by the fact that the lower chlorinated biphenyls degrade more rapidly than the higher chlorinated biphenyls.

To verify that the disappearance of the PCBs was due predominantly to degradation and not to volatilization, off-gases from the Aroclor 1221, MCS 1043, and Aroclor 1016 units were passed through a train of three hexane scrubbers during several complete cycles. At the 0.1 cubic foot per hour aeration rate, the disappearance rates due to volatility were 4.2, 6.1, and 3.6% for Aroclor 1221, MCS 1043, and Aroclor 1016, respectively. These losses are well within the 95% confidence limits of the overall disappearance rates.

MONS 004012

TABLE III
EFFECT OF TIME CYCLE AND FEED LEVEL ON THE AROCLOR 1221 DISAPPEARANCE RATE

Feed Level	Disappearance Rate, % 24-Hr Cycle	48-Hr Cycle
1 mg	73 ± 21	81 ± 6
5 mg	89 ± 17	87 ± 5

In order to observe changes in the distribution of the chlorinated biphenyls in the PCBs mixtures after exposure to the activated sludge, selected samples of Aroclor 1221, MCS 1043, Aroclor 1016 and Aroclor 1242 were analyzed by EC/GC. The chromatogram for Aroclor 1221 is shown in Figure 2. The top trace is a chromatogram of the Aroclor 1221 standard, representative of the feed material. The center trace is that of a concentrated sludge extract taken at the end of a degradation cycle. At the bottom is a trace of an Aroclor 1242 standard run under equivalent conditions. The numbers above each peak indicate the dominant PCB represented by the peak as determined by GC/Mass spectrometry. Comparison of the extract chromatograms to that of the Aroclor 1242 standard shows that the minor components in Aroclor 1221, which do not degrade as rapidly, are the major components in Aroclor 1242.




Figure 2. Typical electron capture chromatograms for Aroclor 1221, after exposure to activated sludge for 24 hours, and Aroclor 1242.

MONS 004013

It is important to note that the electron-capture detector does not have the same response for all components. With PCBs, the sensitivity of the detector generally increases as the degree of chlorination increases. From the Aroclor 1221 chromatograms, it is apparent that the dominant monochlorobiphenyl and dichlorobiphenyl components are readily degraded. Once the major components of Aroclor 1221 are degraded, the minor more slowly degrading components are easily observed after concentration of the sludge extracts.

Similar, less dramatic, alterations were noted for MCS 1043 and Aroclor 1242. No differences were observed in the extract and Aroclor 1254 standard chromatograms.

CONCLUSIONS

The results of this study demonstrate that commercial PCB mixtures which contain predominantly mono- and dichlorobiphenyls readily undergo primary biodegradation under the experimental conditions employed.

The data also illustrates that as the levels of tri-, tetra-, and pentachlorobiphenyls increase, the degradation rates decrease accordingly. This resistance of the more highly chlorinated biphenyls, particularly those containing 5 or more chlorine atoms per molecule, explains in part their detection as residues in weathered biological and environmental samples.

MONS 004014

ACKNOWLEDGEMENT

We are grateful to J. P. Mieure for determining the typical composition of the PCB products studied.

REFERENCES

AHMED, M., and FOCHT, D.D., Bull. Environ. Contam. and Toxicol., 10, 70 (1973a).
AHMED, M., and FOCHT, D.D., Can. J. Microbiol. 19, 47 (1973b).
CATTELINI, D., SORLINI, C., and TRECEANI, V., Experientia, 27, 1174 (1971).
EDWARDS, R., Chemistry and Industry, 20, 1340 (1970).
EVANS, W.C. and LUNT, D., Biochem. J. 118, 54P (1970).
GIBSON, D.T., ROBERTS, R.L., WELLS, M.C. and KOBAL, V.V., Biochem. Biophys. Res. Comm., 50, 211 (1973).
HOLMES, D.C., SIMMONS, J.H., and TATTON, J.O'G., Nature, 216, 1274 (1967).
JENSEN, S., and WIDMARK, G., "Unintended Residues in the Environment", O.E.C.D. Report (1967).
JENSEN, S., New Sci., 32, 612 (1966).
KOEMAN, J.H., TEN NOEVER DE BRAU, M.D., and DE VOS, R.H., Nature 221, 1126 (1969).
Monsanto Company, Chem. Eng. News 49, 15 (1971).
OHMORI, T., IKAI, T., MINODA, Y. and YAMADA, K., Agr. Biol. Chem. 7, 1599 (1973).
PEAKALL, D.B., and LINCER, J.L., Bio Science, 20, 958 (1970).
Soap and Detergent Association Sub-Committee on Biodegradation Test Methods, J. Amer. Oil Chem. Soc. 46, 432 (1969).
Soap and Detergent Association Sub-Committee on Biodegradation Test Methods, J. Amer. Oil Chem. Soc. 42, 986 (1965).
WIDMARK, G., "Determination of the Number of Compounds Which Can Result From the Chlorination of Biphenyl and Development of a Simple System by Which These May be Codified", O.E.C.D. Report, Sweden (1968).

MONS 004015

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test material	Structural formula	Ultimate Biodegradation (% theoretical)		Primary Biodegradability				
				Semi-continuous activated sludge (SCAS)		Viscosity		
		Modified Sturm procedure	Modified Sturm Flask procedure	Reduction Ratio (hour added per cycle)	Degradation Rate ±95% C.L.	Comments	Initial Concentration	% Reduction in Primary Viscosity
						The objective of indicates acceptable, strong, and very viable exhibition of sludge growth rate against valv.		
				Z-Hour Cycle				
HCB 1612 (o-chlorodiphenylmethane)		86 (35-Day)		3	> 97	Volatility loss < 4%.		82.3 ± 8.9 AC-72-M-3
				13	> 99	+ For more detail see AC-73-55-18.		
HCB 1613 (p-chlorodiphenylmethane)		86 (35-Day)		3	> 97	+		88.1 ± 5.9 AC-72-M-3
				13	> 99	+ For more detail see AC-73-55-18.		
HCB 1310 (3,4-Dichlorodiphenylmethane)				3	> 98	Volatility loss < 1%.		91.6 ± 3.7 AC-72-M-3
				13	> 99	+ For more detail see AC-73-55-18.		
HCB 1586 (3,4-Dichlorodiphenylmethane)		83 (35-Day)		3	> 97	Volatility loss < 1%.		76.2 ± 5.5 AC-72-M-3
				13	> 99	+ For more detail see AC-73-55-18.		

MONS 004016



TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test material	Structural formulation	Biodegradability (Shake-flask method) — Static Exposure — Screening test — Sturm procedure	Biodegradability (Shake-flask method) — Dynamic Exposure — Shake flask procedure	Sewage addition Rate (ml/liter per cycle)	Biodegradability (Shake-flask method) — Dynamic Exposure — Semi-batch flow test (% BOD)	Remarks	Solubility (mg/liter)	Toxicity Threshold Concentration (ppm)	Reference
				24-Hour Cycle		A ... and w/- ... dielectric materials ... strongly, the varia... rate ... although ... rate ... reasonably ...			
HCS 1560 (Mixture of 2,4- and 3,4-Dichlorodiphenyl methane)				3	> 97	Volatility loss < 1%.		79.6 ± 1.6	AC-72-M-9
				13	> 99	For more detail see AC-73-55-18.			
HCS 1559 (Mixture of 2,4'- and 4,4'-Dichlorodiphenyl methane)				3	3 ± 6	Volatility loss < 1%. For more detail see AC-73-55-18.		89.7 ± 2.3	AC-72-M-3
HCS 1558 (Trichlorodiphenyl methane)		26 (35-Day)		3	> 99	No detectable volatility loss (40.1%)		31.3 ± 6.7	AC-73-M-5
				13	63 ± 10	+ (13th-23rd week)			
					27 ± 2	+ (24th-31st week) Slowly degrading trichlorophenyl-acetic acid metabolite formed.			
HCS 1414 (Mixture of 2,3',4-, 3,3',4'-, and 4,3',4'-trichlorodiphenyl methane)				3	10 ± 19	Volatility loss < 1%. For more detail see AC-73-55-18.		84.2 ± 5.1	AC-72-M-3

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structural Formula	Ultimate Biodegradability (% of Theoretical) in Soil/Water: Modified Sturm procedure	Ultimate Biodegradability (% of Theoretical) in Soil/Water: Modified Shake Flask procedure	Primary Biodegradability in Static Continuous Activated Sludge (CCAS): Initial Rate (ppm cleaved per cycle)	Primary Biodegradability in Static Continuous Activated Sludge (CCAS): Primary Biodegradation Rate ±95% C.L.	Comments	Primary Biodegradability in Soil/Water: Initial Concentration	Primary Biodegradability in Soil/Water: Time to 50% Primary Degradation	Primary Biodegradability in Soil/Water: Primary Biodegradation Rate ±95% C.L.	Ref.
				24-hour Cycle		+, ++, and +/- indicate moderate, strong, and variable inhibition of sludge growth rate respectively.				
PCB 1260 (Trichlorodiphenyl) +octane mixture)				3	6 ± 11	Volatility loss < 1%. + For more detail see AC-73-65-18.			77.5 ± 2.2	AC-72-M-3
PCB 1260 (Bromodichlorodiphenyl) +octane mixture)				3	1 ± 10	Volatility loss < 1%. + For more detail see AC-73-65-18.			99.1 ± 4.3	AC-72-M-1
PCB 1260 (Bromotrichlorobenzene)				3	7 ± 10	Volatility loss < 1%. +			74.6 ± 4.5	AC-72-M-13
3,3',4,4'-Tetrachlorodiphenyl Ether				3	10 ± 4	+			87.3 ± 4.2	AC-71-M-17
PCB 1268 (Trichlorodiphenyl) Ether				48-Hour Cycle 3	24 ± 9	Volatility loss ~7%. + For more detail see AC-72-65-13.			96.1 ± 6.3	AC-71-M-24

MONS 004018

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structure/ Comments	Criteria Biodegradability (1 of 3 Interpretations) Evaluation: Yes, Slow, or No - Ruthy - Sturm procedure	Modified Sturm Flask procedure	Primary Biodegradation (Significant Pure Activated Sludge, SCAS) Rate Constant Rate (ppm added per cycle)	Primary Biodegradation Rate (ppm/cycle)	Comments	Ultimate Biodegradation (Significant Pure Activated Sludge, SCAS) Initial Concentration	Rate Constant or Half-Life (ppm per cycle)	Ultimate Biodegradation (Significant Pure Activated Sludge, SCAS) Percent Biodegradation	Reference
				24-Hour Cycle		+, ++, and +/- indicate moderate, strong, and variable inhibition of sludge growth rate respectively.				
Pentachlorodiphenyl ether mixture	47.48 Chlorine			1	1 ± 12	Volatility loss not significant.			72.8 ± 3.6	AC-74-M-24
Hexachlorodiphenyl ether mixture	533 Chlorine			1	-4 ± 15	Volatility loss not significant.			78.9 ± 5.3	AC-74-M-24
PCB 3711 (m-Trichloromethyl diphenyl ether)				3 13	68 ± 15 35 ± 12	Volatility loss 8-10%. ++ ++ For more detail see AC-72-55-13.			83.9 ± 3.7	AC-72-M-24
PCB 1339 (Mixture of 2-chlorobenzyl-n-butylether and 2,4-dichlorobenzyl-n-butyl ether)				3	45 ± 6	Volatility loss ~33%. ++ For more detail see AC-72-55-13.			103.4 ± 11.2	AC-72-M-24
PCB 1559 (n-Butyl-tetrachlorobenzyl ether)				1	-1 ± 17	Volatility loss < 1%.			70.2 ± 2.8	AC-74-M-5

MONS 004019

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structural Formula	Ultimate Biodegradation (14C Technique) 72 Cycles		Primary Biodegradation Test (Continuous Activated Sludge (CAS))					
		Test Duration - Days - Start Temperature	Inhibitor Added - Yes - Mass Fraction	Acclimation Ratio (Mass Input/Mass Out per Cycle)	Degradation Rate g/g/h C.V.	Comments	Visual Observations	Use of Soil Microorganisms	Primary Biodegradation Extent %
				24-Hour Cycle		Yes, and +/- indicate moderate, strong, and weak reaction as a function of visual growth rate (arbitrary)			
MCS 1646 (Mixture of 3,3,4,5-Tetrachlorosalicylanilide and ortho-chloro salicylanilide)		87%	82(28-Day)	1 3 13	> 95 > 99 > 99				78.8 ± 3.2 AC-76-M-6
MCS 1647 [2,3,4,6-Tetrachlorophenyl-1-(2-Chloro-2-propenyl) ether]				1	9 ± 5	Volatility loss < 1%.			69.4 ± 3.7 AC-76-M-7
MCS 1648 (Pentachlorodiphenyl sulfide mixture 30% Chlorine				1	5 ± 11	Volatility loss < 1%.			100.4 ± 13.1 AC-76-M-8
MCS 1649 (2,4,5-Trichlorophenyl sulfide)				1	4 ± 4	Volatility loss < 1%.			83.2 ± 1.1 AC-76-M-9

MONS 004020

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test material	Structural Description	Ultimate Biodegradation (% of Theoretical CO2 Evolution) Thirteen-Bottle Manometric Respirometer procedure	Ultimate Biodegradation (% of Theoretical CO2 Evolution) Sealed Flask procedure	Primary Biodegradability: Activated Sludge (ASG) Addition Rate (ppm added per cycle)	Primary Biodegradability: Activated Sludge (ASG) Percent Degradation Rate ±5% C.I.	Primary Biodegradability: Activated Sludge (ASG) Comments	Primary Biodegradability: River Die-away Initial Conc (ppm)	Primary Biodegradability: River Die-away Percent Degradation	Primary Biodegradability: Other (Specify)
				24-Hour Cycle		[illegible]			
PCS 1650 (Dichlorodiphenyl sulfide mixture)				1	19 ± 5	Volatility loss ≤ 13%.			101.6 ± [illegible] AC-74-M-40
PCS 1663 (Tetrachlorothiophene)				1 3	Not detectable	Very high volatility losses.			71.4 ± 7.7 AC-71-M-11
PCS 1664 (Hexachlorotetrahydrothiopyrone)				1 3	Not detectable	Very high volatility losses.			68.8 ± 7.4 AC-71-M-12
Diphenyl Sulfone				3	1 ± 6	Volatility loss ≤ 13%. For more detail see AC-72-SS-16.			98.7 ± 3.4 AC-72-M-6
PCS 1302 (Tolyltolyl sulfone)				3 48-Hour Cycle 3	23 ± 10 42 ± 12	Volatility loss ≤ 13%. For more detail see AC-72-SS-16.			98.8 ± 4.4 AC-71-M-29 AC-72-M-4

MONS 004021

TABLE I





PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Fluid	Structure/ Composition	Surface Chemistry (ESCA) Sturm procedure	Surface Chemistry (ESCA) Sealed Flask procedure	Primary Biodegradation Rate (ppm cooled per cycle)	Primary Biodegradation Rate ±95% C.L.	Comments	Critical Conditions	Ultimate Biodegradation Rate	Ultimate Biodegradation Rate ±95% C.L.
				24-hour Cycle					
PCS 1313 (Tolylethyl tolyl sulfone)				3	36 ± 6	Volatility loss ≤ 1%. For more detail see AC-72-55-16.		105.4 ± 16.1	AC-72-M-4
PCS 1312 (Tolylidiethyl ethyl phenyl sulfone)				3	13 ± 4	Volatility loss ≤ 1%. For more detail see AC-72-55-16.		97.6 ± 3.8	AC-72-M-5
PCS 1314 (Tolyl isopro-cyl phenyl sulfone)				3	27 ± 8	Volatility loss ≤ 1%. For more detail see AC-72-55-16.		111.2 ± 10.0	AC-72-M-6
PCS 1738 (Ethylphenyl tolyl sulfone)				3	17 ± 6	Volatility loss ≤ 1%.		96.8 ± 1.4	AC-75-M-16

MONS 004022

TABLE I




PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structure/ Specification	Ultimate Biodegradability (% of Theoretical) by Evolution: Carbon-Dioxide Sturm procedure	Shake Flask procedure	Primary Biodegradability: Semi-Continuous Activated Sludge (SCAS): Initial Rate (ppm aqueous per cycle)	Degradation Rate 95% C.I.	Comments	Initial Concentration	Test Period for Primary Degradation	Viscosity, centistokes
				24-Hour Cycle		n, m, and o/p ratios reported; strong, and variable inhibition of sludge growth rate respectively.			
Santicizer 711 [Di(heptyl, nonyl, undecyl) phthalate]	 n = 7, 9, 11	86 (27-Day)		3 7 13	52 ± 14 48 ± 9 54 ± 7	For more detail see AC-73-55-20 and AC-75-55-8.	1	> 15	100.7 ± 3.1 AC-73-55-5 AC-73-55-8
Di-2-ethylhexyl phthalate (DEHP, DOP)		86 (27-Day)		3 3	70 ± 11 78 ± 3	For more detail see AC-73-55-20 and AC-75-55-8.	1	10	75.1 ± 5.9 AC-73-55-6
Santosol 100 [Para and poly-benzylethyl - benzene mixture]				8	61 ± 8	Volatility loss ~52. Monobenzyl ethyl benzene degraded much more rapidly than polybenzyl components.			96.9 ± 2.6 AC-73-55-19 AC-73-55-20 AC-75-55-8
HCB 1477 [Mixture of 55% 1-771 and 13% HCB 1308]	 n = 7, 9, 11 55% 1-771 13% HCB 1308			3	38 ± 7	Volatility loss 6.18. For more detail see AC-73-55-16.			97.8 ± 5.1 AC-73-55-16

MONS 004023

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structure/ Composition	Ultimate Biodegradability (% of Theoretical CO_2 Evolution)		Semi-Continuous Activated Sludge (SCAS)			Aerobic Stability	Hydrolytic Stability	Toxicity
		Modified Sturm procedure	Monsanto Shake Flask procedure	Addition Rate (mg/l added per cycle)	Primary Degradation Loss Rate at 25°C (%/hr)	Remarks			
	 n ≥ 1					+, ++, and +/- indicate moderate, strong, and variable inhibition of sludge growth rate respectively.			
				24-Hour Cycle					
MCS 1478 (Mixture of 10% Santosol 150, 35% MCS 1352, and 55% W230L)	 55% W230L (Complex alkyl-benzene mixture)			3	21 ± 12	Volatility loss ≤ 1%.			91.9 ± 5.1 AC-73-M-11
MCS 1352 (Di-ethyl hexaphenone)				3	85 ± 9	Volatility loss ≤ 1%.			88.9 ± 5.6 AC-73-M-25
				13	93 ± 6	+			
					52 ± 21	For more detail see AC-73-57-IR.			
Aroclor 1221 (Polychlorinated biphenyl)	 65(28-Day)			24-Hour Cycle		Volatility loss ≤ 6%.			95.9 ± 1.6 AC-73-M-17
	21% Cl			1	73 ± 21				
	11% Biphenyl			3	52 ± 17	Lot AK-2			
	31% Monochloro-			48-Hour Cycle		For more detail see AC-73-55-6 and AC-73-55-17.			
	32% Dichloro-			1	31 ± 6				
	3% Trichloro-			8	87 ± 5				
	2% Tetrachloro-								

MONS 004024

TABLE I

(19)

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structure/ Composition	Ultimate Biodegradability (Final Microbial Population) 30-Day Exposure: Percent Stable Chlorine Groups	Ultimate Biodegradability (Final Microbial Population) 30-Day Exposure: Percent Stable Phenyl Groups	Primary Biodegradability (Semi-Continuous Activated Sludge Test) Addition Rate (ppm added per cycle)	Primary Biodegradability (Semi-Continuous Activated Sludge Test) Primary Biodegradation Rate (ppm C.L. per hour)	Comments	Concentration	Half-Life for Primary Biodegradation	Reference
				24-Hour Cycle		Data and information indicate primary, and ultimate biodegradation of fluids greater than current levels.			
PCB 1063 (Polychlorinated biphenyl)	 39% Cl 0.1% Biphenyl 23% Monochloro 72% Dichloro 6% Trichloro	43(35-Day) Lot QA47		1	74 ± 7	+ Lot QA47			94.7 ± 1.9 AC-71-M-17
				48-Hour Cycle					
				1	56 ± 16	Sample OR15A91 Volatility loss ~69.			
Arochlor 1232 (Poly Brominated-biphenyl)	 21% Cl, 18% Br			48-Hour Cycle					
				1	54 ± 19	Sample OR16B82 For more detail see AC-71-SS-6.			93.8 ± 1.7 AC-71-M-17
Arochlor 1016 (Polychlorinated biphenyl)	 42% Cl 1% Monochloro- 23% Dichloro- 27% Trichloro- 21% Tetra- 1% Penta-	4(28-Day) 12(35-Day)		48-Hour Cycle					
				1	33 ± 14	Volatility loss ~ 88. Sample OR15B91 For more detail see AC-71-SS-2, AC-71-SS-6 and AC-72-SS-19.			91.6 ± 1.2 AC-71-M-17

MONS 004025

TABLE I

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test material	Structure/ Composition	Ultimate Biodegradability (% of Theoretical CO_2 Evolution) Premium -Ducha -Storm procedure	Ultimate Biodegradability (% of Theoretical CO_2 Evolution) Modified Sturm Flask procedure	Primary Biodegradability Semi-Continuous Activated Sludge (SCAS) Addition Rate (ppm added per cycle)	Primary Biodegradability Semi-Continuous Activated Sludge (SCAS) Primary Degradation Rate ±95% C.L.	Comments	Initial Concentration	Test Duration (days)	Primary Biodegradability Shake Flask Procedure Extent	Reference
						+, ++, and +/- indicate moderate, extensive, and questionable inhibition of sludge growth rate respectively.				
Aroclor 1242 (Polychlorinated Biphenyl)	 42% Cl 1% Monochloro- 16% Dichloro- 49% Trichloro- 35% Tetrachloro- 8% Pentachloro- 1% Hexachloro-	11(35-Day)		48-Hour Cycle 1	26 ± 15	Volatility loss ~4%. Lot AR-255 For more detail see AC-71-55-6 and AC-72-55-19.			83.0 ± 1.1	AC-71-M-1
Aroclor 1254 (Polychlorinated Biphenyl)	 54% Cl 1% Trichloro- 21% Tetrachloro- 45% Pentachloro- 23% Hexachloro- 6% Heptachloro-			48-Hour Cycle 1	14 ± 38	Volatility loss ≤ 1%. Lot AR-38 For more detail see AC-71-55-6.			78.6 ± 2.4	AC-71-M-1

MONS 004026

TABLE 1

PRIMARY AND ULTIMATE BIODEGRADABILITY OF DIELECTRIC FLUIDS AND COMPONENTS

Test Material	Structure/ Composition	Ultimate Biodegradability (% of Theoretical CO2 Evolution)		Primary Biodegradability				
				Semi-Continuous Activated Sludge (SCAS)		Shake Flask Method		
		Modified Sturm Procedure	Modified Sturm Flask Procedure	Solution Ratio (ppm oxidant per cycle)	Primary Degradation Rate ±1σ, C.L.	Comments	Half-Life or 50% Primary Degradation (hrs)	% Primary Degradation ± 1σ, C.L.
				2-Hour Cycle		Enzymes and other indicate reducers, strong oxidants (chlorine) or of toxic products may inactivate		
Dow-Corning 739 (Hexaphenyl-trimethyltrisiloxane)				3	16 ± 13	No detectable volatility loss. For more detail see AC-73-55-23.		77.4 ± 8.2 AC-73-m-
Aroclor 1268 (Pentachlorobiphenyl)				1	14 ± 8	Volatility loss ~ 40%. +/- For more detail see AC-73-55-15.		77.1 ± 2.6 AC-73-m-