



(125 lbs. net)



O'BRIEN

Liquid Velvet

WALL LATEX PAINT

MEDIUM TONE TINT BASE

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND, IND. • BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL.

LIQUID VELVET LATEX

Flat Wall Paint

New Liquid Velvet Latex represents an entirely different and amazing advancement in the field of interior latex finishes! This perfected flat wall paint offers the user a combination of features found in no other latex finish:

EXTRA HIDING . . . EASIER BRUSH AND ROLLER APPLICATION . . . FAST 30 MINUTE DRYING . . . LAP-FREE PAINTING . . . TRUE WASH-ABILITY . . . NEW, LOW PLEASANT ODOR.

While Liquid Velvet Latex is a wall finish primarily, it may be applied over almost any properly prepared interior surface.

DIRECTIONS FOR USE

For New Unpainted Surfaces

1st Coat—Liquid Velvet Latex. (Over unpainted wood or metal, always use an O'Brien oil base primer before applying first coat of Liquid Velvet Latex.)

2nd Coat—Liquid Velvet Latex.

For Old Painted Surfaces

1 Coat Work—One coat of Liquid Velvet Latex will do an excellent job.

2 Coat Work—If the paint film is in bad condition or a radical color change is made, apply two coats of Liquid Velvet Latex.

Surfaces—Surface should be washed perfectly free of kalsomine, dirt, grease, glue size or soluble casein paints. Cracks and nailholes should be filled with a patching plaster, and when dry, sanded smooth.

CAUTION!—Glossy surfaces must be dulled by scrubbing with a scouring powder, steel wooling, sanding or by wiping with O'Brien's Tack-it, as directed.)

Application—Apply generously and evenly with brush, roller or spray. If thinning is necessary, use only a small amount of clean water and stir thoroughly. Wipe splatters immediately with a damp cloth. Wash brush or roller cover in luke warm soapy water immediately after use. Rinse thoroughly.

On most surfaces, Liquid Velvet Latex may be washed after two days. Two weeks drying time, however, is recommended.

Intermixing—Liquid Velvet Latex colors may be intermixed or tinted with O'Brien's Tone-All Colors. Do not tint with conventional paint or oil colors.

LEAD FREE
DO NOT TAKE INTERNALLY

CAUTION!

Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. KEEP OUT OF THE REACH OF CHILDREN.

LIQUID VELVET MEDIUM TONE	
Pigment	Tint Base
Barium Oxide	32.27%
Carbon Black	17.81%
Calcium Carbonate	54.78%
Silica	54.78%
Vehicle	100.00%
Poly Vinyl Acetate Resin	20.27%
Water	79.44%
	100.00%